

# C programming language

---

Jeremy Iverson

College of Saint Benedict & Saint John's University

- Dennis Ritchie and Brian Kernighan creators of C circa 1972
- TODO: more thorough history



Dennis Ritchie in 2011 / CC BY 2.0



Brian Kernighan in 2012 / CC BY 2.0

## comparison

Java	C
object-oriented	procedural
interpreted	compiled
<b>String</b>	<b>char</b> array
condition ( <b>boolean</b> )	condition ( <b>int</b> )
garbage-collected	no memory management
references	pointers
exceptions	error codes

- in Java, everything is a method that is called on an object
- in C, everything is a function
- in Java, source code is compiled to byte code, which is then interpreted by Java VM
- in C, source code is compiled into binary machine code
- in Java, String is a class
- in C, a string is just an array of **char** values which ends with the **char** `'\0'`
- in Java, the Java VM takes care of deallocating memory used
- in C, any memory you allocate, you must also deallocate

# hello, world

```
1 /* file: helloworld.c */
2
3 #include <stdio.h>
4
5 int main() {
6     printf("hello, world\n");
7     return 0;
8 }
```

```
$ gcc -o helloworld helloworld.c
$ ./helloworld
hello, world
```

- The tradition of using the phrase "Hello, world!" as a test message was influenced by an example program in the seminal book *The C Programming Language*

## global variables

```
1 // file: figure2-4.c
2 // Stan Warford
3 // A nonsense program to illustrate global variables
4
5 #include <stdio.h>
6
7 char ch;
8 int j;
9
10 int main() {
11     scanf("%c %d", &ch, &j);
12     j += 5;
13     ch++;
14     printf("%c\n%d\n", ch, j);
15     return 0;
16 }
```

```
$ gcc -o figure2-4 figure2-4.c
$ ./figure2-4
M 419
N
424
```

- What would you expect for input 'Z -3'?
- What would you expect for input '9 a'?
- What would you expect for input '~ 2147483643'?

## program breakdown

```
5  #include <stdio.h>
6
7  char ch;
8  int j;
9
10 int main() { <-----
11     scanf("%c %d", &ch, &j);
12     j += 5;
13     ch++;
14     printf("%c\n%d\n", ch, j);
15     return 0; <-----
16 }
```

C programs ALWAYS  
start execution with  
the `main` function

returning from `main`  
ends the program

# program breakdown

global variables are  
declared here —  
outside of any function

characters in C are  
treated internally  
like signed integers

```
5  #include <stdio.h>
6
7  {char ch;
8    int j;
9
10 int main() {
11     scanf("%c %d", &ch, &j);
12     j += 5;
13     ch++;
14     printf("%c\n%d\n", ch, j);
15     return 0;
16 }
```

## program breakdown

```
5  #include <stdio.h>
6
7  char ch;
8  int j;
9
10 int main() {
11     scanf("%c %d", &ch, &j);
12     j += 5;
13     ch++;
14     printf("%c\n%d\n", ch, j);
15     return 0;
16 }
```

read data from  
**stdin** (the terminal)

print data to **stdout**  
(the terminal)

correct headers must  
be included to access  
library functions

**scanf** and **printf** are  
both library functions  
declared in **stdio.h**

- C has no “built-in” functions; however, it does have a standard library that includes many useful utility functions.



## program breakdown

```
5  #include <stdio.h>
6
7  char ch;
8  int j;
9
10 int main() {
11     scanf("%c %d", &ch, &j); <---
12     j += 5;
13     ch++;
14     printf("%c\n%d\n", ch, j);
15     return 0;
16 }
```

& is the address of operator — **scanf** expects the address of the variables where the data will be stored


## memory model — part i

### global variables

declared outside of any function and remain in place throughout the execution of the entire program. they are stored at a fixed location in memory.

### local variables

declared within a function and come into existence when the function is called and cease to exist when the function terminates. they are stored on the run-time stack.



(a) Fixed location.



(b) Run-time stack.

- I will be using graphical notation consistent with that of the book.
- In this case, (a) and (b) represent the state of relevant memory for the previous program just before it terminates, i.e., in the process of executing line 15.
- How would the previous program behave had it declared `ch` and `j` as local variables instead of global variables?
- What would the memory model look like given the above?






Figure 2: Run-time stack.



(a) Fixed location.



(b) Run-time stack.

## conditions

- under what conditions will each of the following be execute?

```
1  if (x) {  
2      /* ??? */  
3  }  
4  if (x-y) {  
5      /* ??? */  
6  }  
7  if (x=y) {  
8      /* ??? */  
9  }
```

- $x \neq 0$

- $x \neq y$

- $y \neq 0$



except where otherwise noted, this worked is licensed under creative commons attribution-sharealike 4.0 international license