

## Contents

<b>Input Validation</b>	<b>1</b>
Valid and invalid data . . . . .	1
Ensuring data is valid with a loop . . . . .	2
Ensuring the user enters a number with TryParse . . . . .	3

## Input Validation

### Valid and invalid data

- Depending on the purpose of your program, each variable might have a limited range of values that are “valid” or “good,” even if the data type can hold more
- For example, a `decimal` variable that holds a price (in dollars) should have a positive value, even though it is legal to store negative numbers in a `decimal`
- Consider the `Item` class, which represents an item sold in a store. It has a `price` attribute that should only store positive values:

`!include code/snippets/item.cs`

- When you write a program that constructs an `Item` from literal values, you (the programmer) can make sure you only use positive prices. However, if you construct an `Item` based on input provided by the user, you cannot be certain that the user will follow directions and enter a valid price:

```
Console.WriteLine("Enter the item's description");
string desc = Console.ReadLine();
Console.WriteLine("Enter the item's price (must be positive)");
decimal price = decimal.Parse(Console.ReadLine());
Item myItem = new Item(desc, price);
```

In this code, if the user enters a negative number, the `myItem` object will have a negative price, even though that does not make sense.

- One way to guard against “bad” user input values is to use an `if` statement or a conditional operator, as we saw in the previous lecture (Switch and Conditional), to provide a default value if the user’s input is invalid. In our example with `Item`, we could add a conditional operator to check whether `price` is negative before providing it to the `Item` constructor:

```
decimal price = decimal.Parse(Console.ReadLine());
Item myItem = new Item(desc, (price >= 0) ? price : 0);
```

In this code, the second argument to the `Item` constructor is the result of the conditional operator, which will be 0 if price is negative.

- You can also put the conditional operator inside the constructor, to ensure that an `Item` with an invalid price can never be created. If we wrote this constructor inside the `Item` class:

```
public Item(string initDesc, decimal initPrice)
{
    description = initDesc;
    price = (initPrice >= 0) ? initPrice : 0;
}
```

then the instantiation `new Item(desc, price)` would never be able to create an object with a negative price. If the user provides an invalid price, the constructor will ignore their value and initialize the price instance variable to 0 instead.

## Ensuring data is valid with a loop

- Another way to protect your program from “bad” user input is to check whether the data is valid as soon as the user enters it, and prompt him/her to re-enter the data if it is not valid
- A `while` loop is the perfect fit for this approach: you can write a loop condition that is true when the user’s input is *invalid*, and ask the user for input in the body of the loop. This means your program will repeatedly ask the user for input until he/she enters valid data.
- This code uses a `while` loop to ensure the user enters a non-negative price:

```
Console.WriteLine("Enter the item's price.");
decimal price = decimal.Parse(Console.ReadLine());
while(price < 0)
{
    Console.WriteLine("Invalid price. Please enter a non-
negative price.");
    price = decimal.Parse(Console.ReadLine());
}
Item myItem = new Item(desc, price);
```

- The condition for the `while` loop is `price < 0`, which is true when the user’s input is invalid
- If the user enters a valid price the first time, the loop will not execute at all – remember that a `while` loop will skip the code block if the condition is false
- Inside the loop’s body, we ask the user for input again, and assign the result of `decimal.Parse` to the same `price` variable we use in

the loop condition. This is what ensures that the loop will end: the variable in the condition gets changed in the body.

- If the user still enters a negative price, the loop condition will be true, and the body will execute again (prompting them to try again)
- If the user enters a valid price, the loop condition will be false, so the program will proceed to the next line and instantiate the Item
- Note that the *only* way for the program to “escape” from the while loop is for the user to enter a valid price. This means that new Item(desc, price) is guaranteed to create an Item with a non-negative price, even if we did not write the constructor that checks whether initPrice >= 0. On the next line of code after the end of a while loop, you can be certain that the loop’s condition is false, otherwise execution would not have reached that point.

## Ensuring the user enters a number with TryParse

- Another way that user input might be invalid: When asked for a number, the user could enter something that is not a number
- The Parse methods we have been using assume that the string they are given (in the argument) is a valid number, and produce a run-time error if it is not
- For example, this program will crash if the user enters “hello” instead of a number:

```
Console.WriteLine("Guess a number");
int guess = int.Parse(Console.ReadLine());
if(guess == favoriteNumber)
{
    Console.WriteLine("That's my favorite number!");
}
```

- Each built-in data type has a **TryParse method** that will *attempt* to convert a string to a number, but will not crash (produce a run-time error) if the conversion fails. Instead, TryParse indicates failure by returning the Boolean value false
- The TryParse method is used like this:

```
string userInput = Console.ReadLine();
int intVar;
bool success = int.TryParse(userInput, out intVar);
```

- The first parameter is a string to be parsed (userInput)
- The second parameter is an **out parameter**, and it is the name of a variable that will be assigned the result of the conversion. The

keyword *out* indicates that a method parameter is used for *output* rather than *input*, and so the variable you use for that argument will be changed by the method.

- The return type of `TryParse` is `bool`, not `int`, and the value returned indicates whether the input string was successfully parsed
- If the string `userInput` contains an integer, `TryParse` will assign that integer value to `intVar` and return `true` (which gets assigned to `success`)
- If the string `userInput` does not contain an integer, `TryParse` will assign 0 to `intVar` and return `false` (which gets assigned to `success`)
- Either way, the program will not crash, and `intVar` will be assigned a new value
- The other data types have `TryParse` methods that are used the same way. The code will follow this general format:

```
bool success = <numeric datatype>.TryParse(<string to convert>, out <numeric variable>);
```

Note that the variable you use in the `out` parameter must be the same type as the one whose `TryParse` method is being called. If you write `decimal.TryParse`, the `out` parameter must be a `decimal` variable.

- A more complete example of using `TryParse`:

```
Console.WriteLine("Please enter an integer");
string userInput = Console.ReadLine();
int intVar;
bool success = int.TryParse(userInput, out intVar);
if(success)
{
    Console.WriteLine($"The value entered was an integer: {intVar}");
}
else
{
    Console.WriteLine($"\"{userInput}\" was not an integer");
}
Console.WriteLine(intVar);
```

- The `TryParse` method will attempt to convert the user's input to an `int` and store the result in `intVar`
- If the user entered an integer, `success` will be `true`, and the program will display "The value entered was an integer:" followed by the user's value
- If the user entered some other string, `success` will be `false`, and the program will display a message indicating that it was not an

integer

- Either way, `intVar` will be assigned a value, so it is safe to write `Console.WriteLine(intVar)`. This will display the user's input if the user entered an integer, or "0" if the user did not enter an integer.
- Just like with `Parse`, you can use `Console.ReadLine()` itself as the first argument rather than a `string` variable. Also, you can declare the output variable within the `out` parameter, instead of on a previous line. So we can read user input, declare an `int` variable, and attempt to parse the user's input all on one line:

```
bool success = int.TryParse(Console.ReadLine(), out int intVar);
```

- You can use the return value of `TryParse` in a `while` loop to keep prompting the user until they enter valid input:

```
Console.WriteLine("Please enter an integer");
bool success = int.TryParse(Console.ReadLine(), out int number);
while(!success)
{
    Console.WriteLine("That was not an integer, please try again.");
    success = int.TryParse(Console.ReadLine(), out number);
}
```

- The loop condition should be true when the user's input is *invalid*, so we use the negation operator `!` to write a condition that is true when `success` is `false`
- Each time the loop body executes, both `success` and `number` are assigned new values by `TryParse`