2/9/2017 Version 0.3

Team Malaga


Dual-Alarm AM/FM Clock Radio

System Sequence Diagrams

Bryce Charydczak, Eric Hofesmann, Marge Marshall


CSCI 360

System Sequence Diagram: Set Alarm




Operation Contracts for SSD: Set Alarm			
Operation	Cross Reference	Preconditions	Postconditions
selectAlarm(alarm)	Use Case 3: Silence Alarm Use Case 4: Disable Alarm	The alarm clock has power.	currentAlarm is set to equal alarm.
checkMilitaryTime()		The alarm clock has power.	Updates a local variable boolean value
setHour(hour)	Use Case 5: Change Clock Time	An alarm has been selected.	The selected alarm's hour has been set.
setMinute(minute)	Use Case 5: Change Clock Time	An alarm has been selected.	The selected alarm's minute has been set.
setAMPM(am_pm)	Use Case 5: Change Clock Time	Military time is equal to False.	The alarm AMPM parameter is set to equal am_pm.
setRepeat()		The alarm clock has power and an alarm has been set.	isRepeat is equal to True The alarm will now repeat every 24 hours.

System Sequence Diagram: Find Radio Statio




Operation Contracts for SSD: Find Radio Station			
Operation	Cross Reference	Preconditions	Postconditions
radioOn()	Use Case 6: Change Volume	The radio has power and radio stations are broadcasting their signals.	The radio will be on and play. currentStation is set to equal the presently playing radio frequency.
nextStation()		The radio has power and radio stations are broadcasting their signals.	nextStation parameter is set to the frequency of the next radio station. Updates
previousStation()		The radio has power and radio stations are broadcasting their signals.	previousStation parameter is set to the frequency of the next lowest frequency radio station.

System Sequence Diagram: Silence Alarm




Operation Contracts for SSD: Silence Alarm			
Operation	Cross Reference	Preconditions	Postconditions
selectAlarm(alarm)	Use Case 1: Set Alarm Use Case 4: Disable Alarm	The alarm clock has power.	currentAlarm is set to equal alarm.
silenceAlarm()		Alarm is enabled and has power.	Alarm is silenced for a period of 24 hours.
snoozeAlarm()		Alarm is enabled and has power.	Alarm is silenced for a period of 10 minutes.
alarmDelayOneDay()		The silenceAlarm method has been called.	Appends 24 hours of delay to the internal instance variable of the alarm selected.
alarmDelayTenMinutes()		The snoozeAlarm method has been called.	Appends 10 minutes of delay to the internal instance variable of the alarm selected.

System Sequence Diagram: Disable Alarm




Operation Contracts for SSD: Disable Alarm			
Operation	Cross Reference	Preconditions	Postconditions
selectAlarm(alarm)	Use Case 1: Set Alarm	The alarm clock has power.	currentAlarm is set to equal alarm.
disableAlarm()		Alarm is enabled.	Alarm has been disabled and will not go off at the time it is set.

System Sequence Diagram: Change Clock Time



Operation Contracts for SSD: Change Clock Time			
Operation	Cross Reference	Preconditions	Postconditions
selectMilitaryTime(mode)		The alarm clock has power.	The parameter isMilitaryTime is set to equal the boolean mode.
setHour(hour)	Use Case 1: Set An Alarm	An alarm has been selected.	The selected alarm's hour has been set.
setMinute(minute)	Use Case 1: Set An Alarm	An alarm has been selected.	The selected alarm's minute has been set.
setAMPM(am_pm)	Use Case 1: Set An Alarm	Military time is equal to False.	The alarm AMPM parameter is set to equal am_pm.

System Sequence Diagram: Change Volume



Operation Contracts for SSD: Change Volume			
Operation	Cross Reference	Preconditions	Postconditions
radioOn()	Use Case 2: Find Radio Station	The radio has power and radio stations are broadcasting their signals.	The radio will be on and play. currentStation is set to equal the presently playing radio frequency.
volumeIncrease()		Radio is on, volume is not at maximum.	Volume was increased.
voumeDecrease()		Radio is on, volume is not at minimum.	Volume was decreased.