

Blaine Billings  
Julian Smith  
Tyler Newman

## System Sequence Diagrams and Operation Contracts

### **Operation Contracts**


- I. Contract CO1
  - A. Operation:           getRadioStatus()
  - B. Cross References:   SSDs - Tune Radio
  - C. Preconditions:       None
  - D. Postconditions:
    - Returns the current status of the radio (on/off)
- II. Contract CO2
  - A. Operation:           getStation()
  - B. Cross References:   SSDs - Tune Radio
  - C. Preconditions:
    - Radio must be set to a certain station (even if turned off)
  - D. Postconditions:
    - Returns the station that the radio is currently set to
- III. Contract CO3
  - A. Operation:           checkStationChange()
  - B. Cross References:   SSDs - Tune Radio
  - C. Preconditions:
    - The radio must be turned on
  - D. Postconditions:
    - The user has either chosen up, down, or nothing at all
    - This choice is returned
- IV. Contract CO4
  - A. Operation:           increaseStation()
  - B. Cross References:   SSDs - Tune Radio
  - C. Preconditions:
    - The radio must be turned on
  - D. Postconditions:
    - The current station is increased by one interval
- V. Contract CO5
  - A. Operation:           decreaseStation()
  - B. Cross References:   SSDs - Tune Radio
  - C. Preconditions:
    - The radio must be turned on
  - D. Postconditions:
    - The current station is decreased by one interval

- VI. Contract CO6
  - A. Operation: `switchTimeFormat()`
  - B. Cross References: SSDs - Change Time Format
  - C. Preconditions:
    - The time is set to either 12 hour or 24 hour time
  - D. Postconditions:
    - The time is switched to the opposite time format than in the precondition
- VII. Contract CO7
  - A. Operation: `enterAlarmSetMode(alarmNumber: integer)`
  - B. Cross References: SSDs - Set Alarm Time
  - C. Preconditions: None
  - D. PostConditions:
    - The alarm clock is in alarm-setting mode for the specified alarmNumber
- VIII. Contract CO8
  - A. Operation: `setAlarmTime(hours: integer, minutes: integer)`
  - B. Cross References: SSDs - Set Alarm Time
  - C. Preconditions:
    - Alarm clock is in alarm-setting mode
  - D. PostConditions:
    - The time of the previously specified alarm is changed to the inputted time
- IX. Contract CO9
  - A. Operation: `exitAlarmSetMode()`
  - B. Cross References: SSDs - Set Alarm Time
  - C. Preconditions:
    - The alarm clock is in alarm-setting mode
  - D. PostConditions:
    - The alarm clock is no longer in alarm-setting mode
- X. Contract CO10
  - A. Operation: `enterTimeSetMode()`
  - B. Cross References: SSDs - Set Time
  - C. Preconditions: None
  - D. PostConditions:
    - The alarm clock is in time-setting mode
- XI. Contract CO11
  - A. Operation: `setClockTime(hours: integer, minutes: integer)`
  - B. Cross References: SSDs - Set Time
  - C. Preconditions:
    - The alarm clock is in time-setting mode
  - D. Postconditions:
    - The time displayed on the alarm clock is changed to and saved as the inputted time
- XII. Contract CO12


- A. Operation: `exitTimeSetMode()`
- B. Cross References: SSDs - Set Time
- C. Preconditions:
  - The alarm clock is in time-setting mode
- D. Postconditions:
  - The alarm clock is no longer in time-setting mode

XIII. Contraint CO13

- A. Operation: `snoozeAlarm()`
- B. Cross References: SSDs - Snooze Alarm
- C. Preconditions:
  - There must be an alarm currently sounding
- D. Postconditions:
  - All alarms that were sounding at the time of activation are delayed to go off five minutes later



Visual Paradigm Standard(College of Charleston)



Visual Paradigm Standard(College of Charleston)

