


Inheritance

Lecture Question

Question: in a package named "oop.electronics", implement the following. This functionality is the same as the last lecture question, but we will use inheritance to prevent duplicating code.

- class Battery with
 - A constructor that takes a variable named "charge" of type Int
- abstract class Electronic with
 - A constructor that takes no parameters
 - A state variable named "battery" of type Battery
 - A method named "use" that takes no parameters and returns Unit (This can be abstract)
 - A method named "replaceBattery" that takes a Battery as a parameter and returns a Battery
 - This method swaps the input Battery with the Battery currently stored in this Electronic's state variable
 - The returned Battery is the one that was in the state variable when the method is called
- class BoomBox that extends Electronic
 - A constructor that takes a variable of type Battery and assigned it to the inherited state variable named "battery"
 - Your constructor parameter should have a different name than the state variable
 - Override the "use" method to reduce the charge of the battery in the state variable by 3 if its charge is 3 or greater
- class FlashLight that extends Electronic
 - A constructor that takes no parameters
 - When a new FlashLight is created, assign the inherited state variable named "battery" to a new Battery with 5 charge (ie. Batteries included)
 - Override the "use" method to reduce the charge of the battery in the state variable by 1 if its charge is 1 or greater

Scala Type Hierarchy



- All objects share **Any** as their base types
- Classes extending **AnyVal** will be stored on the **stack**
- Classes extending **AnyRef** will be stored on the **heap**

Overview

- Let's do some world building
- If we're making a game, we'll want various objects that will interact with each other
- We'll setup a simple game where
 - Each player has a set health and strength
 - Players can pick up and throw balls
 - If a player gets hit with a ball, they lose health
 - Players can collect health potions to regain health
- Note: We might not build this full game, but we will build some of the game mechanics

Objects Review

- We'll need different objects for this game
 - Player
 - Ball
 - HealthPotion

Objects Review

Player		
State	location: PhysicsVector	(2.0, -2.0, 2.0)
	dimensions: PhysicsVector	(1.0, 1.0, 2.0)
	velocity: PhysicsVector	(0.0, -1.0, 0.0)
	orientation: PhysicsVector	(0.5, -0.5, 0.0)
	health: Int	17
	maxHealth: Int	20
	strength: Int	25
Behavior	useBall(ball: Ball): Unit	
	useHealthPotion(potion: HealthPotion): Unit	

```
object Player {  
  var location: PhysicsVector = new PhysicsVector(2.0, -2.0, 2.0)  
  var dimensions: PhysicsVector = new PhysicsVector(1.0, 1.0, 2.0)  
  var velocity: PhysicsVector = new PhysicsVector(0.0, -1.0, 0.0)  
  var orientation: PhysicsVector = new PhysicsVector(0.5, -0.5, 0.0)  
  
  val maxHealth: Int = 20  
  val strength: Int = 25  
  
  var health: Int = 17  
  
  def useBall(ball: Ball): Unit = {  
    ball.use(this)  
  }  
  
  def useHealthPotion(potion: HealthPotion): Unit = {  
    potion.use(this)  
  }  
}
```

Objects Review

Ball		
State	location: PhysicsVector	(1.0, 5.0, 2.0)
	dimensions: PhysicsVector	(1.0, 1.0, 1.0)
	velocity: PhysicsVector	(1.0, 1.0, 10.0)
	mass: Double	5.0
Behavior	used(player: Player): Unit	

```
object Ball {  
  var location: PhysicsVector = new PhysicsVector(1.0, 5.0, 2.0)  
  var dimensions: PhysicsVector = new PhysicsVector(1.0, 1.0, 1.0)  
  var velocity: PhysicsVector = new PhysicsVector(1.0, 1.0, 10.0)  
  val mass: Double = 5.0  
  
  def use(player: Player): Unit = {  
    this.velocity = new PhysicsVector(  
      player.orientation.x * player.strength,  
      player.orientation.y * player.strength,  
      player.strength  
    )  
  }  
}
```

Objects Review

HealthPotion		
State	location: PhysicsVector	(5.0, 7.0, 0.0)
	dimensions: PhysicsVector	(1.0, 1.0, 1.0)
	velocity: PhysicsVector	(0.0, 0.0, 0.0)
	volume: Int	3
Behavior	use(player: Player): Unit	

```
object HealthPotion {  
  var location: PhysicsVector = new PhysicsVector(5.0, 7.0, 0.0)  
  var dimensions: PhysicsVector = new PhysicsVector(1.0, 1.0, 1.0)  
  var velocity: PhysicsVector = new PhysicsVector(0.0, 0.0, 0.0)  
  val volume: Int = 3  
  
  def use(player: Player): Unit = {  
    player.health = (player.health + this.volume).min(player.maxHealth)  
  }  
}
```


Objects Review

- But this is restrictive
- Game can only have one Ball, one HealthPotion, and on Player
- Can play, but not very fun

Player		
State	location: PhysicsVector	(2.0, -2.0, 2.0)
	dimensions: PhysicsVector	(1.0, 1.0, 2.0)
	velocity: PhysicsVector	(0.0, -1.0, 0.0)
	orientation: PhysicsVector	(0.5, -0.5, 0.0)
	health: Int	17
	maxHealth: Int	20
	strength: Int	25
Behavior	useBall(ball: Ball): Unit	
	useHealthPotion(potion: HealthPotion): Unit	

Ball		
State	location: PhysicsVector	(1.0, 5.0, 2.0)
	dimensions: PhysicsVector	(1.0, 1.0, 1.0)
	velocity: PhysicsVector	(1.0, 1.0, 10.0)
	mass: Double	5.0
Behavior	used(player: Player): Unit	

HealthPotion		
State	location: PhysicsVector	(5.0, 7.0, 0.0)
	dimensions: PhysicsVector	(1.0, 1.0, 1.0)
	velocity: PhysicsVector	(0.0, 0.0, 0.0)
	volume: Int	3
Behavior	use(player: Player): Unit	

Classes Review

- This is why we use classes
- Classes let us create multiple objects of type Ball, HealthPotion, and Player

Player	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	orientation: PhysicsVector
	health: Int
	maxHealth: Int
	strength: Int
Behavior	useBall(ball: Ball): Unit
	useHealthPotion(potion: HealthPotion): Unit

Ball	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	mass: Double
Behavior	use(player: Player): Unit

HealthPotion	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	volume: Int
Behavior	use(player: Player): Unit

Classes Review

Player	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	orientation: PhysicsVector
	health: Int
	maxHealth: Int
	strength: Int
Behavior	useBall(ball: Ball): Unit
	useHealthPotion(potion: HealthPotion): Unit

```
class Player(var location: PhysicsVector,
             var dimensions: PhysicsVector,
             var velocity: PhysicsVector,
             var orientation: PhysicsVector,
             val maxHealth: Int,
             val strength: Int) {

    var health: Int = maxHealth

    def useBall(ball: Ball): Unit = {
        ball.use(this)
    }

    def useHealthPotion(potion: HealthPotion): Unit = {
        potion.use(this)
    }
}
```

Classes Review

Ball	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	mass: Double
Behavior	use(player: Player): Unit

```
class Ball(var location: PhysicsVector,
           var dimensions: PhysicsVector,
           var velocity: PhysicsVector,
           val mass: Double) {

    def use(player: Player): Unit = {
        this.velocity = new PhysicsVector(
            player.orientation.x * player.strength,
            player.orientation.y * player.strength,
            player.strength
        )
    }
}
```

Classes Review

HealthPotion	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	volume: Int
Behavior	use(player: Player): Unit

```
class HealthPotion(var location: PhysicsVector,
                  var dimensions: PhysicsVector,
                  var velocity: PhysicsVector,
                  val volume: Int) {

  def use(player: Player): Unit = {
    player.health = (player.health + this.volume).min(player.maxHealth)
  }

}
```

Classes Review

- Use the class to create multiple objects with different states

```
var ball1: Ball = new Ball(  
    new PhysicsVector(1.0, 5.0, 2.0),  
    new PhysicsVector(1.0, 1.0, 1.0),  
    new PhysicsVector(1.0, 1.0, 10.0),  
    5.0  
)  
// ball1 stores 54224
```

```
var ball2: Ball = new Ball(  
    new PhysicsVector(6.0, -3.0, 2.0),  
    new PhysicsVector(1.0, 1.0, 1.0),  
    new PhysicsVector(0.0, 4.5, 4.5),  
    10.0  
)  
// ball2 stores 21374
```

Ball	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	mass: Double
Behavior	use(player: Player): Unit

Ball@54224		
State	location: PhysicsVector	(1.0, 5.0, 2.0)
	dimensions: PhysicsVector	(1.0, 1.0, 1.0)
	velocity: PhysicsVector	(1.0, 1.0, 10.0)
	mass: Double	5.0
Behavior	use(player: Player): Unit	

Ball@21374		
State	location: PhysicsVector	(6.0, -3.0, 2.0)
	dimensions: PhysicsVector	(1.0, 1.0, 1.0)
	velocity: PhysicsVector	(0.0, 4.5, 4.5)
	mass: Double	10.0
Behavior	use(player: Player): Unit	

Inheritance

- Use inheritance to create classes with different behavior
- Observe: Ball and HealthPotion have a lot in common

Ball	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	mass: Double
Behavior	use(player: Player): Unit

HealthPotion	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	volume: Int
Behavior	use(player: Player): Unit

Inheritance


- Can add much more common functionality (that doesn't fit on a slide)
 - Compute mass of a potion based on volume
 - Compute momentum of both types based on mass * velocity
 - Method defining behavior when either hits the ground (bounce or shatter)

Ball	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	mass: Double
Behavior	use(player: Player): Unit

HealthPotion	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	volume: Int
Behavior	use(player: Player): Unit

Inheritance

- Factor out common state and behavior into a new class
- Ball and HealthPotion classes **inherent** the state and behavior of InanimateObject
- Ball and HealthPotion add their specific state and behavior



Inheritance

- New class defines what every inheriting class must define
- Any behavior that is to be defined by inheriting classes is declared **abstract**
 - We call this an abstract class
 - Cannot create objects of abstract types
- Inheriting classes will define all abstract behavior
 - We call these concrete classes

```
abstract class InanimateObject(var location: PhysicsVector, var dimensions:  
PhysicsVector, var velocity: PhysicsVector) {  
  
    def objectMass(): Double  
  
    def use(player: Player): Unit  
  
}
```

Inheritance

- Use the extends keyword to inherit another class
- Extend the definition of InanimateObject
- We call InanimateObject the superclass of Ball

```
abstract class InanimateObject(  
    var location: PhysicsVector,  
    var dimensions: PhysicsVector,  
    var velocity: PhysicsVector) {  
  
    def objectMass(): Double  
  
    def use(player: Player): Unit  
}
```

```
class Ball(location: PhysicsVector,  
           dimensions: PhysicsVector,  
           velocity: PhysicsVector,  
           mass: Double)  
    extends InanimateObject(location, dimensions, velocity) {  
  
    override def objectMass(): Double = {  
        this.mass  
    }  
  
    override def use(player: Player): Unit = {  
        this.velocity.x = player.orientation.x * player.strength  
        this.velocity.y = player.orientation.y * player.strength  
        this.velocity.z = player.strength  
    }  
}
```

Inheritance

- Ball has it's own constructor
- Ball must call InanimateObject's constructor
- var/val declared in concrete class to make these public

```
abstract class InanimateObject(  
    var location: PhysicsVector,  
    var dimensions: PhysicsVector,  
    var velocity: PhysicsVector) {  
  
    def objectMass(): Double  
  
    def use(player: Player): Unit  
}
```

```
class Ball(location: PhysicsVector,  
           dimensions: PhysicsVector,  
           velocity: PhysicsVector,  
           mass: Double)  
    extends InanimateObject(location, dimensions, velocity) {  
  
    override def objectMass(): Double = {  
        this.mass  
    }  
  
    override def use(player: Player): Unit = {  
        this.velocity.x = player.orientation.x * player.strength  
        this.velocity.y = player.orientation.y * player.strength  
        this.velocity.z = player.strength  
    }  
}
```

Inheritance

- Implement all abstract behavior
- Use the **override** keyword when overwriting behavior from the superclass
- Override all abstract methods with behavior for this class

```
abstract class InanimateObject(  
  var location: PhysicsVector,  
  var dimensions: PhysicsVector,  
  var velocity: PhysicsVector) {  
  
  def objectMass(): Double  
  
  def use(player: Player): Unit  
  
}
```

```
class Ball(location: PhysicsVector,  
           dimensions: PhysicsVector,  
           velocity: PhysicsVector,  
           mass: Double)  
  extends InanimateObject(location, dimensions, velocity) {  
  
  override def objectMass(): Double = {  
    this.mass  
  }  
  
  override def use(player: Player): Unit = {  
    this.velocity.x = player.orientation.x * player.strength  
    this.velocity.y = player.orientation.y * player.strength  
    this.velocity.z = player.strength  
  }  
  
}
```

Inheritance

- Define different behavior for each base class
- Define similar types with some difference

```
abstract class InanimateObject(  
    var location: PhysicsVector,  
    var dimensions: PhysicsVector,  
    var velocity: PhysicsVector) {  
  
    def objectMass(): Double  
  
    def use(player: Player): Unit  
  
}
```

```
class HealthPotion(location: PhysicsVector,  
    dimensions: PhysicsVector,  
    velocity: PhysicsVector,  
    val volume: Int)  
    extends InanimateObject(location, dimensions,  
velocity) {  
  
    override def objectMass(): Double = {  
        val massPerVolume: Double = 7.0  
        volume * massPerVolume  
    }  
    override def use(player: Player): Unit = {  
        player.health = (player.health +  
            this.volume).min(player.maxHealth)  
    }  
}
```

```
class Ball(location: PhysicsVector,  
    dimensions: PhysicsVector,  
    velocity: PhysicsVector,  
    mass: Double)  
    extends InanimateObject(location, dimensions,  
velocity) {  
  
    override def objectMass(): Double = {  
        this.mass  
    }  
  
    override def use(player: Player): Unit = {  
        this.velocity.x = player.orientation.x *  
player.strength  
        this.velocity.y = player.orientation.y *  
player.strength  
        this.velocity.z = player.strength  
    }  
}
```

Inheritance

- OK, BUT WHY?
- Add behavior to InanimateObject
- Behavior is added to ALL inheriting classes

```
abstract class InanimateObject(var location: PhysicsVector, var dimensions: PhysicsVector,
var velocity: PhysicsVector) {

    def objectMass(): Double

    def use(player: Player): Unit

    def magnitudeOfMomentum(): Unit = {
        val magnitudeOfVelocity = Math.sqrt(
            Math.pow(this.velocity.x, 2.0) +
            Math.pow(this.velocity.y, 2.0) +
            Math.pow(this.velocity.z, 2.0)
        )
        magnitudeOfVelocity * this.objectMass()
    }
}
```

Inheritance

- We may want many, many more subtypes of InanimateObjects in our game
- Any common functionality added to InanimateObject
 - Easy to add functionality to ALL subtypes with very little effort

```
abstract class InanimateObject(var location: PhysicsVector, var dimensions: PhysicsVector,
var velocity: PhysicsVector) {

    def objectMass(): Double

    def use(player: Player): Unit

    def magnitudeOfMomentum(): Unit = {
        val magnitudeOfVelocity = Math.sqrt(
            Math.pow(this.velocity.x, 2.0) +
            Math.pow(this.velocity.y, 2.0) +
            Math.pow(this.velocity.z, 2.0)
        )
        magnitudeOfVelocity * this.objectMass()
    }
}
```


Inheritance

- **But wait!**
- **There's more**

```
abstract class InanimateObject(location: PhysicsVector, dimensions: PhysicsVector,
inputVelocity: PhysicsVector) extends DynamicObject(location, dimensions) {

  this.velocity = inputVelocity

  def objectMass(): Double

  def use(player: Player): Unit

  def magnitudeOfMomentum(): Unit = {
    val magnitudeOfVelocity = Math.sqrt(
      Math.pow(this.velocity.x, 2.0) +
      Math.pow(this.velocity.y, 2.0) +
      Math.pow(this.velocity.z, 2.0)
    )
    magnitudeOfVelocity * this.objectMass()
  }
}
```

Inheritance

- If we want Ball, HealthPotion, and all other InanimateObjects to work with our physics engine
 - Extend DynamicObject!

```
abstract class InanimateObject(location: PhysicsVector, dimensions: PhysicsVector,
inputVelocity: PhysicsVector) extends DynamicObject(location, dimensions) {

  this.velocity = inputVelocity

  def objectMass(): Double

  def use(player: Player): Unit

  def magnitudeOfMomentum(): Unit = {
    val magnitudeOfVelocity = Math.sqrt(
      Math.pow(this.velocity.x, 2.0) +
      Math.pow(this.velocity.y, 2.0) +
      Math.pow(this.velocity.z, 2.0)
    )
    magnitudeOfVelocity * this.objectMass()
  }
}
```

Inheritance

- Note that the velocity is inherited
- The velocity parameter in the constructor must have a different name than the inherited variable
 - Allows us to assign its value to the state variable
 - They would both be referred to with **this** causing a name conflict
- No name conflict with multiple location/dimension since they are only in the header

```
abstract class InanimateObject(location: PhysicsVector, dimensions: PhysicsVector,
inputVelocity: PhysicsVector) extends DynamicObject(location, dimensions) {


    this.velocity = inputVelocity

    def objectMass(): Double


    def use(player: Player): Unit

    def magnitudeOfMomentum(): Unit = {
        val magnitudeOfVelocity = Math.sqrt(
            Math.pow(this.velocity.x, 2.0) +
            Math.pow(this.velocity.y, 2.0) +
            Math.pow(this.velocity.z, 2.0)
        )
        magnitudeOfVelocity * this.objectMass()
    }
}
```

Inheritance




Scala Type Hierarchy



- All objects share **Any** as their base types
- Classes extending **AnyVal** will be stored on the **stack**
- Classes extending **AnyRef** will be stored on the **heap**

Scala Type Hierarchy



- Classes you define extend `AnyRef` by default
- `HealthPotion` has 6 different types

```
val potion1: HealthPotion = new HealthPotion(new PhysicsVector(), new PhysicsVector(), new PhysicsVector(), 6)
val potion2: InanimateObject = new HealthPotion(new PhysicsVector(), new PhysicsVector(), new PhysicsVector(), 6)
val potion3: DynamicObject = new HealthPotion(new PhysicsVector(), new PhysicsVector(), new PhysicsVector(), 6)
val potion4: GameObject = new HealthPotion(new PhysicsVector(), new PhysicsVector(), new PhysicsVector(), 6)
val potion5: AnyRef = new HealthPotion(new PhysicsVector(), new PhysicsVector(), new PhysicsVector(), 6)
val potion6: Any = new HealthPotion(new PhysicsVector(), new PhysicsVector(), new PhysicsVector(), 6)
```

Lecture Question

Question: in a package named "oop.electronics", implement the following. This functionality is the same as the last lecture question, but we will use inheritance to prevent duplicating code.

- class Battery with
 - A constructor that takes a variable named "charge" of type Int
- abstract class Electronic with
 - A constructor that takes no parameters
 - A state variable named "battery" of type Battery
 - A method named "use" that takes no parameters and returns Unit (This can be abstract)
 - A method named "replaceBattery" that takes a Battery as a parameter and returns a Battery
 - This method swaps the input Battery with the Battery currently stored in this Electronic's state variable
 - The returned Battery is the one that was in the state variable when the method is called
- class BoomBox that extends Electronic
 - A constructor that takes a variable of type Battery and assigned it to the inherited state variable named "battery"
 - Your constructor parameter should have a different name than the state variable
 - Override the "use" method to reduce the charge of the battery in the state variable by 3 if its charge is 3 or greater
- class FlashLight that extends Electronic
 - A constructor that takes no parameters
 - When a new FlashLight is created, assign the inherited state variable named "battery" to a new Battery with 5 charge (ie. Batteries included)
 - Override the "use" method to reduce the charge of the battery in the state variable by 1 if its charge is 1 or greater

Lecture Question

This question will be checked with the same tests as the previous question except

The code is in a different package so it doesn't interfere with your code from the previous question. Be sure you check that this import works from a different package in your project

```
import oop.electronics.{Battery, BoomBox, FlashLight, Electronic}
```

Your FlashLight and BoomBox classes must inherit Electronic. This will be checked by storing them in variables of type Electronic

```
val flashlight1: Electronic = new FlashLight()  
val boomBox1: Electronic = new BoomBox(new Battery(10))
```

 I just noticed that I put a capital L in flashlight. I'll leave it for consistency, but I am so sorry if this caused you frustration.