

Unit Testing

Lecture Task

- Add testing to lecture tasks 1, 2, and 3 -

Testing: In the tests package, complete the test suite named LectureTask1 to test the functionality of Lecture Task 1.

Testing: In the tests package, complete the test suite named LectureTask2 to test the functionality of Lecture Task 2.

Testing: In the tests package, complete the test suite named LectureTask3 to test the functionality of Lecture Task 3.

Testing

- How do you know if your code is correct?
- Submit to AutoLab?
 - Does not exist outside of class
 - Does not exist for your project

Recall

```
package example
```

```
object Conditional {
```

```
  def computeSize(input: Double): String = {  
    val large: Double = 60.0  
    val medium: Double = 30.0  
    if (input >= large) {  
      "large"  
    } else if (input >= medium) {  
      "medium"  
    } else {  
      "small"  
    }  
  }  
}
```

- How do we test this function to verify that it's correct?

Recall

```
package example
```

```
object Conditional {
```

```
  def computeSize(input: Double): String = {  
    val large: Double = 60.0  
    val medium: Double = 30.0  
    if (input >= large) {  
      "large"  
    } else if (input >= medium) {  
      "medium"  
    } else {  
      "small"  
    }  
  }  
}
```

```
  def main(args: Array[String]): Unit = {  
    println(computeSize(70.0))  
    println(computeSize(50.0))  
    println(computeSize(10.0))  
  }  
}
```

```
}
```

- Call the method from main
- Print the results
- Manually verify

What About Large Projects?

- There may be 100's of files and 1000's of methods
 - Any change in a function might break any code that calls that function
 - Will you manually verify all that code for each change?
-
- Unit Testing
 - Automate testing
 - Provide structure to testing

Unit Testing

- Run a series of tests on your code
- If the code is correct, all tests should pass
- If the code is incorrect, at least one test should fail
- A set of tests should test every possible error that could occur

Scala Unit Testing

```
package tests
```

```
import org.scalatest._  
import example.Conditional
```

```
class TestComputeSize extends FunSuite {  
  
  test("Doubles are checked for size in each category") {  
    val largeDouble: Double = 70.0  
    val mediumDouble: Double = 50.0  
    val smallDouble: Double = 10.0  
  
    assert(Conditional.computeSize(largeDouble) == "large", largeDouble)  
    assert(Conditional.computeSize(mediumDouble) == "medium", mediumDouble)  
    assert(Conditional.computeSize(smallDouble) == "small", smallDouble)  
  }  
}
```

Use Maven to download scalatest (see pom.xml on the course website)

Click Maven in the IntelliJ sidebar to interact with pom.xml

Scala Unit Testing

```
package tests
```

```
import org.scalatest._  
import example.Conditional
```

```
class TestComputeSize extends FunSuite {  
  
  test("Doubles are checked for size in each category") {  
    val largeDouble: Double = 70.0  
    val mediumDouble: Double = 50.0  
    val smallDouble: Double = 10.0  
  
    assert(Conditional.computeSize(largeDouble) == "large", largeDouble)  
    assert(Conditional.computeSize(mediumDouble) == "medium", mediumDouble)  
    assert(Conditional.computeSize(smallDouble) == "small", smallDouble)  
  }  
}
```

Import everything from the org.scalatest package

_ is a Scala wildcard

Scala Unit Testing

```
package tests
```

```
import org.scalatest._  
import example.Conditional
```

```
class TestComputeSize extends FunSuite {  
  
  test("Doubles are checked for size in each category") {  
    val largeDouble: Double = 70.0  
    val mediumDouble: Double = 50.0  
    val smallDouble: Double = 10.0  
  
    assert(Conditional.computeSize(largeDouble) == "large", largeDouble)  
    assert(Conditional.computeSize(mediumDouble) == "medium", mediumDouble)  
    assert(Conditional.computeSize(smallDouble) == "small", smallDouble)  
  }  
}
```

Create a new class of type FunSuite (Function Suite)

*More detail on this syntax throughout LO2. This is inheritance

Scala Unit Testing

```
package tests
```

```
import org.scalatest._  
import example.Conditional
```

```
class TestComputeSize extends FunSuite {
```

```
  test("Doubles are checked for size in each category") {  
    val largeDouble: Double = 70.0  
    val mediumDouble: Double = 50.0  
    val smallDouble: Double = 10.0  
  
    assert(Conditional.computeSize(largeDouble) == "large", largeDouble)  
    assert(Conditional.computeSize(mediumDouble) == "medium", mediumDouble)  
    assert(Conditional.computeSize(smallDouble) == "small", smallDouble)  
  }
```

```
}
```

Create a new test that will be executed when this file is ran

No main method

A main method is inherited from FunSuite

Scala Unit Testing

```
package tests
```

```
import org.scalatest._  
import example.Conditional
```

```
class TestComputeSize extends FunSuite {
```

```
  test("Doubles are checked for size in each category") {  
    val largeDouble: Double = 70.0  
    val mediumDouble: Double = 50.0  
    val smallDouble: Double = 10.0
```

```
    assert(Conditional.computeSize(largeDouble) == "large", largeDouble)  
    assert(Conditional.computeSize(mediumDouble) == "medium", mediumDouble)  
    assert(Conditional.computeSize(smallDouble) == "small", smallDouble)
```

```
  }
```

```
}
```

Call assert to test values

First argument is a boolean that must be true for the test to pass

-Should return false if the code is not correct

Second argument is optional. Is printed if the test fails

Testing Demo

Scala Unit Testing

```
package tests
```

```
import org.scalatest._  
import example.Conditional
```

```
class TestComputeSize extends FunSuite {  
  
  test("Doubles are checked for size in each category") {  
    val largeDouble: Double = 70.0  
    val mediumDouble: Double = 50.0  
    val smallDouble: Double = 10.0  
  
    assert(Conditional.computeSize(largeDouble) == "large", largeDouble)  
    assert(Conditional.computeSize(mediumDouble) == "medium", mediumDouble)  
    assert(Conditional.computeSize(smallDouble) == "small", smallDouble)  
  }  
}
```

This class tests if the inputs 70.0, 50.0, and 10.0 return "large", "medium", and "small" respectively

Is this enough testing?

Correct Solution

```
package example
```

```
object Conditional {
```

```
  def computeSize(input: Double): String = {
```

```
    val large: Double = 60.0
```

```
    val medium: Double = 30.0
```

```
    if (input >= large) {
```

```
      "large"
```

```
    } else if (input >= medium) {
```

```
      "medium"
```

```
    } else {
```

```
      "small"
```

```
    }
```

```
  }
```

```
}
```

Incorrect Solution

-Passes the tests-

```
package example
```

```
object Conditional {
```

```
  def computeSize(input: Double): String = {  
    val large: Double = 65.0  
    val medium: Double = 20.0  
    if (input >= large) {  
      "large"  
    } else if (input >= medium) {  
      "medium"  
    } else {  
      "small"  
    }  
  }  
}
```


Scala Unit Testing

```
package tests

import org.scalatest._
import example.Conditional

class TestComputeSize extends FunSuite {

  test("Size boundaries are checked"){
    val largeDouble: Double = 60.0
    val mediumDoubleUpperBound: Double = 59.99
    val mediumDoubleLowerBound: Double = 30.0
    val smallDouble: Double = 29.99

    assert(Conditional.computeSize(largeDouble) == "large", largeDouble)
    assert(Conditional.computeSize(mediumDoubleUpperBound) == "medium", mediumDoubleUpperBound)
    assert(Conditional.computeSize(mediumDoubleLowerBound) == "medium", mediumDoubleLowerBound)
    assert(Conditional.computeSize(smallDouble) == "small", smallDouble)
  }
}
```

Check the boundaries for more accurate testing

Is this enough testing?

Scala Unit Testing

```
package tests

import org.scalatest._
import example.Conditional

class TestComputeSize extends FunSuite {

  test("Size boundaries are checked"){
    val largeDouble: Double = 60.0
    val mediumDoubleUpperBound: Double = 59.99
    val mediumDoubleLowerBound: Double = 30.0
    val smallDouble: Double = 29.99

    assert(Conditional.computeSize(largeDouble) == "large", largeDouble)
    assert(Conditional.computeSize(mediumDoubleUpperBound) == "medium", mediumDoubleUpperBound)
    assert(Conditional.computeSize(mediumDoubleLowerBound) == "medium", mediumDoubleLowerBound)
    assert(Conditional.computeSize(smallDouble) == "small", smallDouble)
  }
}
```

Check the boundaries for more accurate testing

Is this enough testing?

We could reasonable stop here.. but we could do more thorough testing

Scala Unit Testing

```
package tests

import org.scalatest._
import example.Conditional

class TestComputeSize extends FunSuite {

  test("Use many test cases for each category"){
    // notice largeDoubles must be declared with var we change its value
    var largeDoubles: List[Double] = List(60.0, 60.01, 70.0, 90.0, 1000.0)
    val mediumDoubles: List[Double] = List(59.9, 30.0, 30.01, 40.0, 50.0)
    val smallDoubles: List[Double] = List(29.99, 20.0, 10.0, 0.0, -100.0, -10000.0)

    largeDoubles = largeDoubles :+ 10000.0 // Example of adding an element to a List


    for(largeDouble <- largeDoubles){
      assert(Conditional.computeSize(largeDouble) == "large", largeDouble)
    }
    for(mediumDouble <- mediumDoubles){
      assert(Conditional.computeSize(mediumDouble) == "medium", mediumDouble)
    }
    for(smallDouble <- smallDoubles){
      assert(Conditional.computeSize(smallDouble) == "small", smallDouble)
    }
  }
}
```

Use data structures to run many test cases

Testing Doubles

Double

- Number with a whole number and a decimal portion
- 64 bit representation
- Values are truncated to fit in 64 bits
- Loss of precision!




https://en.wikipedia.org/wiki/Double-precision_floating-point_format

Double


- Checking for equality with Doubles
- Allow a small amount of tolerance when comparing two doubles
- `Math.abs(x - y) < small_value`
 - As long as x and y are within a small value of each other this will be true

```
val b: Double = 0.1
val c: Double = b * 3
val expected: Double = 0.3
println(c == expected)
```



false

```
val epsilon: Double = 0.00000001
val b: Double = 0.1
val c: Double = b * 3
val expected: Double = 0.3
println(Math.abs(c - 0.3) < epsilon)
```



true

Unit Testing Tasks

- Most/all tasks will require thorough testing
- When these tasks are graded, your test suite is ran:
 - Against your solution
 - Against a correct solution stored on the server
 - Against a variety of incorrect solutions stored on the server
- Your test suite should pass both your solution and the correct solution
- Your test suite should fail on all the incorrect solutions

Old Lecture Task

Method: In a package named "lecture" create an object named "FirstObject" with a method named "computeShippingCost" that takes a Double representing the weight of a package as a parameter and returns a Double representing the shipping cost of the package

The shipping cost is (\$) $5 + 0.25$ for each pound over 30

Unit Testing: In a package named "tests" create a class/file named "UnitTesting" as a test suite that tests the computeShippingCost method

rounding_weight

```
def computeShippingCost(weight: Double): Double = {  
  if (weight < 3.0) {  
    5.0  
  } else {  
    5.0 + (Math.round(weight) - 30.0) * 0.25  
  }  
}
```

always_over_thirty

```
def computeShippingCost(weight: Double): Double = {  
  5.0 + (weight - 30.0) * 0.25  
}
```

boundary_overweight

```
def computeShippingCost(weight: Double): Double = {  
  if (weight < 33.0) {  
    5.0  
  } else {  
    5.0 + (weight - 33.0) * 0.25  
  }  
}
```

light_employee_discount

```
def computeShippingCost(weight: Double): Double = {  
  if (weight < 30.0) {  
    4.0  
  } else {  
    5.0 + (weight - 30.0) * 0.25  
  }  
}
```

always_under_thirty

```
def computeShippingCost(weight: Double): Double = {  
  5.0  
}
```

Examples in IntelliJ

Lecture Task

- Add testing to lecture tasks 1, 2, and 3 -

Testing: In the tests package, complete the test suite named LectureTask1 to test the functionality of Lecture Task 1.

Testing: In the tests package, complete the test suite named LectureTask2 to test the functionality of Lecture Task 2.

Testing: In the tests package, complete the test suite named LectureTask3 to test the functionality of Lecture Task 3.