

Inheritance

Lecture Question

Objective: Study the syntax of inheritance in Scala

Question: [Scala] In a package named "inheritance" create an abstract class named "Animal" and concrete classes named "Cat" and "Dog". Implement the following in each class:

Animal:

- A constructor that takes a String called name (Do not use either val or var. It will be declared with val in the concrete classes)
- An abstract method named sound that takes no parameters and returns a String

Cat:

- Inherent Animal
- A constructor that take a String called name as a value (use **val** to declare name to make it accessible from outside this class)
- Override sound() to return "meow"

Dog:

- Inherent Animal
- A constructor that take a String called name as a value (use **val** to declare name to make it accessible from outside this class)
- Override sound() to return "woof"

Index	Value
81078	
81079	
81080	
81081	
81082	
81083	
81084	
81085	

Index	Value
42976	
42977	
42978	

Index	Value
27177	
27178	
27179	

Index	Value
59683	
59684	
59685	

```
def main(args: Array[String]): Unit = {
  val bird: Bird = new Bird()
  var action: String = "Nothing"
  if(bird.inDanger()){
    val action: String = "Panic!"
  }else{
    val action: String = "Check bird"
  }
  println(action)
  val box: Box = new Box(bird, new Bird())
  if(box.inDanger()){
    action = "Stay in the boat"
  }
  println(action)
}
```




- Sample Quiz question:
 - Draw the stack and heap memory when execution is at the green arrow

```
class Bird {
  val timesHelpful: Int = 0
  var timesChecked: Int = 0

  def inDanger(): Boolean = {
    timesChecked += 1
    true
  }
}
```

```
class Box(val bird1: Bird, val bird2: Bird) {
  def inDanger(): Boolean = {
    bird1.inDanger() || bird2.inDanger()
  }
}
```

Scala Type Hierarchy



- All objects share **Any** as their base types
- Classes extending **AnyVal** will be stored on the **stack**
- Classes extending **AnyRef** will be stored on the **heap**

Overview

- Let's do some world building
- If we're making a game (we're making a game) we'll want various objects that will interact with each other
- We'll setup a simple game where
 - Each player has a set health and strength
 - Players can pick up and throw balls
 - If a player gets hit with a ball, they lose health
 - Players can collect health potions to regain health
- Note: We might not build this full game, but we will build some of the game mechanics

Objects Review

- We'll need different objects for this game
 - Player
 - Ball
 - HealthPotion

Objects Review

Player		
State	location: PhysicsVector	(2.0, -2.0, 2.0)
	dimensions: PhysicsVector	(1.0, 1.0, 2.0)
	velocity: PhysicsVector	(0.0, -1.0, 0.0)
	orientation: PhysicsVector	(0.5, -0.5, 0.0)
	health: Int	17
	maxHealth: Int	20
	strength: Int	25
Behavior	useBall(ball: Ball): Unit	
	useHealthPotion(potion: HealthPotion): Unit	

```
object Player {  
  var location: PhysicsVector = new PhysicsVector(2.0, -2.0, 2.0)  
  var dimensions: PhysicsVector = new PhysicsVector(1.0, 1.0, 2.0)  
  var velocity: PhysicsVector = new PhysicsVector(0.0, -1.0, 0.0)  
  var orientation: PhysicsVector = new PhysicsVector(0.5, -0.5, 0.0)  
  
  val maxHealth: Int = 20  
  val strength: Int = 25  
  
  var health: Int = 17  
  
  def useBall(ball: Ball): Unit = {  
    ball.use(this)  
  }  
  
  def useHealthPotion(potion: HealthPotion): Unit = {  
    potion.use(this)  
  }  
}
```

Objects Review

Ball		
State	location: PhysicsVector	(1.0, 5.0, 2.0)
	dimensions: PhysicsVector	(1.0, 1.0, 1.0)
	velocity: PhysicsVector	(1.0, 1.0, 10.0)
	mass: Double	5.0
Behavior	used(player: Player): Unit	

```
object Ball {  
  var location: PhysicsVector = new PhysicsVector(1.0, 5.0, 2.0)  
  var dimensions: PhysicsVector = new PhysicsVector(1.0, 1.0, 1.0)  
  var velocity: PhysicsVector = new PhysicsVector(1.0, 1.0, 10.0)  
  val mass: Double = 5.0  
  
  def use(player: Player): Unit = {  
    this.velocity = new PhysicsVector(  
      player.orientation.x * player.strength,  
      player.orientation.y * player.strength,  
      player.strength  
    )  
  }  
}
```


Objects Review

HealthPotion		
State	location: PhysicsVector	(5.0, 7.0, 0.0)
	dimensions: PhysicsVector	(1.0, 1.0, 1.0)
	velocity: PhysicsVector	(0.0, 0.0, 0.0)
	volume: Int	3
Behavior	use(player: Player): Unit	

```
object HealthPotion {  
  var location: PhysicsVector = new PhysicsVector(5.0, 7.0, 0.0)  
  var dimensions: PhysicsVector = new PhysicsVector(1.0, 1.0, 1.0)  
  var velocity: PhysicsVector = new PhysicsVector(0.0, 0.0, 0.0)  
  val volume: Int = 3  
  
  def use(player: Player): Unit = {  
    player.health = (player.health + this.volume).min(player.maxHealth)  
  }  
}
```

Objects Review

- But this is restrictive
- Game can only have one Ball, one HealthPotion, and on Player
- Can play, but not very fun

Player		
State	location: PhysicsVector	(2.0, -2.0, 2.0)
	dimensions: PhysicsVector	(1.0, 1.0, 2.0)
	velocity: PhysicsVector	(0.0, -1.0, 0.0)
	orientation: PhysicsVector	(0.5, -0.5, 0.0)
	health: Int	17
	maxHealth: Int	20
	strength: Int	25
Behavior	useBall(ball: Ball): Unit	
	useHealthPotion(potion: HealthPotion): Unit	

Ball		
State	location: PhysicsVector	(1.0, 5.0, 2.0)
	dimensions: PhysicsVector	(1.0, 1.0, 1.0)
	velocity: PhysicsVector	(1.0, 1.0, 10.0)
	mass: Double	5.0
Behavior	used(player: Player): Unit	

HealthPotion		
State	location: PhysicsVector	(5.0, 7.0, 0.0)
	dimensions: PhysicsVector	(1.0, 1.0, 1.0)
	velocity: PhysicsVector	(0.0, 0.0, 0.0)
	volume: Int	3
Behavior	use(player: Player): Unit	

Classes Review

- This is why we use classes
- Classes let us create multiple objects of type Ball, HealthPotion, and Player

Player	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	orientation: PhysicsVector
	health: Int
	maxHealth: Int
	strength: Int
Behavior	useBall(ball: Ball): Unit
	useHealthPotion(potion: HealthPotion): Unit

Ball	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	mass: Double
Behavior	use(player: Player): Unit

HealthPotion	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	volume: Int
Behavior	use(player: Player): Unit

Classes Review

Player	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	orientation: PhysicsVector
	health: Int
	maxHealth: Int
	strength: Int
Behavior	useBall(ball: Ball): Unit
	useHealthPotion(potion: HealthPotion): Unit

```
class Player(var location: PhysicsVector,
             var dimensions: PhysicsVector,
             var velocity: PhysicsVector,
             var orientation: PhysicsVector,
             val maxHealth: Int,
             val strength: Int) {

    var health: Int = maxHealth

    def useBall(ball: Ball): Unit = {
        ball.use(this)
    }

    def useHealthPotion(potion: HealthPotion): Unit = {
        potion.use(this)
    }
}
```

Classes Review

Ball	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	mass: Double
Behavior	use(player: Player): Unit

```
class Ball(var location: PhysicsVector,
           var dimensions: PhysicsVector,
           var velocity: PhysicsVector,
           val mass: Double) {

    def use(player: Player): Unit = {
        this.velocity = new PhysicsVector(
            player.orientation.x * player.strength,
            player.orientation.y * player.strength,
            player.strength
        )
    }
}
```

Classes Review

HealthPotion	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	volume: Int
Behavior	use(player: Player): Unit

```
class HealthPotion(var location: PhysicsVector,
                  var dimensions: PhysicsVector,
                  var velocity: PhysicsVector,
                  val volume: Int) {

  def use(player: Player): Unit = {
    player.health = (player.health + this.volume).min(player.maxHealth)
  }

}
```

Classes Review

- Use the class to create multiple objects with different states

```
var ball1: Ball = new Ball(  
    new PhysicsVector(1.0, 5.0, 2.0),  
    new PhysicsVector(1.0, 1.0, 1.0),  
    new PhysicsVector(1.0, 1.0, 10.0),  
    5.0  
)  
// ball1 stores 54224
```

```
var ball2: Ball = new Ball(  
    new PhysicsVector(6.0, -3.0, 2.0),  
    new PhysicsVector(1.0, 1.0, 1.0),  
    new PhysicsVector(0.0, 4.5, 4.5),  
    10.0  
)  
// ball2 stores 21374
```

Ball	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	mass: Double
Behavior	use(player: Player): Unit

Ball@54224		
State	location: PhysicsVector	(1.0, 5.0, 2.0)
	dimensions: PhysicsVector	(1.0, 1.0, 1.0)
	velocity: PhysicsVector	(1.0, 1.0, 10.0)
	mass: Double	5.0
Behavior	use(player: Player): Unit	

Ball@21374		
State	location: PhysicsVector	(6.0, -3.0, 2.0)
	dimensions: PhysicsVector	(1.0, 1.0, 1.0)
	velocity: PhysicsVector	(0.0, 4.5, 4.5)
	mass: Double	10.0
Behavior	use(player: Player): Unit	

Inheritance

- Use inheritance to create classes with different behavior
- Observe: Ball and HealthPotion have a lot in common

Ball	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	mass: Double
Behavior	use(player: Player): Unit

HealthPotion	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	volume: Int
Behavior	use(player: Player): Unit

Inheritance


- Can add much more common functionality (that doesn't fit on a slide)
 - Compute mass of a potion based on volume
 - Compute momentum of both types based on mass * velocity
 - Method defining behavior when either hits the ground (bounce or shatter)

Ball	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	mass: Double
Behavior	use(player: Player): Unit

HealthPotion	
State	location: PhysicsVector
	dimensions: PhysicsVector
	velocity: PhysicsVector
	volume: Int
Behavior	use(player: Player): Unit

Inheritance

- Factor out common state and behavior into a new class
- Ball and HealthPotion classes **inherent** the state and behavior of InanimateObject
- Ball and HealthPotion add their specific state and behavior



Inheritance

- New class defines what every inheriting class must define
- Any behavior that is to be defined by inheriting classes is declared **abstract**
 - We call this an abstract class
 - Cannot create objects of abstract types
- Inheriting classes will define all abstract behavior
 - We call these concrete classes

```
abstract class InanimateObject(location: PhysicsVector, dimensions: PhysicsVector,  
velocity: PhysicsVector) {  
  
    def objectMass(): Double  
  
    def use(player: Player): Unit  
  
}
```

Inheritance

- Use the extends keyword to inherit another class
- Extend the definition of InanimateObject
- We call InanimateObject the superclass of Ball

```
abstract class InanimateObject(  
    location: PhysicsVector,  
    dimensions: PhysicsVector,  
    velocity: PhysicsVector) {  
  
    def objectMass(): Double  
  
    def use(player: Player): Unit  
}
```

```
class Ball(var location: PhysicsVector,  
          var dimensions: PhysicsVector,  
          var velocity: PhysicsVector,  
          val mass: Double)  
    extends InanimateObject(location, dimensions, velocity) {  
  
    override def objectMass(): Double = {  
        0.0  
    }  
  
    override def use(player: Player): Unit = {  
        this.velocity.x = player.orientation.x * player.strength  
        this.velocity.y = player.orientation.y * player.strength  
        this.velocity.z = player.strength  
    }  
}
```

Inheritance

- Ball has it's own constructor
- Ball must call InanimateObject's constructor
- var/val declared in concrete class to make these public

```
abstract class InanimateObject(  
    location: PhysicsVector,  
    dimensions: PhysicsVector,  
    velocity: PhysicsVector) {  
  
    def objectMass(): Double  
  
    def use(player: Player): Unit  
}
```

```
class Ball(var location: PhysicsVector,  
          var dimensions: PhysicsVector,  
          var velocity: PhysicsVector,  
          val mass: Double)  
    extends InanimateObject(location, dimensions, velocity) {  
  
    override def objectMass(): Double = {  
        0.0  
    }  
  
    override def use(player: Player): Unit = {  
        this.velocity.x = player.orientation.x * player.strength  
        this.velocity.y = player.orientation.y * player.strength  
        this.velocity.z = player.strength  
    }  
}
```

Inheritance

- Implement all abstract behavior
- Use the **override** keyword when overwriting behavior from the superclass
- Override all abstract methods with behavior for this class

```
abstract class InanimateObject(  
    location: PhysicsVector,  
    dimensions: PhysicsVector,  
    velocity: PhysicsVector) {  
  
    def objectMass(): Double  
  
    def use(player: Player): Unit  
  
}
```

```
class Ball(var location: PhysicsVector,  
           var dimensions: PhysicsVector,  
           var velocity: PhysicsVector,  
           val mass: Double)  
    extends InanimateObject(location, dimensions, velocity) {  
  
    override def objectMass(): Double = {  
        0.0  
    }  
  
    override def use(player: Player): Unit = {  
        this.velocity.x = player.orientation.x * player.strength  
        this.velocity.y = player.orientation.y * player.strength  
        this.velocity.z = player.strength  
    }  
  
}
```

Inheritance

- Define different behavior for each base class
- Define similar types with some difference

```
abstract class InanimateObject(
    location: PhysicsVector,
    dimensions: PhysicsVector,
    velocity: PhysicsVector) {

    def objectMass(): Double

    def use(player: Player): Unit
}
```

```
class HealthPotion(var location: PhysicsVector,
                  var dimensions: PhysicsVector,
                  var velocity: PhysicsVector,
                  val volume: Int)
    extends InanimateObject(location, dimensions,
    velocity) {

    override def objectMass(): Double = {
        val massPerVolume: Double = 7.0
        volume * massPerVolume
    }

    def use(player: Player): Unit = {
        player.health = (player.health +
            this.volume).min(player.maxHealth)
    }
}
```

```
class Ball(var location: PhysicsVector,
           var dimensions: PhysicsVector,
           var velocity: PhysicsVector,
           val mass: Double)
    extends InanimateObject(location, dimensions,
    velocity) {

    override def objectMass(): Double = {
        0.0
    }

    override def use(player: Player): Unit = {
        this.velocity.x = player.orientation.x *
        player.strength
        this.velocity.y = player.orientation.y *
        player.strength
        this.velocity.z = player.strength
    }
}
```

Inheritance

- OK, BUT WHY?
- Add behavior to InanimateObject
- Behavior is added to ALL inheriting classes

```
abstract class InanimateObject(location: PhysicsVector, dimensions: PhysicsVector,
velocity: PhysicsVector) {

    def objectMass(): Double

    def use(player: Player): Unit

    def magnitudeOfMomentum(): Unit = {
        val magnitudeOfVelocity = Math.sqrt(
            Math.pow(this.velocity.x, 2.0) +
            Math.pow(this.velocity.y, 2.0) +
            Math.pow(this.velocity.z, 2.0)
        )
        magnitudeOfVelocity * this.objectMass()
    }
}
```


Inheritance

- We may want many, many more subtypes of InanimateObjects in our game
- Any common functionality added to InanimateObject
 - Easy to add functionality to ALL subtypes with very little effort

```
abstract class InanimateObject(location: PhysicsVector, dimensions: PhysicsVector,
velocity: PhysicsVector) {

    def objectMass(): Double

    def use(player: Player): Unit

    def magnitudeOfMomentum(): Unit = {
        val magnitudeOfVelocity = Math.sqrt(
            Math.pow(this.velocity.x, 2.0) +
            Math.pow(this.velocity.y, 2.0) +
            Math.pow(this.velocity.z, 2.0)
        )
        magnitudeOfVelocity * this.objectMass()
    }
}
```

Inheritance

- **But wait!**
- **There's more**

```
abstract class InanimateObject(location: PhysicsVector, dimensions: PhysicsVector,
velocity: PhysicsVector) extends DynamicObject(location, dimensions) {

    super.velocity = velocity

    def objectMass(): Double

    def use(player: Player): Unit

    def magnitudeOfMomentum(): Unit = {
        val magnitudeOfVelocity = Math.sqrt(
            Math.pow(this.velocity.x, 2.0) +
            Math.pow(this.velocity.y, 2.0) +
            Math.pow(this.velocity.z, 2.0)
        )
        magnitudeOfVelocity * this.objectMass()
    }
}
```

Inheritance

- If we want Ball, HealthPotion, and all other InanimateObjects to work with our physics engine
 - Extend DynamicObject!

```
abstract class InanimateObject(location: PhysicsVector, dimensions: PhysicsVector,
velocity: PhysicsVector) extends DynamicObject(location, dimensions) {


    super.velocity = velocity

    def objectMass(): Double


    def use(player: Player): Unit

    def magnitudeOfMomentum(): Unit = {
        val magnitudeOfVelocity = Math.sqrt(
            Math.pow(this.velocity.x, 2.0) +
            Math.pow(this.velocity.y, 2.0) +
            Math.pow(this.velocity.z, 2.0)
        )
        magnitudeOfVelocity * this.objectMass()
    }
}
```

Inheritance




Scala Type Hierarchy



- All objects share **Any** as their base types
- Classes extending **AnyVal** will be stored on the **stack**
- Classes extending **AnyRef** will be stored on the **heap**

Scala Type Hierarchy



- Classes you define extend `AnyRef` by default
- `HealthPotion` has 5 different types

```
val potion1: HealthPotion = new HealthPotion(new PhysicsVector(), new PhysicsVector(), new PhysicsVector(), 6)
val potion2: DynamicObject = new HealthPotion(new PhysicsVector(), new PhysicsVector(), new PhysicsVector(), 6)
val potion3: PhysicalObject = new HealthPotion(new PhysicsVector(), new PhysicsVector(), new PhysicsVector(), 6)
val potion4: AnyRef = new HealthPotion(new PhysicsVector(), new PhysicsVector(), new PhysicsVector(), 6)
val potion5: Any = new HealthPotion(new PhysicsVector(), new PhysicsVector(), new PhysicsVector(), 6)
```

Lecture Question

Objective: Study the syntax of inheritance in Scala

Question: [Scala] In a package named "inheritance" create an abstract class named "Animal" and concrete classes named "Cat" and "Dog". Implement the following in each class:

Animal:

- A constructor that takes a String called name (Do not use either val or var. It will be declared in the concrete classes)
- An abstract method named sound that takes no parameters and returns a String

Cat:

- Inherent Animal
- A constructor that take a String called name as a value (use **val** to declare name to make it accessible from outside this class)
- Override sound() to return "meow"

Dog:

- Inherent Animal
- A constructor that take a String called name as a value (use **val** to declare name to make it accessible from outside this class)
- Override sound() to return "woof"