

Databases

Databases

- Software that stores data on disk
- Runs as a server and is communicated with via TCP sockets
- Provides an API to store/retrieve data
 - The software handles the low-level file IO
 - Allows us to think about our data, not how to store it
- Provides many optimizations

Databases

- We'll look at 2 different databases
- Both are pieces of software that must be downloaded, installed, ran, then connected to via TCP
- MongoDB
 - An unstructured server based on document stores
- MySQL
 - A server implementing SQL (Structured Query Language)

MongoDB

- Runs on port 27017 (By default)
- A document-based database
- Stores data in a structure very similar to JSON
- In python/JS
 - Insert dictionaries/objects directly
- Each object is stored in a collection

MongoDB - Connection

- Download a connection library and use to establish a connection with MongoDB
- MongoDB is separated into several layers
 - Databases - Named by Strings; Contains collections
 - Collections - Where the data is stored; similar to a SQL table
- Access your collections to insert/retrieve/update/delete data

```
from pymongo import MongoClient  
  
mongo_client = MongoClient("localhost")  
db = mongo_client["cse312"]  
chat_collection = db["chat"]
```


MongoDB - Insert Data

- Insert dictionaries/objects directly
- For languages without a data structure comparable to dictionaries/objects
- More work to do to prepare your data for Mongo

```
chat_collection.insert_one({"username": "hartloff", "message": "hello"})
```

MongoDB - Security

- No Mongo injection attacks
- Mongo does not rely on parsing statements as strings
- Any injected code would be treated as values

```
chat_collection.insert_one({ "username": "hartloff", "message": "hello" })
```

MongoDB - Retrieve Data

- Retrieve documents using find
- Find takes a key-value store and returns all documents with those values stored at the given keys
 - Ex. {"username": "hartloff"} returns all documents with a username of "hartloff"
- To retrieve all documents, use an empty key-value store {}

```
my_data = chat_collection.find({"username": "hartloff"})  
all_data = chat_collection.find({})
```


MySQL

- Listens for TCP connections on port 3306 (By default)
- Install a library for your language that will connect to the MySQL server
- SQL is based on tables with rows and column
- Similar in structure to CSV except the values have types other than string

MySQL - Connection

- MySQL runs and you install a library to connect to it
- Connect to MySQL Server by providing:
 - The url of the database
 - username/password for the database
 - Whatever you chose when setting up the database

```
val url = "jdbc:mysql://localhost/mysql"  
val username = "root"  
val password = "12345678"
```

```
var connection: Connection = DriverManager.getConnection(url, username, password)
```

MySQL - Insert Data

- Once connected, we can send SQL statements to the server

```
val statement = connection.createStatement()  
statement.execute("CREATE TABLE IF NOT EXISTS players (username TEXT, points INT)")
```

- If using inputs from the user, always use prepared statements

```
val statement = connection.prepareStatement("INSERT INTO players VALUE (?, ?)")  
  
statement.setString(1, "mario")  
statement.setInt(2, 10)  
  
statement.execute()
```

MySQL - Security

- Not using prepared statements?
 - **Vulnerable to SQL injection attacks**
- If you concatenate user inputs directly into your SQL statements
 - Attacker chooses a username of `'';DROP TABLE players;`
 - You lose all your data
 - Even worse, they find a way to access the entire database and steal other users' data
 - SQL Injection is the most common successful attack on servers

MySQL - Retrieve Data

- Send queries to pull data from the database

```
val statement = connection.createStatement()
val result: ResultSet = statement.executeQuery("SELECT * FROM players")

var allScores: Map[String, Int] = Map()

while (result.next()) {
    val username = result.getString("username")
    val score = result.getInt("points")
    allScores = allScores + (username -> score)
}
```

MongoDB vs. SQL

- MongoDB is unstructured
 - Can add objects in any format to a collection
 - Can mix formats in a single collection
 - I.e. In a single collection the documents can have different attributes
- SQL is structured (That's what the S stands for)
 - Table columns must be pre-defined
 - All rows have the same attributes
 - Adding a column can be difficult
 - Fast!

MongoDB vs. SQL

- Hot Take
 - MongoDB is best for prototyping when the structure of your data is constantly changing
 - Take advantage of the flexibility
 - SQL is best once your data has a defined structure
 - Take advantage of the efficiency

Docker Compose Revisited

`docker-compose.yml`

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- Let's modify our docker compose configuration to run our database

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- "services" is a list of all the images/containers to create
- We'll add a second service for the DB

Docker Compose

`docker-compose.yml`

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- Name each service
- These names are used as the hostnames for each container
- Used to communicate between containers

Docker Compose

`docker-compose.yml`

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- This service named 'mongo' uses a pre-built image
- Same as having a 1-line Dockerfile:
 - "FROM mongo:4.2.5"
- No Dockerfile is needed

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- Use 'environment' to set any needed environment variables
- If using MySQL, set variables for your username/password

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- We use an environment variable to tell our app to wait until the database is running before connecting to it

```
FROM python:3.8.2
```

```
ENV HOME /root
```

```
WORKDIR /root
```

```
COPY . .
```

```
RUN pip install -r requirements.txt
```

```
EXPOSE 8000
```

```
ADD https://github.com/ufoscout/docker-compose-wait/releases/download/2.2.1/wait /wait
```

```
RUN chmod +x /wait
```

```
CMD /wait && python app.py
```

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- If the app runs before the database, it won't be able to establish a DB connection
- Solution: Wait for the DB to start before running the app

```
FROM python:3.8.2
```

```
ENV HOME /root
```

```
WORKDIR /root
```

```
COPY . .
```

```
RUN pip install -r requirements.txt
```

```
EXPOSE 8000
```

```
ADD https://github.com/ufoscout/docker-compose-wait/releases/download/2.2.1/wait /wait
```

```
RUN chmod +x /wait
```

```
CMD /wait && python app.py
```

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- This solution from github user "ufoscout" works well

```
FROM python:3.8.2
```

```
ENV HOME /root
```

```
WORKDIR /root
```

```
COPY . .
```

```
RUN pip install -r requirements.txt
```

```
EXPOSE 8000
```

```
ADD https://github.com/ufoscout/docker-compose-wait/releases/download/2.2.1/wait /wait
```

```
RUN chmod +x /wait
```

```
CMD /wait && python app.py
```

Docker Compose

`docker-compose.yml`

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- This file is used to build both images and run both containers using docker-compose

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

```
mongo_client = MongoClient('localhost')
```

```
mongo_client = MongoClient('mongo')
```

- Recall that we chose names for each service
- When connecting to the database in your app
 - The service name is the hostname for the container

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

```
mongo_client = MongoClient('localhost')
```

```
mongo_client = MongoClient('mongo')
```

- Use the name of the service
- docker-compose will resolve this hostname to the appropriate container

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mysupercooldatabase:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mysupercooldatabase:27017
    ports:
      - '8080:8000'
```

```
mongo_client = MongoClient('localhost')
```

```
mongo_client = MongoClient('mysupercooldatabase')
```

- We can name our services whatever we want
- Make sure you are consistent!

Running Your App

- `docker-compose up --build --force-recreate`
- Will now start both containers
- Use the service name as the host name to communicate across containers

HTML Templates

The Problem

- We want to serve custom HTML
- You want to build a chat feature for your app
 - Users will submit their messages
 - Messages will appear to all users
 - Messages are contained in your HTML
- How do we serve HTML that will change as users send messages?

HTML Templates

- Instead of writing complete HTML files
 - Write HTML templates
- An HTML template is an "incomplete" HTML file that is used to generate complete pages
- Use additional markup to add placeholders in the HTML
- Replace the placeholders with data at runtime

HTML Templates

- Example template with 3 placeholders
- The title, description, and image_filename will be replaced later
- Provide values for these 3 placeholders to serve a response

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>This page was generated from a template</title>
</head>
<body>

<h1>{{title}}</h1>

<p>{{description}}</p>



</body>
</html>
```


HTML Templates

- To substitute the placeholders
 - Use any string manipulation that gets the job done
 - Find/replace is the simplest solution
 - May want more advanced approaches if you want to add more functionality

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>This page was generated from a template</title>
</head>
<body>

<h1>{{title}}</h1>

<p>{{description}}</p>



</body>
</html>
```


Common Template Features

- Loops
- To add loops to your templates
 - Choose syntax for the start and end of the loop

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>This page was generated from a template</title>
</head>
<body>

  {{loop}}
  <h6>{{content_from_data_structure}}</h6>
  {{end_loop}}

</body>
</html>
```


Common Template Features

- Use string manipulation to find the start and end tags
- Iterate over your data
- Add the contained HTML with the placeholder replaced for each value of your data

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>This page was generated from a template</title>
</head>
<body>

  {{loop}}
  <h6>{{content_from_data_structure}}</h6>
  {{end_loop}}

</body>
</html>
```


Common Template Features

- Conditionals
- Can use similar approach as loops
- Choose syntax for the start and end of each block in the conditional

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>This page was generated from a template</title>
</head>
<body>

  {{if cookie_set}}
  <h6>Welcome back!</h6>
  {{else}}
  <h6>Welcome!</h6>
  {{end_if}}

</body>
</html>
```


Common Template Features

- Search for your tags
- Extract and evaluate the conditional
 - Choose how this will be evaluated
- Add the appropriate block of HTML to the page

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>This page was generated from a template</title>
</head>
<body>

  {{if cookie_set}}
  <h6>Welcome back!</h6>
  {{else}}
  <h6>Welcome!</h6>
  {{end_if}}

</body>
</html>
```