

# HTTP Overview

# Roadmap

- The physical Internet
  - The Internet is a network of networks
  - Physically connected by cables and routers
- Internet Protocol (IP)
  - How routers move data through the Internet
  - Best effort basis
- Transport Control Protocol (TCP)
  - Transport information reliably through an unreliable network
  - Used by the client and server

# Network Stack (A simplified view)

- Enter HTTP

## Packet Structure

IP Headers

TCP Headers

HTTP Headers

Content

# HyperText Transfer Protocol (HTTP)

- HTTP is an application layer protocol
  - Protocols used by our applications
  - Protocols that are not concerned with the transmission of data
- [Almost] Always uses TCP for reliable communication
  - Always in this course
- Today:
  - A quick overview of many HTTP topics
  - We'll spend several week exploring these topics in more detail


# HTTP

- HTTP is a protocol used by the browser to access content from a web server
- Protocol: An agreed upon set of rules
  - HTTP: Defines the format of messages sent to/from a web server
- HTTP is a Request - Response protocol
  - Client makes request to server
  - Server returns a response
- Ex. Request The latest tweets from a user. Twitter server returns the tweets in its response
- Response can require more requests
  - Ex. Get HTML which requires CSS/JS/Images

# Web Server

- Software that "speaks" HTTP
- Listens for HTTP requests and responds with HTTP responses
- We've been opening web pages by loading \*.html files in the browser
  - This uses the 'file' protocol which loads a file from disk
- We want to host our web pages/apps on the Internet using HTTP
- Terminology:
  - Front End - The part a web app that runs in the browser (HTML/CSS/JS)
  - Back End - The web server and all software that does not run on the user's machine

# Loading a Web Site



# HTTP Request

- Each HTTP request will contain the request type:
  - GET: Request information from a server
  - POST: Send information to a server
  - PUT (less common): Add information to a service
  - DELETE (less common): Delete information form a service
  - etc.
- We'll focus on GET/POST requests



# HTTP Request

- HTTP GET Request

- Used when requesting content from a server
- Contains only a URL [And HTTP headers]
- All examples on the query string/fragment slide were GET requests
- Whenever you click a link your browser makes a get request
- Requesting HTML/CSS/Javascript/Images/etc are GET requests

- HTTP POST Request

- Used when sending data to a website
- Contains a URL and a body [And HTTP headers]
- When you submit a form your browser [typically] makes a POST request
- The contents of the form are sent in the body of the request

# HTTP Request

Protocol://host:port/path?query\_string#fragment

- Each request is made to a specific URL (Uniform Resource Location)
  - A URL uniquely identifies a web resource and has the following parts
- Protocol - The protocol being used (ex. file, HTTP, HTTPS)
- Host - The IP address or domain name of the server
  - Used to route the request to appropriate machine
- Port - The TCP port number of the host server
  - Defaults to 80/443 for HTTP/HTTPS respectively
- Path - Specifies the specific resource being requested from the server

# HTTP Request

Protocol://host:port/path?query\_string#fragment

- Query String - [Optional] Contains key-value pairs set by the client
- <https://www.google.com/search?q=web+development>
  - HTTPS request to Google search for the phrase "web development"
- <https://duckduckgo.com/?q=web+development&ia=images>
  - An HTTPS request to Duck Duck Go image search for the phrase "web development"
- Fragment - [Optional] Specifies a single value commonly used for navigation
- [https://en.wikipedia.org/wiki/Uniform\\_Resource\\_Identifier](https://en.wikipedia.org/wiki/Uniform_Resource_Identifier)
  - HTTPS Request for the URI Wikipedia page
- [https://en.wikipedia.org/wiki/Uniform\\_Resource\\_Identifier#Definition](https://en.wikipedia.org/wiki/Uniform_Resource_Identifier#Definition)
  - HTTPS Request for the URI Wikipedia page that will scroll to the definition of URI

# HTTP Request

- Head of request
  - A Request-Line
    - <Request\_Method> <Path> <HTTP\_Version>
  - Header Fields
    - Contains additional information about the request in key-value pairs
    - <Header\_Name>: <Header\_Value>
- Body of request [Optional]
  - Content to be sent to the server

**GET / HTTP/1.1**  
**Host: cse312.com**

**POST /path HTTP/1.1**  
**Host: cse312.com**  
**Content-Length: 48**

**{"data": "Some data in the body of the request"}**

# HTTP Request

- Head and body of request are separated by a blank line
- If the request has a body, the Content-Length header will be set to the size of the body
  - Lets the server know when the request ends
  - `https://www.google.com/search?q=hello+google&oq=hello+google&aqs=chrome..69i57.2494j0j1&sourceid=chrome&ie=UTF-8`

**GET / HTTP/1.1**  
**Host: cse312.com**

**POST /path HTTP/1.1**  
**Host: cse312.com**  
**Content-Length: 48**

**{"data": "Some data in the body of the request"}**

# HTTP Response

- When the server receives an HTTP request
  - Process the request and send a response to the client
- Whether the request was GET or POST, the response will have a body containing the requested content
- Response also contains HTTP headers including meta information about the response and the server
  - Must include the content length and type
- Response includes a response code indicating the status of the response

# HTTP Response

- Mostly the same format as a request
- Response line
  - <HTTP\_Version> <Response\_Code> <Response\_Text>
- Specify the content length and type in headers
- Response itself goes in the body

**HTTP/1.1 200 OK**

**Content-Type: text/html; charset=utf-8**

**Content-Length: 152**

**<html> ... </html>**

# HTTP - Response

Common Response codes include:

- 200 OK
  - Request was handled as expected
- 301 Moved Permanently
  - Redirect to the new location
- 304 Not Modified
  - File in local cache can be used
- 403 Forbidden
  - You don't have access to the requested page
- 404 Not Found
  - Requested data could not be found
- 500
  - Internal server error



# HTTP

- HTTP is a stateless protocol
  - Saves time and memory on the server
  - Each request is handled in isolation even if a client just made another request
- If state is desired (ex. Login) it must sent the state with each request
  - Cookies
  - Tokens

# HTTP

- HTTP is a stateless protocol
- Each request is handled in isolation even if a client just made another request
- If state is desired (ex. Login), the state must be sent with each request
- Cookies
- Tokens
- When handling an HTTP request, do not have to care who sent it



<https://xkcd.com/869/>