

Docker and docker compose

Vocab

- Development Environment (dev)
 - The environment where you write your code
 - Ex. Your laptop
 - Add features; Find and eliminate bugs
- Production environment (prod)
 - The environment where your app will eventually live
 - The live server with real end users
 - Do everything we can to avoid bugs in production

Deployment Headaches

- It works on my laptop!
- Run your code in production and it's broken
- Many causes
 - Different version of compiler/interpreter
 - Dependancies not linked
 - Hard-coded paths
 - Different environment variables
 - etc.

Virtual Machines

- Simulate an entire machine
- Run the virtual machine (VM) in your development environment for testing
- Run an exact copy of the VM on the production server
- No more surprise deployment issues

- Simulating an entire machine can be inefficient
 - If you've ran a VM on your laptop you know how slow this can get

Security

- *Can't* break out of the VM [Without sophisticated attacks]
- If an attacker compromises the server, they can only access what you put in the container
 - Can't "rm -rf /" your entire machine
 - Patch the exploited vulnerability and rebuild the image
- The attacker can still cause significant damage and steal private data
 - They just can't destroy your server box

Security

- Sometimes an app has to allow code injection attacks to function
 - AutoLab
 - AWS
 - Digital Ocean
- Run user code in their own VM/Container

Containers

- Effectively, lightweight VMs

Docker

- Docker is software that's used to create containers
- **Install** Docker in your development environment to test containers
- Install Docker in your production environment and run the same containers

Dockerfile

- To start working with Docker, write a Dockerfile
- This file contains all the instructions needed to build a Docker image
- Some similarities to a Makefile

Dockerfile

- Let's explore this sample Dockerfile
- This Dockerfile creates an image for a node.js app

```
FROM ubuntu:18.04

RUN apt-get update

# Set the home directory to /root
ENV HOME /root

# cd into the home directory
WORKDIR /root

# Install Node
RUN apt-get update --fix-missing
RUN apt-get install -y nodejs
RUN apt-get install -y npm

# Copy all app files into the image
COPY . .

# Download dependencies
RUN npm install

# Allow port 8000 to be accessed
# from outside the container
EXPOSE 8000

# Run the app
CMD node app-www.js
```

Dockerfile

- The first line of your Dockerfile will specify the base image
- This image is downloaded and the rest of your Dockerfile adds to this image
- In this example: We start with Ubuntu 18.04
 - Our Dockerfile can run Linux commands in Ubuntu

```
FROM ubuntu:18.04

RUN apt-get update

# Set the home directory to /root
ENV HOME /root

# cd into the home directory
WORKDIR /root

# Install Node
RUN apt-get update --fix-missing
RUN apt-get install -y nodejs
RUN apt-get install -y npm

# Copy all app files into the image
COPY . .

# Download dependencies
RUN npm install

# Allow port 8000 to be accessed
# from outside the container
EXPOSE 8000

# Run the app
CMD node app-www.js
```


Dockerfile

- Use the RUN keyword to run commands in the base image
- Use this for any setup of your OS before setting up your app
- In this example:
Updating apt-get which is used to install software

```
FROM ubuntu:18.04

RUN apt-get update

# Set the home directory to /root
ENV HOME /root

# cd into the home directory
WORKDIR /root

# Install Node
RUN apt-get update --fix-missing
RUN apt-get install -y nodejs
RUN apt-get install -y npm

# Copy all app files into the image
COPY . .

# Download dependencies
RUN npm install

# Allow port 8000 to be accessed
# from outside the container
EXPOSE 8000

# Run the app
CMD node app-www.js
```


Dockerfile

- Use ENV to set environment variables
 - Setting the home directory here
 - Can use ENV to setup any other variables you need
- Use WORKDIR to change your current working directory
 - Same as "cd"

```
FROM ubuntu:18.04

RUN apt-get update

# Set the home directory to /root
ENV HOME /root

# cd into the home directory
WORKDIR /root

# Install Node
RUN apt-get update --fix-missing
RUN apt-get install -y nodejs
RUN apt-get install -y npm

# Copy all app files into the image
COPY . .

# Download dependencies
RUN npm install

# Allow port 8000 to be accessed
# from outside the container
EXPOSE 8000

# Run the app
CMD node app-www.js
```

Dockerfile

- Since we're starting with a fresh image of Ubuntu:
 - Only the default software is installed
- RUN commands to install all required software for your app
 - Typically the development tools for your language of choice

```
FROM ubuntu:18.04

RUN apt-get update

# Set the home directory to /root
ENV HOME /root

# cd into the home directory
WORKDIR /root

# Install Node
RUN apt-get update --fix-missing
RUN apt-get install -y nodejs
RUN apt-get install -y npm

# Copy all app files into the image
COPY . .

# Download dependencies
RUN npm install

# Allow port 8000 to be accessed
# from outside the container
EXPOSE 8000

# Run the app
CMD node app-www.js
```

Dockerfile

- COPY all your app file into the image
- "." denotes the current directory
- Run docker from your apps root directory
 - The the first "." will refer to your apps directory
- We changed the home and working directory to /root
 - The second "." refers to /root in the image

```
FROM ubuntu:18.04

RUN apt-get update

# Set the home directory to /root
ENV HOME /root

# cd into the home directory
WORKDIR /root

# Install Node
RUN apt-get update --fix-missing
RUN apt-get install -y nodejs
RUN apt-get install -y npm

# Copy all app files into the image
COPY . .

# Download dependancies
RUN npm install

# Allow port 8000 to be accessed
# from outside the container
EXPOSE 8000

# Run the app
CMD node app-www.js
```


Dockerfile

- Now that your apps files are in the image, run all app specific commands
- Order is important
 - Don't depend on your app files before copying them into the image
- Use RUN to install dependancies and perform any other required setup

```
FROM ubuntu:18.04

RUN apt-get update

# Set the home directory to /root
ENV HOME /root

# cd into the home directory
WORKDIR /root

# Install Node
RUN apt-get update --fix-missing
RUN apt-get install -y nodejs
RUN apt-get install -y npm

# Copy all app files into the image
COPY . .

# Download dependancies
RUN npm install

# Allow port 8000 to be accessed
# from outside the container
EXPOSE 8000

# Run the app
CMD node app-www.js
```


Dockerfile

- Use EXPOSE to allow specific ports to be accessed from outside the container
- By default, all ports are blocked
 - Container is meant to run in isolation
- To run a web app in a container, expose the port you need

```
FROM ubuntu:18.04

RUN apt-get update

# Set the home directory to /root
ENV HOME /root

# cd into the home directory
WORKDIR /root

# Install Node
RUN apt-get update --fix-missing
RUN apt-get install -y nodejs
RUN apt-get install -y npm

# Copy all app files into the image
COPY . .

# Download dependencies
RUN npm install

# Allow port 8000 to be accessed
# from outside the container
EXPOSE 8000

# Run the app
CMD node app-www.js
```

Dockerfile

- Finally, use CMD to run your app
- Important: Do not use RUN to run your app!
- RUN will execute the command when the image is being **built**
- CMD will execute when the container is **ran**
- We do not want the app to run when the image is being built

```
FROM ubuntu:18.04

RUN apt-get update

# Set the home directory to /root
ENV HOME /root

# cd into the home directory
WORKDIR /root

# Install Node
RUN apt-get update --fix-missing
RUN apt-get install -y nodejs
RUN apt-get install -y npm

# Copy all app files into the image
COPY . .

# Download dependencies
RUN npm install

# Allow port 8000 to be accessed
# from outside the container
EXPOSE 8000

# Run the app
CMD node app-www.js
```

Dockerfile

- There are many base images to choose from
- Start with an image with your language installed to simplify your docker file
 - Search "docker <language>" to find images/tutorials for your favorite language
- This image starts with node installed so we can remove the node installation lines

```
FROM node:13
```

```
ENV HOME /root  
WORKDIR /root
```

```
COPY . .
```

```
# Download dependencies  
RUN npm install
```

```
EXPOSE 8000
```

```
CMD node app-www.js
```


Dockerfile

- Example for Python

```
FROM python:3.8

ENV HOME /root
WORKDIR /root

COPY . .

# Download dependencies
RUN pip3 install -r requirements.txt

EXPOSE 8000

CMD python3 -u app.py
```


Dockerfile

- For Python
 - Make sure you add this `-u` flag
 - This will force stdout and stderr to be unbuffered
 - Without it, when running in Docker, you might not see your print statements

```
FROM python:3.8

ENV HOME /root
WORKDIR /root

COPY . .

# Download dependencies
RUN pip3 install -r requirements.txt

EXPOSE 8000

CMD python3 -u app.py
```

Running Your App

- When preparing your app to run in a container
 - **Do not use "localhost"** [in your code]
 - Use "0.0.0.0" as the host instead
 - This allows your app to be accessed from outside the container

Docker Compose

Docker Compose

- Manages building/running docker images/containers
- Build and run with one command
 - `docker compose up --build --force-recreate`
- No need to use `docker build` and `docker run`
- Will be used to manage multiple containers
 - Separate container for your database
- Let's walk through a `docker-compose.yml` file

Docker Compose

docker-compose.yml

```
version: '3'
services:
  app:
    build: .
    ports:
      - '8080:8000'
```

- Specify the docker compose file format version
- Version 3[.8] is the current latest version
- This line is now optional

Docker Compose

docker-compose.yml

```
version: '3'
services:
  app:
    build: .
    ports:
      - '8080:8000'
```

- List of all the services for docker compose to run
- A docker container is created for each service

Docker Compose

docker-compose.yml

```
version: '3'
services:
  app:
    build: .
    ports:
      - '8080:8000'
```

- Name each service
- We have one service that we name "app"
- This name becomes the hostname when communicating between containers

Docker Compose

docker-compose.yml

```
version: '3'
services:
  app:
    build: .
    ports:
      - '8080:8000'
```

- Use 'build' to specify the path to build from
- Docker compose will look in this directory for a Dockerfile and use it to build the image
- Same as the trailing '.' when building an image

Docker Compose

docker-compose.yml

```
version: '3'
services:
  app:
    build: .
    ports:
      - '8080:8000'
```

- Map a local port to a container port
- Same as using "-p 8080:8000" when running a single container

Docker Compose

docker-compose.yml

```
version: '3'
services:
  app:
    build: .
    ports:
      - '8080:8000'
```


- Mapping a port allows your app [inside the container] to be accessed from your machine
- This line maps your local port 8080 [On your machine] to port 8000 inside your container

Docker Compose

docker-compose.yml

```
version: '3'
services:
  app:
    build: .
    ports:
      - '8080:8000'
```

http://localhost:8080



- When your machine receives a request for the mapped port
- Docker forwards the request to the container on the specified port

Running Your App

- To run your app
 - `docker compose up`
- To run in detached mode
 - `docker compose up -d`
- To **rebuild** and restart the containers
 - `docker compose up --build --force-recreate`
 - *This is the best command to use!
- To restart the container without rebuilding
 - `docker compose restart`

Running Your App

- To **rebuild** and restart the containers
 - `docker compose up --build --force-recreate`
- Use this command during development
- Very important to rebuild your images after you change code
- If you don't, you will not see your changes since you'll be running your old code

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- Let's modify our docker compose configuration to run our database

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- "services" is a list of all the images/containers to create
- We'll add a second service for the DB

Docker Compose

`docker-compose.yml`

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- Name each service
- These names are used as the hostnames for each container
- Used to communicate between containers

Docker Compose

`docker-compose.yml`

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- This service named 'mongo' uses a pre-built image
- Same as having a 1-line Dockerfile:
 - "FROM mongo:4.2.5"
- No Dockerfile is needed

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- Use 'environment' to set any needed environment variables
- If using MySQL, set variables for your username/password

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- We use an environment variable to tell our app to wait until the database is running before connecting to it

```
FROM python:3.8.2
```

```
ENV HOME /root
```

```
WORKDIR /root
```

```
COPY . .
```

```
RUN pip install -r requirements.txt
```

```
EXPOSE 8000
```

```
ADD https://github.com/ufoscout/docker-compose-wait/releases/download/2.2.1/wait /wait
```

```
RUN chmod +x /wait
```

```
CMD /wait && python app.py
```

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- If the app runs before the database, it won't be able to establish a DB connection
- Solution: Wait for the DB to start before running the app

```
FROM python:3.8.2
```

```
ENV HOME /root
```

```
WORKDIR /root
```

```
COPY . .
```

```
RUN pip install -r requirements.txt
```

```
EXPOSE 8000
```

```
ADD https://github.com/ufoscout/docker-compose-wait/releases/download/2.2.1/wait /wait
```

```
RUN chmod +x /wait
```

```
CMD /wait && python app.py
```


Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- This solution from github user "ufoscout" works well

```
FROM python:3.8.2
```

```
ENV HOME /root
```

```
WORKDIR /root
```

```
COPY . .
```

```
RUN pip install -r requirements.txt
```

```
EXPOSE 8000
```

```
ADD https://github.com/ufoscout/docker-compose-wait/releases/download/2.2.1/wait /wait
```

```
RUN chmod +x /wait
```

```
CMD /wait && python app.py
```

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

- This file is used to build both images and run both containers using docker-compose

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

```
mongo_client = MongoClient('localhost')
```

```
mongo_client = MongoClient('mongo')
```

- Recall that we chose names for each service
- When connecting to the database in your app
 - The service name is the hostname for the container

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mongo:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mongo:27017
    ports:
      - '8080:8000'
```

```
mongo_client = MongoClient('localhost')
```

```
mongo_client = MongoClient('mongo')
```

- Use the name of the service
- docker-compose will resolve this hostname to the appropriate container

Docker Compose

docker-compose.yml

```
version: '3.3'
services:
  mysupercooldatabase:
    image: mongo:4.2.5
  app:
    build: .
    environment:
      WAIT_HOSTS: mysupercooldatabase:27017
    ports:
      - '8080:8000'
```

```
mongo_client = MongoClient('localhost')
```

```
mongo_client = MongoClient('mysupercooldatabase')
```

- We can name our services whatever we want
- Make sure you are consistent!

Running Your App

- `docker-compose up --build --force-recreate`
- Will now start both containers
- Use the service name as the host name to communicate across containers