HTTP

Activity

Write a server that does

- -Responds to the root with HTML containing a form
- -Responds to a POST request from the form with custom HTML using the form inputs
- -Has a 404 response for invalid paths

You can use libraries for


- -TCP sockets
- [-Database]

The Physical Internet

A Network of Networks

ISP Networks

- Connect customers to the Internet
- Maintain city and regional networks
- Addresses the last mile problem



https:// bijanghayyoomi.files.w ordpress.com/ 2010/08/picture20.jpg

http://oldforum.paradoxplaza.com/forum/showthread.php?837998-Underground-power-lines-and-capacity/page2



Tier 1 Networks

AT&T

CenturyLink

Global Telcon & Communications

Portland

Boise

Minneapolis

Rochester

New York City

Omaha

Chicago

New York City

To Hawaii

To Japan

Las Vegas

Phoenix

San Diego

Phoenix

El Paso

Houston

Tampa

Miami

http://www.vootwerk.com/network.html

Level 3 Communications

NTT Communications

Verizon Enterprise Solutions

Zayo Group





(https://en.wikipedia.org/wiki/Tier_1_network for more)

Internet Exchanges (IX)

- Tier 1 networks must connect to ISP networks and other Tier 1 networks
- These connections are made in Internet Exchanges
- 60 Hudson Street (pictured) houses one such IX in Manhattan




https://www.wired.com/ 2015/11/peter-garritano-wherethe-internet-lives/





Cables Connect Continents



https://arstechnica.com/information-technology/2016/05/how-the-internet-works-submarine-cables-data-centres-last-mile/

Data Centers Power Apps




http://americanbuildersquarterly.com/2015/yahoo/



Google Cloud Submarine Cable Investments

Google Cloud's well-provisioned global network is comprised of hundreds of thousands of miles of fiber optic cable and seven submarine cable investments



https://www.blog.google/topics/google-cloud/google-invests-indigo-undersea-cable-improve-cloud-infrastructure-southeast-asia/

Internet Protocol

Internet Protocol (IP)

- The Internet is a network of networks connected by cables
- Now, how do these networks and devices communicate with each other?
- Internet Protocol
 - Official standard for IPv4: https://tools.ietf.org/html/
 rfc760
- Every device connected to the Internet has an IP address
 - Routers use this address to send data to its destination

Internet Protocol

- Data is sent in packets/datagrams
 - Large messages are sent in multiple packets
- Each packet contains a header and a payload
- Header
 - Contains metadata about the packet
 - Most importantly, contains the source and destination IP addresses

Payload

- The data to be sent to the destination device
- IP has no concern about the content of the payload
- Payload often/always follows additional protocols agreed upon by the source and destination
 - Ex: TCP, UDP, HTTP[S]

IP

- Address of a machine on the Internet
 - o Ex: 172.217.12.211
- Routers read the address and send it to the next step
- Often read a prefix
- IPs with a common prefix are related
- Two parts: Network, host
- Organizations will receive a prefix and own all IP's that start with that prefix
 - One of Google's ranges: 172.217.0.0-172.217.255.255
 - Network prefix: 172.217.x.x

IP

- IPv4 (8.8.4.4)
 - Consists of 4 numbers ranging from 0 to 255
 - O How many total addresses?
 - 4 numbers, 8 bits each, 32 total bits, 2^32 total addresses
 - **4**,294,967,296
 - A lot, but not enough
- IPv6 (2001:4860:4860:0000:0000:0000:0000:8844)
 - 128 bit addresses
 - 2¹28 total addresses
 - **■** 340,282,366,920,938,463,463,374,607,431,768,211,456
 - That should be enough
 - Used in conjunction with IPv4
 - Routers must be able to route both versions

```
Type of Service
Version|
    IHL
                 Total Length
Identification
             Flags
                  Fragment Offset
Time to Live
        Protocol
                 Header Checksum
Source Address
       _+_+_+_+_+_+_+_+_+_+
        Destination Address
        Options
                      Padding
```

Example Internet Datagram Header

Figure 4.


From the IPv4 official standard: https://tools.ietf.org/html/ rfc791

Domain Name Service (DNS)

- We don't want to remember IP address for all our favorite sites
- With DNS, we don't have to
- DNS
 - Remember a Domain Name instead of an IP address
 - Domain Name: google.com
 - When you click a link, first a DNS request is made to get the IP address for that Domain Name
 - Then the IP address is used to make your request
- Can access sites directly by IP
 - http://172.217.6.228/
- Not all sites allow direct IP access
 - http://104.16.40.2/

Routing Through the Internet

- ISP and Tier 1 networks contain many routers to direct Internet traffic
 - These routers are made for speed!
 - To maximize speed, they are simple
- Router reads the destination IP address of a packet and sends it to the next router
 - Only knows the next step
 - No one needs to map the entire Internet
 - Routing tables can be updated



https://superuser.com/questions/959242/how-is-next-hop-defined-in-routing-table


Transmission Control Protocol

Transmission Control Protocol (TCP)

- The Internet is unreliable
 - Router sends a packet to its next step, then forgets about it
 - May have sent packets to a failed router
 - Cables may be cut
 - Regions can have power outages
 - Router never gets confirmation of delivery even if the packet made it to its destination
- Internet users (Browsers) and apps are responsible for reliability

TCP: Making a Connection

- 3-way handshake to confirm a connection
- SYN
 - Client sends a packet with a random number to the server
- SYN-ACK
 - Server acknowledges that it received the client's SYN by returning the random number+1
 - Also send another random number
- ACK
 - Client returns the server's random number plus 1
- After all three steps, both side have verified the connection



https://lwn.net/Articles/508865/

TCP: Transmitting Data

- When request/response is too large for a single packet
 - Receiver reassembles the packets on the other side of the connection
- Once a connection is established, send all the packets
- Packets can arrive out of order
 - Each packet contains a sequence number for reordering
 - If a sequence number is missing, request a resend
- Many streams simultaneously
 - TCP uses port numbers
 - Allows multiple programs to all use the Internet simultaneously

TCP: In code

 Use TCP sockets in your language of choice to listen for TCP connections on a chosen port

HTTP

Roadmap

- The physical Internet
 - The Internet is a network of networks
 - Physically connected by cables and routers
- Internet Protocol (IP)
 - How routers move data through the Internet
 - Best effort basis
- Transport Control Protocol (TCP)
 - Transport information reliably through an unreliable network
 - Used by the client and server

Network Stack

Enter HTTP

Packet Structure IP **TCP HTTP** Content

HyperText Transfer Protocol (HTTP)

- HTTP is an Application Protocol
 - Protocols used by our applications
 - Protocols that are not concerned with the transmission of data
- [Almost] Always uses TCP for reliable communication

HTTP

- HTTP is a stateless protocol
 - Saves time and memory on the server
 - Each request is handled in isolation even if a client just made another request
- If state is desired (ex. Login) it must sent the state with each request
 - Cookies
 - Tokens

Response codes

- 200 OK
 - Request was handled as expected
- 301 Moved Permanently
 - Redirect to the new location
- 304 Not Modified
 - File in local cache can be used
- 403 Forbidden
 - You don't have access to the requested page
- 404 Not Found
 - Requested data could not be found
- 500
 - Internal server error

HTTP Request

- Head of request
 - A Request-Line
 - <Request_Method> <Path> <HTTP_Version>
 - Header Fields
 - <Header_Name>: <Header_Value>
- Body of request [Optional]
 - Content to be sent to the server

GET / HTTP/1.1 Host: cse312.com

POST /path HTTP/1.1

Host: cse312.com

User-Agent: Mozilla/5.0 ...

{"data": "Some data in the body of the request"}

HTTP Request

- Head and body of request are separated by a blank line
- If the request has a body, the Content-Length header will be set to the size of the body
 - Lets the server know when the request ends

GET / HTTP/1.1 Host: cse312.com POST /path HTTP/1.1

Host: cse312.com

Content-Length: 48

{"data": "Some data in the body of the request"}

HTTP Response

- Mostly the same format as a request
- Response line
 - <HTTP_Version> <Response_Code> <Response_Text>
- Specify the content length and type in headers
- Response itself goes in the body

HTTP/1.1 200 OK

Content-Type: text/html; charset=utf-8

Content-Length: 152

<html> ... </html>

Activity

Write a server that does

- -Responds to the root with HTML containing a form
- -Responds to a POST request from the form with custom HTML using the form inputs
- -Has a 404 response for invalid paths

You can use libraries for

- -TCP sockets
- [-Database]