

macOS Architectural Policy Documentation

for *The TOW Foundation*

macOS MDM and NinjaOne policy architecture

Version	1.0
Author	Ryan Schreiber
Owner	Toga Technology, Jake Donaldson, & Ryan Schreiber
Last Updated	September 2026
Document Scope	macOS MDM and NinjaOne policy architecture for The TOW Foundation
Source Policy Identifier	000 // TOW Master MacOS Policy

DOCUMENT GOVERNANCE

This documentation describes the current implementation and does not constitute authorization to modify it. Configuration changes should be coordinated with the endpoint-management owner and reflected in the corresponding source configuration.

TABLE OF CONTENTS

Click a section or topic to jump directly to it. Detailed payload, script, transferred-file, and explanation-document placeholders are retained in the body for final link insertion.

Section I (S.I) // MacOS MDM

- [S.I // Topic I \(T.I\) - Passcode/Password](#)
- [S.I // Topic II \(T.II\) - Restrictions](#)
- [S.I // Topic III \(T.III\) - macOS VPP Application Deployment](#)
- [S.I // Topic IV \(T.IV\) - Network / Wi-Fi Configuration](#)
- [S.I // Topic V \(T.V\) - OS Updates](#)
- [S.I // Topic VI \(T.VI\) - Encryption / FileVault](#)
- [S.I // Topic VII \(T.VII\) - Privacy Preferences](#)
- [S.I // Topic VIII \(T.VIII\) - System Extensions](#)
- [S.I // Topic IX \(T.IX\) - Custom Payloads](#)

Section II (S.II) // MacOS NinjaOne Specific Configurations

- [S.II // Topic I \(T.I\) - Conditions](#)
- [S.II // Topic II \(T.II\) - Compound Conditions](#)
- [S.II // Topic III \(T.III\) - Scheduled Automations](#)
- [S.II // Topic IV \(T.IV\) - OS Patching](#)
- [S.II // Topic V \(T.V\) - Software Patching](#)
- [S.II // Topic VI \(T.VI\) - Antivirus Deployment](#)
- [S.II // Topic VII \(T.VII\) - Activity Monitoring](#)
- [S.II // Topic VIII \(T.VIII\) - NinjaOne Backup \[Lockhart\]](#)
- [S.II // Topic IX \(T.IX\) - NinjaOne Warranty Tracking](#)

DOCUMENT NAVIGATION & SOURCE HIERARCHY

This document is the policy-level architectural reference. It records effective configuration, lifecycle status, sequencing, and operational behavior across the 000 Master, 001 Pre-Enrollment, and 002 Post-Enrollment macOS policies.

Detailed explanation documents provide component-level rationale, behavior, dependencies, warnings, and implementation notes.

Raw scripts and payloads remain the authoritative implementation source for the exact executable/configuration content.

The [Insert File / Link] placeholders are intentionally retained for final linking to the corresponding raw files, transferred assets, and explanation documents.

Section I (S.I) // MacOS MDM

MDM-delivered configuration, application, security, networking, and custom-payload architecture.

S.I // Topic I (T.I) - Passcode/Password

[Back to Table of Contents](#)

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

Description:

This configuration controls macOS password requirements, password reuse/expiration, failed authentication behavior, and device-lock behavior. Because the Passcode payload is disabled, none of the configured values below are currently enforced by this policy.

Reason Disabled:

Passcode enforcement is intentionally disabled because imposing local macOS password requirements can interfere with identity-driven account workflows, including password synchronization and automatic account creation. Password requirements are therefore managed through the appropriate identity/authentication mechanisms rather than through the macOS MDM Passcode payload.

Apple's Passcode payload applies these requirements directly to the Mac's local account passwords, which is why it can interact poorly with environments where those passwords are expected to remain synchronized with an external identity provider.

Settings, Configured Values, & their Descriptions

Passcode enforcement enabled toggle = Off

// Master control for the Passcode payload. When disabled, the settings below are not enforced.

Require alphanumeric value toggle = Off

// When enabled, requires the password to contain at least one letter and at least one number.

Allow simple passcode toggle = Off

// Controls whether simple passwords containing repeated or sequential characters—such as 3333 or DEFG—are permitted.

Maximum number of failed attempts = 11

// Defines the number of incorrect password attempts permitted before macOS disables and prevents further login attempts.

Maximum passcode age (days) = 0

// Defines how long a password may be used before the user is required to change it. A value of 0 disables password expiration.

Maximum grace period for device lock = No grace period

// Controls how long after the Mac locks that it may be unlocked again without requiring the user's password. No grace period means authentication is required immediately after the device is locked.

Minimum number of complex characters = 1

// If enforced, requires the password to contain at least one complex/special character, such as \$ or !.

Minimum passcode length = 8

// If enforced, requires the local account password to contain at least eight characters.

Passcode history = 2

// Prevents reuse of the previous two passwords when the user changes their password.

Maximum Auto-Lock (minutes) = 0

```
// Controls the maximum amount of inactivity permitted before macOS automatically locks the  
device and requires authentication.
```

S.I // Topic II (T.II) - Restrictions

[Back to Table of Contents](#)

Description:

This configuration controls which macOS features, Apple services, user actions, system-setting changes, sharing capabilities, security functions, and application features are permitted or restricted on managed devices.

Unlike the Passcode configuration, Restrictions is not a single enabled/disabled control. Each individual restriction is configured independently. For this reason, the effective status of each setting is documented separately for the 000 Master MacOS Policy, 001 Pre-Enrollment Policy, and 002 Post-Enrollment Policy.

Settings, Configured Values, & their Descriptions

FUNCTIONALITY

Allow modifying account settings

000 Master Status: Restricted

001 Pre-Enrollment Status: Restricted

002 Post-Enrollment Status: Restricted

// Prevents users from adding, changing, or removing account configurations such as Apple Accounts and internet-based accounts used by Mail, Contacts, Calendar, and similar services.

Allow Handoff

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

// Allows Handoff and related Continuity functionality between compatible Apple devices.

Allow AirDrop

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

// Allows users to send and receive files through AirDrop.

Allow AirPlay

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

// Allows the Mac to receive incoming AirPlay requests from compatible devices.

Allow Apple personalized advertising

000 Master Status: Restricted

001 Pre-Enrollment Status: Restricted

002 Post-Enrollment Status: Restricted

```
| // Disables Apple's personalized advertising functionality on the device.
```

Allow modifying Bluetooth settings

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows users to modify Bluetooth settings in System Settings.
```

Allow Camera

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows applications and users to use the device's camera, subject to normal macOS privacy permissions.
```

Allow Content Caching

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows the Mac to use Apple's Content Caching functionality.
```

Allow Definition Lookup

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows users to use macOS Definition Lookup functionality.
```

Allow modifying device name

```
000 Master Status: Restricted
```

```
001 Pre-Enrollment Status: Restricted
```

```
002 Post-Enrollment Status: Restricted
```

```
| // Prevents users from changing the Mac's device/computer name.
```

Allow submitting diagnostic and usage data to Apple

```
000 Master Status: Restricted
```

```
001 Pre-Enrollment Status: Restricted
```

```
002 Post-Enrollment Status: Restricted
```

```
| // Prevents the device from automatically submitting diagnostic and usage information to Apple.
```

Allow dictation

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows users to use macOS Dictation.
```

Allow Erase All Content and Settings

000 Master Status: Restricted

001 Pre-Enrollment Status: Restricted

002 Post-Enrollment Status: Restricted

| // Prevents users from accessing the Erase All Content and Settings option from macOS System Settings.

Allow Find My Device

000 Master Status: Restricted

001 Pre-Enrollment Status: Restricted

002 Post-Enrollment Status: Restricted

| // Prevents the Mac from using Find My Device functionality through Apple's Find My service.

Allow Find My Friends

000 Master Status: Restricted

001 Pre-Enrollment Status: Restricted

002 Post-Enrollment Status: Restricted

| // Prevents use of Find My Friends functionality through the Find My application.

Allow iTunes file sharing

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows supported file-sharing functionality between applications and devices using Apple's file-sharing services.

Allow screenshots and screen recording

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows users and authorized applications to capture screenshots and screen recordings. Restricting this setting can also affect Classroom screen observation functionality.

Allow Siri Suggestions

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows Siri Suggestions and supported internet-based Spotlight/Siri search results.

Allow user installation of configuration profiles

000 Master Status: Restricted

001 Pre-Enrollment Status: Restricted

002 Post-Enrollment Status: Restricted

```
// Prevents users from interactively installing configuration profiles and certificates themselves.
```

Allow Universal Control

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
// Allows Universal Control functionality between the Mac and compatible Apple devices.
```

Allow authorization to connect USB devices

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
// Allows users to authorize newly connected USB and Thunderbolt accessories, as well as supported removable media such as SD cards.
```

Allow modifying Wallpaper

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
// Allows users to change the Mac's desktop wallpaper.
```

Force on-device only dictation

```
000 Master Status: Disabled
```

```
001 Pre-Enrollment Status: Disabled
```

```
002 Post-Enrollment Status: Disabled
```

```
// Dictation is not forced to operate exclusively on-device. Where supported by macOS, Siri/Apple server-based processing may still be used.
```

Allow iPhone Mirroring

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
// Allows users to use iPhone Mirroring with a compatible iPhone.
```

Allow Remote Management Sharing modification

```
000 Master Status: Restricted
```

```
001 Pre-Enrollment Status: Restricted
```

```
002 Post-Enrollment Status: Restricted
```

```
// Prevents users from changing Remote Management sharing settings in System Settings.
```

Allow Bluetooth Sharing modification

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows users to modify Bluetooth Sharing settings.
```

Allow File Sharing modification

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows users to modify File Sharing settings.
```

Allow Internet Sharing modification

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows users to modify Internet Sharing settings.
```

Allow local user creation

```
000 Master Status: Restricted
```

```
001 Pre-Enrollment Status: Restricted
```

```
002 Post-Enrollment Status: Restricted
```

```
| // Prevents users from creating additional local user accounts through System Settings.
```

Allow Printer Sharing modification

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows users to modify Printer Sharing settings.
```

Allow Remote Apple Events Sharing modification

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows users to modify Remote Apple Events sharing settings.
```

Allow Startup Disk modification

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows users to modify Startup Disk settings.
```

Allow Time Machine backup

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows users to configure and use Time Machine backups.
```

APPLICATION

Allow Game Center

```
000 Master Status: Restricted
001 Pre-Enrollment Status: Restricted
002 Post-Enrollment Status: Restricted

| // Disables Game Center functionality on the Mac.
```

Allow adding Game Center friends

```
000 Master Status: Restricted
001 Pre-Enrollment Status: Restricted
002 Post-Enrollment Status: Restricted

| // Prevents users from adding friends through Game Center. Game Center itself is also restricted
| by the parent Game Center setting.
```

Allow multiplayer gaming

```
000 Master Status: Restricted
001 Pre-Enrollment Status: Restricted
002 Post-Enrollment Status: Restricted

| // Prevents multiplayer gaming through Game Center. Game Center itself is also restricted by the
| parent Game Center setting.
```

Allow Siri

```
000 Master Status: Allowed
001 Pre-Enrollment Status: Allowed
002 Post-Enrollment Status: Allowed

| // Allows users to access and use Siri.
```

Enable Siri profanity filter assistant

```
000 Master Status: Disabled
001 Pre-Enrollment Status: Disabled
002 Post-Enrollment Status: Disabled

| // Does not force Siri and Dictation to use Apple's profanity filtering functionality.
```

Allow iBooks Store

```
000 Master Status: Restricted
001 Pre-Enrollment Status: Restricted
002 Post-Enrollment Status: Restricted

| // Prevents access to the Book Store within the Apple Books application.
```

Allow Apple Music

```
000 Master Status: Restricted
001 Pre-Enrollment Status: Restricted
002 Post-Enrollment Status: Restricted
```

```
// Disables the Apple Music subscription/service functionality. The Music application may still retain functionality for locally stored or otherwise permitted media.
```

Enable Autofill on Safari

```
000 Master Status: Disabled
```

```
001 Pre-Enrollment Status: Disabled
```

```
002 Post-Enrollment Status: Disabled
```

```
// Disables Safari's built-in AutoFill functionality for passwords, contact information, and credit cards. This also prevents use of iCloud Keychain for Safari AutoFill while still permitting supported third-party password managers.
```

SECURITY & PRIVACY

Allow auto unlock

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
// Allows supported automatic device-unlock functionality.
```

Allow Touch ID / Face ID to unlock device

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
// Allows biometric authentication, such as Touch ID, to be used for unlocking the Mac where supported.
```

Allow modifying passcode

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
// Allows users to add, change, or remove their local account password/passcode.
```

Allow modifying Touch ID / Face ID

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
// Allows users to enroll, remove, and otherwise modify Touch ID or other supported biometric authentication settings.
```

Allow password autofill

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
// Allows password AutoFill functionality, including compatible Apple and third-party password-management solutions.
```

Allow proximity based password sharing requests

000 Master Status: **Restricted**

001 Pre-Enrollment Status: **Restricted**

002 Post-Enrollment Status: **Restricted**

| // Prevents the Mac from requesting passwords from nearby Apple devices through proximity-based password sharing.

Allow password sharing

000 Master Status: **Restricted**

001 Pre-Enrollment Status: **Restricted**

002 Post-Enrollment Status: **Restricted**

| // Prevents users from sharing passwords using Apple's password-sharing functionality.

Enforced Fingerprint Timeout (seconds)

000 Master Status: **172800 seconds / 48 hours**

001 Pre-Enrollment Status: **172800 seconds / 48 hours**

002 Post-Enrollment Status: **172800 seconds / 48 hours**

| // Defines how long biometric authentication may continue to be used before the user's password must be entered again. The configured value of 172800 seconds equals 48 hours.

Bypass user notification when using screen capture

000 Master Status: **Enabled**

001 Pre-Enrollment Status: **Enabled**

002 Post-Enrollment Status: **Enabled**

| // Suppresses the normal user-facing notification or alert associated with managed screen-capture activity where supported by macOS.

MEDIA

Allow explicit sexual content in Apple Books

000 Master Status: **Allowed**

001 Pre-Enrollment Status: **Allowed**

002 Post-Enrollment Status: **Allowed**

| // Allows Apple Books content that has been classified or tagged as explicit/erotic content.

Allow playback of explicit music, podcasts & iTunes U media

000 Master Status: **Allowed**

001 Pre-Enrollment Status: **Allowed**

002 Post-Enrollment Status: **Allowed**

| // Allows playback of music, podcasts, and other supported media marked as explicit by the content provider.

Allowed content ratings - Apps

000 Master Status: All

001 Pre-Enrollment Status: All

002 Post-Enrollment Status: All

| // No application content-rating restriction is imposed through this setting.

Allowed content ratings - Movies

000 Master Status: All

001 Pre-Enrollment Status: All

002 Post-Enrollment Status: All

| // No movie content-rating restriction is imposed through this setting.

Allowed content ratings - TV Shows

000 Master Status: All

001 Pre-Enrollment Status: All

002 Post-Enrollment Status: All

| // No television content-rating restriction is imposed through this setting.

Allow Media Sharing modification

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows users to modify Media Sharing settings.

ICLOUD

Allow iCloud Address Book

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows Contacts/Address Book synchronization through supported personal iCloud accounts.

Allow iCloud Bookmark

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows bookmark synchronization through iCloud.

Allow iCloud Calendar

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows Calendar synchronization through iCloud.

Allow iCloud Desktop and Document

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows the Desktop and Documents folders to synchronize through iCloud Drive.

Allow iCloud Keychain sync

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows iCloud Keychain synchronization for supported personal Apple Accounts.

Allow iCloud Mail

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows use of iCloud Mail services.

Allow iCloud Notes

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows Notes synchronization through iCloud.

Allow iCloud Photo Library

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows use of iCloud Photos and iCloud Photo Library.

Allow iCloud Private Relay

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows iCloud Private Relay for supported personal Apple Accounts.

Allow iCloud Reminder

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows Reminders synchronization through iCloud.

Allow cloud document sync

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

```
// Allows document and key-value synchronization through iCloud for supported personal Apple Accounts.
```

Allow iCloud Freeform

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

```
// Allows Freeform documents and data to synchronize through iCloud.
```

Implementation Note:

```
// Individual iCloud services are allowed by this Restrictions payload; however, "Allow modifying account settings" is restricted. As a result, allowing an iCloud service does not necessarily mean that users are able to independently add or modify an Apple Account on the device.
```

CLASSROOM

Allow AirPlay screen view

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

```
// Allows remote screen observation through Apple's Classroom functionality.
```

Allow Classroom screen view without prompting

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

```
// Allows an authorized Classroom teacher to observe the student's screen without requiring the user to approve each individual request.
```

Automatically join Classroom classes without prompting

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

```
// Does not automatically allow the Mac to join Classroom classes without prompting the user.
```

Require teacher permission to leave Classroom unmanaged classes

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

```
// Users are not required by this setting to obtain teacher permission before leaving an unmanaged Classroom course.
```

Allow Classroom to lock apps or the device without prompting

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

| // Classroom is not permitted by this setting to silently lock an application or the entire device without prompting the user.

APPLE INTELLIGENCE

Allow Genmoji

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows users to create and use Genmoji through Apple Intelligence.

Allow Image Playground

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows use of Apple's Image Playground and supported image-generation functionality.

Allow Writing Tools

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows Apple Intelligence Writing Tools, including supported rewriting, proofreading, summarization, and related functionality.

Allow Mail summary

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows users to generate Apple Intelligence summaries of supported Mail messages.

Allow external intelligence integrations

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

| // Allows Apple Intelligence and Siri to communicate with supported external cloud-based intelligence services.

Allow external intelligence integrations sign-in

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

```
| // Allows users to sign in to supported external intelligence providers rather than being forced  
| to use them anonymously.
```

Allowed External Intelligence Workspace IDs

```
000 Master Status: None Configured
```

```
001 Pre-Enrollment Status: None Configured
```

```
002 Post-Enrollment Status: None Configured
```

```
| // No external intelligence workspace allowlist is currently configured. If Workspace IDs are  
| added, supported external intelligence integrations can be restricted to those designated  
| workspaces.
```

Allow Notes transcription summary

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows Apple Intelligence to summarize supported transcriptions created within Notes.
```

Allow Apple Intelligence Report

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows Apple Intelligence reporting functionality provided by macOS.
```

Allow smart replies in Mail

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows Apple Intelligence-generated Smart Replies within Mail.
```

Allow transcription in Notes

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows supported audio transcription functionality within Notes.
```

Allow Safari summary

```
000 Master Status: Allowed
```

```
001 Pre-Enrollment Status: Allowed
```

```
002 Post-Enrollment Status: Allowed
```

```
| // Allows Apple Intelligence to generate summaries of supported content viewed within Safari.
```

S.I // Topic III (T.III) - macOS VPP Application Deployment

[Back to Table of Contents](#)

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

Description:

This configuration deploys required macOS applications through Apple Apps and Books (VPP).

All applications in this section use a Forced Installed assignment and are automatically installed on Mac devices scoped to any of the three applicable policies.

The same 11 VPP applications are configured in:

000 Master MacOS Policy

001 Pre-Enrollment Policy

002 Post-Enrollment Policy

Deployment Behavior:

Assignment Type: Forced Installed

Distribution Type: Apps and Books

Uninstall When No Longer Scoped: Enabled

// If a device is no longer scoped to a policy containing the application, the application is configured to be automatically removed from the device.

Platform Scope: macOS only

Applications, Deployment Status, & Application Information

MICROSOFT WORD

000 Master Status: Forced Installed

001 Pre-Enrollment Status: Forced Installed

002 Post-Enrollment Status: Forced Installed

Distribution Type: Apps and Books

Seller: Microsoft Corporation

Cost: Free

Package ID: com.microsoft.Word

Minimum OS Support: macOS 12.0

Uninstall When No Longer Scoped: Enabled

// Deploys Microsoft Word through Apple Apps and Books as a required application.

MICROSOFT EXCEL

000 Master Status: Forced Installed

001 Pre-Enrollment Status: Forced Installed

002 Post-Enrollment Status: Forced Installed

Distribution Type: Apps and Books

Seller: Microsoft Corporation

Cost: Free

Package ID: com.microsoft.Excel

Minimum OS Support: macOS 12.0

Uninstall When No Longer Scoped: Enabled

| // Deploys Microsoft Excel through Apple Apps and Books as a required application.

MICROSOFT POWERPOINT

000 Master Status: Forced Installed

001 Pre-Enrollment Status: Forced Installed

002 Post-Enrollment Status: Forced Installed

Distribution Type: Apps and Books

Seller: Microsoft Corporation

Cost: Free

Package ID: com.microsoft.Powerpoint

Minimum OS Support: macOS 12.0

Uninstall When No Longer Scoped: Enabled

| // Deploys Microsoft PowerPoint through Apple Apps and Books as a required application.

MICROSOFT ONEDRIVE

000 Master Status: Forced Installed

001 Pre-Enrollment Status: Forced Installed

002 Post-Enrollment Status: Forced Installed

Distribution Type: Apps and Books

Seller: Microsoft Corporation

Cost: Free

Package ID: com.microsoft.OneDrive-mac

Minimum OS Support: macOS 12.3

Uninstall When No Longer Scoped: Enabled

| // Deploys Microsoft OneDrive through Apple Apps and Books as a required application.

MICROSOFT ONENOTE

000 Master Status: Forced Installed

001 Pre-Enrollment Status: Forced Installed

002 Post-Enrollment Status: Forced Installed

Distribution Type: Apps and Books

Seller: Microsoft Corporation

Cost: Free

Package ID: com.microsoft.onenote.mac

Minimum OS Support: macOS 12.0

Uninstall When No Longer Scoped: Enabled

```
| // Deploys Microsoft OneNote through Apple Apps and Books as a required application.
```

MEETING OWL

000 Master Status: Forced Installed

001 Pre-Enrollment Status: Forced Installed

002 Post-Enrollment Status: Forced Installed

Distribution Type: Apps and Books

Seller: Owl Labs

Cost: Free

Package ID: com.owllabs.meeting.owl

Minimum OS Support: macOS 12.0

Uninstall When No Longer Scoped: Enabled

```
| // Deploys the Meeting Owl application used with supported Owl Labs conferencing hardware.
```

404 NETWORK

000 Master Status: Forced Installed

001 Pre-Enrollment Status: Forced Installed

002 Post-Enrollment Status: Forced Installed

Distribution Type: Apps and Books

Seller: Christine Martin

Cost: Free

Package ID: com.lorislabs.app404

Minimum OS Support: macOS 26.2

Uninstall When No Longer Scoped: Enabled

```
| // Deploys the 404 Network application through Apple Apps and Books as a required application.
```

HP SMART FOR DESKTOP

000 Master Status: Forced Installed

001 Pre-Enrollment Status: Forced Installed

002 Post-Enrollment Status: Forced Installed

Distribution Type: Apps and Books

Seller: HP Inc.

Cost: Free

Package ID: com.hp.SmartMac

Minimum OS Support: macOS 11.0

Uninstall When No Longer Scoped: Enabled

```
| // Deploys HP Smart for Desktop for supported HP printer setup, management, and related functionality.
```

SLACK FOR DESKTOP

000 Master Status: Forced Installed

001 Pre-Enrollment Status: Forced Installed

002 Post-Enrollment Status: Forced Installed

Distribution Type: Apps and Books

Seller: Slack Technologies, Inc.

Cost: Free

Package ID: com.tinyspeck.slackmacgap

Minimum OS Support: macOS 11.0

Uninstall When No Longer Scoped: Enabled

| // Deploys the Slack desktop application through Apple Apps and Books as a required application.

MICROSOFT OUTLOOK

000 Master Status: Forced Installed

001 Pre-Enrollment Status: Forced Installed

002 Post-Enrollment Status: Forced Installed

Distribution Type: Apps and Books

Seller: Microsoft Corporation

Cost: Free

Package ID: com.microsoft.Outlook

Minimum OS Support: macOS 12.0

Uninstall When No Longer Scoped: Enabled

| // Deploys Microsoft Outlook through Apple Apps and Books as a required application.

1PASSWORD FOR SAFARI [Extension]

000 Master Status: Forced Installed

001 Pre-Enrollment Status: Forced Installed

002 Post-Enrollment Status: Forced Installed

Distribution Type: Apps and Books

Seller: AgileBits Inc.

Cost: Free

Package ID: com.1password.safari

Minimum OS Support: macOS 11.0

Uninstall When No Longer Scoped: Enabled

| // Deploys the 1Password for Safari application/extension through Apple Apps and Books as a required application.

S.I // Topic IV (T.IV) - Network / Wi-Fi Configuration

[Back to Table of Contents](#)

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

Description:

This configuration deploys the organization's managed Wi-Fi network configuration to macOS devices.

The same Wi-Fi network configuration is present in:

000 Master MacOS Policy

001 Pre-Enrollment Policy

002 Post-Enrollment Policy

No Global Proxy configuration is defined within this section.

Configured Wi-Fi Networks

TOW FOUNDATION TEAM WIFI

000 Master Status: Configured

001 Pre-Enrollment Status: Configured

002 Post-Enrollment Status: Configured

Configuration Name: Tow Foundation Team Wifi

Wi-Fi Name (SSID): TFTeam

Security: Any

Password: Configured / Redacted

```
// Defines the managed Wi-Fi network configuration for the TFTeam wireless network. The
// configured password is stored within the policy but is intentionally omitted from documentation.
```

Auto join = Disabled

```
// The Mac is not explicitly instructed by this configuration to automatically join the TFTeam
// network whenever it is available.
```

Enable IPv6 = Enabled

```
// Allows IPv6 networking to remain enabled for this Wi-Fi configuration.
```

Hidden network = Disabled

```
// The TFTeam SSID is not designated as a hidden network. The network is expected to advertise
// its SSID normally.
```

Hotspot = Disabled

```
// The Wi-Fi configuration is not designated as a hotspot network.
```

Disable random MAC address = Disabled

```
// Randomized/private MAC addressing is not disabled by this configuration. macOS may therefore
// continue using its supported private Wi-Fi address behavior.
```

Proxy = None

```
| // No per-network proxy configuration is defined for the TFTeam Wi-Fi network.
```

GLOBAL PROXY

```
000 Master Status: Not Configured
```

```
001 Pre-Enrollment Status: Not Configured
```

```
002 Post-Enrollment Status: Not Configured
```

```
| // No Global Proxy configuration has been added to any of the three macOS policies. Network  
| traffic is therefore not routed through an MDM-defined global proxy by this policy section.
```

S.I // Topic V (T.V) - OS Updates

[Back to Table of Contents](#)

000 Master Status: Configured

001 Pre-Enrollment Status: Configured

002 Post-Enrollment Status: Configured

Description:

This configuration controls macOS software-update behavior, including when users may install updates, whether updates are downloaded or installed automatically, Rapid Security Response behavior, major-version deferrals, and manually enforced or rejected operating-system updates.

The configuration separates update behavior into:

- User behavior
- Device behavior
- Enforced updates

The values below represent the currently configured settings within the 000 Master MacOS Policy.

Settings, Configured Values, & their Descriptions

USER BEHAVIOR

Delay when new major macOS upgrades can be self-installed

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

Configured Delay: 90 days

```
// Prevents newly released major macOS versions from becoming available for user-initiated
installation until 90 days after Apple makes the upgrade available.
```

```
// This provides a testing and compatibility-validation period before users may independently
upgrade to a new major macOS release.
```

Delay when new minor macOS updates can be self-installed

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

```
// Minor macOS updates are not intentionally deferred through this setting. Users may install
them when they become available, subject to any other update-management rules or enforced-update
configuration.
```

Delay when new non-OS software updates can be self-installed

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

```
// Non-OS software updates delivered through Apple's software-update mechanism are not intentionally deferred through this setting.
```

Allow user to install beta OS versions (macOS 15+)

```
000 Master Status: Always Off
```

```
001 Pre-Enrollment Status: Always Off
```

```
002 Post-Enrollment Status: Always Off
```

```
// Prevents users from enabling or installing beta macOS releases through the normal Software Update interface.
```

Allow the user to install Rapid Security Responses

```
000 Master Status: Enabled
```

```
001 Pre-Enrollment Status: Enabled
```

```
002 Post-Enrollment Status: Enabled
```

```
// Allows users to install Apple's Rapid Security Responses when they are made available for the installed macOS version.
```

Allow the user to remove Rapid Security Responses

```
000 Master Status: Disabled
```

```
001 Pre-Enrollment Status: Disabled
```

```
002 Post-Enrollment Status: Disabled
```

```
// Prevents users from removing or rolling back an installed Rapid Security Response through normal user-facing controls.
```

Allow standard user accounts to self-install OS updates (macOS 15+)

```
000 Master Status: Enabled
```

```
001 Pre-Enrollment Status: Enabled
```

```
002 Post-Enrollment Status: Enabled
```

```
// Allows non-administrator standard user accounts to initiate and install supported macOS operating-system updates without requiring elevation to a local administrator account.
```

Show additional notifications for scheduled updates (macOS 15+)

```
000 Master Status: Disabled
```

```
001 Pre-Enrollment Status: Disabled
```

```
002 Post-Enrollment Status: Disabled
```

```
// Additional macOS notifications specifically associated with scheduled updates are not enabled by this configuration.
```

DEVICE BEHAVIOR

Automatically download new macOS updates when available (macOS 15+)

```
000 Master Status: Always On
```

```
001 Pre-Enrollment Status: Always On
```

```
002 Post-Enrollment Status: Always On
```

```
// Requires macOS to automatically download available operating-system updates in the background.
```

```
// This reduces the amount of time required to begin installation once an update is approved,  
scheduled, or initiated by the user.
```

Automatically install macOS updates (macOS 15+)

000 Master Status: Allowed

001 Pre-Enrollment Status: Allowed

002 Post-Enrollment Status: Allowed

```
// Allows macOS to automatically install operating-system updates.  
  
// "Allowed" permits automatic installation but does not by itself mean that every available  
macOS update is forcibly or immediately installed. Installation behavior may also be affected by  
Apple's update logic and the enforced-update configuration below.
```

Automatically install Security Responses and system files (macOS 15+)

000 Master Status: Always On

001 Pre-Enrollment Status: Always On

002 Post-Enrollment Status: Always On

```
// Requires macOS to automatically install supported security responses and Apple-provided  
system-data/security-file updates.  
  
// These updates may be delivered independently from full macOS operating-system updates and are  
intended to address security or system-level issues more quickly.
```

ENFORCED UPDATES

Manually scheduled updates

000 Master Status: Configured

001 Pre-Enrollment Status: Configured

002 Post-Enrollment Status: Configured

Approved Updates: Changes over time

Rejected Updates: Changes over time

```
// The policy contains manually defined update-management rules consisting of one approved update  
and seven rejected updates.  
  
// Approved updates are explicitly permitted within the enforced-update configuration.  
// Rejected updates are explicitly excluded from installation through this configuration.  
  
// The screenshot provided displays only the summary count of approved and rejected updates. The  
specific macOS versions represented by the 1 approved and 7 rejected entries are not visible in  
the current view and should be documented separately after opening the "Edit" configuration.
```

S.I // Topic VI (T.VI) - Encryption / FileVault

[Back to Table of Contents](#)

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

Description:

This configuration manages FileVault full-disk encryption on managed macOS devices.

FileVault encryption is required across all three macOS policies. Devices are configured to enable FileVault during Setup Assistant for new enrollments or during login when applicable, and the resulting personal recovery key is escrowed to NinjaOne for administrative recovery purposes.

The same FileVault configuration is present in:

000 Master MacOS Policy

001 Pre-Enrollment Policy

002 Post-Enrollment Policy

Settings, Configured Values, & their Descriptions

FILEVAULT

Require encryption

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

// Requires managed devices to enable FileVault full-disk encryption.

// Depending on the device's enrollment state and configuration, FileVault activation occurs during Setup Assistant or is initiated during a subsequent user login.

Escrow recovery key

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

// Requires the FileVault personal recovery key generated for each encrypted Mac to be reported to and stored by NinjaOne.

// The escrowed recovery key can be retrieved from the applicable device's details within NinjaOne for administrative recovery purposes.

// If recovery-key escrow were later disabled, devices that previously reported their key would no longer continue reporting future recovery-key changes. If the key changed afterward, NinjaOne would not receive the new value unless the device were re-enrolled or otherwise caused to escrow the new key again.

Force enable in Setup Assistant

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// Configures FileVault to be enabled during Setup Assistant for newly enrolled devices.  
// This causes encryption enablement to occur as part of the initial device onboarding process  
rather than relying solely on a later user-login prompt.
```

Show recovery key**000 Master Status: Disabled****001 Pre-Enrollment Status: Disabled****002 Post-Enrollment Status: Disabled**

```
// The FileVault personal recovery key is not displayed to the end user after encryption is  
completed.  
// Recovery-key custody is instead handled through the configured NinjaOne escrow process.
```

Number of allowed deferrals**000 Master Status: 0****001 Pre-Enrollment Status: 0****002 Post-Enrollment Status: 0**

```
// Defines how many times a user may postpone the FileVault enablement prompt.  
// A value of 0 means no deferrals are permitted. When FileVault enablement is required and has  
not already occurred during Setup Assistant, the user is prompted to enable FileVault at the next  
applicable login.  
// NinjaOne also supports a value of -1 for unlimited deferrals, but that behavior is not  
configured here.
```

Defer don't ask at user logout**000 Master Status: Enabled****001 Pre-Enrollment Status: Enabled****002 Post-Enrollment Status: Enabled**

```
// Prevents the FileVault enablement prompt from appearing during user logout.  
// If FileVault still needs to be enabled, the user is prompted during login rather than during  
logout.
```

EFFECTIVE FILEVAULT BEHAVIOR

```
// FileVault encryption is mandatory on managed macOS devices.  
// New enrollments are configured to enable FileVault during Setup Assistant.  
// If encryption still requires user interaction after enrollment, no user deferrals are  
permitted.  
// FileVault prompts are presented at login rather than logout.  
// The personal recovery key is automatically escrowed to NinjaOne.  
// The personal recovery key is not displayed to the end user after encryption.
```

S.I // Topic VII (T.VII) - Privacy Preferences

[Back to Table of Contents](#)

000 Master Status: Configured

001 Pre-Enrollment Status: Configured

002 Post-Enrollment Status: Configured

Description:

This configuration manages macOS Privacy Preferences Policy Control (PPPC) permissions for specifically identified applications.

These entries grant or permit access to protected macOS privacy services such as Accessibility, Screen Capture, Listen Event, All Files, System Administration, and Bluetooth.

Each application is identified using its Bundle ID and Apple code-signing requirement so that the permissions apply only to the intended signed application.

The same six Privacy Preference entries are configured in:

000 Master MacOS Policy

001 Pre-Enrollment Policy

002 Post-Enrollment Policy

These entries are configured through NinjaOne's native Privacy Preferences configuration interface. Privacy permissions delivered separately through Custom Payloads are documented independently in a later section.

Authorization Behavior:

Allow

```
// The specified privacy permission is pre-authorized for the identified application through MDM
and does not require the user to manually grant the permission where macOS permits MDM
authorization.
```

Allow standard user to enable

```
// The permission is not silently enabled outright. Instead, macOS permits a standard user to
enable the specified privacy permission without requiring administrator authorization. This is
commonly used for privacy services such as Screen Capture where Apple requires user interaction.
```

Statically validate the code requirement

```
// When enabled, NinjaOne would perform static validation against the supplied code requirement.
This option is disabled for all entries documented below.
```

Applications, Identifiers, Code Requirements, & Privacy Preferences

LOGITECH ONBOARDING

000 Master Status: Configured

001 Pre-Enrollment Status: Configured

002 Post-Enrollment Status: Configured

App Name: Logitech Onboarding

Identifier Type: Bundle ID

Identifier: com.logitech.Onboarding

Code Requirement:

```

identifier "com.logitech.Onboarding" and anchor apple generic and certificate
1[field.1.2.840.113635.100.6.2.6] /* exists */ and certificate
leaf[field.1.2.840.113635.100.6.1.13] /* exists */ and certificate leaf[subject.OU] =
QED4VVPZWA

```

Statically Validate Code Requirement: **Disabled**

```

// The code requirement ensures the PPPC permissions apply specifically to the correctly signed
Logitech Onboarding application.

```

Accessibility

000 Master Status: Allow

001 Pre-Enrollment Status: Allow

002 Post-Enrollment Status: Allow

```

// Grants Logitech Onboarding Accessibility permission, allowing the application to perform
supported accessibility-controlled interactions with the macOS user interface.

```

Listen Event

000 Master Status: Allow standard user to enable

001 Pre-Enrollment Status: Allow standard user to enable

002 Post-Enrollment Status: Allow standard user to enable

```

// Allows a standard user to enable Listen Event/Input Monitoring-related access for Logitech
Onboarding without requiring administrator elevation.

```

Screen Capture

000 Master Status: Allow standard user to enable

001 Pre-Enrollment Status: Allow standard user to enable

002 Post-Enrollment Status: Allow standard user to enable

```

// Allows a standard user to enable Screen Recording/Screen Capture access for Logitech
Onboarding without requiring administrator elevation.

```

MICROSOFT TEAMS

000 Master Status: Configured

001 Pre-Enrollment Status: Configured

002 Post-Enrollment Status: Configured

App Name: Microsoft Teams

Identifier Type: Bundle ID

Identifier: com.microsoft.teams2

Code Requirement:

```

identifier "com.microsoft.teams2" and anchor apple generic and certificate
1[field.1.2.840.113635.100.6.2.6] /* exists */ and certificate
leaf[field.1.2.840.113635.100.6.1.13] /* exists */ and certificate leaf[subject.OU] =
UBF8T346G9

```

Statically Validate Code Requirement: **Disabled**

```
// The code requirement ensures the PPPC permissions apply specifically to the correctly signed
Microsoft Teams application.
```

Accessibility

000 Master Status: Allow

001 Pre-Enrollment Status: Allow

002 Post-Enrollment Status: Allow

```
// Grants Microsoft Teams Accessibility permission for supported interactions requiring macOS
Accessibility access.
```

Screen Capture

000 Master Status: Allow standard user to enable

001 Pre-Enrollment Status: Allow standard user to enable

002 Post-Enrollment Status: Allow standard user to enable

```
// Allows a standard user to enable Screen Recording/Screen Capture permission for Microsoft
Teams without requiring administrator elevation.
```

```
// This permission is required for supported meeting screen-sharing and presentation
functionality.
```

All Files

000 Master Status: Allow

001 Pre-Enrollment Status: Allow

002 Post-Enrollment Status: Allow

```
// Grants Microsoft Teams access to protected file locations covered by macOS All Files / Full
Disk Access privacy controls where required by the application.
```

LOGITECH PRESENTER

000 Master Status: Configured

001 Pre-Enrollment Status: Configured

002 Post-Enrollment Status: Configured

App Name: Logitech Presenter

Identifier Type: Bundle ID

Identifier: com.logitech.presenter

Code Requirement:

```
identifier "com.logitech.presenter" and anchor apple generic and certificate
1[field.1.2.840.113635.100.6.2.6] /* exists */ and certificate
leaf[field.1.2.840.113635.100.6.1.13] /* exists */ and certificate leaf[subject.OU] =
QED4VVPZWA
```

Statically Validate Code Requirement: Disabled

```
// The code requirement ensures the PPPC permissions apply specifically to the correctly signed
Logitech Presenter application.
```

Screen Capture

000 Master Status: Allow standard user to enable

001 Pre-Enrollment Status: Allow standard user to enable

002 Post-Enrollment Status: Allow standard user to enable

```
// Allows a standard user to enable Screen Recording/Screen Capture permission for Logitech Presenter without requiring administrator elevation.
```

Accessibility

000 Master Status: Allow

001 Pre-Enrollment Status: Allow

002 Post-Enrollment Status: Allow

```
// Grants Logitech Presenter Accessibility permission for supported application interactions with the macOS user interface.
```

Listen Event

000 Master Status: Allow standard user to enable

001 Pre-Enrollment Status: Allow standard user to enable

002 Post-Enrollment Status: Allow standard user to enable

```
// Allows a standard user to enable Listen Event/Input Monitoring-related access for Logitech Presenter without requiring administrator elevation.
```

NCSTREAMER

000 Master Status: Configured

001 Pre-Enrollment Status: Configured

002 Post-Enrollment Status: Configured

App Name: NCStreamer

Identifier Type: Bundle ID

Identifier: com.ninjarmm.ncstreamer

Code Requirement:

```
identifier "com.ninjarmm.ncstreamer" and anchor apple generic and certificate
1[field.1.2.840.113635.100.6.2.6] /* exists */ and certificate
leaf[field.1.2.840.113635.100.6.1.13] /* exists */ and certificate leaf[subject.OU] =
EBNT3ZX97E
```

Statically Validate Code Requirement: Disabled

```
// The code requirement ensures the PPPC permissions apply specifically to the correctly signed NinjaOne NCStreamer application.
```

Accessibility

000 Master Status: Allow

001 Pre-Enrollment Status: Allow

002 Post-Enrollment Status: Allow

```
// Grants NCStreamer Accessibility permission, allowing the remote-access component to perform supported interactions with the macOS user interface.
```

All Files

000 Master Status: Allow

001 Pre-Enrollment Status: Allow

002 Post-Enrollment Status: Allow

```
// Grants NCStreamer access to protected file locations covered by macOS All Files / Full Disk
Access privacy controls.
```

Screen Capture

000 Master Status: Allow standard user to enable

001 Pre-Enrollment Status: Allow standard user to enable

002 Post-Enrollment Status: Allow standard user to enable

```
// Allows a standard user to enable Screen Recording/Screen Capture permission for NCStreamer
without requiring administrator elevation.
```

```
// This permission enables supported remote-session screen viewing once the user has enabled the
applicable macOS privacy permission.
```

COMPANY PORTAL

000 Master Status: Configured

001 Pre-Enrollment Status: Configured

002 Post-Enrollment Status: Configured

App Name: Company Portal

Identifier Type: Bundle ID

Identifier: com.microsoft.CompanyPortalMac

Code Requirement:

```
identifier "com.microsoft.CompanyPortalMac" and anchor apple generic and certificate
1[field.1.2.840.113635.100.6.2.6] /* exists */ and certificate
leaf[field.1.2.840.113635.100.6.1.13] /* exists */ and certificate leaf[subject.OU] =
UBF8T346G9
```

Statically Validate Code Requirement: Disabled

```
// The code requirement ensures the PPPC permissions apply specifically to the correctly signed
Microsoft Company Portal application.
```

All Files

000 Master Status: Allow

001 Pre-Enrollment Status: Allow

002 Post-Enrollment Status: Allow

```
// Grants Company Portal access to protected file locations covered by macOS All Files / Full
Disk Access privacy controls where required for device registration and management functionality.
```

System Administration

000 Master Status: Allow

001 Pre-Enrollment Status: Allow

002 Post-Enrollment Status: Allow

```
// Grants Company Portal access to protected system-administration-related files and resources
controlled by macOS privacy protections.
```

Bluetooth

```
000 Master Status: Allow
001 Pre-Enrollment Status: Allow
002 Post-Enrollment Status: Allow
```

```
// Grants Company Portal access to Bluetooth-related functionality controlled by macOS privacy
protections.
```

ZOOM

```
000 Master Status: Configured
001 Pre-Enrollment Status: Configured
002 Post-Enrollment Status: Configured
```

```
App Name: Zoom
```

```
Identifier Type: Bundle ID
```

```
Identifier: us.zoom.xos
```

Code Requirement:

```
identifier "us.zoom.xos" and anchor apple generic and certificate
1[field.1.2.840.113635.100.6.2.6] /* exists */ and certificate
leaf[field.1.2.840.113635.100.6.1.13] /* exists */ and certificate leaf[subject.OU] =
BJ4HAAB9B3
```

```
Statically Validate Code Requirement: Disabled
```

```
// The code requirement ensures the PPPC permissions apply specifically to the correctly signed
Zoom application.
```

Accessibility

```
000 Master Status: Allow
001 Pre-Enrollment Status: Allow
002 Post-Enrollment Status: Allow
```

```
// Grants Zoom Accessibility permission for supported Zoom functionality requiring interaction
with the macOS user interface.
```

Screen Capture

```
000 Master Status: Allow standard user to enable
001 Pre-Enrollment Status: Allow standard user to enable
002 Post-Enrollment Status: Allow standard user to enable
```

```
// Allows a standard user to enable Screen Recording/Screen Capture permission for Zoom without
requiring administrator elevation.
```

```
// This permits supported screen-sharing functionality after the user enables the corresponding
macOS privacy permission.
```

S.I // Topic VIII (T.VIII) - System Extensions

[Back to Table of Contents](#)

000 Master Status: Configured

001 Pre-Enrollment Status: Configured

002 Post-Enrollment Status: Configured

Description:

This configuration defines which developer-signed macOS System Extensions are permitted to load on managed devices.

System Extensions are modern macOS extensions used by applications for functionality such as endpoint security, networking, authentication, device control, and other privileged system-level operations.

The same System Extension configuration is present in:

000 Master MacOS Policy

001 Pre-Enrollment Policy

002 Post-Enrollment Policy

Settings, Configured Values, & their Descriptions

GENERAL SYSTEM EXTENSION BEHAVIOR

Allow user to approve additional System extensions

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

// Prevents users from independently approving additional System Extensions that are not already authorized through the managed System Extension configuration.

// Only extensions allowed by the configured Team ID entries below are intended to be permitted without requiring unmanaged user approval.

MICROSOFT

000 Master Status: Allow all system extensions

001 Pre-Enrollment Status: Allow all system extensions

002 Post-Enrollment Status: Allow all system extensions

Display Name: Microsoft

Team ID: UBF8T346G9

Type: Allow all system extensions

// Allows all macOS System Extensions signed by Microsoft's Apple Developer Team ID UBF8T346G9.

// This avoids requiring each individual Microsoft System Extension identifier to be separately listed within the policy.

BITDEFENDER

000 Master Status: Allow all system extensions

001 Pre-Enrollment Status: Allow all system extensions

002 Post-Enrollment Status: Allow all system extensions

Display Name: BitDefender

Team ID: GUNFMW623Y

Type: Allow all system extensions

```
// Allows all macOS System Extensions signed by Bitdefender's Apple Developer Team ID GUNFMW623Y.  
// This permits Bitdefender components that rely on System Extensions to load without requiring  
separate user approval.
```

NINJAONE

000 Master Status: Allow all system extensions

001 Pre-Enrollment Status: Allow all system extensions

002 Post-Enrollment Status: Allow all system extensions

Display Name: NinjaOne

Team ID: EBNT3ZX97E

Type: Allow all system extensions

```
// Allows all macOS System Extensions signed by NinjaOne's Apple Developer Team ID EBNT3ZX97E.  
// This permits NinjaOne management and remote-support components that rely on System Extensions  
to load without requiring separate user approval.
```

1PASSWORD

000 Master Status: Allow all system extensions

001 Pre-Enrollment Status: Allow all system extensions

002 Post-Enrollment Status: Allow all system extensions

Display Name: 1Password

Team ID: 2BUA8C4S2C

Type: Allow all system extensions

```
// Allows all macOS System Extensions signed by 1Password's Apple Developer Team ID 2BUA8C4S2C.  
// This permits supported 1Password components requiring System Extension authorization to load  
without requiring separate user approval.
```

LOGITECH

000 Master Status: Allow all system extensions

001 Pre-Enrollment Status: Allow all system extensions

002 Post-Enrollment Status: Allow all system extensions

Display Name: Logitech

Team ID: QED4VVPZWA

Type: Allow all system extensions

```
// Allows all macOS System Extensions signed by Logitech's Apple Developer Team ID QED4VVPZWA.
```

```
// This permits supported Logitech software components requiring System Extension authorization  
to load without requiring separate user approval.
```

EFFECTIVE SYSTEM EXTENSION BEHAVIOR

```
// Users are not permitted to independently approve additional System Extensions outside the  
managed allowlist.
```

```
// All System Extensions signed by the following approved developer Team IDs are permitted:
```

Microsoft: **UBF8T346G9**

BitDefender: **GUNFMW623Y**

NinjaOne: **EBNT3ZX97E**

1Password: **2BUA8C4S2C**

Logitech: **QED4VVPZWA**

```
// Because each entry is configured as "Allow all system extensions," authorization is based on  
the developer Team ID rather than individual System Extension bundle identifiers.
```

S.I // Topic IX (T.IX) - Custom Payloads

[Back to Table of Contents](#)

000 Master Status: Configured

001 Pre-Enrollment Status: Configured / Contains Overrides

002 Post-Enrollment Status: Configured / Contains Overrides

Description:

This configuration contains custom MDM payloads that are deployed directly through the NinjaOne macOS policy.

All custom payloads listed below are enabled at the 000 Master MacOS Policy level.

Some payloads are intentionally overridden and disabled within the 001 Pre-Enrollment Policy or 002 Post-Enrollment Policy depending on when the configuration should become active during the device enrollment lifecycle.

The specific effective status of each payload is therefore documented individually below.

Each payload will also include or reference:

- The raw custom payload file
- A detailed explanation document describing the payload's purpose, configuration, behavior, dependencies, and implementation logic

These supporting files serve as the detailed technical documentation for each payload, while this section documents policy-level inclusion and lifecycle status.

Custom Payloads & Policy Status

001 // AUTHENTICATION | PASSWORD SYNCHRONIZATION W/ COMPANY PORTAL V2.1 [PSS0]

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Disabled

// Custom Platform SSO payload related to Company Portal-based password synchronization.

// Detailed configuration, behavior, and implementation logic are documented in the associated explanation document and raw payload file.

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

001 // AUTHENTICATION | SECURE ENCLAVE W/ COMPANY PORTAL V2.3 [PSS0]

000 Master Status: Enabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Enabled

```
// Custom Platform SSO payload related to Secure Enclave authentication using Microsoft Company Portal.
```

```
// Detailed configuration, behavior, and implementation logic are documented in the associated explanation document and raw payload file.
```

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

002 // NINJAONE MDM | LOCKHART DEVICE ACCESS [PPPC]

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// Custom PPPC payload granting the required macOS privacy permissions for the Lockhart component.
```

```
// Detailed permissions, identifiers, code requirements, and implementation behavior are documented in the associated explanation document and raw payload file.
```

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

002 // NINJAONE MDM | MAC AGENT DEVICE ACCESS [PPPC]

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// Custom PPPC payload granting required macOS privacy permissions to the NinjaOne Mac Agent and related management functionality.
```

```
// Detailed permissions, identifiers, code requirements, and implementation behavior are documented in the associated explanation document and raw payload file.
```

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

003 // SYSTEM | APP STORE RESTRICTION

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// Custom system payload controlling App Store availability or behavior on managed macOS devices.  
// Exact restrictions and implementation behavior are documented in the associated explanation  
document and raw payload file.
```

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

003 // SYSTEM | DOCK LAYOUT

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// Custom payload defining the managed macOS Dock configuration and application layout.  
// Exact Dock contents, ordering, behavior, and management logic are documented in the associated  
explanation document and raw payload file.
```

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

003 // SYSTEM | LOCK SCREEN BEHAVIOR

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// Custom system payload controlling managed lock-screen behavior on macOS devices.  
// Exact behavior and configured values are documented in the associated explanation document and  
raw payload file.
```

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

003 // SYSTEM | TOGA ASSIST MENU BAR ITEM

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// Custom payload related to the TOGA Assist menu bar item and its managed macOS configuration.
```

```
// Exact behavior, deployment logic, and configured values are documented in the associated
// explanation document and raw payload file.
```

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

004 // APPLICATION | 1PASSWORD DEVICE ACCESS [PPPC]

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// Custom PPPC payload granting required macOS privacy permissions to 1Password components.
// Detailed permissions, identifiers, code requirements, and implementation behavior are
// documented in the associated explanation document and raw payload file.
```

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

004 // APPLICATION | BITDEFENDER DEVICE ACCESS [PPPC]

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// Custom PPPC payload granting required macOS privacy permissions to BitDefender components.
// Detailed permissions, identifiers, code requirements, and implementation behavior are
// documented in the associated explanation document and raw payload file.
```

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

004 // APPLICATION | BROWSER MANAGEMENT ENROLLMENT TOKEN

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// Custom application-management payload providing the browser management enrollment token used
// to enroll or associate supported managed browsers with the organization's browser-management
// environment.
```

// Exact token configuration and browser-management behavior are documented in the associated explanation document and raw payload file.

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

004 // APPLICATION | GLOBALPROTECT

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

// Custom payload containing managed configuration for the GlobalProtect application.

// Exact application settings, connection behavior, and configuration values are documented in the associated explanation document and raw payload file.

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

004 // APPLICATION | HIDE MICROSOFT AUTO UPDATE PRIVACY NOTICE

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

// Custom payload suppressing the Microsoft AutoUpdate privacy notice presented to users.

// Exact preference keys and implementation behavior are documented in the associated explanation document and raw payload file.

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

004 // APPLICATION | OUTLOOK DOMAIN RESTRICTION

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

// Custom Outlook configuration restricting or controlling which account/domain types may be used within Microsoft Outlook on managed devices.

```
// Exact domain restrictions, preference keys, and behavior are documented in the associated
// explanation document and raw payload file.
```

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

005 // PERMISSIONS | USER PRINTER ACCESS

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// Custom payload controlling user access or permissions related to printer configuration and
// usage on managed macOS devices.
```

```
// Exact permissions and implementation behavior are documented in the associated explanation
// document and raw payload file.
```

Raw Payload:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

CUSTOM PAYLOAD LIFECYCLE BEHAVIOR

```
// All 15 custom payloads are enabled at the 000 Master MacOS Policy level.
```

```
// The 001 Pre-Enrollment Policy and 002 Post-Enrollment Policy may override individual payloads
// and disable them where their configuration should not apply during that stage of the device
// lifecycle.
```

```
// A payload marked Disabled within 001 or 002 should be interpreted as an intentional policy
// override rather than removal from the overall macOS configuration architecture.
```

```
// The raw payload and explanation document associated with each entry contain the authoritative
// technical details of that payload.
```

```
// This section primarily documents:
```

```
// 1. Which custom payloads exist
```

```
// 2. Whether each payload is active within each policy
```

```
// 3. Where the detailed payload documentation is located
```

Section II (S.II) // MacOS NinjaOne Specific Configurations

NinjaOne automation, patching, security, monitoring, backup, and lifecycle architecture.

S.II // Topic I (T.I) - Conditions

[Back to Table of Contents](#)

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

Description:

This section defines NinjaOne Conditions used to evaluate device state and automatically execute associated automations when specified criteria are met.

The currently configured condition, "Enrollment Complete Automations," uses the custom device field "MacOS Enrollment Status" to determine when the macOS enrollment process has reached the Enrollment Complete state.

When the condition is met, NinjaOne executes the associated automation sequence. These automations include file transfers and shell scripts responsible for application/setup tasks, user-environment configuration, system configuration, resource deployment, and other post-enrollment actions.

The custom field "MacOS Enrollment Status," the logic responsible for populating and changing its value, and each individual automation executed by this condition are documented in greater detail within their respective later sections.

The same condition and automation configuration is active within:

000 Master MacOS Policy

001 Pre-Enrollment Policy

002 Post-Enrollment Policy

Configured Conditions

ENROLLMENT COMPLETE AUTOMATIONS

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

Condition Name: Enrollment Complete Automations

Condition Type: Custom Fields

Custom Field: MacOS Enrollment Status

Operator: Contains

Required Value: Enrollment Complete

```
// The condition becomes active when the "MacOS Enrollment Status" custom field contains the
value "Enrollment Complete."
```

```
// When this rule evaluates as true, NinjaOne executes the automations assigned to the condition.
```

CONDITION BEHAVIOR

Severity: None

```
// No NinjaOne alert severity is assigned to this condition.
```

Priority: **None**

```
| // No alert or condition priority is assigned.
```

Auto-reset After Time Period: **Disabled**

Configured Time Field: **4 hours**

```
| // Time-based auto-reset is not enabled. Although the interface displays a 4-hour value, it is
| inactive because the associated "After" option is unchecked.
```

Auto-reset When No Longer Met: **Enabled**

```
| // The condition automatically resets when the device no longer satisfies the configured
| condition.
```

```
| // In this case, if "MacOS Enrollment Status" no longer contains "Enrollment Complete," the
| condition returns to its reset state.
```

```
| // This is separate from the automation trigger itself. The automations execute when the
| condition becomes met; "When no longer met" controls when the condition resets afterward.
```

Health Status - Use Global Default: **Disabled**

Health Status: **Healthy**

```
| // Devices meeting this condition are assigned a Healthy condition health status rather than
| inheriting the global default.
```

Channels: **None Configured**

```
| // No notification or communication channels are assigned to this condition.
```

Notify Technicians: **Do Not Send Notifications**

```
| // The condition does not generate technician notifications when it is triggered.
```

ASSOCIATED AUTOMATIONS

Automation Count: **22**

```
| // NinjaOne reports 22 automations associated with the "Enrollment Complete Automations"
| condition.
```

```
| // The automation sequence contains a combination of:
```

```
| // - File transfers
```

```
| // - macOS shell scripts
```

```
| // - Device/user configuration actions
```

```
| // - Resource deployment
```

```
| // - Post-enrollment setup actions
```

```
| // Automations execute in the order defined within the condition.
```

```
| // Each individual automation, its purpose, script or transferred resource, dependencies,
| execution behavior, and expected result will be documented separately within the Automations
| section.
```

```
| // Examples of functions represented within the current automation sequence include:
```

```
| // - Deployment of wallpaper and prompt resources
```

```
| // - Rosetta installation
```

```
| // - macOS display/environment configuration
```

```
| // - Downloads folder configuration
```

```
// - Application cleanup
// - Resource-folder permissions
// - Menu bar configuration
// - Local device administrator configuration
// - Wallpaper configuration
// - Screensaver configuration
// - Default application/protocol-handler configuration
// - Standard-user printer functionality
// - Enrollment/system validation through Swift Dialog
```

CONDITION LIFECYCLE SUMMARY

```
// 1. Enrollment-related processes update the "MacOS Enrollment Status" custom field.
// 2. When the custom field contains "Enrollment Complete," the Enrollment Complete Automations
condition becomes met.
// 3. NinjaOne executes the 22 automations associated with the condition.
// 4. The condition remains in its triggered/met state while the rule continues to evaluate as
true.
// 5. If "MacOS Enrollment Status" later stops containing "Enrollment Complete," the condition
automatically resets because "When no longer met" is enabled.
// 6. Once reset, the condition may become eligible to trigger again if its criteria are
subsequently met again.
```

S.II // Topic II (T.II) - Compound Conditions

[Back to Table of Contents](#)

000 Master Status: Not Configured

001 Pre-Enrollment Status: Not Configured

002 Post-Enrollment Status: Not Configured

Description:

Compound Conditions allow multiple individual conditions or criteria to be combined into a larger logical condition for more precise device targeting, monitoring, health-state evaluation, notification behavior, or automation triggering.

Unlike the standard Condition documented in Topic I, a Compound Condition can evaluate multiple underlying condition states together before determining whether the overall condition is considered met.

Compound Conditions are not currently used within the macOS policy architecture.

Current Configuration:

000 Master MacOS Policy:

No Compound Conditions configured.

001 Pre-Enrollment Policy:

No Compound Conditions configured.

002 Post-Enrollment Policy:

No Compound Conditions configured.

```
// No compound-condition rules, health-state logic, severities, priorities, notification
channels, technician notifications, or associated automation behavior are currently defined.
```

```
// This section is retained in the documentation so that the absence of Compound Conditions is
explicitly recorded rather than leaving the feature undocumented.
```

POTENTIAL FUNCTION

```
// Compound Conditions may be used in the future if a workflow requires multiple device-state
conditions to be evaluated together before an action or monitoring state should apply.
```

```
// Examples could include requiring multiple enrollment, application, service, hardware, or
compliance conditions to simultaneously meet specified criteria before triggering a resulting
condition state or automation.
```

```
// Any future Compound Conditions added to these policies should be documented here individually,
including:
```

```
// - Compound Condition name
```

```
// - Policies where the condition is enabled
```

```
// - Underlying conditions
```

```
// - Logical relationship between those conditions
```

```
// - Health status
```

```
// - Severity
```

```
// - Priority
```

```
// - Notification behavior
```

```
// - Associated automations  
// - Auto-reset behavior
```

REFERENCE

NinjaOne Documentation:

Getting Started With Compound Conditions

```
// Vendor documentation covering the creation and use of Compound Conditions within NinjaOne policies.
```

Resource:

<https://ninjarmm.zendesk.com/hc/en-us/articles/23495246509325-NinjaOne-Policies-Getting-Started-With-Compound-Conditions>

https://ninjarmm.zendesk.com/access/jwt?&return_to=https://ninjarmm.zendesk.com/hc/en-us/articles/23495246509325

S.II // Topic III (T.III) – Scheduled Automations

[Back to Table of Contents](#)

000 Master Status: Configured

001 Pre-Enrollment Status: Configured / Contains Overrides

002 Post-Enrollment Status: Configured / Contains Overrides

Description:

Scheduled Automations define groups of NinjaOne automation items that execute according to a specified device or user event, recurring interval, or one-time execution schedule.

Each Scheduled Automation acts as a parent container for one or more individual automation items. These child automation items may include:

- Application installations
- File transfers
- macOS shell scripts
- Device configuration actions
- User environment configuration
- Resource deployment
- Other NinjaOne-supported automation types

Scheduled Automation groups 001 through 008 are configured at the 000 Master MacOS Policy level. Individual Scheduled Automation groups may be enabled or disabled differently within the 001 Pre-Enrollment Policy and 002 Post-Enrollment Policy.

The effective status of each Scheduled Automation is therefore documented independently below.

Each child automation will be documented in greater detail later. Depending on the automation type, supporting documentation may include:

- Raw script file
- Transferred resource/file
- Application/package information
- Detailed explanation document
- Dependencies
- Execution logic
- Expected behavior/result

The information in this section primarily documents:

1. Which Scheduled Automation groups exist
2. Their execution schedule
3. Whether each group is active within each policy
4. Which child automations are contained within each group
5. The order in which those child automations are configured

General Behavior:

```
// Child automations are executed according to the schedule configured on their parent Scheduled Automation.
```

```
// The ordering documented below reflects the configured automation order within NinjaOne.
```

```
// Disabling a Scheduled Automation prevents its configured automation sequence from being
invoked by that Scheduled Automation, while the individual automation objects themselves may
continue to exist within NinjaOne.

// Individual scripts, applications, and file-transfer actions may also be reused by Conditions
or other Scheduled Automations elsewhere in the policy architecture.
```

001 // RUN ONCE IMMEDIATELY AUTOMATIONS

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

Description: Not Configured

Schedule: Run Once Immediately

Automation Count: 24

Channels: None Configured

Notify Technicians: Do Not Send Notifications

```
// Executes the configured automation sequence once when the Scheduled Automation becomes
applicable to the device.
```

```
// This automation group primarily performs the initial deployment of required applications,
utilities, shared resources, system configuration, and supporting onboarding components.
```

Configured Automation Order:

01. Intune Company Portal

Type: Install application (Mac)

```
// Installs Microsoft Intune Company Portal.
```

Explanation Document:

[\[Insert File / Link\]](#)

02. Google Chrome Enterprise...

Type: Install application (Mac)

```
// Installs the managed Google Chrome Enterprise application.
```

Explanation Document:

[\[Insert File / Link\]](#)

03. Zoom Workplace US

Type: Install application (Mac)

```
// Installs Zoom Workplace.
```

Explanation Document:

[\[Insert File / Link\]](#)

04. Adobe Acrobat Reader

Type: Install application (Mac)

```
// Installs Adobe Acrobat Reader.
```

Explanation Document:[\[Insert File / Link\]](#)

05. Dock Utility V3.1.3

Type: **Install application (Mac)**

```
| // Installs the Dock Utility application/package used by related Dock-management workflows.
```

Explanation Document:[\[Insert File / Link\]](#)

06. Swift Dialogue V3.1.0-4994

Type: **Install application (Mac)**

```
| // Installs Swift Dialog for use by managed scripts and user-facing workflow dialogs.
```

Explanation Document:[\[Insert File / Link\]](#)

07. 1Password V8.12.26

Type: **Install application (Mac)**

```
| // Installs the managed 1Password desktop application.
```

Explanation Document:[\[Insert File / Link\]](#)

08. Microsoft Teams

Type: **Install application (Mac)**

```
| // Installs Microsoft Teams.
```

Explanation Document:[\[Insert File / Link\]](#)

09. Asana V2.8.1

Type: **Install application (Mac)**

```
| // Installs the managed Asana desktop application.
```

Explanation Document:[\[Insert File / Link\]](#)

10. NinjaOne Remote Access

Type: **Install application (Mac)**

```
| // Installs the NinjaOne Remote Access component.
```

Explanation Document:[\[Insert File / Link\]](#)

11. Toolbar Network iCon

Type: **ShellScript (Mac)**

```
| // Configures or manages the applicable network-related menu bar / toolbar item.
```

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

12. Menu Bar Preferences

Type: **ShellScript** (Mac)

| // Configures managed macOS menu bar preferences.

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

13. Time Zone

Type: **ShellScript** (Mac)

| // Configures the applicable macOS time-zone settings.

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

14. MacOS Standard User Printer...

Type: **ShellScript** (Mac)

| // Provides or configures printer-related functionality for standard macOS users.

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

15. Download TTF-Wallpaper-Light-full

Type: **File transfer** (Mac)

| // Transfers the light TTF wallpaper resource to the device.

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

16. Download TTF-Wallpaper-Medium-...

Type: **File transfer** (Mac)

| // Transfers the medium TTF wallpaper resource to the device.

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

17. Download TTF-Wallpaper-Dark-full

Type: File transfer (Mac)

| // Transfers the dark TTF wallpaper resource to the device.

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

18. Prompt Image: Finder Guy...

Type: File transfer (Mac)

| // Transfers a Finder Guy prompt image resource used by managed user-facing workflows.

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

19. Prompt Image: Finder Guy Security...

Type: File transfer (Mac)

| // Transfers the Finder Guy security-related prompt image resource.

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

20. Prompt Image: Finder Guy Director...

Type: File transfer (Mac)

| // Transfers the Finder Guy directory-related prompt image resource.

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

21. Toga Prompt Background

Type: File transfer (Mac)

| // Transfers the managed background resource used by Toga user-facing prompts.

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:[\[Insert File / Link\]](#)**22. Toga Notification Sound**Type: **File transfer (Mac)**

```
| // Transfers the notification sound resource used by Toga-managed user prompts or notifications.
```

Transferred File:[\[Insert File / Link\]](#)**Explanation Document:**[\[Insert File / Link\]](#)**23. Resource Folder Access**Type: **ShellScript (Mac)**

```
| // Configures the required access or permissions for the local shared resource folder used by  
| managed scripts and resources.
```

Raw Script:[\[Insert File / Link\]](#)**Explanation Document:**[\[Insert File / Link\]](#)**24. Install Dark Blue TTF Wallpaper**Type: **ShellScript (Mac)**

```
| // Configures or installs the default dark-blue TTF wallpaper on the Mac.
```

Raw Script:[\[Insert File / Link\]](#)**Explanation Document:**[\[Insert File / Link\]](#)

002 // ON USER LOGIN AUTOMATIONS**000 Master Status:** Enabled**001 Pre-Enrollment Status:** Enabled**002 Post-Enrollment Status:** Enabled**Description:** Not Configured**Schedule:** On User Login**Automation Count:** 6**Channels:** None Configured**Notify Technicians:** Do Not Send Notifications

```
| // Executes the configured automation sequence when a user logs in.
```

```
| // These actions primarily refresh user-context configuration and resources that may need to be  
| evaluated or reapplied at login.
```

Configured Automation Order:

01. ZSH | Dynamic MacOS Display Names

Type: **ShellScript (Mac)**

```
| // Executes the dynamic macOS display-related configuration script.
```

Raw Script:[\[Insert File / Link\]](#)**Explanation Document:**[\[Insert File / Link\]](#)

02. Menu Bar Preferences

Type: **ShellScript (Mac)**

```
| // Configures managed menu bar preferences for the logged-in user.
```

Raw Script:[\[Insert File / Link\]](#)**Explanation Document:**[\[Insert File / Link\]](#)

03. Toga Prompt Background

Type: **File transfer (Mac)**

```
| // Ensures the Toga prompt background resource is present on the device.
```

Transferred File:[\[Insert File / Link\]](#)**Explanation Document:**[\[Insert File / Link\]](#)

04. Toga Notification Sound

Type: **File transfer (Mac)**

```
| // Ensures the Toga notification sound resource is present on the device.
```

Transferred File:[\[Insert File / Link\]](#)**Explanation Document:**[\[Insert File / Link\]](#)

05. Resource Folder Access

Type: **ShellScript (Mac)**

```
| // Ensures the required shared-resource folder access or permissions are configured.
```

Raw Script:[\[Insert File / Link\]](#)**Explanation Document:**[\[Insert File / Link\]](#)

06. Swift Dialog | Systems Check

Type: **ShellScript** (Mac)

```
| // Executes the Swift Dialog-based system validation/check workflow.
```

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

003 // SHARED RESOURCES FOLDER

000 Master Status: **Enabled**

001 Pre-Enrollment Status: **Enabled**

002 Post-Enrollment Status: **Enabled**

Description: Deploys assets used in scripts, as well as sets access level for the "Shared" users folder; By default, whenever NinjaOne engages a file transfer, it does so at root context. As a result it will set access level to deployed files as root access only regardless of inheritance. This is why this specific script is run often, as new files can be deployed to this specific folder at any time.

Schedule: **On System Startup**

Automation Count: **9**

Channels: **None Configured**

Notify Technicians: **Do Not Send Notifications**

```
| // Executes at system startup to ensure resources required by managed scripts, prompts,
| wallpapers, and related workflows are available locally.
```

Configured Automation Order:

01. Prompt Image: **Finder Guy...**

Type: **File transfer** (Mac)

```
| // Transfers the applicable Finder Guy prompt image resource.
```

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

02. Prompt Image: **Finder Guy Security...**

Type: **File transfer** (Mac)

```
| // Transfers the Finder Guy security prompt image resource.
```

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

03. Prompt Image: **Finder Guy Director...**

Type: **File transfer (Mac)**

| // Transfers the Finder Guy directory-related prompt image resource.

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

04. Toga Notification Sound

Type: **File transfer (Mac)**

| // Transfers the managed Toga notification sound resource.

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

05. Toga Prompt Background

Type: **File transfer (Mac)**

| // Transfers the managed Toga prompt background resource.

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

06. Download TTF-Wallpaper-Dark-full

Type: **File transfer (Mac)**

| // Transfers the dark TTF wallpaper resource.

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

07. Download TTF-Wallpaper-Light-full

Type: **File transfer (Mac)**

| // Transfers the light TTF wallpaper resource.

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

08. Download TTF-Wallpaper-Medium-...

Type: **File transfer (Mac)**

| // Transfers the medium TTF wallpaper resource.

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

09. Resource Folder Access

Type: **ShellScript (Mac)**

| // Configures or validates access and permissions for the shared resource folder containing these managed resources.

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

004 // LOCAL ADMIN MANAGEMENT

000 Master Status: **Disabled**

001 Pre-Enrollment Status: **Disabled**

002 Post-Enrollment Status: **Enabled**

Description: Post-Enrollment Policy Only: Ensures local admin access is configured correctly upon every boot up.

Schedule: On User Login

Automation Count: 1

Channels: None Configured

Notify Technicians: Do Not Send Notifications

| // This Scheduled Automation is configured within the Master policy but is disabled at the 000 Master level.

| // The configured description identifies this workflow as intended for post-enrollment use.

Configured Automation Order:

01. Local Device Administrator...

Type: **ShellScript (Mac)**

| // Executes the local-device-administrator management workflow.

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

005 // DEFAULT PERSONALIZATION SETTINGS

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Disabled

Description: Pre-Enrollment Policy Only: As the Post-Enrollment Policy is designated as the final destination policy for most MacOS devices, this specific automation is disabled from running again in the future; If it were to remain enabled, then if the user decides to change the wallpaper, screensaver, etc, it would be reset back to the default settings upon every login. We have no interest in mandating a personalization settings, only inserting a default/starting pair.

Schedule: On User Login

Automation Count: 4

Channels: None Configured

Notify Technicians: Do Not Send Notifications

```
// Provides the default managed wallpaper/screensaver configuration associated with the pre-
enrollment device state.
```

Configured Automation Order:

01. Download TTF-Wallpaper-Dark-full

Type: File transfer (Mac)

```
// Transfers the dark TTF wallpaper resource required by this workflow.
```

Transferred File:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

02. Install Dark Blue TTF Wallpaper

Type: ShellScript (Mac)

```
// Installs or applies the managed dark-blue TTF wallpaper.
```

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

03. Set Screensaver to Drift

Type: ShellScript (Mac)

```
// Configures the macOS screensaver to use the Drift screensaver.
```

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

04. Clear Non-Forced Apps From...

Type: **ShellScript (Mac)**

```
// Removes or clears applicable non-forced application items from the managed user environment.
```

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

006 // MACOS ENROLLMENT STATUS FIELD [EVERY 3MIN]

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Disabled

Description: Pre-Enrollment Only; This designed to function right as enrollment is finishing up, in an effort to act as the "logic" behind makeshift dynamic policy assignments. Essentially, this scripts evaluates if the device has met three specific conditions, and upon doing so, it writes a new value to the devices inventory record in NinjaOne for the Enrollment Status custom field, indicating that enrollment is complete. When this happens, eventually, another script or logic instance will move the device into the post-enrollment location, and as a result, change the assigned policy as well.

Schedule: Every

Occurs Every: 3 Minutes

Automation Count: 1

Channels: None Configured

Notify Technicians: Do Not Send Notifications

```
// Executes every three minutes while this Scheduled Automation remains active.  
  
// This workflow manages the custom "MacOS Enrollment Status" field referenced by the Enrollment Complete condition documented in S.II / T.I.  
  
// The internal logic of the script and the possible custom-field values will be documented separately in the detailed automation documentation.
```

Configured Automation Order:

01. MacOS Enrollment Status Field

Type: **ShellScript (Mac)**

```
// Evaluates enrollment-related device state and updates the "MacOS Enrollment Status" NinjaOne custom field accordingly.  
  
// The resulting custom-field value is used by other policy logic, including the "Enrollment Complete Automations" condition.
```

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

007 // DEFAULT HANDLERS & APPS

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Disabled

Description: Pre-Enrollment Only; These settings technically fall under what we would classify as personal preferences; Thus, they do not run again after the initial enrollment phase is complete.

Schedule: On User Login

Automation Count: 4

Channels: None Configured

Notify Technicians: Do Not Send Notifications

```
| // Executes default-application and protocol-handler configuration during user login.  
| // The configured description identifies this workflow as intended for the pre-enrollment stage.
```

Configured Automation Order:

01. Set Default Mailto Handler to...

Type: ShellScript (Mac)

```
| // Configures the default application associated with the mailto: URL scheme.
```

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

02. Prompts User to Set Default...

Type: ShellScript (Mac)

```
| // Presents the applicable user-facing workflow for setting a default application where macOS  
| requires user interaction or confirmation.
```

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

03. Set Default callto/tel Handler...

Type: ShellScript (Mac)

```
| // Configures the default application associated with supported callto: and tel: URL schemes.
```

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

04. Set Adobe to Default PDF...

Type: **ShellScript** (Mac)

```
// Configures Adobe Acrobat as the default application for supported PDF documents, including any required user-facing confirmation workflow.
```

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

008 // PRINTERS

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Enabled

Description: For this automation to work correctly/succeed, the device must be on the same network as the printers, as well as actively reachable. Due to these requirements, it was deemed that the best chance of success would appear only after the device has fully completed enrollment. This script may need to be run again manually if it initially fails due to improper requisites.

Schedule: Run Once Immediately

Automation Count: 5

Channels: None Configured

Notify Technicians: Do Not Send Notifications

```
// Contains the automated deployment workflow for managed printer drivers and printer configurations.  
  
// This Scheduled Automation is configured but disabled at the 000 Master policy level.
```

Configured Automation Order:

01. Install Rosetta

Type: **ShellScript** (Mac)

```
// Installs Rosetta where required for compatibility with applicable printer software or drivers on Apple silicon Macs.
```

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

02. Toshiba Printer Drivers

Type: **Install application** (Mac)

```
// Installs the managed Toshiba printer-driver package.
```

Explanation Document:

[\[Insert File / Link\]](#)

03. Kyocera Printer Drivers

Type: **Install application (Mac)**

```
| // Installs the managed Kyocera printer-driver package.
```

Explanation Document:

[\[Insert File / Link\]](#)

04. TOW Toshiba Main Printer...

Type: **ShellScript (Mac)**

```
| // Configures the applicable TOW Toshiba main printer after the required driver components are  
| available.
```

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

05. Kyocera Printer Install

Type: **ShellScript (Mac)**

```
| // Configures the managed Kyocera printer after the required driver components are available.
```

Raw Script:

[\[Insert File / Link\]](#)

Explanation Document:

[\[Insert File / Link\]](#)

000 MASTER POLICY SCHEDULED AUTOMATION SUMMARY

001 // Run Once Immediately Automations

Status: Enabled

Schedule: Run Once Immediately

Automation Count: 24

002 // On User Login Automations

Status: Enabled

Schedule: On User Login

Automation Count: 6

003 // Shared Resources Folder

Status: Enabled

Schedule: On System Startup

Automation Count: 9

004 // Local Admin Management

Status: Disabled

Schedule: On User Login

Automation Count: 1

Description: Post-Enrollment Only

005 // Default Blue Wallpaper Theme

Status: Enabled

Schedule: On User Login

Automation Count: 4

Description: Pre-Enrollment Only

006 // MacOS Enrollment Status Field [Every 3min]

Status: Enabled

Schedule: Every 3 Minutes

Automation Count: 1

Description: Pre-Enrollment Only

007 // Default Handlers & Apps

Status: Enabled

Schedule: On User Login

Automation Count: 4

Description: Pre-Enrollment Only

008 // Printers

Status: Disabled

Schedule: Run Once Immediately

Automation Count: 5

S.II // Topic IV (T.IV) - OS Patching

[Back to Table of Contents](#)

000 Master Status: Enabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Enabled

Description:

This configuration manages NinjaOne agent-based macOS operating-system patch scanning, update installation, maintenance behavior, approval rules, and reboot handling. Pre-Enrollment is intentionally disabled, as devices are not expected to remain in this policy for an extended period of time; During said time, the device is already processing a large amount of data, so its best if the patching waits until after the device setup is fully complete.

OS patching is intentionally scheduled on days separate from the environment's Software Patching update schedule. This separates operating-system maintenance from third-party/application patching and avoids both maintenance workflows being scheduled on the same day.

NinjaOne agent-based macOS patching requires an applicable local account with Volume Owner / Secure Token permissions due to macOS security requirements.

The exact enabled/disabled state of OS Patching may differ between the:

000 Master MacOS Policy

001 Pre-Enrollment Policy

002 Post-Enrollment Policy

The effective state for each policy is therefore documented separately.

Settings, Configured Values, & their Descriptions

OS PATCHING STATUS

Enable OS patching

000 Master Status: Enabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Enabled

// Enables NinjaOne agent-based macOS operating-system patch management for devices receiving this policy.

// When enabled, NinjaOne performs OS update scans and installation according to the schedules and approval behavior configured below.

SCAN SCHEDULE

Schedule

000 Master Status: Weekly

001 Pre-Enrollment Status: Weekly

002 Post-Enrollment Status: Weekly

// OS update scans are scheduled on a recurring weekly basis.

Days of the Week

000 Master Status:

Tuesday: Enabled

Thursday: Enabled

Saturday: Enabled

001 Pre-Enrollment Status:

Tuesday: Enabled

Thursday: Enabled

Saturday: Enabled

002 Post-Enrollment Status:

Tuesday: Enabled

Thursday: Enabled

Saturday: Enabled

```
// NinjaOne scans managed Macs for applicable macOS operating-system updates every Tuesday,  
Thursday, and Saturday.
```

Scan Time

000 Master Status: 08:30 AM

001 Pre-Enrollment Status: 08:30 AM

002 Post-Enrollment Status: 08:30 AM

Time Zone

000 Master Status: Local device time

001 Pre-Enrollment Status: Local device time

002 Post-Enrollment Status: Local device time

```
// The scan schedule is evaluated according to the local time configured on each managed Mac  
rather than a single centralized time zone.
```

Stagger Over

000 Master Status: 2 Hours / 0 Minutes

001 Pre-Enrollment Status: 2 Hours / 0 Minutes

002 Post-Enrollment Status: 2 Hours / 0 Minutes

```
// Scan execution may be distributed across a two-hour window rather than every device beginning  
the scan at exactly 08:30 AM.
```

```
// Staggering reduces the likelihood of all managed devices initiating update-related network and  
processing activity simultaneously.
```

Duration

000 Master Status: 0 Hours / 0 Minutes

001 Pre-Enrollment Status: 0 Hours / 0 Minutes

002 Post-Enrollment Status: 0 Hours / 0 Minutes

```
// No additional scan-duration window is configured.
```

Run scan immediately, if missed

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
| // If the device misses its scheduled scan, NinjaOne is configured to perform the scan as soon as  
| possible afterward rather than waiting for the next scheduled scan window.
```

UPDATE SCHEDULE

Schedule

000 Master Status: Weekly

001 Pre-Enrollment Status: Weekly

002 Post-Enrollment Status: Weekly

```
| // Approved macOS updates are scheduled for installation on a recurring weekly schedule.
```

Days of the Week

000 Master Status:

Sunday: Enabled

Monday: Enabled

Wednesday: Enabled

Friday: Enabled

001 Pre-Enrollment Status:

Sunday: Enabled

Monday: Enabled

Wednesday: Enabled

Friday: Enabled

002 Post-Enrollment Status:

Sunday: Enabled

Monday: Enabled

Wednesday: Enabled

Friday: Enabled

```
| // Approved OS updates may be installed on Sunday, Monday, Wednesday, and Friday.
```

```
| // These days are intentionally separated from the OS scan schedule and are also designed around  
| the separate Software Patching maintenance schedule.
```

Update Time

000 Master Status: 08:30 AM

001 Pre-Enrollment Status: 08:30 AM

002 Post-Enrollment Status: 08:30 AM

Time Zone

000 Master Status: Local device time

001 Pre-Enrollment Status: Local device time

002 Post-Enrollment Status: Local device time

| // Update execution is evaluated according to the managed Mac's local device time.

Stagger Over

000 Master Status: 1 Hour / 0 Minutes

001 Pre-Enrollment Status: 1 Hour / 0 Minutes

002 Post-Enrollment Status: 1 Hour / 0 Minutes

| // OS update installation may begin at varying times throughout a one-hour window beginning from the scheduled update time.

| // This prevents all managed devices from initiating update installation simultaneously.

Duration

000 Master Status: 0 Hours / 0 Minutes

001 Pre-Enrollment Status: 0 Hours / 0 Minutes

002 Post-Enrollment Status: 0 Hours / 0 Minutes

| // No additional update execution-duration window is configured.

Run update immediately, if missed

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

| // If the scheduled OS update window is missed, NinjaOne is not configured through this option to immediately begin the update outside the normal schedule.

MAINTENANCE MODE

Maintenance mode: suppress Emails/SMS/Push notifications

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

| // Enables maintenance-mode notification suppression during the OS patching process.

| // This helps prevent expected update/reboot-related device behavior from unnecessarily generating operational notifications.

Suppress condition alerts

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

| // Suppresses condition-generated alerts while the OS patching maintenance process is active.

Suppress notification channels

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
| // Suppresses configured notification-channel messages during the applicable maintenance period.
```

REBOOT OPTIONS - LOGGED-IN USER

Reboot Behavior**000 Master Status: Prompt to reboot until reboot accepted****001 Pre-Enrollment Status: Prompt to reboot until reboot accepted****002 Post-Enrollment Status: Prompt to reboot until reboot accepted**

```
| // When an OS update requires a restart and a user is logged in, the device does not immediately
| reboot.
```

```
| // Instead, NinjaOne repeatedly prompts the logged-in user to restart the Mac.
```

Prompt Period**000 Master Status: 35 Minutes****001 Pre-Enrollment Status: 35 Minutes****002 Post-Enrollment Status: 35 Minutes**

```
| // If the user defers the restart, another reboot prompt is presented every 35 minutes.
```

Force reboot after**000 Master Status: Enabled****001 Pre-Enrollment Status: Enabled****002 Post-Enrollment Status: Enabled****Maximum Prompts****000 Master Status: 9 Prompts****001 Pre-Enrollment Status: 9 Prompts****002 Post-Enrollment Status: 9 Prompts**

```
| // The user may defer the required restart through up to nine reboot prompts.
```

```
| // NinjaOne's configured reboot schedule therefore prompts the user nine times at 35-minute
| intervals.
```

```
| // The final prompt remains displayed for five minutes before the forced reboot occurs.
```

Reboot Prompt Schedule:

Prompt 9 times every 35 minutes.

Final prompt is displayed for 5 minutes before reboot occurs.

CUSTOM REBOOT DIALOG

Custom reboot dialog**000 Master Status: Enabled****001 Pre-Enrollment Status: Enabled****002 Post-Enrollment Status: Enabled**

```
// Uses a customized user-facing message instead of relying solely on NinjaOne's default reboot
messaging.
```

Title:

Imperative MacOS Update Pending (Restart Required)

Message:

Your Macs' operating system is ready to update.

Click the "Restart" button to install it now, or defer for a limited number of times, and we will ask you to restart again in 35 minutes.

Note: There is a short delay from when you select "Restart" to when the device actually does so, and once underway, it will usually take between 10-60 minutes to complete.

```
// The configured message informs the user that:
// - A macOS update is ready for installation.
// - A restart is required.
// - The user may restart immediately or temporarily defer.
// - Deferrals are limited.
// - The user will be prompted again after 35 minutes.
// - Restart initiation may not occur immediately after the user selects Restart.
// - The update process may require an extended amount of time to complete.

// The screenshot exposes only the visible portion of the configured message. The complete raw
message should be copied directly from NinjaOne when the final documentation is assembled.
```

REBOOT OPTIONS - NO LOGGED-IN USER

Attempt to reboot until successful

```
000 Master Status: Disabled
001 Pre-Enrollment Status: Disabled
002 Post-Enrollment Status: Disabled
```

Reboot immediately

```
000 Master Status: Enabled
001 Pre-Enrollment Status: Enabled
002 Post-Enrollment Status: Enabled
```

```
// If no user is logged into the Mac when an update requires a restart, NinjaOne immediately
reboots the device rather than presenting or waiting on an interactive user prompt.
```

GENERAL APPROVALS

Critical Updates

```
000 Master Status: Approved
001 Pre-Enrollment Status: Approved
002 Post-Enrollment Status: Approved
```

```
// Updates categorized as Critical by NinjaOne's patch-management system are automatically
approved for installation.
```

Unassigned Updates

000 Master Status: Approved

001 Pre-Enrollment Status: Approved

002 Post-Enrollment Status: Approved

```
// Updates that do not fall into another configured approval classification are also approved for installation.
```

APPROVAL OVERRIDES

Approved Patch Overrides

000 Master Status: Will vary over time

001 Pre-Enrollment Status: Will vary over time

002 Post-Enrollment Status: Will vary over time

Rejected Patch Overrides

000 Master Status: Will vary over time

001 Pre-Enrollment Status: Will vary over time

002 Post-Enrollment Status: Will vary over time

```
// No individual macOS patches currently have explicit approval or rejection overrides.  
// Patch installation therefore follows the configured general approval behavior unless additional overrides are added later.
```

000 MASTER POLICY EFFECTIVE OS PATCHING BEHAVIOR

```
// OS patching is enabled.  
  
// Update scans occur:  
// Tuesday  
// Thursday  
// Saturday  
  
// Scans begin at 08:30 AM local device time and are staggered across two hours.  
  
// Missed scans execute as soon as possible afterward.  
  
// Approved update installation occurs:  
// Sunday  
// Monday  
// Wednesday  
// Friday  
  
// Updates begin at 08:30 AM local device time and are staggered across one hour.  
  
// Missed update windows do not automatically trigger immediate installation through the "Run update immediately, if missed" option.  
  
// Maintenance mode suppresses:  
// - Email/SMS/Push notifications  
// - Condition alerts
```

```
// - Notification channels
// If a restart is required while a user is logged in:
// - The user is prompted to restart.
// - The prompt repeats every 35 minutes.
// - Up to 9 prompts are permitted.
// - The final prompt lasts 5 minutes.
// - The Mac is then forcibly restarted if necessary.
// If no user is logged in:
// - The Mac reboots immediately when the update requires a restart.
// Critical and Unassigned updates are approved.
// No individual patch approval/rejection overrides are currently configured.
```

S.II // Topic V (T.V) - Software Patching

[Back to Table of Contents](#)

000 Master Status: Enabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Enabled

Description:

This configuration manages NinjaOne agent-based third-party software patch scanning, approval, installation, user-notification behavior, application-close behavior, and reboot handling. This is once again disabled for Pre-Enrollment for the same reasons that OS patching is disabled for Pre-Enrollment.

Software Patching is used to maintain supported third-party applications independently from macOS operating-system patching.

The Software Patching update schedule is intentionally configured on different days from the OS Patching update schedule so that third-party application maintenance and operating-system maintenance are not scheduled to execute on the same day.

The exact enabled/disabled state of Software Patching may vary between:

000 Master MacOS Policy

001 Pre-Enrollment Policy

002 Post-Enrollment Policy

However, the software catalog included within Software Patching remains consistent across all three policies.

Applications installed and managed through Apple Apps and Books / VPP are configured to be excluded from NinjaOne Software Patching. This prevents NinjaOne agent-based patching from independently updating applications whose installation/update lifecycle is being managed through VPP.

Settings, Configured Values, & their Descriptions

SOFTWARE PATCHING STATUS

Enable software patching

000 Master Status: Enabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Enabled

```
// Enables NinjaOne agent-based third-party application patch management.
```

```
// When enabled, NinjaOne scans applicable supported applications for available patches and
installs approved updates according to the configuration below.
```

APPLICATION MANAGEMENT SOURCE EXCLUSION

Applications installed through VPP / Apps and Books

000 Master Status: Excluded from Software Patching

001 Pre-Enrollment Status: Excluded from Software Patching

002 Post-Enrollment Status: Excluded from Software Patching

// Applications whose installation is managed through Apple Apps and Books / VPP are excluded from NinjaOne's agent-based Software Patching workflow.

// This prevents two separate management systems from attempting to independently control the update lifecycle of the same managed application.

// An application may still appear in the Software Patching software catalog documented later in this section. Its presence in the supported software list does not mean that a VPP-installed instance of that application will be patched through NinjaOne.

SCAN SCHEDULE

Schedule

000 Master Status: Weekly

001 Pre-Enrollment Status: Weekly

002 Post-Enrollment Status: Weekly

Days of the Week

000 Master Status:

Monday: Enabled

Wednesday: Enabled

Friday: Enabled

001 Pre-Enrollment Status:

Monday: Enabled

Wednesday: Enabled

Friday: Enabled

002 Post-Enrollment Status:

Monday: Enabled

Wednesday: Enabled

Friday: Enabled

// NinjaOne scans managed devices for applicable third-party software patches every Monday, Wednesday, and Friday.

Scan Time

000 Master Status: 08:30 AM

001 Pre-Enrollment Status: 08:30 AM

002 Post-Enrollment Status: 08:30 AM

Time Zone

000 Master Status: Local device time

001 Pre-Enrollment Status: Local device time

002 Post-Enrollment Status: Local device time

// The scan schedule is evaluated according to the local time configured on each managed Mac.

Stagger Over

000 Master Status: 2 Hours / 30 Minutes

001 Pre-Enrollment Status: 2 Hours / 30 Minutes

002 Post-Enrollment Status: 2 Hours / 30 Minutes

```
// Scan execution may occur at varying times throughout a two-hour-and-thirty-minute stagger window rather than all devices beginning simultaneously.
```

Run scan immediately, if missed

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// If a device misses its scheduled software-patch scan, NinjaOne performs the scan as soon as possible afterward rather than waiting for the next scheduled scan.
```

Apply immediately

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

```
// Newly detected and approved patches are not automatically installed immediately as part of the scan.
```

```
// Installation instead follows the separately configured Software Patching update schedule.
```

UPDATE SCHEDULE

Schedule

000 Master Status: Weekly

001 Pre-Enrollment Status: Weekly

002 Post-Enrollment Status: Weekly

Days of the Week

000 Master Status:

Tuesday: Enabled

Thursday: Enabled

Saturday: Enabled

001 Pre-Enrollment Status:

Tuesday: Enabled

Thursday: Enabled

Saturday: Enabled

002 Post-Enrollment Status:

Tuesday: Enabled

Thursday: Enabled

Saturday: Enabled

```
| // Approved third-party software patches are scheduled for installation every Tuesday, Thursday,  
| and Saturday.  
|  
| // These update days are intentionally separated from the OS Patching update schedule.
```

Update Time

```
000 Master Status: 08:30 AM  
001 Pre-Enrollment Status: 08:30 AM  
002 Post-Enrollment Status: 08:30 AM
```

Time Zone

```
000 Master Status: Local device time  
001 Pre-Enrollment Status: Local device time  
002 Post-Enrollment Status: Local device time
```

```
| // Update execution is evaluated according to each managed Mac's local device time.
```

Stagger Over

```
000 Master Status: 2 Hours / 0 Minutes  
001 Pre-Enrollment Status: 2 Hours / 0 Minutes  
002 Post-Enrollment Status: 2 Hours / 0 Minutes
```

```
| // Patch installation may begin at varying times throughout a two-hour stagger window beginning  
| from the configured update time.
```

Run update immediately, if missed

```
000 Master Status: Disabled  
001 Pre-Enrollment Status: Disabled  
002 Post-Enrollment Status: Disabled
```

```
| // A device that misses its scheduled Software Patching update window is not configured through  
| this setting to immediately install the update outside of the normal update schedule.
```

MAINTENANCE MODE

Maintenance mode: suppress Emails/SMS/Push notifications

```
000 Master Status: Enabled  
001 Pre-Enrollment Status: Enabled  
002 Post-Enrollment Status: Enabled
```

```
| // Enables maintenance-mode notification suppression while Software Patching is occurring.
```

Suppress condition alerts

```
000 Master Status: Enabled  
001 Pre-Enrollment Status: Enabled  
002 Post-Enrollment Status: Enabled
```

```
| // Suppresses NinjaOne condition alerts generated during the applicable maintenance period.
```

Suppress notification channels

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

| // Suppresses configured notification-channel messages during the applicable maintenance period.

SOFTWARE UPDATE NOTIFICATIONS

Update Behavior

000 Master Status: Prompt user to close software and update

001 Pre-Enrollment Status: Prompt user to close software and update

002 Post-Enrollment Status: Prompt user to close software and update

| // When an update requires an application to be closed, the logged-in user is prompted before NinjaOne closes the application and installs the patch.

Prompt Period

000 Master Status: 15 Minutes

001 Pre-Enrollment Status: 15 Minutes

002 Post-Enrollment Status: 15 Minutes

| // A user who defers installation is prompted again every 15 minutes.

Force update after

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

Maximum Prompts

000 Master Status: 6 Prompts

001 Pre-Enrollment Status: 6 Prompts

002 Post-Enrollment Status: 6 Prompts

| // NinjaOne is configured to present six software-update prompts at 15-minute intervals.

Software Update Prompt Schedule:

Prompt 6 times every 15 minutes.

CUSTOM SOFTWARE UPDATE DIALOG

Custom software update dialog

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

Title:

Application Update(s) Pending

Message:

Updates are available for the below app(s).

Install it now to apply, or defer by 15 minutes up to 5 times. Note: Updating will force the app to close automatically after a short delay.

```
| // Provides custom user-facing messaging explaining that application updates are available, that  
| the update may temporarily be deferred, and that the applicable application will ultimately be  
| closed so installation can proceed.
```

Configuration Note:

```
| // The custom message states that the user may defer "up to 5 times."  
|  
| // NinjaOne's actual configuration is set to:  
| // Force update after: Enabled  
| // Prompt Count: 6  
|  
| // NinjaOne's generated schedule also explicitly states:  
| // "Prompt 6 times every 15 minutes."
```

REBOOT OPTIONS - LOGGED-IN USER

Reboot Behavior

000 Master Status: Prompt to reboot until reboot accepted

001 Pre-Enrollment Status: Prompt to reboot until reboot accepted

002 Post-Enrollment Status: Prompt to reboot until reboot accepted

```
| // If an installed third-party software patch requires a device restart while a user is logged  
| in, NinjaOne prompts the user rather than immediately rebooting the Mac.
```

Prompt Period

000 Master Status: 25 Minutes

001 Pre-Enrollment Status: 25 Minutes

002 Post-Enrollment Status: 25 Minutes

```
| // A user who defers the required restart is prompted again every 25 minutes.
```

Force reboot after

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

Maximum Prompts

000 Master Status: 6 Prompts

001 Pre-Enrollment Status: 6 Prompts

002 Post-Enrollment Status: 6 Prompts

```
| // NinjaOne is configured to present six restart prompts at 25-minute intervals.
```

Reboot Prompt Schedule:

Prompt 6 times every 25 minutes.

CUSTOM REBOOT DIALOG

Custom reboot dialog

```
000 Master Status: Enabled
001 Pre-Enrollment Status: Enabled
002 Post-Enrollment Status: Enabled
```

Title:

Application Update(s) Pending (Restart Required)

Message:

Updates are available for the below app(s).

Restart your device now to apply, or defer by 25 minutes up to 5 times. Note: There is a short delay from when you select "Restart" to when your device actually does so.

```
// Provides custom user-facing messaging when completion of an application update requires a Mac
restart.
```

Configuration Note:

```
// The custom reboot message states that the user may defer "up to 5 times."
// NinjaOne's actual configuration is set to:
// Force reboot after: Enabled
// Prompt Count: 6
// NinjaOne's generated schedule explicitly states:
// "Prompt 6 times every 25 minutes."
```

REBOOT OPTIONS - NO LOGGED-IN USER

Attempt to reboot until successful

```
000 Master Status: Disabled
001 Pre-Enrollment Status: Disabled
002 Post-Enrollment Status: Disabled
```

Reboot immediately

```
000 Master Status: Enabled
001 Pre-Enrollment Status: Enabled
002 Post-Enrollment Status: Enabled
```

Do nothing

```
000 Master Status: Disabled
001 Pre-Enrollment Status: Disabled
002 Post-Enrollment Status: Disabled
```

```
// If no user is logged into the Mac and an installed software patch requires a restart, NinjaOne
immediately reboots the device.
```

APPROVALS

Approvals

```
000 Master Status: Enabled
001 Pre-Enrollment Status: Enabled
002 Post-Enrollment Status: Enabled
```

Critical patches

```
000 Master Status: Approve
001 Pre-Enrollment Status: Approve
002 Post-Enrollment Status: Approve
```

```
| // Third-party software patches classified as Critical are approved for installation.
```

Recommended patches

```
000 Master Status: Approve
001 Pre-Enrollment Status: Approve
002 Post-Enrollment Status: Approve
```

```
| // Third-party software patches classified as Recommended are approved for installation.
```

APPROVAL OVERRIDES

Approved Patch Overrides

```
000 Master Status: Will vary over time
001 Pre-Enrollment Status: Will vary over time
002 Post-Enrollment Status: Will vary over time
```

Rejected Patch Overrides

```
000 Master Status: Will vary over time
001 Pre-Enrollment Status: Will vary over time
002 Post-Enrollment Status: Will vary over time
```

MANAGED SOFTWARE CATALOG

```
| // The following software products are included in the Software Patching catalog for all three
| macOS policies.
```

```
| // The software catalog does not change between:
```

```
| // 000 Master MacOS Policy
| // 001 Pre-Enrollment Policy
| // 002 Post-Enrollment Policy
```

```
| // Applications installed through VPP remain excluded from NinjaOne Software Patching even when
| the corresponding software product appears within this catalog.
```

ADOBE READER DC CONTINUOUS

000 Master Catalog Status: Included

001 Pre-Enrollment Catalog Status: Included

002 Post-Enrollment Catalog Status: Included

Publisher: Adobe

Software: Adobe Reader DC Continuous

Critical Patch Behavior: Approve

Recommended Patch Behavior: Default (Approve)

```
| // Critical patches are explicitly approved.
```

```
| // Recommended patches inherit the global Recommended approval setting, which is currently  
| Approve.
```

ACROBAT DC CONTINUOUS

000 Master Catalog Status: Included

001 Pre-Enrollment Catalog Status: Included

002 Post-Enrollment Catalog Status: Included

Publisher: Adobe

Software: Acrobat DC Continuous

Critical Patch Behavior: Approve

Recommended Patch Behavior: Default (Approve)

ADOBE ACROBAT 2020 CLASSIC

000 Master Catalog Status: Included

001 Pre-Enrollment Catalog Status: Included

002 Post-Enrollment Catalog Status: Included

Publisher: Adobe

Software: Adobe Acrobat 2020 Classic

Critical Patch Behavior: Approve

Recommended Patch Behavior: Default (Approve)

GOOGLE CHROME

000 Master Catalog Status: Included

001 Pre-Enrollment Catalog Status: Included

002 Post-Enrollment Catalog Status: Included

Publisher: Google

Software: Google Chrome

Critical Patch Behavior: Approve

Recommended Patch Behavior: Default (Approve)

FIREFOX

000 Master Catalog Status: Included

001 Pre-Enrollment Catalog Status: Included

002 Post-Enrollment Catalog Status: Included

Publisher: Mozilla

Software: Firefox

Critical Patch Behavior: Approve

Recommended Patch Behavior: Default (Approve)

SPOTIFY

000 Master Catalog Status: Included

001 Pre-Enrollment Catalog Status: Included

002 Post-Enrollment Catalog Status: Included

Publisher: Spotify

Software: Spotify

Critical Patch Behavior: Approve

Recommended Patch Behavior: Default (Approve)

ZOOM CLIENT

000 Master Catalog Status: Included

001 Pre-Enrollment Catalog Status: Included

002 Post-Enrollment Catalog Status: Included

Publisher: Zoom Video Communications

Software: Zoom Client

Critical Patch Behavior: Approve

Recommended Patch Behavior: Default (Approve)

```
// Zoom is included in the supported Software Patching catalog; however, a Zoom installation
// managed through VPP is excluded from NinjaOne agent-based patching.
```

1PASSWORD 8

000 Master Catalog Status: Included

001 Pre-Enrollment Catalog Status: Included

002 Post-Enrollment Catalog Status: Included

Publisher: AgileBits Inc

Software: 1Password 8

Critical Patch Behavior: Approve

Recommended Patch Behavior: Default (Approve)

```
// 1Password is included in the supported Software Patching catalog; however, any applicable VPP-
// managed installation is excluded from NinjaOne agent-based patching.
```

000 MASTER POLICY EFFECTIVE SOFTWARE PATCHING BEHAVIOR

```
// Software Patching is enabled.
```

```
// VPP / Apps and Books-managed application installations are excluded from NinjaOne Software
// Patching.
```

```
// Software patch scans occur:
```

```
// Monday
// Wednesday
// Friday

// Scans begin at 08:30 AM local device time and are staggered across 2 hours and 30 minutes.
// Missed scans execute as soon as possible afterward.
// Detected patches are not configured to install immediately during the scan.
// Approved third-party application updates occur:
// Tuesday
// Thursday
// Saturday

// Updates begin at 08:30 AM local device time and are staggered across 2 hours.
// These Software Patching update days do not overlap with the configured OS Patching update
days.

// Missed update windows do not trigger immediate installation through the "Run update
immediately, if missed" option.

// Maintenance mode suppresses:
// - Email/SMS/Push notifications
// - Condition alerts
// - Notification channels

// If an update requires currently running software to close:
// - The user is prompted before the application is closed.
// - The prompt repeats every 15 minutes.
// - NinjaOne is configured for 6 prompts.
// - The final prompt remains for 5 minutes.
// - The application is then forcibly closed and the patch proceeds.

// If an application patch requires a restart while a user is logged in:
// - The user is prompted to restart.
// - Restart prompts repeat every 25 minutes.
// - NinjaOne is configured for 6 prompts.
// - The final prompt remains for 5 minutes.
// - The Mac is then forcibly restarted if required.

// If no user is logged in and the patch requires a restart:
// - The Mac reboots immediately.

// Critical patches are approved.
// Recommended patches are approved.
// No individual patch approval or rejection overrides are currently configured.
// Nine third-party software products are included within the Software Patching catalog.
```

S.II // Topic VI (T.VI) - Antivirus Deployment

[Back to Table of Contents](#)

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

Description:

This configuration controls deployment of the organization's antivirus integration through NinjaOne.

Bitdefender GravityZone is configured as the antivirus integration for managed macOS devices.

This section documents only the NinjaOne-side antivirus deployment behavior, including installation conflict handling, failed-install retry behavior, and post-install reboot handling.

The underlying Bitdefender GravityZone antivirus/security policy is managed separately within the Bitdefender platform and is not currently included within this document.

The Bitdefender security-policy configuration may be documented separately or added as an additional section at a later date.

Settings, Configured Values, & their Descriptions

ANTIVIRUS INTEGRATION

Antivirus integration

000 Master Status: Bitdefender GravityZone

001 Pre-Enrollment Status: Bitdefender GravityZone

002 Post-Enrollment Status: Bitdefender GravityZone

```
// Configures NinjaOne to deploy and manage the Bitdefender GravityZone endpoint-security
integration on applicable managed devices.
```

INSTALLATION BEHAVIOR

If another antivirus software is installed

000 Master Status: Proceed with installation anyway

001 Pre-Enrollment Status: Proceed with installation anyway

002 Post-Enrollment Status: Proceed with installation anyway

```
// If NinjaOne detects another antivirus product already installed on the Mac, deployment of
Bitdefender is still permitted to continue.
```

```
// The presence of another antivirus product does not cause NinjaOne to automatically abandon the
Bitdefender installation attempt.
```

If Bitdefender GravityZone installation fails, reattempt

000 Master Status: Daily

001 Pre-Enrollment Status: Daily

002 Post-Enrollment Status: Daily

Retry Time: 10:00 AM

Time Zone: Local device time

```
// If the Bitdefender installation fails, NinjaOne retries the deployment once per day.  
// Retry execution is scheduled for 10:00 AM according to the local time configured on the  
managed Mac.
```

Interval Retry

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

```
// Installation retries are not configured to occur on a repeating interval throughout the day.
```

Do nothing after failed installation

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

```
// NinjaOne does not abandon deployment after an installation failure. Daily retry behavior  
remains enabled.
```

POST-INSTALL REBOOT OPTIONS - LOGGED-IN USER

Automatically reboot

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

Do nothing

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// If Bitdefender installation completes while a user is logged into the Mac, NinjaOne does not  
automatically restart the device.  
// Any restart that may ultimately be required can therefore occur separately rather than  
interrupting an active user session immediately after installation.
```

POST-INSTALL REBOOT OPTIONS - NO LOGGED-IN USER

Reboot immediately

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// If no user is currently logged into the Mac after installation, NinjaOne immediately restarts  
the device where a post-install reboot is applicable.
```

Attempt to reboot until successful

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

Do nothing

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

000 MASTER POLICY EFFECTIVE ANTIVIRUS DEPLOYMENT BEHAVIOR

```
// Bitdefender GravityZone is the configured antivirus integration.  
// Bitdefender installation proceeds even if another antivirus product is detected.  
// Failed Bitdefender installations are retried daily at 10:00 AM local device time.  
// If a user is logged in after installation:  
// - NinjaOne does not automatically restart the Mac.  
// If no user is logged in after installation:  
// - NinjaOne immediately restarts the Mac where a post-install reboot is applicable.  
// This section does not document the Bitdefender GravityZone security policy itself.  
// Bitdefender policy configuration remains external to the current scope of this document and  
may be added separately later.
```

S.II // Topic VII (T.VII) - Activity Monitoring

[Back to Table of Contents](#)

000 Master Status: Configured

001 Pre-Enrollment Status: Configured

002 Post-Enrollment Status: Configured

Description:

Activity Monitoring controls which NinjaOne-generated device, security, application, backup, operating-system, and integration events generate technician notifications and which notification channels receive those events.

The Activity Monitoring configuration is identical across:

000 Master MacOS Policy

001 Pre-Enrollment Policy

002 Post-Enrollment Policy

Most events configured to notify technicians are routed through the Microsoft Teams notification channel named:

Technicians (Teams)

Certain higher-priority events are additionally routed through:

TOW Technicians (Teams)

Events configured with "Notify Technicians: No" do not generate a technician notification through this policy configuration.

This section documents the event-monitoring and notification-routing configuration only. It does not modify the configuration of the underlying integrations or services that generate these events.

General Notification Behavior:

000 Master Status: Same Configuration

001 Pre-Enrollment Status: Same Configuration

002 Post-Enrollment Status: Same Configuration

Default Notification Channel for Enabled Events:

Technicians (Teams) [Microsoft Teams]

```
// Unless otherwise specified below, events marked "Notify Technicians: Yes" are routed through
the Technicians (Teams) notification channel.
```

```
// Events specifically marked with "+ TOW Technicians" are routed to both the standard
Technicians (Teams) channel and the additional TOW Technicians (Teams) channel.
```

CROWDSTRIKE

CrowdStrike Existing Installation Detected

Notify Technicians: No

CrowdStrike Installation Detected Another AV

Notify Technicians: Yes

Channel(s): Technicians (Teams)

CrowdStrike Mitigation Failed

Notify Technicians: Yes

Channel(s):

- Technicians (Teams)
- TOW Technicians (Teams)

CrowdStrike Mitigation Succeeded

Notify Technicians: Yes

Channel(s): Technicians (Teams)

CrowdStrike Quarantine Failed

Notify Technicians: Yes

Channel(s):

- Technicians (Teams)
- TOW Technicians (Teams)

CrowdStrike Quarantine Succeeded

Notify Technicians: Yes

Channel(s): Technicians (Teams)

CrowdStrike Machine Registration Failed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

CrowdStrike Machine Registration Succeeded

Notify Technicians: No

CrowdStrike Remediation Failed

Notify Technicians: Yes

Channel(s):

- Technicians (Teams)
- TOW Technicians (Teams)

CrowdStrike Remediation Succeeded

Notify Technicians: Yes

Channel(s): Technicians (Teams)

CrowdStrike Retry Install Completed

Notify Technicians: No

CrowdStrike Sensor Installation Failed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

CrowdStrike Sensor Installation Succeeded

Notify Technicians: No

CrowdStrike Sensor Migrated

Notify Technicians: No

CrowdStrike Sensor Provisioning

Notify Technicians: No

CrowdStrike Threat Detected

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

CrowdStrike Integration Detected Unmanaged Installation

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GRAVITYZONE

GravityZone Advanced Threat Control detected and blocked a threat

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GravityZone Advanced Threat Control detected and disinfected a threat

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GravityZone company associated with this device cannot be accessed

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GravityZone Device changed status to managed

Notify Technicians: **No**

GravityZone Device changed status to unmanaged

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GravityZone Extended Incident Reported

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GravityZone Incident Reported

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GravityZone installation detected another AV

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GravityZone Installation Failed

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GravityZone Installation Completed

Notify Technicians: **No**

GravityZone Installation Completed with Warnings

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GravityZone Purge of Quarantined Files Failed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

GravityZone Quarantined Threats Purged

Notify Technicians: No

GravityZone synchronize threats process

Notify Technicians: No

GravityZone Scan Completed

Notify Technicians: No

GravityZone Scan Failed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

GravityZone Scan Started

Notify Technicians: No

GravityZone Threat Blocked

Notify Technicians: Yes

Channel(s): Technicians (Teams)

GravityZone Threat Cleaned

Notify Technicians: Yes

Channel(s): Technicians (Teams)

GravityZone Threat Deleted

Notify Technicians: Yes

Channel(s): Technicians (Teams)

GravityZone Remove Threat From Quarantine Initiated

Notify Technicians: No

GravityZone Remove Threat From Quarantine Completed

Notify Technicians: No

GravityZone Remove Threat From Quarantine Failed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

GravityZone Threat Ignored

Notify Technicians: Yes

Channel(s):

- Technicians (Teams)
- TOW Technicians (Teams)

GravityZone Threat Quarantined

Notify Technicians: Yes

Channel(s): Technicians (Teams)

GravityZone Threat Reported

Notify Technicians: Yes

Channel(s): Technicians (Teams)

GravityZone Restore and Exclude Threat From Quarantine Initiated

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GravityZone Restore and Exclude Threat From Quarantine Failed

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GravityZone Restore Threat From Quarantine Initiated

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GravityZone Restore Threat From Quarantine Completed

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

GravityZone Restore Threat From Quarantine Failed

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

BACKUP

Backup job canceled

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

Backup job completed

Notify Technicians: **No**

Backup job completed with warning

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

Backup job failed

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

Backup job started

Notify Technicians: **No**

Backup plan added

Notify Technicians: **No**

Backup plan deleted

Notify Technicians: **Yes**

Channel(s): **Technicians (Teams)**

Backup plan edited

Notify Technicians: **No**

Backup downloaded

Notify Technicians: **No**

Image Download Canceled

Notify Technicians: Yes
Channel(s): Technicians (Teams)

Image download completed
Notify Technicians: No

Image download failed
Notify Technicians: Yes
Channel(s): Technicians (Teams)

Image download resumed
Notify Technicians: No

Image download started
Notify Technicians: No

Image Restore Canceled
Notify Technicians: No

Image restore completed
Notify Technicians: No

Image restore failed
Notify Technicians: No

Image restore resumed
Notify Technicians: No

Image restore started
Notify Technicians: No

Backup installed
Notify Technicians: No

Backup install failed
Notify Technicians: Yes
Channel(s): Technicians (Teams)

Integrity Check Completed
Notify Technicians: No

Integrity Check Failed
Notify Technicians: Yes
Channel(s): Technicians (Teams)

Restore job canceled
Notify Technicians: No

Restore job completed
Notify Technicians: No

Restore job failed
Notify Technicians: No

Restore job started
Notify Technicians: No

Backup uninstalled

Notify Technicians: Yes
Channel(s): Technicians (Teams)

Backup uninstall failed
Notify Technicians: Yes
Channel(s): Technicians (Teams)

Sync to cloud canceled
Notify Technicians: No

Sync to cloud completed
Notify Technicians: No

Sync to cloud failed
Notify Technicians: Yes
Channel(s): Technicians (Teams)

Sync to cloud started
Notify Technicians: No

MAC

FileVault turned off
Notify Technicians: Yes
Channel(s): Technicians (Teams)

```
| // Generates a technician notification if FileVault encryption is disabled on a managed Mac.
```

FileVault turned on
Notify Technicians: No

Mac daemon started
Notify Technicians: No

Mac daemon stopped
Notify Technicians: Yes
Channel(s): Technicians (Teams)

```
| // Generates a technician notification if the NinjaOne macOS daemon stops.
```

SENTINELONE

SentinelOne Agent Installation Failed
Notify Technicians: Yes
Channel(s): Technicians (Teams)

SentinelOne Agent Installation Succeeded
Notify Technicians: No

SentinelOne Agent Sync Cancelled
Notify Technicians: No

SentinelOne Agent Failed To Sync
Notify Technicians: Yes

Channel(s): Technicians (Teams)
SentinelOne Agent Failed To Sync: Retrying
Notify Technicians: Yes
Channel(s): Technicians (Teams)
SentinelOne Agent Sync Mapping Failed
Notify Technicians: Yes
Channel(s): Technicians (Teams)
SentinelOne Agent Successfully Synced
Notify Technicians: No
SentinelOne Agent Upgrade Succeeded
Notify Technicians: No
SentinelOne Existing Installation Detected
Notify Technicians: Yes
Channel(s): Technicians (Teams)
SentinelOne Installation Detected Another AV
Notify Technicians: Yes
Channel(s): Technicians (Teams)
SentinelOne Mitigation Succeeded
Notify Technicians: No
SentinelOne Quarantine Succeeded
Notify Technicians: No
SentinelOne Remediation Succeeded
Notify Technicians: No
SentinelOne Scan Aborted
Notify Technicians: No
SentinelOne Scan Completed
Notify Technicians: No
SentinelOne Scan Started
Notify Technicians: No
SentinelOne Threat Detected
Notify Technicians: Yes
Channel(s): Technicians (Teams)

SOFTWARE

Software Added
Notify Technicians: Yes
Channel(s): Technicians (Teams)
Software Removed
Notify Technicians: Yes
Channel(s): Technicians (Teams)

Software Updated

Notify Technicians: No

SYSTEM

Adapter added

Notify Technicians: Yes

Channel(s): Technicians (Teams)

Adapter config changed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

Adapter removed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

Adapter status changed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

CPU added

Notify Technicians: Yes

Channel(s): Technicians (Teams)

CPU removed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

Disk drive added

Notify Technicians: Yes

Channel(s): Technicians (Teams)

Disk drive removed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

Disk partition added

Notify Technicians: Yes

Channel(s): Technicians (Teams)

Disk partition removed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

Disk volume added

Notify Technicians: Yes

Channel(s): Technicians (Teams)

Disk volume removed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

Asset management tag assigned

Notify Technicians: No

Asset management tag removed

Notify Technicians: No

Memory added

Notify Technicians: Yes

Channel(s): Technicians (Teams)

Memory removed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

Port closed

Notify Technicians: No

Port opened

Notify Technicians: Yes

Channel(s): Technicians (Teams)

Process started

Notify Technicians: No

Process stopped

Notify Technicians: No

System rebooted

Notify Technicians: Yes

Channel(s): Technicians (Teams)

USER

User account added

Notify Technicians: Yes

Channel(s): Technicians (Teams)

User account removed

Notify Technicians: Yes

Channel(s): Technicians (Teams)

User logged in

Notify Technicians: No

User logged out

Notify Technicians: No

POLICY BEHAVIOR SUMMARY

// Activity Monitoring is configured identically across all three macOS policies.

// Activity Monitoring does not itself define the underlying antivirus, backup, software, or operating-system behavior. It determines which events generated by NinjaOne or its integrations are surfaced to technicians.

```
// Events marked "Notify Technicians: Yes" generally route alerts to:  
// Technicians (Teams)  
  
// Certain events additionally route to:  
// TOW Technicians (Teams)  
  
// Events observed with the additional TOW Technicians notification channel include:  
// - CrowdStrike Mitigation Failed  
// - CrowdStrike Quarantine Failed  
// - CrowdStrike Remediation Failed  
// - GravityZone Threat Ignored  
  
// Routine success/start/completion events are frequently configured without notifications, while  
// failure, threat, security-state, hardware-change, and other notable events are generally  
// configured to notify technicians.  
  
// CrowdStrike and SentinelOne activity rules remain configured within Activity Monitoring even  
// though Bitdefender GravityZone is the antivirus integration currently selected for this macOS  
// policy.  
  
// Those monitoring entries do not deploy CrowdStrike or SentinelOne themselves; they define  
// notification behavior if NinjaOne receives the corresponding activity event.
```

S.II // Topic VIII (T.VIII) - NinjaOne Backup [Lockhart]

[Back to Table of Contents](#)

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

Description:

This configuration defines the NinjaOne Backup / Lockhart File/Folder backup plan assigned through the macOS policy architecture.

The configured backup plan is named:

TOW Foundation File Backup Plan

The plan performs file/folder-level backups to NinjaOne Cloud storage rather than creating a full-device image backup.

At the 000 Master MacOS Policy level, the backup plan exists and is fully configured but is currently Disabled. Therefore, the configuration documented below represents the intended backup behavior if/when the plan is enabled by an applicable policy.

The plan includes user-profile data, applies NinjaOne's configured/default backup exclusions, retains up to 30 revisions, and runs once daily according to the local device time.

Settings, Configured Values, & their Descriptions

BACKUP PLAN

Plan Name

TOW Foundation File Backup Plan

000 Master Status: Disabled

001 Pre-Enrollment Status: Disabled

002 Post-Enrollment Status: Disabled

Type: File/Folder

Destination: Cloud

Overrides: None

```
// The backup plan copies selected files and folders to NinjaOne-hosted cloud backup storage.
// This is a File/Folder backup plan rather than a full-system/image backup plan.
```

GENERAL

Backup Destination

Value: Cloud

```
// Backup data is stored in NinjaOne's configured cloud backup destination.
```

Schedule

Value: `Daily`

Backup Time

Value: `04:30 PM`

Time Zone

Value: `Local device time`

| `// The backup schedule is evaluated according to the local time configured on each managed Mac.`

POWER OPTIONS

Prevent device from sleeping

Status: `Enabled`

| `// Prevents the Mac from entering sleep while the backup operation is actively running.`

Attempt to wake device if sleeping

Status: `Enabled`

| `// Allows the backup workflow to attempt to wake a sleeping device so that the scheduled backup can execute.`

Run plan immediately if missed

Status: `Enabled`

| `// If the scheduled backup is missed, NinjaOne is configured to execute the backup as soon as possible afterward rather than waiting until the following day's scheduled window.`

REVISION RETENTION

Limit revisions to

Status: `Enabled`

Maximum Revisions: `30`

| `// NinjaOne retains up to 30 revisions of backed-up files under this plan.`

Trim revisions older than

Status: `Disabled`

Configured Value Shown: `30 Days`

| `// Age-based revision trimming is not enabled.`

| `// Revision retention is therefore controlled by the maximum revision count rather than automatically deleting revisions solely because they exceed a configured age.`

FOLDER SCOPE

Full Disk Access Requirement

```
// NinjaOne indicates that Full Disk Access is required for a successful File/Folder backup on macOS.
```

Included Common Folders

Value: All current and future user profiles

```
// The plan is configured to include data belonging to existing user profiles as well as user profiles created in the future.
```

Additional Included Folder Paths

None Configured

Excluded Common Folders

None Configured

Additional Excluded Folder Paths

None Configured

```
// No custom folder-level inclusions or exclusions are configured beyond the common-folder selection and the Advanced exclusions documented later in this section.
```

FILE FILTERS

Filter Mode

Status: All files

```
// All files contained within the selected backup source scope are eligible for backup unless excluded by an Advanced exclusion rule.
```

Include file masks

Status: Disabled

Exclude file masks

Status: Disabled

```
// No additional custom include/exclude file masks are configured within the Filters section.
```

ADVANCED / PLAN EXCLUSIONS

```
// The backup plan contains a substantial list of enabled exclusions.
```

```
// These exclusions prevent system files, operating-system locations, virtual-machine files, application packages, disk images, temporary files, metadata, and other unsuitable or unnecessary data from being included in the backup.
```

```
// All exclusions shown below are Enabled.
```

```
// NinjaOne warns that modifying default exclusions may cause excessive storage usage, synchronization problems, or access errors.
```

GENERAL / SYSTEM EXCLUSION

System Files

Type: -

Status: Enabled

FILE EXTENSION EXCLUSIONS

*.ithmb

Type: Extension

Status: Enabled

*.vmdk

Type: Extension

Status: Enabled

*.vmem

Type: Extension

Status: Enabled

*.vmsd

Type: Extension

Status: Enabled

*.vmsn

Type: Extension

Status: Enabled

*.vmx

Type: Extension

Status: Enabled

*.vmxf

Type: Extension

Status: Enabled

*.menudata

Type: Extension

Status: Enabled

*.appicon

Type: Extension

Status: Enabled

*.appinfo

Type: Extension

Status: Enabled

*.pva

Type: Extension

Status: Enabled

*.pvs

Type: Extension

Status: Enabled

*.pvi

Type: Extension

Status: Enabled

*.pvm

Type: Extension

Status: Enabled

*.fdd

Type: Extension

Status: Enabled

*.hds

Type: Extension

Status: Enabled

*.drk

Type: Extension

Status: Enabled

*.mem

Type: Extension

Status: Enabled

*.nvram

Type: Extension

Status: Enabled

*.hdd

Type: Extension

Status: Enabled

*.wab~

Type: Extension

Status: Enabled

*.sys

Type: Extension

Status: Enabled

*.cab

Type: Extension

Status: Enabled

*.exe

Type: Extension

Status: Enabled

*.msi

Type: Extension

Status: Enabled

*.dll

Type: Extension

Status: Enabled

*.dl_

Type: Extension

Status: Enabled

*.wim

Type: Extension

Status: Enabled

*.ost

Type: Extension

Status: Enabled

*.o

Type: Extension

Status: Enabled

*.qtch

Type: Extension

Status: Enabled

*.log

Type: Extension

Status: Enabled

*.vmc

Type: Extension

Status: Enabled

***.vhd**

Type: Extension

Status: Enabled

***.v01**

Type: Extension

Status: Enabled

***.v02**

Type: Extension

Status: Enabled

***.vsv**

Type: Extension

Status: Enabled

***.vud**

Type: Extension

Status: Enabled

***.iso**

Type: Extension

Status: Enabled

***.dmg**

Type: Extension

Status: Enabled

***.pkg**

Type: Extension

Status: Enabled

***.sparseimage**

Type: Extension

Status: Enabled

***.icloud**

Type: Extension

Status: Enabled

```
// These exclusions primarily prevent virtual-machine disk/state files, installers,
executable/application files, disk images, temporary/system files, and other large or
reconstructable data from consuming File/Folder backup storage.
```

FOLDER EXCLUSIONS

/Applications**Status: Enabled****/Desktop DB****Status: Enabled****/Desktop DF****Status: Enabled****/Home****Status: Enabled****/Library****Status: Enabled****/Network****Status: Enabled****/Private****Status: Enabled****/System****Status: Enabled****/Volumes****Status: Enabled****/automount****Status: Enabled****/bin****Status: Enabled****/cores****Status: Enabled****/dev****Status: Enabled****/etc****Status: Enabled****/mach****Status: Enabled****/mach_kernel**

Status: Enabled

/mach.sym

Status: Enabled

/net

Status: Enabled

/opt

Status: Enabled

/sbin

Status: Enabled

/sw

Status: Enabled

/tmp

Status: Enabled

/usr

Status: Enabled

/\/.app

Status: Enabled

/\/.DS_Store

Status: Enabled

/\/.fsevents

Status: Enabled

/\/.hotfiles.btree

Status: Enabled

/\/.Spotlight

Status: Enabled

/\/.Trashes

Status: Enabled

/\/.vol

Status: Enabled

/Users/[^/]+/Library

Status: Enabled

/Users/[^/]+/Applications

Status: Enabled

/Users/[^/]+/Parallels

Status: Enabled

/Users/[^/]+/Virtual Machines.+

Status: Enabled

/Users/[^/]+/.config/Carbonite

Status: Enabled

/Users/[^/]+/.Trash

Status: Enabled

/Library/Application Support/com.apple...

Status: Enabled

```
// NinjaOne truncates the complete value of this entry in the visible policy interface
// screenshot. The exact exclusion should be copied directly from NinjaOne if the full raw value is
// required in the final documentation.
```

/var

Status: Enabled

```
// Folder exclusions remove operating-system directories, application directories, virtual-
// machine storage, caches, trash locations, system metadata, and other non-user-data locations from
// the File/Folder backup scope.
```

COMMON EXCLUSIONS

.*\.DS_Store

Type: Common

Status: Enabled

```
// Excludes macOS .DS_Store metadata files from backup.
```

FILENAME EXCLUSIONS

.localized

Type: Filename

Status: Enabled

```
// Excludes macOS localization metadata files from backup.
```

000 MASTER POLICY EFFECTIVE BACKUP BEHAVIOR

```
// The TOW Foundation File Backup Plan is configured but Disabled at the 000 Master policy level.
// If enabled by an applicable policy:
```

```
// Backup Type:
// File/Folder

// Destination:
// Cloud

// Schedule:
// Daily at 04:30 PM local device time

// Missed backups:
// Run immediately when possible

// Power behavior:
// - Prevent sleep during backup
// - Attempt to wake sleeping device

// Source scope:
// - All current user profiles
// - Future user profiles

// File filtering:
// - All files eligible
// - Subject to enabled Advanced exclusions

// Revision retention:
// - Maximum 30 revisions
// - No age-based trimming

// Custom include paths:
// None

// Custom exclude paths:
// None

// Plan overrides:
// None

// A large set of NinjaOne-defined system, application, virtual-machine, installer, disk-image,
metadata, and operating-system exclusions are enabled to prevent unsuitable data from being
included in the File/Folder backup set.
```

S.II // Topic IX (T.IX) - NinjaOne Warranty Tracking

[Back to Table of Contents](#)

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

Description:

This configuration enables NinjaOne Warranty Tracking activity for managed devices and defines when warranty-expiration activity should be evaluated.

The configuration is identical across:

000 Master MacOS Policy

001 Pre-Enrollment Policy

002 Post-Enrollment Policy

Warranty Tracking is configured to evaluate devices whose warranty expiration date is approaching within 60 days. The activity is evaluated weekly on Tuesday.

No notification channels, severity, priority, or SMS/Email technician notifications are currently configured. As a result, the warranty-tracking activity is enabled, but this policy does not currently configure an outbound technician notification for the resulting activity.

Settings, Configured Values, & their Descriptions

WARRANTY TRACKING ACTIVITY

Enable Warranty Tracking activity

000 Master Status: Enabled

001 Pre-Enrollment Status: Enabled

002 Post-Enrollment Status: Enabled

```
// Enables NinjaOne's Warranty Tracking activity for devices receiving the policy.
```

```
// The configured schedule below determines when NinjaOne evaluates devices against the configured warranty-expiration threshold.
```

WARRANTY EXPIRATION SCHEDULE

Threshold

Value: 60 Days

```
// Defines the warranty-expiration threshold used by the activity.
```

```
// Devices whose warranty is approaching the configured threshold may satisfy the Warranty Tracking activity criteria.
```

Type

Value: Before warranty expires

```
// Applies the 60-day threshold before the recorded device warranty expiration date.
```

```
| // In practical terms, the activity is configured to identify devices approaching warranty  
| expiration rather than devices whose warranty has already expired.
```

Frequency

Value: **Weekly**

```
| // Warranty Tracking is evaluated on a weekly schedule.
```

Day

Value: **Tuesday**

```
| // The weekly Warranty Tracking evaluation is scheduled for Tuesday.
```

NOTIFICATIONS

Notification Channels

000 Master Status: **None Configured**

001 Pre-Enrollment Status: **None Configured**

002 Post-Enrollment Status: **None Configured**

```
| // No notification channel is currently selected for Warranty Tracking activity.
```

Severity

Value: **None**

```
| // No NinjaOne severity classification is assigned to the Warranty Tracking activity.
```

Priority

Value: **None**

```
| // No NinjaOne priority classification is assigned to the Warranty Tracking activity.
```

Notify Technicians via SMS/Email

Status: **Disabled**

```
| // Technician SMS/Email notifications are not enabled for Warranty Tracking.
```

EFFECTIVE WARRANTY TRACKING BEHAVIOR

```
| // Warranty Tracking activity is enabled across all three macOS policies.
```

```
| // Warranty expiration threshold:
```

```
| // 60 days before warranty expiration
```

```
| // Evaluation frequency:
```

```
| // Weekly
```

```
| // Evaluation day:
```

```
| // Tuesday
```

```
| // Notification channels:
```

```
| // None configured
```

```
| // Severity:
```

// None

// Priority:

// None

// Technician SMS/Email notifications:

// Disabled

// The policy therefore enables and evaluates Warranty Tracking activity, but does not currently configure an outbound technician notification through the available notification settings.