

# GeoPIXE Change Log

## GeoPIXE-open-source

Note: For complex changes, tag the source file lines with: ;@month-year (e.g. ;@3-16).

### 8 Apr, 2025

1. Fix case sensitive filenames and dirs used in database build on Linux.
  - a. Fix filenames on PC to match case in routines.
  - b. Fix case in routines: build\_ebel\_data.

### 1 Apr, 2025

1. Bug in device name shown in *Spectrum History* window for old files (pre about 2012).
  - a. Would display as Mpsys\_device, when not so.
  - b. Read\_spec
    - i. Type of old 'device' not declared properly (appears as Float). Now fixed as Integer. Seems default behaviour in IDL has changed at some time.
2. Bug with the selection of a ADC # in the *Energy Cal* window for a "Get" of that selected energy calibration.
  - a. Read\_spec
    - i. Now form 'find\_offset' for use in call to 'get\_spec' to retrieve selected ADC # spectrum:
      1. find\_offset = find - 1 - adc\_offset\_device(obj), clipped at zero,
        - a. where 'find' is the *Cal* Get droplist index (e.g. 0 for "any", 1 for "0", 2 for "1", etc.).
        - b. The 'adc\_offset\_device(obj)' function returns 0 for devices where the ADC # start at 1, -1 for devices where the ADC # start at 0 and 2 for devices where the ADC # start at 3, etc. (i.e. "start ADC" -1).
      - ii. Tested OK for a range of device spec files with different Start ADC and offsets.
      - iii. Note that some old spec files have inconsistent ADC # shown in the "label" field.
3. Version 8.8t

### 27 Mar, 2025

1. Revisit Linux IDL display/resize bug
  - a. Background
    - i. In the main *gImage* window, when resized (either by dragging the window size or using the "+", "-" buttons) it sometimes displays the image offset in Y, with grey beneath and the top of the image truncated. This only happens when the whole image is visible and hence (normally) the scroll bars disappear.
    - ii. This only happens under Linux, and has persisted through IDL 8.8 to 9.1.
    - iii. And only if the Y scroll bars disappear.
    - iv. Attempts to use the viewport position controls fail to fix this.
    - v. Tests manually using the "tv" command, to draw an image into the Draw widget's wid also show this offset, but not on a fresh window (using the "window" command).
  - b. Work-around
    - i. The previous work-around simply prevented the scroll bars from disappearing.
    - ii. The new work-around allows the X scroll bars to disappear, but not Y.
    - iii. It also adjusts this to the pixel level, to minimize the area of image hidden in Y.
2. Set\_image\_view
  - a. Add new offsets 'scr\_xtrim' and 'scr\_ytrim' to prevent Y scroll bars going in setting 'new.w', 'new.h'. These are zero except for Linux.
3. OnSize\_image
  - a. Add new offsets 'scr\_xtrim' and 'scr\_ytrim' to prevent Y scroll bars going in setting 'w', 'h'. These are zero except for Linux.

## 24 Mar, 2025

1. Layer\_setup
  - a. Problem arose if manual enter parameters into layer setup (not restore from LCM).
    - i. Then 'beam' not defined.
  - b. 'calculate-button' event:
    - i. Only assign beam.continuum and beam.energy if 'beam' is defined.
2. Geo\_yield2
  - a. Move 'beam2' spectrum code inside the continuum==true if block.
3. Compare tests:
  - a. Tested (i) simple PIXE yield calc (single detector) – donuts2, and (ii) MM continuum yield calculation with Maia detector – rock-slab-poly2.
  - b. Used 'compare\_yield' test: Results equal to reference yields.

## 24 Mar, 2025

1. Geopixe\_default
  - a. Tests for valid "path data" and "path config" in '.geopixe/geopixe.conf' file only happen once now, reducing annoying popups.

## 14 Mar, 2025

1. Geopixe\_default
  - a. Tests for valid "path data" and "path config" in '.geopixe/geopixe.conf' file.
  - b. Pops up a warning if these are not setup, suggests Edit of "geopixe.conf" file.
2. Strip\_non\_alphanumeric, strip\_non\_print
  - a. Extended to vector string arguments.

## 5 Mar, 2025

1. Maia\_launch
  - a. maia\_launch\_version2
    - i. Add set *antialias.enable*, once and for all to enable antialiasing in the Maia FPGA pipeline to prevent aliasing using Linearization and Gain-trimming.
  - b. Version 8.8s
2. GeoPIXE
  - a. Version 8.8s

## 4 Mar, 2025

1. Plot\_maia\_parameters
  - a. This calls 'file\_requester', which may use 'file\_search2', which uses the 'progress' bar. The 'progress' bar will set a new window to draw the progress bar in.
  - b. Hence, in 'plot\_maia\_parameters', do not call 'file\_requester' between opening a new window and plotting to it.
2. Pulser\_FWHM\_map\_spectrum\_plugin
  - a. Don't need to open window with 'window,0' as this is done in 'plot\_maia\_parameters'.

## 17 Feb, 2025

1. Petra P06 H5 Nexus device object (draft)
  - a. Reads P06 tree of NXS files into spectra.
  - b. Get flux and dwell working, but no gain scales.
2. Scan\_list
  - a. Updated tests of python and IDL versions in scan\_list.
  - b. Fixed errors in bin/ scripts for this.
  - c. Changed it to make settings from 'geopixe.conf' take precedence, if found.
3. Maia\_launch
  - a. Fixed bug in LED[3] used to flag all background processes running.

**12 Feb, 2025**

1. Petra P06 H5 Nexus device object (draft)
  - a. Added adding 'adc\_\*/value1, value2, ...', 'qbpm\_\*/value1, value2, ...' as PVs.
  - b. Added reading this PV in 'read\_setup' for each data file.

**4 Feb, 2025**

1. Python\_valid
  - a. Check python version against IDL for compatibility.

IDL version	Python version									
	2.7	3.4	3.5	3.6	3.7	3.8	3.9	3.10	3.11	3.12
8.5	✓	✓								
8.5.1	✓	✓								
8.5.2	✓	✓	✓							
8.6	✓	✓	✓							
8.6.1	✓	✓	✓	✓						
8.7	✓	✓	✓	✓						
8.7.1	✓		✓	✓						
8.7.2	✓		✓	✓						
8.7.3	✓		✓	✓						
8.8				✓	✓	✓				
8.8.1				✓	✓	✓	✓			
8.8.2					✓	✓	✓	✓		
8.8.3					✓	✓	✓	✓		
8.9						✓	✓	✓		
9.0						✓	✓	✓	✓	
9.1							✓	✓	✓	✓

NOTE: IDL versions prior to 8.5 do not support Python bridge functionality.

This fixes an error in doing these tests in Maia-Control.

2. Maia\_control
  - a. Check python against IDL using 'python\_valid()'.

**27 Jan, 2025**

1. File\_requester
  - a. 'updir' was stopping one level short. Fixed.
2. Detector\_update
  - a. If a detector is not found on path1 (geopixe\_root), path2 (prefs.path.config) or the detector file's path, then popup file\_requester (with updir=3 from local dir) to prompt for it, and append it to the list (at end, not alphabetically sorted).
3. Fit\_setup
  - a. Only read detector once: pending after normal detector entry and done after yield detector entry.
  - b. As detector file is saved in PCM with no path, use the path for the PCM as a start (as well as config/detectors in 'detector\_update').
  - c. Make detector Layout behave similarly, inheriting the path for the detector file.
4. Deleted rogue SAV file
  - a. A plugin (FWHM map) had been compiled into the local project dir.
    - i. This SAV file then gets included in the next compile in that project (a nasty habit of IDL).
    - ii. It included 'resolve\_all', which means it included ALL GeoPIXE routines into the plugin's SAV file.
    - iii. On running GeoPIXE, these SAV files get loaded and write over newer versions of many routines that have been compiled (into GeoPIXE.sav) since the plugin. This of course a really bad thing, and confusing for debugging.
  - b. Deleted the offending SAV file.

- i. There should be NO SAV files in any plugin dir, only in the “geopixe” Runtime dir.
- 5. Version 8.8r.

## 20 Jan, 2025

- 1. maia\_launch
  - a. Instead of just reporting an over-leakage event, it now takes action to set the bias back to minimum.
- 2. maia\_launch\_read\_da\_info
  - a. Removed illegal ref to \*pl.

## 10 Jan, 2025

- 1. maia\_launch
  - a. Corrected code to check compatibility between python and IDL.
  - b. Maia Version 8.8r
- 2. Idl\_query
  - a. Added code to check compatibility between python and IDL.

## 8 Jan, 2025

- 1. maia\_launch
  - a. The frame=0 option on widget\_text used to have this behavior:
    - i. Ignored under Windows, frame drawn anyway.
    - ii. Seemed to draw a frame under Linux as well.
  - b. Now in v9.1 IDL
    - i. Windows does not draw a frame.
    - ii. Linux still does, weird.
  - c. Fixed by explicitly using frame=1 for widget\_text
    - i. Status field, help field, blog number field.
    - ii. Under Linux, frame seems a bit wider now.
- 2. Idl\_query
  - a. Lmgr2
    - i. Can't spawn “activate” in IDL v9, as it does not exist; skip.
- 3. Version 8.8q

## 7 Jan, 2025

- 1. Plot\_maia\_parameters
  - a. Add a call to “file\_requester( /read, /skip\_if\_exists, updir=2, ...) to find the default layout file ‘Maia\_384C.csv’ on a neighbouring path in the runtime distribution.
  - b. This is used in: ‘Pulser\_FWHM\_map\_spectrum\_plugin’, ‘Peak\_Stats\_spectrum\_plugin’, ‘Peak\_Fit\_Stats\_spectrum\_plugin’ and compiled in main ‘GeoPIXE.sav’. The latter (‘Peak\_Fit\_Stats\_spectrum\_plugin’) does supply an explicit filename.
  - c. Only need to recompile main GeoPIXE.
- 2. Merged develop branch, which had conflicts to fix:
  - a. Firstly, I forgot I was in “develop” when upgrading the Workspace in IDL 9.1.
  - b. No way to fix this except merging “develop” into main.
  - c. There were duplicates: bat file to run IDLDE, GeoPIXE.sav.
  - d. Deleted the sav files and fix bat, git Add and Commit.
  - e. Did not fix new “No explicit project encoding” project warnings.

## 3 Dec, 2024

- 1. Plot\_corr
  - a. Add options for /PNG (bit mapped) and /JPEG (true) plots for *Association* window following prescription in ‘plot\_images’.
- 2. Plot\_corr\_select
  - a. Add options for /PNG and /JPEG plots for *Association* window.

3. Corr\_export
  - a. Add options for /PNG and /JPEG plots for *Association* window.
4. Corr\_event
  - a. Make /JPEG plot the default for call to 'corr\_export'.
5. Gimage
  - a. Add Test menu item to test Pink Beam sources, calling 'compare\_pink'.
6. Export\_da2
  - a. Added more notes in software organization doc for binary export for DA real-time imaging.

## 20 Nov, 2024

1. Compare\_yield
  - a. Test for New and Ref both array detectors, else flag error in output file.

## 11 Nov, 2024

1. Compare\_fit
  - b. Add ability to deal with a PFR file with multiple rows (e.g. for ROI or individual array detectors).
  - c. Shows any models that differ by more than 0.1 % generally and 3% for fitted areas/concs.
  - d. Veto "Compton", "elastic" and "sum" in comparisons.
2. Compare\_source
  - a. Add 'tol' argument, defaults to 0.001.
3. Compare\_pink
  - a. Add 'tol' argument, defaults to 0.001.
4. Compare\_yields
  - a. Add 'tol' argument, defaults to 0.001.
5. Builder
  - a. Make sure !path is not cumulative as projects are processed.
  - b. Output 'build.spro' always to "main" dir.
6. Gimage
  - a. Add a "tests" menu for the 'compare' routines.

## 28 Oct, 2024

1. Compare\_fit
  - e. New routine to compare fit results files (.PFR files) as a step towards a unit test.
  - f. Simply prints out any inconsistencies found to the 'output' file.
  - g. Also reports diffs for derived area, conc, MDL, etc.
2. Pixe\_fit
  - a. The order of "state" and "e\_beam" in the 'ryield' struct have been reversed at some stage (2 instances of 'ryield'). But this effects the format in the PFR fit results file. Hence, newer PFR files read back with these switched.
  - b. Fortunately, these parameters do not get used - they are for info only. However, the 'compare\_fit' routine flagged them as inconsistent.
  - c. Hence, they have been switched back, so that new PFR files are consistent with old ones.
  - d. This will mean some instances of PFR file in between remain switched, which will be flagged harmlessly by 'compare\_fit'.
3. Pixe\_initial
  - a. For negative Z, and Compton line index, name "element", e.g. as "cIn".
  - b. But do these cIn lines inherit normal In rel-ints, rather than from beam lines?
    - i. Rel-ints for Comptons lines do come from beam lines. Good. However, the rel-int of the source lines is coming from normal rel-ints at the moment.
    - ii. Fixed this in 'select\_element\_lines'.
4. Sum\_peaks
  - a. Use abs(z) to form el names for lines (to account for -Z used for Comptons).
5. Select\_element\_lines
  - a. Use -Z for Compton peaks from source lines (mark all changes with ;@10-24).

- b. Add option (in line) to match lines for any element that is also in source, to source rel-ints.
    - i. Uses 'match\_source\_intensity' = 1 in code.
  - c. Do not change Continuum Beam Lines rel int here (done now in 'source\_calculate').
- 6. Source\_calculate
  - a. Calculate change to lines rel due to polycapillary (not in 'select\_element\_lines' now).
- 7. Version 8.8p

## 16-21 Oct, 2024

- 1. Compare\_source
  - a. New routine to compare Lab source model results (.source files) as a step towards a unit test for the lab source modelling.
  - b. Checks beam.model should be "1".
  - c. Shows any results that differ by more than 0.1 %.
  - d. Simply prints out any inconsistencies found to the 'output' file.
  - e. Also reports diffs for derived source spectra.
- 2. Sig\_change
  - a. Shows any results that differ by more than a 'tol' value, defaults to 1 ppm.
- 3. Source\_calculate
  - a. Veto any input or interpolated polycapillary transmission table values less than zero.
- 4. Source\_setup
  - a. Fix the mapping of polycapillary and monochromator widgets.
- 5. Compare\_pink
  - a. New routine to compare Pink Beam source model results (.pink files) as a step towards a unit test for the pink beam modelling.
  - b. Checks beam.model should be "2".
  - c. Ignores polycapillary, for later.
  - d. Shows any results that differ by more than 0.1 %.
  - e. Simply prints out any inconsistencies found to the 'output' file.
  - f. Also reports diffs for derived pink beam spectra.
- 6. Compare\_yields
  - a. Needs to switch between 'compare\_source'; and 'compare\_pink' depending on beam.model.
  - b. Tests for consistent beam.model.

## 7 Oct, 2024

- 1. /sec\_fl in yield calculation - tidy up.
  - a. Geo\_array\_yield
    - i. Argument 'sec\_fl' not used, remove
  - b. Results\_properties
    - i. Remove arg 'sec\_fl' passed to geo\_array\_yield.
  - c. Geo\_yield2
    - i. Tidy comments about 'sec\_fl'.
- 2. Compare\_yields
  - a. New routine to compare yield calculation results (.yield files) as a step towards a unit test for the yield modelling.
  - b. Shows any results that differ by more than 0.1 %.
  - c. Simply prints out any inconsistencies found to the 'output' file for the time being.
- 3. Geopixe\_do\_command
  - a. If first argv[0] is NOT a GCF file name, then assume a simple command execution, with three arguments: "command, files (string vector in stringify format), output".
  - b. This enables the test to be run in a script or workflow.
  - c. See test in BAT script: "Unit test Runtime GeoPIXE.bat".
- 4. Q\_to\_xyz
  - a. Routine to convert index vector 'q' into a 3D array to vectors of the indices for x,y,z in the array. Analogous to old 'q\_to\_xy' for a 2D array.
- 5. File\_requester

- a. Will now call 'startupp' if `geopixe_root` is not defined.

## 2 Oct, 2024

1. Make branch 'develop' for development and beta release.
  - a. This is identical with current 'main' at the moment.
2. Recommend to make other branches off 'develop' for feature additions and other fixes.

## 1 Oct, 2024

1. Export\_DA2
  - a. Accepts keywords for pileup, throttle and linear, which can be set from fields in Evt window.
    - i. Linear is not used at present, as we don't have tools for realtime use of the Maia v2 Linearization functions.
  - b. Binary (dmx) mode changed:
    - i. Does not output individual detector E cals to the export file. These are supposed to be set elsewhere and should not be part of the DA matrix.
    - ii. Version now -2.
  - c. iThemba (dmm) mode changed:
    - i. Similar to DMX binary, but limits size of DA matrix (compressed if necessary).
    - ii. Does not output individual detector E cals to the export file. These are supposed to be set elsewhere and should not be part of the DA matrix.
    - iii. Version now -2.
  - d. Further work:
    - i. Does not export the *rGamma* matrix or *Pure* arrays. This is needed(?) to properly integrate contributions across an array (using selected channels) for quantitative estimation from regions/spectra, or at least for the spectra overlays.
2. EVT
  - a. Add "Exp" button next to DA matrix file fields to call 'export\_DA2' to export the chosen DA matrix for use in a data acquisition system for realtime imaging and spectra analysis.
3. Fit\_setup
  - a. Used to call 'export\_DA' from "Export" button next to "Generate DA" button to output an expot file for use in a data acquisition system for realtime imaging and spectra analysis.
  - b. Now it calls 'Export\_DA2', which does not include the pointers to spectra and does not output individual detector E cals to the export file. These are supposed to be set elsewhere and should not be part of the DA matrix. These files now have version = -2.

## 4 June, 2024

1. spectrum\_display\_eventcb
  - a. Spectrum\_Menu\_Clear\_Cal
    - i. Only check second string in label for "/X" and "/Y", not whole label, which may include path components with these sub-strings. Only want to test the post-fix tags.
2. wizard\_standards
  - a. Allow "serial" to be blank, and match with a blank in "standards.csv" table.
  - b. Do not set "On" zero if serial is blank.
3. NSLS MARS Ge device
  - a. Swapped to big endian byte order for read in device.
4. Version 8.8n

## 3 June, 2024

1. Maia device
  - a. Added an options widget to adjust/correct a skew in X values, expressed as "correct X by one for every 'n' Y rows", with this set via a droplist.
  - b. Read/write options now version -7 to cater for skew.x
    - i. This will require this new version Maia device to read DAI file.

- c. 'Read\_buffer' - corrects x1 by y1 (i.e.  $x1 = x1 - \text{long}(y1 / \text{float}(\text{self.sort\_options.skew.x}))$ ). This is done before any xoffset, so should work fine in cluster mode. Also done before any flip axis options, so applies to raw X1,Y1.
2. GUI Image Table XFM AS plugin
  - a. image\_table\_xfm\_as\_gui\_plugin
    - i. Renamed this plugin from "image\_table\_xfm\_as\_gui\_plugin" for the XFM beamline of the Australian Synchrotron.
    - ii. Writes a CSV table with region details to be loaded into the online run spreadsheet.
3. GUI Image Table XFM NSLS plugin
  - a. image\_table\_xfm\_nsls\_gui\_plugin
    - i. Adapted this plugin from the AS version for the XFM beamline of the NSLS-II synchrotron, BNL, NY.
    - ii. Writes a CSV table with region details to be loaded into the online run spreadsheet.

## 31 May, 2024

1. Builder issue
  - a. Some plugins are missing routines. These used to be done as IDLDE build options, not supported in new 'builder'.
  - b. Needed to resolve missing routines and save/routines a new SAV file.
  - c. Applies to: linearize2\_spectrum\_plugin, linearize\_cuts\_energies\_spectrum\_plugin, linearize\_cuts\_fit\_offset\_spectrum\_plugin, linearize\_cuts\_spectrum\_plugin, linearize\_spectrum\_plugin.
  - d. Need to add: *lmfit*.
  - e. Add a new place for miscellaneous resolves: 'resolve\_misc'.
2. Resolve\_misc:
  - a. Resolve routines: *lmfit*.
  - b. Users who add plugins can also resolve their own added routines before saving a SAV file. But many basic ones can be added here, as this is not supported yet in builder.

## 19 May, 2024

1. Notes about /modal, /floating, blocking (File Requester and Progress)
  - a. Originally, 'file\_requester' was setup as a normal modal widget, which blocks until it closes. It's also floating, which means it sits in front of other windows.
    - i. Blocking is similar, keeping control in xmanager near the end of the main file requester program.
    - ii. We don't want to set no\_block=1 on xmanager, to keep it modal.
    - iii. However, we should never set no\_block=0 on xmanager
      1. This does some weird stuff, like disable debugging.
      2. Simply, *omit* the no\_block keyword to xmanager to achieve the same result. See 'file\_requester' code.
  - b. Then file\_requester was changed to permit a progress bar popup while searching for a file match using "Find".
    - i. i.e. It was found that you could use modal=0, floating=1 on the top base widget and *omit* no\_block on xmanager.
  - c. However, then file\_requester could not work properly if called from another modal widget (e.g. 'flux\_select').
    - i. In that case, we use another option '/within\_modal' to remind file\_requester to use /modal (and disable the Find).
    - ii. *Only use '/within\_modal' when called from a modal widget.*
2. File\_requester
  - a. New '/within\_modal' option, if called from a modal popup (e.g. 'flux\_select').
  - b. This means that the file "Find" does not work as the Progress window cannot function properly then.
3. Flux\_select
  - a. As this is a modal popup, all calls from it to 'file\_requester' use /within\_modal.



4. Spectrum\_load\_prep
  - a. Call 'file\_requester' for pileup, linearize and throttle with 'updir=3' so that it looks in the local neighbourhood for a file match.
5. Version 8.8m.

## 15 May, 2024

1. Plugin: Cal by centroids
  - a. peak\_cal\_cut\_centroid\_spectrum\_plugin
    - i. Use a common to save the 2 energies, so they appear next invocation.
2. Write\_source, write\_pink, read\_source, read\_pink
  - a. Only set 'file' in struct if file opened here, not if 'unit' passed.
3. Fit\_results/save\_fit\_results
  - a. Write a new version -16 and write 'continuum' first, then 'model'
  - b. Then call either source or pink write.
4. Read\_fit\_results
  - a. New code for version -16, to read 'continuum' first, then 'model'.
  - b. Then call either source or pink read.
5. Pink\_calculate
  - a. Use file\_requester(/skip\_if\_exists) to search local tree and also along 'path' tree for a file match.

## 6 May, 2024

1. Continuum source
  - a. Moved back into 'main/xray' and 'main/' for 'source\_setup'.
  - b. Delete "continuum\_Source" plugin project.
2. Pink beam source
  - a. New pink beam routines in 'main/xray' and 'main/' for 'pink\_setup'.
3. Pink\_setup
  - a. New setup for a pink beam that parallel 'source\_setup' for lab sources.
  - b. Uses FE beam spectrum and up to 4 mirrors, based on CXRO reflectivity data files.
  - c. Disable inline optics extras for now.
4. Define
  - a. New /pink for pink beam
  - b. Set **model=1 for lab, model=2 for pink**, as was not used before.
5. Layer\_setup
  - a. No source plugin load, fixed new droplist options for photon sources.
  - b. (\*p).source is now a pointer to either a lab source or pink beam 'beam' struct
  - c. (\*p).source → \*(\*)p.source in most places.
  - d. Cater for 'new-pink' Notify event, similar to new-source.
  - e. 'beam-mode' now just handles lab and pink in "else".
  - f. 'load-source' now handles cases of 6:lab, 7: pink beam.
  - g. 'new-source' launches 'source\_setup' or 'pink\_setup' according to beam.mode.
  - h. Add 'ppink' to pstate for notify to pink\_setup.
6. Geo\_yield2
  - a. At the end, add "rel\_int[1:\*,q] = 0.0" for the zero 'q' array, to avoid NaN 'rel\_int' for elements where the yield drops to zero.
  - b. Some bad elements get through, despite 'zero', so add this to 'q' test:
    - i. Q = where( (zero eq 1) or (finite(rel\_int[1,\*]) eq 0))
  - c. Catch all /0 conditions that affect: branch\_ratio, ppm, mass\_yield, total\_yield, rel\_int.
7. Geo\_array\_yield
  - a. Catch all /0 conditions that affect: rIntensity, enhance, rY.
8. Select\_element\_lines
  - a. Detect lack of "Lines" tag in 'beam' struct and set add\_lines=0
9. Write\_yield
  - a. Write beam.model before beam, if 'use\_beam'.

- b. New version -11
- 10. Read\_yield
  - a. If version -11, after read 'use\_beam', read 'model'.
  - b. If 'model = 2' then switch to a pink beam 'beam' struct.
- 11. Read\_beam
  - a. Read a text file of energy versus beam or CXRO reflectivity data.
  - b. Has a 'skip=' option to skip header of CXRO files.
  - c. Has option 'remap\_energy=' to remap E,data onto a given energy vector.
  - d. Clip output to >0
- 12. Pink\_calculate
  - a. Just use FE beam \* mirror and filter reflectivity/transmission, with no solid angle, etc. terms applied. Commented out for now.
  - b. Disable inline optics now, as this involves solid-angle considerations also.
  - c. Set e\_beam, which is used to 'init\_xrf' in 'get\_lines':
    - i. pink.energy = E[ max(where(spec gt 1.0e-10)) ]
  - d. Add pressure and temp args to 'transmit' like in 'source\_tube\_spectrum' called from 'source\_calculate' to cater for spectra with P.T values.
- 13. Read\_pink
  - a. Read a pink beam file, like read\_source.
- 14. Write\_pink
  - a. Write a pink beam file, like write\_source.
- 15. fit\_recalculate\_yields
  - a. Add case to either 'source\_calculate' or 'pink\_calculate' based on beam.model
  - b. Note for non continuum beam these return passively.
- 16. Version 8.8k.

## 22 Apr, 2024

- 1. Maia Launch
  - a. Maia\_launch\_version2
    - i. Cater for 'number' zero for spectra, et2d, roi.
    - ii. Zero means the variable vanishes in Kandinski.
  - b. Maia\_launch\_initial, maia\_launch\_read\_enable, maia\_launch\_read\_groups
    - i. Only set spectra parameters if number not zero
  - c. Maia\_launch
    - i. Only setup groups shared memory is number > 0
    - ii. Catch anywhere shrmem referenced
  - d. Maia\_update\_group\_spectra
    - i. Return if no shared mem
- 2. Spawn\_blog\_parameters
  - a. Pass in region enable, else veto spawn of region spectra
- 3. Maia\_setup
  - a. Maia\_setup\_event, maia\_setup\_apply\_groups
    - i. Only set spectra parameters if number not zero
- 4. Maia\_client\_parameters
  - a. Test for (\*pm).number.spectra, roi and skip enable.
- 5. Startupp
  - a. Construct path to 'maia' and 'daq' subdirs correctly.
- 6. pixe\_fit
  - a. Set default value for 'sum\_deficit' to 0.5%
- 7. Version 8.8j

## 8 Apr, 2024

- 1. File-requester
  - a. File\_requester\_preview
    - i. Use \*((\*pstate).p).pfile (array) for files, rather than (\*pstate).file (concatenated list).

## 14 Feb, 2024

1. Blog browse
  - a. Change format of output to correct a field width.
2. GitHub
  - a. Fresh load of GeoPIXE to local Git and to GeoPIXE on GitHub at URL:
  - b. <https://github.com/CSIRO-GeoscienceAnalytics/GeoPIXE> as branch “main”.

## 27 Nov, 2023

1. Use *WinMerge* to view and merge changes across from GeoPIXE-source3 to *Open Source* (between Mar 27 and Nov 27). Take care to:
  - a. Not merge across differences due to licensing.
  - b. Watch for different path constructs, e.g. for Wizards.
2. Need to run all tests

## 24 Nov, 2023

1. GeoPIXE
  - a. gImage
    - i. Add menu for Export → Simple Image -> Save as TIFF
    - ii. Call Image\_Save\_GIF, Event, /TIFF
  - b. Image\_Save\_GIF
    - i. Add /TIFF option
    - ii. For TIFF use ‘write\_tiff’ to save as 32-bit float TIFF.

## 8 May, 2023

1. GeoPIXE
  - a. Removed modules with non CSIRO code, although the code had been supplied by the laboratories to enable an import object or plugin to be devised for their data and attribution was included.
    - i. These include:
      1. Devices:
        - a. “APS LST”, “ESRF EDF”, “GSE-CARS MCA”, “Lund VME”, “NSLS MCA”, “NSLS NetCDF”.
      2. Plugins:
        - a. “Image Align”, “Image Combine Align”, “Image Shear Correct”.
      3. Background:
        - a. Bayes.
      4. These may be added to the GitHub repository by the labs concerned at a later time.
1. Builder
  - a. Add build for GUI plugins.
2. Eclipse “clean up”
  - a. Move .log and log files to “old/old-files-Open-Source” directory, from:
    - i. .metadata
    - ii. .metadata/.plugins/org.eclipse.ui.workbench
  - b. Move the following dirs with history to “old” as well:
    - i. .metadata/.plugins/org.eclipse.core.resources/.history
    - ii. .metadata/.plugins/org.eclipse.ltk.core.refactoring/.refactorings

## 21 Dec, 2022

1. builder (NEW)
  - a. Build a script “build.spro” to be used (use: “@build.spro”) to selectively build the SAV files, by categories ('all', 'plugin', 'back', 'spectrum', 'image', 'device', 'wizard', 'source', 'maia', 'daq', 'main', 'browse']).

- i. This avoids issue with poor control of !PATH and using ‘.compile’ by file-name, rather than ‘resolve\_routine’.
  - b. Does .full\_reset\_session for each project build to clear compiled routines.
    - i. But this makes it very slow if run from IDLDE.
  - c. !PATH built afresh for each project build to include whole “main” tree plus the project.
  - d. Build\_project:
    - i. Does the fiddly work for builder.
  - e. Build\_database
    - i. Does the database build part.
  - f. The following builds do a resolve\_all:
    - i. Main, IDL Query, GeoPIXE update and Builder.
    - ii. IDL Query now does not need the make routine anymore.
    - iii. GeoPIXE update of a non-GUI version is not done yet.
2. projects:
- a. Needed to enforce consistency in naming:
    - i. SAV file name constructed from project name, with additional options to tag a suffix to SAV filename.
    - ii. Build from Eclipse must match this SAV filename.
    - iii. Deleted some projects not needed for open source, such as junk tests, etc.
  - b. image\_table\_evt
3. Organization
- a. The “builder” imposed some rules that needed to be enforced:
    - i. Plugins must start with “Back”, “Spectrum”, “Image” and end with “plugin”.
    - ii. Except “source” and “Wizards” plugins.
    - iii. Maia projects start with “Blog” or “Maia”.
    - iv. All Maia SAV end up in /maia, including maia\_control.sav and maia\_scan\_list.sav.
    - v. All DAQ SAV end up in /daq, including daq\_control.sav.
    - vi. All browsers start with “Browse”.
    - vii. Some get renamed: mm\_scan\_list → maia\_scan\_list, GeoPIXE worker → GeoPIXE parallel, “ftp update” → “GeoPIXE update”.
    - viii. ‘misc’ compiles/builds include ‘geopixe\_index’, ‘geopixe\_update’, “builder”, ...
    - ix. Fake Blogs divided into ET2 and DA2 versions.
  - b. Database build
    - i. ‘make\_database.pro’ has changed, so it gets called from ‘builder’.
  - c. Build
    - i. Use ‘builder’ (pops up index selection) to select which classes to build, which creates “build.spro” (note: this will be in “geopixe” for runtime execution and “main” for IDLDE execution). A pop-up reminds the user of “build.spro”, its path and the need to run “@build.spro” from the IDL command line after a “cd” to path.
    - ii. “@build.spro” from IDL command line to build (after “cd” to the dir). This is much faster than in IDLDE due to long lag after a full reset.
4. Version 8.7o.