

{Title}

Open Geospatial Consortium

Submission Date: <yyyy-mm-dd>

Approval Date: <yyyy-mm-dd>

Publication Date: 2020-02-13

External identifier of this OGC® document: <http://www.opengis.net/doc/>

Internal reference number of this OGC® document: 19-086

Version: 0.0.2

Category: OGC® Implementation Specification

Editor: Mark Burgoyne

OGC API - Environmental Data Retrieval Standard

Copyright notice

Copyright © 2020 Open Geospatial Consortium

To obtain additional rights of use, visit <http://www.opengeospatial.org/legal/>

Warning

This document is not an OGC Standard. This document is distributed for review and comment. This document is subject to change without notice and may not be referred to as an OGC Standard.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Document type:

OGC®ImplementationSpecification

Document stage: Draft

Document language: English

License Agreement

Permission is hereby granted by the Open Geospatial Consortium, ("Licensor"), free of charge and subject to the terms set forth below, to any person obtaining a copy of this Intellectual Property and any associated documentation, to deal in the Intellectual Property without restriction (except as set forth below), including without limitation the rights to implement, use, copy, modify, merge, publish, distribute, and/or sublicense copies of the Intellectual Property, and to permit persons

to whom the Intellectual Property is furnished to do so, provided that all copyright notices on the intellectual property are retained intact and that each person to whom the Intellectual Property is furnished agrees to the terms of this Agreement.

If you modify the Intellectual Property, all copies of the modified Intellectual Property must include, in addition to the above copyright notice, a notice that the Intellectual Property includes modifications that have not been approved or adopted by LICENSOR.

THIS LICENSE IS A COPYRIGHT LICENSE ONLY, AND DOES NOT CONVEY ANY RIGHTS UNDER ANY PATENTS THAT MAY BE IN FORCE ANYWHERE IN THE WORLD.

THE INTELLECTUAL PROPERTY IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE DO NOT WARRANT THAT THE FUNCTIONS CONTAINED IN THE INTELLECTUAL PROPERTY WILL MEET YOUR REQUIREMENTS OR THAT THE OPERATION OF THE INTELLECTUAL PROPERTY WILL BE UNINTERRUPTED OR ERROR FREE. ANY USE OF THE INTELLECTUAL PROPERTY SHALL BE MADE ENTIRELY AT THE USER'S OWN RISK. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR ANY CONTRIBUTOR OF INTELLECTUAL PROPERTY RIGHTS TO THE INTELLECTUAL PROPERTY BE LIABLE FOR ANY CLAIM, OR ANY DIRECT, SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM ANY ALLEGED INFRINGEMENT OR ANY LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR UNDER ANY OTHER LEGAL THEORY, ARISING OUT OF OR IN CONNECTION WITH THE IMPLEMENTATION, USE, COMMERCIALIZATION OR PERFORMANCE OF THIS INTELLECTUAL PROPERTY.

This license is effective until terminated. You may terminate it at any time by destroying the Intellectual Property together with all copies in any form. The license will also terminate if you fail to comply with any term or condition of this Agreement. Except as provided in the following sentence, no such termination of this license shall require the termination of any third party end-user sublicense to the Intellectual Property which is in force as of the date of notice of such termination. In addition, should the Intellectual Property, or the operation of the Intellectual Property, infringe, or in LICENSOR's sole opinion be likely to infringe, any patent, copyright, trademark or other right of a third party, you agree that LICENSOR, in its sole discretion, may terminate this license without any compensation or liability to you, your licensees or any other party. You agree upon termination of any kind to destroy or cause to be destroyed the Intellectual Property together with all copies in any form, whether held by you or by any third party.

Except as contained in this notice, the name of LICENSOR or of any other holder of a copyright in all or part of the Intellectual Property shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Intellectual Property without prior written authorization of LICENSOR or such copyright holder. LICENSOR is and shall at all times be the sole entity that may authorize you or any third party to use certification marks, trademarks or other special designations to indicate compliance with any LICENSOR standards or specifications. This Agreement is governed by the laws of the Commonwealth of Massachusetts. The application to this Agreement of the United Nations Convention on Contracts for the International Sale of Goods is hereby expressly excluded. In the event any provision of this Agreement shall be deemed unenforceable, void or invalid, such provision shall be modified so as to make it valid and enforceable, and as so modified the entire Agreement shall remain in full force and effect. No decision, action or inaction by LICENSOR shall be construed to be a waiver of any rights or remedies available to it.

Table of Contents

- [1. Introduction](#)
- [2. Scope](#)
- [3. Conformance](#)
- [4. References](#)

- 5. Terms and Definitions
 - 5.1. Conformance Module; Conformance Test Module
 - 5.2. Conformance Class; Conformance Test Class
 - 5.3. dataset
 - 5.4. Distribution
 - 5.5. Executable Test Suite (ETS)
 - 5.6. Recommendation
 - 5.7. Requirement
 - 5.8. Requirements Class
 - 5.9. Requirements Module
 - 5.10. Standardization Target
- 6. Conventions
 - 6.1. Identifiers
 - 6.2. Link relations
 - 6.3. Use of HTTPS
 - 6.4. API definition
 - 6.4.1. General remarks
 - 6.4.2. Role of OpenAPI
 - 6.4.3. References to OpenAPI components in normative statements
 - 6.4.4. Paths in OpenAPI definitions
 - 6.4.5. Reusable OpenAPI components
- 7. Overview
 - 7.1. Evolution from OGC Web Services
 - 7.2. Encodings
- 8. Requirement Class "Core"
 - 8.1. Overview
 - 8.1.1. Resources
 - 8.1.2. Modular APIs
 - 8.1.3. Navigation
 - 8.2. Foundation Resources
 - 8.2.1. API landing page
 - 8.2.2. API Definition
 - 8.2.3. Declaration of Conformance Classes
 - 8.3. Spatial Resources
 - 8.4. Information Resources
 - 8.5. General Requirements
 - 8.5.1. HTTP 1.1
 - 8.5.2. HTTP Status Codes
 - 8.5.3. Web Caching
 - 8.5.4. Support for Cross-Origin Requests
 - 8.5.5. Asynchronous queries
 - 8.5.6. Encodings
 - 8.5.7. Link Headers
- 9. Requirement Class "Collections"
 - 9.1. Overview
 - 9.2. Spatial Resources

9.2.1. Collections Metadata	
9.2.2. Collection Metadata	
9.2.3. Collection Instance Information	
9.3. Information Resources	
9.4. Parameter Modules	
9.4.1. Parameter coords	
9.4.2. Parameter datetime	
9.4.3. Parameter parametername	
9.4.4. Parameter crs	
9.4.5. Parameter outputFormat	
9.5. QueryType specific Operations	
9.5.1. Point	
9.5.2. Parameters	
9.5.3. Parameter coords	
9.5.4. Parameter interpolation	
9.5.5. Parameter within	
9.5.6. Parameter withinUnits	
9.5.7. Polygon	
9.5.8. Parameters	
9.5.9. Parameter coords	
9.5.10. Parameter interpolationX	
9.5.11. Parameter interpolationY	
9.5.12. Cube	
9.5.13. Trajectory (corridor)	
9.5.14. Parameters	
9.5.15. Parameter coords	
9.5.16. Parameter interpolation	
9.5.17. Parameter interpolationZ	
9.5.18. Item	
9.5.19. Parameters	
9.6. General Requirements	
9.6.1. Coordinate Reference Systems	
10. Requirements classes for encodings	
10.1. Overview	
10.2. Requirement Class "HTML"	
10.3. Requirement Class "GeoJSON"	
11. Requirements class "OpenAPI 3.0"	
11.1. Basic requirements	
11.2. Complete definition	
11.3. Exceptions	
11.4. Security	
12. Media Types	
Annex A: Abstract Test Suite (Normative)	
A.1. Introduction	
A.2. Conformance Class Core	
A.2.1. General Tests	

- [A.2.2. Landing Page {root}/](#)
 - [A.2.3. API Definition Path {root}/api \(link\)](#)
 - [A.2.4. Conformance Path {root}/conformance](#)
- [A.3. Conformance Class Collections](#)
 - [A.3.1. General Tests](#)
 - [A.3.2. Feature Collections {root}/collections](#)
 - [A.3.3. Feature Collection {root}/collections/{collectionId}](#)
 - [A.3.4. Features {root}/collections/{collectionId}/items](#)
 - [A.3.5. Second Tier Tests](#)
- [A.4. Conformance Class GeoJSON](#)
 - [A.4.1. GeoJSON Definition](#)
 - [A.4.2. GeoJSON Content](#)
- [A.5. Conformance Class HTML](#)
 - [A.5.1. HTML Definition](#)
 - [A.5.2. HTML Content](#)
- [A.6. Conformance Class OpenAPI 3.0](#)
- [Annex B: Examples \(Informative\)](#)
 - [B.1. Example Landing Pages](#)
 - [B.2. API Description Examples](#)
 - [B.3. Conformance Examples](#)
 - [B.4. Collections Metadata Examples](#)
 - [B.5. Collection Instance Metadata Examples](#)
 - [B.6. Collection Query Metadata Examples](#)
 - [B.7. Collection Information Examples](#)
- [Annex C: Revision History](#)
- [Annex D: Bibliography](#)

1. Introduction

i. Abstract

The OGC has extended their suite of standards to include Resource Oriented Architectures and Web APIs, these standards are based on a common foundation upon which all OGC APIs will be built. This document defines the Environmental Data Retrieval (EDR) API which aims to simplify access to geo-spatial data.

An Environmental Data Retrieval (EDR) API provides a family of lightweight interfaces to access the resources. The resources addressed by EDR API each map to a defined query pattern. These patterns are described in section 8, Requirement Class Core.

The EDR Common standard defines resources and access paths that are supported by all EDR APIs. These are listed in [Table 1](#).

Table 1. Overview of Resources

Resource	Path	HTTP Method	Document Reference
Landing page	/	GET	API Landing Page
API definition	/api	GET	API Definition
Conformance classes	/conformance	GET	Declaration of Conformance Classes
Collections metadata	/collections	GET	Collections Metadata
Collection instance metadata	/collections/{collection_id}	GET	Collection Metadata
Collection instance metadata	/collections/{collection_id}/{instance_id}	GET	Collection Instance Metadata

The resources identified in [Table 1](#) primarily support Discovery operations. Discovery operations allow clients to interrogate the API to determine its capabilities and retrieve information (metadata) about this distribution of the resource. This includes the API definition of the server(s) as well as metadata about the resources provided by those servers.

This standard extends the common Query operations for OGC APIs. Query operations allow resources or values extracted from those resources to be retrieved from the underlying data store. The information to be returned is based upon selection criteria (query string) provided by the client. This standard only defines simple query parameters which should be applicable to all resource types. Other OGC API standards may define additional query capabilities specific to their resource type.

ii. Keywords

The following are keywords to be used by search engines and document catalogues.

ogcdoc, OGC document, property, geographic information, spatial data, spatial things, dataset, distribution, API, geojson, covJSON,, html, OpenAPI, AsyncAPI, REST, Common

iii. Preface

OGC Declaration

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium Inc. shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide supporting documentation.

iv. Submitting organizations

The following organizations submitted this Document to the Open Geospatial Consortium (OGC):

- Met Office
- others TBD

v. Submitters

All questions regarding this submission should be directed to the editors or the submitters:

Name	Affiliation
Mark Burgoyne (<i>editor</i>)	Met Office
others	TBD

2. Scope

This specification identifies resources, captures compliance classes, and specifies requirements which are applicable to all OGC EDR API's. It should be included as a normative reference by all such standards.

This specification addresses two fundamental operations; discovery and query.

Discovery operations allow the API to be interrogated to determine its capabilities and retrieve information (metadata) about this distribution of a resource. This includes the API definition of the server as well as metadata about the spatial resources provided by the server.

Query operations allow spatial resources to be retrieved from the underlying data store based upon simple selection criteria, defined by the client.

3. Conformance

Conformance with this standard shall be checked using the tests specified in Annex A (normative) of this document. The framework, concepts, and methodology for testing, and the criteria to claim conformance are specified in the OGC Compliance Testing Policies and Procedures and the OGC Compliance Testing web site.

The one Standardization Target for this standard is Web APIs.

OGC API-Common provides a common foundation for OGC API standards. It is anticipated that this standard will only be implemented through inclusion in other standards. Therefore, all the relevant abstract tests in Annex A shall be included or referenced in the Abstract Test Suite in each separate standard that normatively references this standard.

This standard identifies five conformance classes. The conformance classes implemented by an API are advertised through the /conformance path on the landing page. Each conformance class is defined by one requirements class. The tests in Annex A are organized by Requirements Class. So an

implementation of the *Core* conformance class must pass all tests specified in Annex A for the *Core* requirements class.

The requirements classes for OGC API-Common are:

- [Core](#)

The *Core Requirements Class* is the minimal useful service interface for an OGC API. The requirements specified in this requirements class are mandatory for all OGC APIs

Additional capabilities such as support for transactions, complex data structures, and rich queries are specified in additional OGC API standards and in OGC managed API extensions. Those standards and extensions build on the API-Common foundation to provide the full functionality required of the API implementation.

- [Collections](#)

The *Collections Requirements Class* extends the *Core* to enable fine-grained access to spatial resources. This requirements class is mandatory for all OGC APIs which expose spatial resources.

The structure and organization of a collection of spatial resources is very much dependent on the nature of that resource and the expected access patterns. This is information which cannot be specified in a common manner. The *Collections Requirements Class* specifies the requirements necessary to discover and understand that structure and organization. Requirements governing the resource collections themselves are specified in the resource-specific OGC API standards.

- [HTML](#)
- [GeoJSON](#)
- [CovJSON](#)

Neither the *Core* nor *Collections* requirements class mandate a specific encoding or format for representing resources. The *HTML* and *GeoJSON* requirements classes specify representations for these resources in commonly used encodings for spatial data on the web. *CovJSON* is a more structured format for representing geo-spatial information.

None of these encodings are mandatory. An implementation of the *EDR* standard may decide to implement another encoding instead of, or in addition those listed but a common format does simplify interoperability so support for *CovJSON* is highly recommended.

- [OpenAPI 3.0](#)

Whilst the *OGC API-Common* does not mandate any encoding or format for the formal definition of the API. The preferred option is the OpenAPI 3.0 specification. Therefore the EDR API's will be defined in *OpenAPI 3.0*.

4. References

The following normative documents contain provisions that, through reference in this text, constitute provisions of this document. For dated references, subsequent amendments to, or revisions of, any of

these publications do not apply. For undated references, the latest edition of the normative document referred to applies.

- Open API Initiative: **OpenAPI Specification 3.0.2**, <https://github.com/OAI/OpenAPI-Specification/blob/master/versions/3.0.2.md>
- Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., Berners-Lee, T.: **IETF RFC 2616, HTTP/1.1**, <http://tools.ietf.org/rfc/rfc2616.txt>
- Rescorla, E.: **IETF RFC 2818, HTTP Over TLS**, <http://tools.ietf.org/rfc/rfc2818.txt>
- Klyne, G., Newman, C.: **IETF RFC 3339, Date and Time on the Internet: Timestamps**, <http://tools.ietf.org/rfc/rfc3339.txt>
- Berners-Lee, T., Fielding, R., Masinter, L.: **IETF RFC 3896, Uniform Resource Identifier (URI): Generic Syntax**, <http://tools.ietf.org/rfc/rfc3896.txt>
- Butler, H., Daly, M., Doyle, A., Gillies, S., Hagen, S., Schaub, T.: **IETF RFC 7946, The GeoJSON Format**, <https://tools.ietf.org/rfc/rfc7946.txt>
- Nottingham, M.: **IETF RFC 8288, Web Linking**, <http://tools.ietf.org/rfc/rfc8288.txt>
- W3C: **HTML5, W3C Recommendation**, <http://www.w3.org/TR/html5/>
- **Schema.org**: <http://schema.org/docs/schemas.html>
- Blower, J., Riechert, M., Roberts, B.: **Overview of the CoverageJSON format**, <https://www.w3.org/TR/covjson-overview/>
- Weibel, S., Kunze, J., Lagoze, C., Wolf, M.: **IETF RFC 2413, Dublin Core Metadata for Resource Discovery**, <https://tools.ietf.org/rfc/rfc2413.txt>
- Herring, J.: **Simple feature access - Part 1: Common architecture**, http://portal.opengeospatial.org/files/?artifact_id=25355
- Lott, R.: **Well-known text representation of coordinate reference systems**, <http://docs.opengeospatial.org/is/18-010r7/18-010r7.html>

5. Terms and Definitions

This document uses the terms defined in Sub-clause 5.3 of [OGC Web Services Common](#) (OGC 06-121r9), which is based on the ISO/IEC Directives, Part 2, Rules for the structure and drafting of International Standards. In particular, the word “shall” (not “must”) is the verb form used to indicate a requirement to be strictly followed to conform to this standard.

For the purposes of this document, the following additional terms and definitions apply.

5.1. Conformance Module; Conformance Test Module

set of related tests, all within a single conformance test class ([OGC 08-131](#))

NOTE: When no ambiguity is possible, the word ‘test’ may be omitted. i.e. conformance test module is the same as conformance module. Conformance modules may be nested in a hierarchical way.

5.2. Conformance Class; Conformance Test Class

set of conformance test modules that must be applied to receive a single certificate of conformance ([OGC 08-131](#))

NOTE: When no ambiguity is possible, the word `_test_` may be left out, so conformance test class maybe called a conformance class.

5.3. dataset

collection of data, published or curated by a single agent, and available for access or download in one or more formats (DCAT)

5.4. Distribution

represents an accessible form of a **dataset** (DCAT)

EXAMPLE: a downloadable file, an RSS feed or a web service that provides the data.

5.5. Executable Test Suite (ETS)

A set of code (e.g. Java and CTL) that provides runtime tests for the assertions defined by the ATS. Test data required to do the tests are part of the ETS ([OGC 08-134](#))

5.6. Recommendation

expression in the content of a document conveying that among several possibilities one is recommended as particularly suitable, without mentioning or excluding others, or that a certain course of action is preferred but not necessarily required, or that (in the negative form) a certain possibility or course of action is deprecated but not prohibited ([OGC 08-131](#))

5.7. Requirement

expression in the content of a document conveying criteria to be fulfilled if compliance with the document is to be claimed and from which no deviation is permitted ([OGC 08-131](#))

5.8. Requirements Class

aggregate of all requirement modules that must all be satisfied to satisfy a conformance test class ([OGC 08-131](#))

5.9. Requirements Module

aggregate of requirements and recommendations of a specification against a single standardization target type ([OGC 08-131](#))

5.10. Standardization Target

entity to which some requirements of a standard apply ([OGC 08-131](#))

NOTE: The standardization target is the entity which may receive a certificate of conformance for a requirements class.

6. Conventions

6.1. Identifiers

The normative provisions in this draft standard are denoted by the URI <http://www.opengis.net/spec/ogcapi-common/1.0>.

All requirements and conformance tests that appear in this document are denoted by partial URIs which are relative to this base.

6.2. Link relations

To express relationships between resources, [RFC 8288 \(Web Linking\)](#) and [registered link relation types](#) are used.

6.3. Use of HTTPS

For simplicity, this document in general only refers to the HTTP protocol. This is not meant to exclude the use of HTTPS and simply is a shorthand notation for "HTTP or HTTPS". In fact, most servers are expected to use [HTTPS](#), not [HTTP](#).

6.4. API definition

6.4.1. General remarks

Good documentation is essential for every API so that developers can more easily learn how to use the API. In the best case, documentation would be available both in HTML for human consumption and in a machine readable format that can be processed by software for run-time binding.

This standard specifies requirements and recommendations for APIs that share spatial resources and want to follow a standard way of doing so. In general, APIs will go beyond the requirements and recommendations stated in this standard. They will support additional operations, parameters, etc. that are specific to the API or the software tool used to implement the API.

6.4.2. Role of OpenAPI

This document uses OpenAPI 3.0 fragments as examples and to formally state requirements. Using OpenAPI 3.0 is not required for implementing an OGC API. Other API definition languages may be used along with, or instead of OpenAPI. However, any API definition language used should have an associated conformance class advertised through the /conformance path.

This approach is used to avoid lock-in to a specific approach to defining an API. This standard includes a [conformance class](#) for API definitions that follow the [OpenAPI specification 3.0](#). Conformance classes for additional API definition languages will be added as the API landscape continues to evolve.

In this document, fragments of OpenAPI definitions are shown in YAML since YAML is easier to format than JSON and is typically used in OpenAPI editors.

6.4.3. References to OpenAPI components in normative statements

Some normative statements (requirements, recommendations and permissions) use a phrase that a component in the API definition of the server must be "based upon" a schema or parameter component in the OGC schema repository.

In this case, the following changes to the pre-defined OpenAPI component are permitted:

- If the server supports an XML encoding, `xml` properties may be added to the relevant OpenAPI schema components.
- The range of values of a parameter or property may be extended (additional values) or constrained (if a subset of all possible values are applicable to the server). An example for a constrained range of values is to explicitly specify the supported values of a string parameter or property using an enum.
- Additional properties may be added to the schema definition of a Response Object.
- Informative text may be changed or added, like comments or description properties.

For API definitions that do not conform to the [OpenAPI Specification 3.0](#) the normative statement should be interpreted in the context of the API definition language used.

6.4.4. Paths in OpenAPI definitions

All paths in an OpenAPI definition are relative to the base URL of a server. Unlike Web Services, an API is decoupled from the server(s). Some ramifications of this are:

- An API may be hosted (replicated) on more than one server.
- Parts of an API may be distributed across multiple servers.

Example 1. URL of the OpenAPI definition

If the OpenAPI Server Object looks like this:

```
servers:
- url: https://dev.example.org/
  description: Development server
- url: https://data.example.org/
  description: Production server
```

The path `"/mypath"` in the OpenAPI definition of the API would be the URL <https://data.example.org/mypath> for the production server.

6.4.5. Reusable OpenAPI components

Reusable components for OpenAPI definitions for a OGC API are referenced from this document.

CAUTION

During the development phase, these components use a base URL of `"https://raw.githubusercontent.com/engeospatial/oapi_common/master/"`, but eventually they are expected to be available under the base URL `"http://schemas.opengis.net/ogcapi_common/1.0/openapi/"`.

7. Overview

7.1. Evolution from OGC Web Services

OGC Web Service (OWS) standards implement a Remote-Procedure-Call-over-HTTP architectural style using XML for payloads. This was the state-of-the-art when OGC Web Services (OWS) were originally designed in the late 1990s. However, times have changed. New Resource-Oriented APIs have begun to replace Service-Oriented Web Services. And new OGC API standards are under development to provide API alternatives to the OWS standards.

OGC API (OAPI) Common specifies the common kernel of this API approach to services that follows the current Web architecture. In particular, the [W3C/OGC best practices for sharing Spatial Data on the Web](#) as well as the [W3C best practices for sharing Data on the Web](#).

Beside the general alignment with the architecture of the Web (e.g., consistency with HTTP/HTTPS, hypermedia controls), another goal for OGC API standards is modularization. This goal has several facets:

- Clear separation between common core requirements and more resource specific capabilities. This document specifies the core or *common* requirements that are relevant for almost everyone who wants to build a spatial API. Additional capabilities that several communities are using today will be specified as extensions to the Common API.
- Technologies that change more frequently are decoupled and specified in separate modules ("conformance classes" in OGC terminology). This enables, for example, the use/re-use of new encodings for spatial data or API descriptions.
- Modularization is not just about a single "service". OGC APIs will provide building blocks that can be reused in APIs in general. In other words, a server supporting the OGC-Feature API should not be seen as a standalone service. Rather it should be viewed as a collection of API building blocks which together implement API-Feature capabilities. A corollary of this is that it should be possible to implement an API that simultaneously conforms to conformance classes from the Feature, Coverage, and other OGC Web API standards.

Implementations of OGC API Common are intended to support two different approaches for how clients can use the API.

In the first approach, clients are implemented with knowledge about this standard and its resource types. The clients navigate the resources based on this knowledge and based on the responses provided by the API. The API definition may be used to determine details, e.g., on filter parameters, but this may not be necessary depending on the needs of the client. These are clients that are in general able to use multiple APIs as long as they implement OGC API Common.

The other approach targets developers that are not familiar with the OGC API standards, but want to interact with spatial data provided by an API that happens to implement OGC API Common. In this case the developer will study and use the API definition, typically an OpenAPI document, to understand the API and implement client code to interact with the API. This assumes familiarity with the API definition language and the related tooling, but it should not be necessary to study the OGC API standards.

7.2. Encodings

NOTE

Arguably this requires a conformance class for every possible encoding. Do we really want a conformance class for GeoTIFF? or NITF?, or Protobuf? Should this requirement be limited to those resources defined in this standard?

This standard does not mandate any encoding or format. But it does provide extensions for encodings which are commonly used in OGC APIs. In addition to HTML as the standard encoding for Web content,

rules for commonly used encodings for spatial data on the web are provided (GeoJSON).

None of these encodings is mandatory. An implementation of the *Core* requirements class does not have to support any of them. It may instead implement an entirely different set of encodings.

Support for HTML is [recommended](#). HTML is the core language of the World Wide Web. An API that supports HTML will support browsing the spatial resources with a web browser and will also enable search engines to crawl and index those resources.

GeoJSON is a commonly used format that is simple to understand and well supported by tools and software libraries. Since most Web developers are comfortable with using a JSON-based format, GeoJSON is [recommended](#) for APIs which expose feature data **and** where GeoJSON is capable of supporting the intended use.

Some examples of cases that are out-of-scope for GeoJSON are:

- When solids are used for geometries (e.g. in a 3D city model),
- Geometries that include non-linear curve interpolations that cannot be simplified (e.g., use of arcs in authoritative geometries),
- Geometries that have to be represented in a coordinate reference system that is not based on WGS 84 longitude/latitude (e.g. an authoritative national reference system),
- Features that have more than one geometric property.

The recommendations for using HTML and GeoJSON reflect the importance of HTML and the current popularity of JSON-based data formats. As the practices in the Web community evolve, these recommendations will likely be updated in future versions of this standard to provide guidance on using other encodings.

This part of the OAPI standard does not provide any guidance on other encodings. The supported encodings, or more precisely the media types of the supported encodings, can be determined from the API definition. The desired encoding is selected using HTTP content negotiation.

For example, if the server supports [GeoJSON Text Sequences](#) an encoding that is based on JSON text sequences and GeoJSON to support streaming by making the data incrementally parseable, the media type `application/geo+json-seq` would be used.

8. Requirement Class "Core"

Requirements Class	
http://www.opengis.net/spec/ogcapi_common/1.0/req/core	
Target type	Web API
Dependency	RFC 2616 (HTTP/1.1)
Dependency	RFC 2818 (HTTP over TLS)
Dependency	RFC 8288 (Web Linking)

8.1. Overview

8.1.1. Resources

An OGC API provides a lightweight interface to access one or more resources. The resources addressed by OGC APIs fall into three categories; Foundation Resources, Spatial Resources, and Information Resources.

Foundation Resources are those resources which are common across all OGC APIs. Those resources are defined in this OGC API-Common standard. Other OGC API standards re-use these resources and, where necessary, extend them to address their unique requirements.

Spatial Resources are the resources which we usually think of as Geospatial Data. They include Features, Coverages, and Images. This Standard defines basic patterns for accessing Spatial Resources. Additional OGC API Standards have been developed to address specific API requirements for each Spatial Resource type.

Information Resources are non-spatial resources which support the operation of the API or the access and use of the Spatial Resources.

8.1.2. Modular APIs

A goal of OGC API standards is to provide rapid and easy access to spatial resources. To meet this goal, the needs of both the resource provider and the resource consumer must be considered. Our approach is to provide a modular framework of API components. This framework provides a consistent "look and feel" across all OGC APIs. When API servers and clients are built from the same set of modules, the likelihood that they will integrate at run-time is greatly enhanced.

A more detailed discussion of modular APIs can be found in the API-Common [Best Practices](#) document.

8.1.3. Navigation

OGC APIs are designed to support two access patterns; Hypermedia Access, and Direct Access. OGC APIs support both access patterns through the use of API Definition documents, standardized paths, and standardized hypermedia schemas.

Hypermedia Access

Hypermedia Access is the use of hypermedia links to navigate from one resource to another. This pattern is typical of the Web Browser environment. A resource consumer (typically a human) starts from a landing page, selects a link on that page, then moves on to the referenced resource.

Navigation of hyperlinks is facilitated if the hyperlink includes information about the resource type at the link destination. Therefore, OGC APIs use a set of common link relationships. These link relationships are described in [Table 2](#).

Table 2. Link Relations

Link Relation	Purpose
alternate	links to this resource in another media type (the media type is specified in the type link attribute)
conformance	links to conformance information
data	links to an information resource
describedBy	links to external resources which further describe the subject resource
items	links to each individual resource which is included in a collection resource
self	links to this resource,
service-desc	links to the API Definition
service-doc	an alternative to service-desc

OGC API hyperlinks are defined using the following [Hyperlink Schema](#).

Hyperlink Schema

```
{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "title": "Link Schema",
  "description": "Schema for external references",
  "type": "object",
  "required": [
    "href"
  ],
  "properties": {
    "href": {
      "type": "string"
    },
    "rel": {
      "type": "string"
    },
    "hreflang": {
      "type": "string"
    },
    "title": {
      "type": "string"
    }
  }
}
```

Direct Access

Direct Access requires that the resource consumer possesses knowledge of the path to the resource prior to attempting access. Typically this knowledge comes from the use of standard paths, receiving the path from another entity, or by processing an API definition resource. Direct access is particularly applicable to software analytics where there is no human in the loop.

Direct access is facilitated by the use of standard URL paths. The requirements in this Requirements Class are organized around these standard paths.

8.2. Foundation Resources

Foundation resources are those resources which are provided by every OGC API.

The standard paths defined in this Standard for Foundation Resources are:

1. "/" - the landing page
2. "/api" - the API Definition document for this API
3. "/conformance" - the conformance information for this API

8.2.1. API landing page

Each OGC API has a single `LandingPage` (path `/`).

The purpose of the landing page is to provide users with the basic information they need to use this API as well as links to the resources exposed through the API.

Operation

Requirement 1	<code>/req/core/root-op</code>
A	The server SHALL support the HTTP GET operation at the path <code>/</code> .

Response

Requirement 2	<code>/req/core/root-success</code>
A	A successful execution of the operation SHALL be reported as a response with an HTTP status code <code>200</code> .
B	<p>The content of that response SHALL be based upon the schema landingPage.json and include links to the following resources:</p> <ul style="list-style-type: none">• the API definition (relation type 'service-desc' or 'service-doc')• <code>/conformance</code> (relation type 'conformance')• one or more information resources (relation type 'data')

In addition to the required resources, links to additional resources may be included in the Landing Page.

The landing page returned by this operation is based on the following [Landing Page Schema](#). Examples of OGC landing pages are provided in [Example Landing Pages](#).

```
{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "title": "Landing Page Schema",
  "description": "JSON schema for the OGC API-Common landing page",
  "type": "object",
  "required": [
    "links"
  ],
  "properties": {
    "title": {
      "description": "The title of the API",
      "type": "string"
    },
    "description": {
      "description": "A textual description of the API",
      "type": "string"
    },
    "links": {
      "description": "Links to the resources exposed through this API.",
      "type": "array",
      "items": {"$href": "link.json"}
    },
    "patternProperties": {
      "^x-": {}
    },
    "additionalProperties": true
  }
}
```

Error Situations

See [HTTP Status Codes](#) for general guidance.

8.2.2. API Definition

Every API is expected to provide a definition that describes capabilities provided by the API. This document can be used by developers to understand the API, by software clients to connect to the server, and by development tools to support the implementation of servers and clients.

Operation

Requirement 3	/req/core/api-definition-op
A	The URIs of all API definitions referenced from the landing page SHALL support the HTTP GET method.

Response

Requirement 4	/req/core/api-definition-success
A	A GET request to the URI of an API definition linked from the landing page (link relations <code>service-desc</code> or <code>service-doc</code>) with an <code>Accept</code> header with the value of the link property <code>type</code> SHALL return a document consistent with the requested media type.

Recommendation 1	/rec/core/api-definition-oas
A	If the API definition document uses the OpenAPI Specification 3.0, the document SHOULD conform to the OpenAPI Specification 3.0 requirements class .

If multiple API definition formats are supported, use content negotiation to select the desired representation.

Error Situations

See [HTTP Status Codes](#) for general guidance.

8.2.3. Declaration of Conformance Classes

To support "generic" clients that want to accessing OGC APIs in general - and not "just" a specific API / server, the API has to declare the conformance classes it implements and conforms to.

Operation

Requirement 5	/req/core/conformance-op
A	The API SHALL support the HTTP GET operation at the path <code>/conformance</code> .

Response

Requirement 6	/req/core/conformance-success
A	A successful execution of the operation SHALL be reported as a response with a HTTP status code <code>200</code> .
B	The content of that response SHALL be based upon the OpenAPI 3.0 schema confClasses.json and list all OGC API conformance classes that the API conforms to.

The conformance resource returned by this operation is based on the following [Conformance Schema](#). Examples of OGC conformance resources are provided in [Conformance Examples](#).

```
{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "title": "Conformance Classes Schema",
  "description": "This schema defines the resource returned from the /Conformance path",
  "type": "object",
  "required": [
    "conformsTo"
  ],
  "properties": {
    "conformsTo": {
      "type": "array",
      "description": "ConformsTo is an array of URLs. Each URL should correspond to a defined OGC Conformance class. Unrecognized URLs should be ignored",
      "items": {
        "type": "string",
        "example": "http://www.opengis.net/spec/OAPI_Common/1.0/req/core"
      }
    }
  }
}
```

Error situations

See [HTTP Status Codes](#) for general guidance.

8.3. Spatial Resources

There is no requirement that every OGC API support Spatial Resources. Therefore, Spatial Resources are addressed in a separate [Collections Requirement Class](#). This class is described in the [Collections](#) section.

8.4. Information Resources

Information Resources are non-spatial resources which support the operation of the API or the access and use of the Spatial Resources. These resources are usually specific to a spatial resource type and will be defined in the appropriate API standards.

Information Resources can be exposed using two path templates:

- /collections/{collectionId}/{instanceId}/{queryType}
- }/{instanceId}/{queryType}

Where

{collectionId} = a unique identifier for a Spatial Resource collection.

{instanceId} = a text string identifying the 'Version' or 'Instance' of the chosen collection.

{queryType} = a text string identifying the type of geo-spatial query pattern performed by the API.

Information Resources associated with a specific collection should be accessed through the `/collections` path. Those which are not associated with a specific collection should use the `/instanceId/{queryType}` template.

The EDR API `instanceId` parameter allows support for multiple iterations or versions of the same underlying datasource to be accessed by the API. This is applicable when the entire datasource has been regenerated rather than individual values in the datasource being changed. If only one instance of the datasource exists a value of *default* or *latest* could be used.

The EDR API standard has identified an initial set of common `queryTypes` to implement, this list may change as the standard is used. The [Table 3](#) provides a list of the proposed `queryTypes`.

Table 3. Information Resource Types

Query Type	API Standard
Corridor	<code>/corridor</code>
Cube	<code>/cube</code>
Items	<code>/items</code>
Point	<code>/point</code>
Polygon	<code>/polygon</code>
Trajectory	<code>/trajectory</code>

8.5. General Requirements

The following general requirements and recommendations apply to all OGC APIs.

8.5.1. HTTP 1.1

The standards used for Web APIs are built on the HTTP protocol. Therefore, conformance with HTTP or a closely related protocol is required.

Requirement 7	<code>/req/core/http</code>
A	The API SHALL conform to HTTP 1.1 .
B	If the API supports HTTPS, then the API SHALL also conform to HTTP over TLS .

8.5.2. HTTP Status Codes

[Table 4](#) lists the main HTTP status codes that clients should be prepared to receive. This includes support for specific security schemes or URI redirection. In addition, other error situations may occur in the transport layer outside of the server.

Table 4. Typical HTTP status codes

Status code	Description
200	A successful request.
202	A successful request, but the response is still being generated. The response will include a <code>Retry-After</code> header field giving a recommendation in seconds for the client to retry.
304	An entity tag was provided in the request and the resource has not been changed since the previous request.
308	The server cannot process the data through a synchronous request. The response includes a <code>Location</code> header field which contains the URI of the location the result will be available at once the query is complete Asynchronous queries .
400	The server cannot or will not process the request due to an apparent client error. For example, a query parameter had an incorrect value.
401	The request requires user authentication. The response includes a <code>WWW-Authenticate</code> header field containing a challenge applicable to the requested resource.
403	The server understood the request, but is refusing to fulfill it. While status code 401 indicates missing or bad authentication, status code 403 indicates that authentication is not the issue, but the client is not authorised to perform the requested operation on the resource.
404	The requested resource does not exist on the server. For example, a path parameter had an incorrect value.
405	The request method is not supported. For example, a POST request was submitted, but the resource only supports GET requests.
406	Content negotiation failed. For example, the <code>Accept</code> header submitted in the request did not support any of the media types supported by the server for the requested resource.
413	Request entity too large. For example the query would involve returning more data than the server is capable of processing, the implementation should return a message explaining the query limits imposed by the server implementation.
500	An internal error occurred in the server.

More specific guidance is provided for each resource, where applicable.

Permission 1	/per/core/additional-status-codes
A	Servers MAY support other capabilities of the HTTP protocol and, therefore, MAY return other status codes than those listed in Table 4 , too.

8.5.3. Web Caching

Entity tags are a mechanism for web cache validation and for supporting conditional requests to reduce network traffic. Entity tags are specified by [HTTP/1.1 \(RFC 2616\)](#).

Recommendation 2	/rec/core/etag
A	The service SHOULD support entity tags and the associated headers as specified by HTTP/1.1.

8.5.4. Support for Cross-Origin Requests

Access to data from a HTML page is by default prohibited for security reasons, if the data is located on another host than the webpage ("same-origin policy"). A typical example is a web-application accessing feature data from multiple distributed datasets.

Recommendation 3	/rec/core/cross-origin
A	If the server is intended to be accessed from the browser, cross-origin requests SHOULD be supported. Note that support can also be added in a proxy layer on top of the server.

Two common mechanisms to support cross-origin requests are:

- [Cross-origin resource sharing \(CORS\)](#)
- [JSONP \(JSON with padding\)](#)

8.5.5. Asynchronous queries

It will not always be possible to respond to queries synchronously, if the query requires handling asynchronously the system should respond with a HTTP code of 308 and include a `Location` response header field with the URI of the location of the data once the query has completed. If the user queries the URI of the product of the query before the data is available that response should respond with a HTTP code of 202 and include a `Retry-after` response header field with a suggested interval in seconds to retry the data retrieval.

Recommendation 4	/rec/core/asynchronous-query
A	If a requests will require significant time to execute, asynchronous queries SHOULD be supported.
B	User SHOULD be redirected to a URI location where the result will be available once completed using a HTTP statuts code of 308 with a header field of <i>Location</i> containing the URI.
C	The result URI SHOULD return a HTTP statuts code of 202 with a header field of <i>Retry_after</i> with a recommendation in seconds of how long to wait before retrying the request.
D	Once the data is available the result URI SHOULD return a HTTP statuts code of 200 with the data.

- [Asynchrony](#)

8.5.6. Encodings

While the OAPI Common standard does not specify any mandatory encoding, the following encodings are recommended. See [Clause 7 \(Overview\)](#) for a discussion of this issue.

HTML encoding recommendation:

Recommendation 5	/rec/core/html
A	To support browsing a API with a web browser and to enable search engines to crawl and index the dataset, implementations SHOULD consider to support an HTML encoding.

GeoJSON encoding recommendation:

Recommendation 6	/rec/core/geojson
A	If the resource can be represented for the intended use in GeoJSON, implementations SHOULD consider to support GeoJSON as an encoding.

CoverageJSON encoding recommendation:

Recommendation 7	/rec/core/covjson
A	If the resource can be represented for the intended use in CoverageJSON, implementations SHOULD consider to support CoverageJSON as an encoding.

Requirement `/req/core/http` implies that the encoding of a response is determined using content negotiation as specified by the HTTP RFC.

The section [Media Types](#) includes guidance on media types for encodings that are specified in this document.

Note that any API that supports multiple encodings will have to support a mechanism to mint encoding-specific URIs for resources in order to express links, for example, to alternate representations of the same resource. This document does not mandate any particular approach how this is supported by the API.

As clients simply need to dereference the URI of the link, the implementation details and the mechanism how the encoding is included in the URI of the link are not important. Developers interested in the approach of a particular implementation, for example, to manipulate ("hack") in the browser address bar, can study the API definition.

NOTE

- Two common approaches are:
- an additional path for each encoding of each resource (this can be expressed, for example, using format specific suffixes like ".html");
 - an additional query parameter (for example, "accept" or "f") that overrides the Accept header of the HTTP request.

8.5.7. Link Headers

Recommendation 8	/rec/core/link-header
A	Links included in payload of responses SHOULD also be included as Link headers in the HTTP response according to RFC 8288, Clause 3 .
B	This recommendation does not apply, if there are a large number of links included in a response or a link is not known when the HTTP headers of the response are created.

9. Requirement Class "Collections"

Requirements Class	
http://www.opengis.net/spec/ogcapi_common/1.0/req/collections	
Target type	Web API
Dependency	Requirements Class "OAPI Core"
Dependency	RFC 3339 (Date and Time on the Internet: Timestamps)
Dependency	RFC 2413 (Dublin Core Metadata for Resource Discovery)
Dependency	OGC 103r4 (Simple feature access - Part 1:Common architecture)
Dependency	18-010r7 (Well-known text representation of coordinate reference systems)

9.1. Overview

Spatial Resources are the resources which we usually think of as Geospatial Data. They include Features, Coverages, and Images. This Conformance Class defines basic patterns for accessing Spatial Resources. Additional OGC API Standards have been developed to address specific API requirements for each Spatial Resource type.

OGC APIs are designed to support two access patterns; Hypermedia Access, and Direct Access. OGC APIs support both access patterns through the use of API Definition documents, standardized paths, and standardized hypermedia schemas.

Hypermedia Access was described in the [Navigation](#) section of Clause 8. For Spatial Resources, hypermedia navigation is enabled through the links included in each schema defined by this Requirement Class.

Direct access is the use of know URL paths to access a resource directly. The requirements in this Requirement Class are organized around the standard paths for Spatial Data.

9.2. Spatial Resources

Detailed requirements for each Spatial Resource type are dealt with in the resource-specific API standards. However, this API Common standard has the responsibility to see that all OGC API standards work together by:

1. Providing specifications for the description of each collection (`/collections/{collectionId}`), and the list of collections (`/collections`)
2. Providing a consistent framework for serving spatial data from the OGC API, regardless of the type. Consistent means that #1 works exactly the same (potentially with type-specific additional properties) and that the different types of data can all be collections on the same OGC API end-point.
3. Providing a tie point for other OGC API modules to connect to and reference (processes inputs & outputs, cataloging, searching and filtering collections, detailed metadata, tiles, styles, clipping and intersecting bounding boxes in common) Just by virtue of understanding that `/collections/{collectionId}` points to a spatial **data layer**.

Spatial Resources are exposed using the path template.

```
/collections/{collectionId}/{instanceId}/{queryType}
```

The resources returned from each node in this template are described in [Table 5](#).

Table 5. Spatial Resource Paths

Path Template	Resource
/collections	Metadata describing the spatial collections available from this API.
/collections/{collectionId}	Metadata describing the collection with the unique identifier {collectionId}
/collections/{collectionId}/{instanceId}	Metadata describing the instance or version of the collection with the unique identifier {collectionId} parameter and with the unique identifier {instanceId} parameter.
/collections/{collectionId}/{instanceId}/{queryType}	Spatial query type to perform against the resource with the unique identifier {collectionId} parameter and with the unique identifier {instanceId} parameter.

9.2.1. Collections Metadata

OGC APIs typically organize their Spatial Resources into collections. Information about those collections is accessed through the /collections path.

Operation

Requirement 8	/req/collections/rc-md-op
A	The API SHALL support the HTTP GET operation at the path /collections.

Response

Requirement 9	/req/collections/rc-md-success
A	A successful execution of the operation SHALL be reported as a response with a HTTP status code 200 .
B	The content of that response SHALL be based upon the JSON schema link: https://raw.githubusercontent.com/openeospatial/ Environmental-Data-Retrieval-API/master/standard/openapi/schemas/collections_edr.json [collections_edr.json].

The collections metadata returned by this operation is based on the [Collections Metadata Schema](#). Examples of collections metadata are provided in [Collections Metadata Examples](#).

Collections Metadata Schema

```
{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "title": "Collections Schema",
  "description": "This schema defines the metadata resource returned from /collections.",
  "type": "object",
  "required": [
    "links",
    "collections"
  ],
  "properties": {
    "links": {
      "type": "array",
      "items": {"$href": "link.json"}
    },
    "collections": {
      "type": "array",
      "items": {"$href": "collectionInfo.json"}
    }
  }
}
```

This schema is further constrained by the following requirements and recommendations.

To support hypermedia navigation, the `links` property must be populated with sufficient hyperlinks to navigate through the whole dataset.

Requirement 10	/req/collections/rc-md-links
A	<p>A 200 -response SHALL include the following links in the <code>links</code> property of the response:</p> <ul style="list-style-type: none"> • a link to this response document (relation: <code>self</code>), • a link to the response document in every other media type supported by the API (relation: <code>alternate</code>).
B	All links SHALL include the <code>rel</code> and <code>type</code> link parameters.

Additional information may be available to assist in understanding and using this dataset. Links to those resources should be provided as well.

Recomendation 9	/rec/collections/rc-md-descriptions
A	<p>If external schemas or descriptions exist that provide additional information about the structure or semantics for the resource, a 200 -response SHOULD include links to each of those resources in the <code>links</code> property of the response (relation: <code>describedBy</code>).</p>
B	The <code>type</code> link parameter SHOULD be provided for each link. This applies to resources that describe to the whole dataset.

The `collections` property of the Collections Metadata provides a description of each collection. These descriptions are based on the [Collection Information Schema](#). This schema is described in detail in the [\[collection-information\]](#) section of this Standard. The following requirements and recommendations govern the use of Collection Information in the Collections Metadata.

Requirement 11	/req/collections/rc-md-items
A	For each spatial resource collection accessible through this API, metadata describing that collection SHALL be provided in the <code>collections</code> property of the Collections Metadata.
B	This metadata shall be based on the same schema as the Collection Information resource.

While it is preferred that the Collections Metadata describe all of the collections accessible through the API, in some cases that is impractical. Developers have an option to only return a subset, as long as they provide a way to retrieve the remaining metadata as well.

Permission 2	/per/collections/rc-md-items
A	To support servers with many collections, servers MAY limit the number of items included in the <code>collections</code> property.

Error situations

See [HTTP Status Codes](#) for general guidance.

9.2.2. Collection Metadata

Each resource collection can support one or more instances or versions of the collection. The metadata that describes the instances that are available for a collection is accessed directly using the `/collections/{collectionId}` path

Operation

Requirement 12	/req/collections/rc-md-op
A	The API SHALL support the HTTP GET operation at the path <code>/collections</code> .

Response

Requirement 13	/req/collections/rc-md-success
A	A successful execution of the operation SHALL be reported as a response with a HTTP status code <code>200</code> .
B	The content of that response SHALL be based upon the JSON schema link: https://raw.githubusercontent.com/opengeospatial/Environmental-Data-Retrieval-API/master/standard/openapi/schemas/collections_edr.json [collections_edr.json].

The collections metadata returned by this operation is based on the [EDR Collection Metadata Schema](#). Examples of collection metadata are provided in [\[edr-collection-metadata-examples\]](#).

```

{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "title": "Collection Information Schema",
  "description": "This schema defines metadata resource returned from
/collections/{collectionId}.",
  "type": "object",
  "required": [
    "id",
    "links"
  ],
  "properties": {
    "id": {
      "type": "string"
    },
    "title": {
      "type": "string"
    },
    "description": {
      "type": "string"
    },
    "dataDetails": {
      "$href": "dataDefinition.json"
    },
    "links": {
      "type": "array",
      "items": {"$href": "link.json"}
    },
    "extent": {"$href": "extent.json"},
    "itemType": {
      "type": "array",
      "items": {
        "type": "string",
        "enum": ["cube", "item", "point", "polygon", "trajectory", "profile"],
        "example" : ["wfs", "cube", "point"]
      }
    },
    "crs": {
      "description": "the list of coordinate reference systems supported by the
API; the first item is the default coordinate reference system",
      "type": "array",
      "items": {
        "type": "object",
        "properties": {
          "name": {"type": "string"},
          "wkt": {"type": "string"}
        }
      },
      "default": [
        {
          "name": "EPSG:4326", "wkt": "GEOGCS[\"WGS
84\", DATUM[\"WGS_1984\", SPHEROID[\"WGS
84\", 6378137, 298.257223563, AUTHORITY[\"EPSG\", \"7030\"]], AUTHORITY[\"EPSG\", \"6326\"]], P
RIMEM[\"Greenwich\", 0, AUTHORITY[\"EPSG\", \"8901\"]], UNIT[\"degree\", 0.01745329251994328,
AUTHORITY[\"EPSG\", \"9122\"]], AUTHORITY[\"EPSG\", \"4-

```

```

326\"]]"}
    ],
    "example": [
        {
            "name": "EPSG:4326", "wkt": "GEOGCS[\"WGS
84\", DATUM[\"WGS_1984\", SPHEROID[\"WGS
84\", 6378137, 298.257223563, AUTHORITY[\"EPSG\", \"7030\"], AUTHORITY[\"EPSG\", \"6326\"], P
RIMEM[\"Greenwich\", 0, AUTHORITY[\"EPSG\", \"8901\"], UNIT[\"degree\", 0.01745329251994328,
AUTHORITY[\"EPSG\", \"9122\"], AUTHORITY[\"EPSG\", \"4326\"]]",
            {
                "name": "CUSTOM_EXAMPLE", "wkt": "GEODCRS[\"WGS 84\", DATUM[\"World
Geodetic System 1984\", ELLIPSOID[\"WGS
84\", 6378137, 298.257223563, LENGTHUNIT[\"metre\", 1.0]], CS[\"ellipsoidal\", 3], AXIS[\"
(lat)\", north, ANGLEUNIT[\"degree\", 0.0174532925199433], AXIS[\"
(lon)\", east, ANGLEUNIT[\"degree\", 0.0174532925199433], AXIS[\"ellipsoidal height
(h)\", up, LENGTHUNIT[\"metre\", 1.0]]]"
            }
        }
    ]
}
}
}

```

This schema is further constrained by the following requirements and recommendations.

To support hypermedia navigation, the `links` property must be populated with sufficient hyperlinks to navigate through the whole dataset.

Requirement 14	/req/collections/rc-md-links
A	<p>A 200 -response SHALL include the following links in the <code>links</code> property of the response:</p> <ul style="list-style-type: none"> a link to this response document (relation: <code>self</code>), a link to the response document in every other media type supported by the API (relation: <code>alternate</code>).
B	All links SHALL include the <code>rel</code> and <code>type</code> link parameters.

Additional information may be available to assist in understanding and using this dataset. Links to those resources should be provided as well.

Unresolved directive in clause_8_collections.adoc - include::recommendations/collections/REC_rc-md-instance-descriptions.adoc[]

The `instance` property of the Collection Metadata provides a description of each instance. These descriptions are based on the [EDR Collection Instance Information Schema](#). This schema is described in detail in the [Collection Instance Information](#) section of this Standard. The following requirements and recommendations govern the use of Collection Instance Information in the Collection Instance Metadata.

Requirement 15	/req/collections/rc-md-items
A	For each spatial resource collection accessible through this API, metadata describing that collection SHALL be provided in the <code>collections</code> property of the Collections Metadata.
B	This metadata shall be based on the same schema as the Collection Information resource.

While it is preferred that the Collection Instance Metadata fully describe the collection instance through the API, in some cases that is impractical. Developers have an option to only return a subset, as long as they provide a way to retrieve the remaining metadata as well.

Unresolved directive in clause_8_collections.adoc - include::recommendations/collection/PER_rc-md-instance-items.adoc[]

Error situations

See [HTTP Status Codes](#) for general guidance.

If the parameter `collectionId` does not exist on the server, the status code of the response will be 404 (see [Table 4](#)).

9.2.3. Collection Instance Information

Each instance of a resource collection is described by a set of metadata. That metadata is accessed directly using the `/collections/{collectionId}/{instanceId}` path or as an entry in the `collections` property of the Collections Metadata resource.

Operation

Requirement 16	/req/collections/src-md-op
A	The API SHALL support the HTTP GET operation at the path <code>/collections/{collectionId}</code> .
B	The parameter <code>collectionId</code> is each <code>id</code> property in the resource collections response (JSONPath: <code>\$.collections[*].id</code>).

Response

Requirement 17	/req/collections/src-md-success
A	A successful execution of the operation SHALL be reported as a response with a HTTP status code 200 .
B	The content of that response SHALL be based upon the JSON schema link: https://raw.githubusercontent.com/opengeospatial/Environmental-Data-Retrieval-API/master/standard/openapi/schemas/collectionInfo_edr.json [collectionInfo_edr.json].
C	The content of that response SHALL be consistent with the content for this resource collection in the /collections response. That is, the values for id, title, description and extent SHALL be identical.

Collection Information is based on the link:https://raw.githubusercontent.com/opengeospatial/Environmental-Data-Retrieval-API/master/standard/openapi/schemas/collectionInfo_edr.json[Collection Information Schema]. Examples of Collection Information are provided in [Collection Information Examples](#).

```

{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "title": "Collection Instance Information Schema",
  "description": "This schema defines metadata resource returned from
/collections/{collectionId}/{instanceId}.",
  "type": "object",
  "required": [
    "id",
    "title",
    "description",
    "parameters"
  ],
  "properties": {
    "id": {
      "type": "string"
    },
    "title": {
      "type": "string"
    },
    "description": {
      "type": "string"
    },
    "dataDetails": {
      "$href": "dataDefinition.json"
    },
    "pointQuery" :{
      "type" : "object",
      "description" : "Enumerated value lists for those query parameters that only
apply to point queries.",
      "properties": {
        "interpolation" : {
          "type" : "array",
          "description" : "List of the interpolation approaches supported by
the point query for the collection",
          "items": {
            "type" : "string"
          }
        },
        "withinUnits" : {
          "type" : "array",
          "description" : "List of the distance units supported if the query
supports a within a defined radius query",
          "items": {
            "type" : "string"
          }
        }
      }
    }
  }
}

```

```

    }
  },
  "polygonQuery" :{
    "type" : "object",
    "description" : "Enumerated value lists for those query parameters that only apply
to point queries.",
    "properties": {

```

```

"interpolationX" : {
  "type" : "array",
  "description" : "List of the X axis interpolation approaches supported by
the polygon query for the collection",
  "items": {
    "type" : "string"
  }
},
"interpolationY" : {
  "type" : "array",
  "description" : "List of the Y axis interpolation approaches supported by
the polygon query for the collection",
  "items": {
    "type" : "string"
  }
},
"BBOXonly" : {
  "type" : "boolean",
  "description" : "If set to true the collection will only support simple
polygon queries defined by a rectangular area."
}

```

```

}
},
"parameters": {
  "$ref": "#/definitions/mapParameter"
},
"definitions": {
  "mapLang": {
    "type": "object",
    "additionalProperties": {
      "type": "string"
    }
  },
  "mapParameter": {
    "type": "object",
    "title": "Parameter metadata Schema",
    "description": "This schema defines properties required to describe a collection
data parameter.",
    "additionalProperties": {
      "type": "object",
      "required": [
        "description",
        "unit",
        "type",
        "observedProperty",
        "extent"
      ],
      "properties": {
        "description": {
          "type": "object",
          "required": [
            "en"
          ],
          "properties": {
            "$ref": "#/definitions/mapLang"

```

```

    }
    },
    "unit": {
      "type": "object",
      "required": [
        "label",
        "symbol"
      ],
      "properties": {
        "label": {
          "$ref": "#/definitions/mapLang"
        },
        "symbol": {
          "type": "object",
          "required": [
            "value",
            "type"
          ],
          "properties": {
            "value": {
              "type": "string"
            },
            "type": {
              "type": "string"
            }
          }
        }
      }
    },
    },
    "measurementType": {
      "type": "object",
      "title": "Parameter measurement type",
      "description": "This schema describes the type of calculation that a
parameter is derived from and the length of time it represents.",
      "required": [
        "method",
        "period"
      ],
      "properties": {
        "method": {
          "type": "string",
          "examples": ["instantaneous", "sum", "maximum"]
        },
        "duration": {
          "title": "Time duration",
          "description": "The time duration that the parameter value
is calculated over expressed as an RFC3339 duration value, if the method is
instantaneous this property is not needed.",
          "type": "string"
        }
      }
    },
    "observedProperty": {
      "type": "object",
      "required": [
        "id",

```

```

"label"
    ],
    "properties": {
        "id": {
            "type": "string"
        },
        "label": {
            "$ref": "#/definitions/mapLang"
        }
    }
},
"extent": {
    "type": "object",
    "required": [
        "horizontal"
    ],
    "properties": {
        "horizontal": {
            "type": "object",
            "required": [
                "name",
                "coordinates",
                "geographic"
            ],
            "properties": {
                "name": {
                    "type": "array",
                    "items": {
                        "type": "string"
                    }
                },
                "coordinates": {
                    "type": "array",
                    "items": {
                        "type": "string"
                    }
                },
                "geographic": {
                    "type": "string"
                }
            }
        },
        "vertical": {
            "type": "object",
            "required": [
                "name",
                "coordinates",
                "range"
            ],
            "properties": {
                "name": {
                    "type": "array",
                    "items": {
                        "type": "string"
                    }
                },
                "coordinates": {
                    "type": "array",

```

} }

$$\left. \begin{array}{l} \{ \\ \} \end{array} \right\}$$

39

To support hypermedia navigation, the `links` property must be populated with sufficient hyperlinks to navigate through the whole dataset.

Requirement 18	<code>/req/collections/rc-md-items-links</code>
A	<p>200 -response SHALL include the following links in the <code>links</code> property of the response:</p> <ul style="list-style-type: none">• a link to this response document (relation: <code>self</code>),• a link to the response document in every other media type supported by the API (relation: <code>alternate</code>).
B	<p>The <code>links</code> property of the response SHALL include an item for each supported encoding of that collection with a link to the collection resource (relation: <code>items</code>).</p>
B	<p>All links SHALL include the <code>rel</code> and <code>type</code> properties.</p>

Additional information may be available to assist in understanding and using this dataset. Links to those resources should be provided as well.

Recomendation 10	<code>/rec/core/rc-md-items-descriptions</code>
A	<p>If external schemas or descriptions exist that provide additional information about the structure or semantics of the collection, a 200 -response SHOULD include links to each of those resources in the <code>links</code> property of the response (relation: <code>describedBy</code>).</p>
B	<p>The <code>type</code> link parameter SHOULD be provided for each link.</p>

Additional requirements and recomendations apply to the `extent` property of the Collection Information.

Requirement 19	/req/collections/rc-md-extent
A	For each spatial resource collection, the <code>extent</code> property, if provided, SHALL provide bounding boxes that include all spatial geometries and time intervals that include all temporal geometries in this collection. The temporal extent may use <code>null</code> values to indicate an open time interval.
B	If a spatial resource has multiple properties with spatial or temporal information, it is the decision of the API implementation whether only a single spatial or temporal geometry property is used to determine the extent or all relevant geometries.

Recommendation 11	/rec/core/rc-md-extent-single
A	While the spatial and temporal extents support multiple bounding boxes (<code>bbox</code> array) and time intervals (<code>interval</code> array) for advanced use cases, implementations SHOULD provide only a single bounding box or time interval unless the use of multiple values is important for the use of the dataset and agents using the API are known to be support multiple bounding boxes or time intervals.

Permission 3	/per/collections/rc-md-extent-extensions
A	The Core only specifies requirements for spatial and temporal extents. However, the <code>extent</code> object MAY be extended with additional members to represent other extents, for example, thermal or pressure ranges.
B	The Core only supports spatial extents in WGS84 longitude/latitude and temporal extents in the Gregorian calendar (these are the only enum values in extent.yaml).
C	Extensions to the Core MAY add additional reference systems to the <code>extent</code> object.

Error situations

See [HTTP Status Codes](#) for general guidance.

If either of the parameters `collectionId` or `instanceId` does not exist on the server, the status code of the response will be `404` (see [Table 4](#)).

9.3. Information Resources

Information Resources are non-spatial resources which support the operation of the API or the access and use of the Spatial Resources. They are described in the [Information Resources](#) section.

Information Resources related to Spatial Resources can be exposed using the path template:

- `/collections/{collectionId}/{resourceType}`

The resources returned from each node in this template are described in [Table 6](#).

Table 6. Information Resource Paths

Path Template	Resource
<code>/collections</code>	The root resource describing the spatial collections available from this API.
<code>/collections/{collectionId}</code>	Identifies a collection with the unique identifier <code>{collectionId}</code>
<code>/collections/{collectionId}/{instanceId}</code>	Metadata that describes the instance with unique identifier <code>{instanceId}</code> associated with the <code>{collectionId}</code> collection.
<code>/collections/{collectionId}/{instanceId}/{queryType}</code>	Query of type <code>{queryType}</code> that acts on the unique <code>{instanceId}</code> instance associated with the <code>{collectionId}</code> collection.

The OGC EDR will have a defined a list of Query Types that can be invoked. The [\[query-type-resource-table\]](#) provides a mapping of the current query types supported by the standard.

9.4. Parameter Modules

Query parameters are used in URLs to define the resources which are returned on a GET request. The EDR standard defines the following as standard parameters for use in EDR API standards.

9.4.1. Parameter coords

Requirement 20	/req/edr/coords-definition
A	<p>Each resource collection operation SHALL support a parameter <code>coords</code> with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: coords in: query required: true schema: type: string style: form explode: false </pre>
B	<p>The <code>coords</code> string value will be a Well Known Text of representation geometry as defined in Simple Feature Access - Part 1: Common Architecture. The representation type will depend on the queryType of the API</p>

Requirement 21	/req/edr/coords-response
A	Only those resources that have a spatial geometry that intersects the area defined by the <code>coords</code> p
B	The coordinates SHALL consist of a Well Known Text (WKT) geometry string
C	<p>The coordinate reference system of the values SHALL be interpreted as WGS84 longitude/latitude</p> <pre> WKT: GEOGCS["WGS 84",DATUM["WGS_1984",SPHEROID["WGS 84",6378137,298.257223563,AUTHORITY["EPSG","7030"]],AUTHORITY["EPSG","6326"]],PRIMEM["Greenwich",0, </pre> <pre> EPSG: http://www.opengis.net/def/crs/OGC/1.3/CRS84 </pre> <p>unless a different coordinate reference system is specified in a parameter <code>crs</code>.</p>

9.4.2. Parameter datetime

Requirement 22	/req/collections/rc-time-definition
A	<p>The <code>datetime</code> parameter SHALL have the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: datetime in: query required: false schema: type: string style: form explode: false </pre>

Requirement 23	/req/collections/rc-time-response
A	If the <code>datetime</code> parameter is provided, only resources that have a temporal geometry that intersects the temporal information in the <code>datetime</code> parameter SHALL be part of the result set.
B	If a resourcee has multiple temporal properties, it is the decision of the API whether only a single temporal property is used to determine the extent or all relevant temporal properties.
C	The <code>datetime</code> parameter SHALL match all resources in the collection that are not associated with a temporal geometry.
D	<p>The temporal information is either a date-time or a time interval. The parameter value SHALL conform to the following syntax (using ABNF):</p> <pre> interval-closed = date-time "/" date-time interval-open-start = "../" date-time interval-open-end = date-time "/.." interval = interval-closed / interval-open-start / interval-open-end datetime = date-time / interval </pre>
E	The syntax of <code>date-time</code> is specified by RFC 3339, 5.6 .
F	Open ranges in time intervals at the start or end SHALL be supported using a double-dot (<code>..</code>).

"Intersects" means that the time (instant or period) specified in the parameter `datetime` includes a timestamp that is part of the temporal geometry of the resource (again, a time instant or period). For time periods this includes the start and end time.

Example 2. A date-time

February 12, 2018, 23:20:52 GMT:

```
time=2018-02-12T23%3A20%3A52Z
```

For resources with a temporal property that is a timestamp (like `lastUpdate` in the building features), a date-time value would match all resources where the temporal property is identical.

For resources with a temporal property that is a date or a time interval, a date-time value would match all resources where the timestamp is on that day or within the time interval.

Example 3. Intervals

February 12, 2018, 00:00:00 GMT to March 18, 2018, 12:31:12 GMT:

```
datetime=2018-02-12T00%3A00%3A00Z%2F2018-03-18T12%3A31%3A12Z
```

February 12, 2018, 00:00:00 UTC or later:

```
datetime=2018-02-12T00%3A00%3A00Z%2F..
```

March 18, 2018, 12:31:12 UTC or earlier:

```
datetime=..%2F2018-03-18T12%3A31%3A12Z
```

A template for the definition of the parameter in YAML according to OpenAPI 3.0 is available at [datetime.yaml](#).

9.4.3. Parameter `parametername`

Requirement 24	<code>/req/edr/parameters-definition</code>
A	<p>Each resource collection operation SHALL support a parameter <code>`parametername`</code> with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre>name: parametername in: query required: true explode: false schema: minItems: 1 type: array items: type: string</pre>

Requirement 25	/req/edr/parameters-response
A	If the <code>parametername</code> parameter is provided, only those parameters named SHALL be returned. If the <code>parametername</code> parameter is not specified all parameters in the collection SHALL be returned.
B	The <code>parametername</code> parameter SHALL consist of a comma delimited string value based on an enumerated list of options listed in the collections metadata

Example 4. A single parameter

Only return values for the Maximum_temperature

```
parametername=Maximum_temperature
```

Example 5. Return multiple parameters

Values for the Maximum_temperature, Minimum_temperature and Total_precipitation

```
parametername=Maximum_temperature,Minimum_temperature,Total_precipitation
```

If none of the requested parameters exist in the collection a 403 message SHOULD be returned.

9.4.4. Parameter crs

Requirement 26	/req/edr/outputCRS-definition
A	<p>Each resource collection operation SHALL support a parameter CRS with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: CRS in: query required: false schema: type: string style: form explode: false </pre>

Requirement 27	/req/edr/outputCRS-response
A	If the CRS parameter is provided, the returned information should be reprojected (if required) to the defined coordinate system. If the CRS parameter is not specified the data will be returned in its native projection.
B	The CRS parameter SHALL consist of an identifier selected from the enumerated list of valid values supplied in the collections metadata.

The value of the crs query parameter will be one of the name values described in the instance metadata for supported crs transformations.

9.4.5. Parameter outputFormat

Requirement 28	/req/edr/outputFormat-definition
A	<p>Each resource collection operation SHALL support a parameter `outputFormat` with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: outputFormat in: query required: false schema: type: string style: form explode: false </pre>

Requirement 29	/req/edr/outputFormat-response
A	If the outputFormat parameter is provided, the returned information should be transformed to the defined data format.
B	The outputFormat parameter SHALL consist of a string value based on an enumerated list of available options provided in the collections metadata.

Example 6. Return data as coverageJSON

```
outputFormat=coverageJSON
```

If not specified the query will return data in the native format of the collection. If the requested format system does not match an entry in the defined list of valid outputFormats for the collection a 403

message SHOULD be returned.

9.5. QueryType specific Operations

The following describes the query parameters that are unique or specialised to the individual query types:

9.5.1. Point

9.5.2. Parameters

9.5.3. Parameter coords

Requirement 30	/req/edr/coords-definition
A	<p>Each resource collection operation SHALL support a parameter <code>coords</code> with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre>name: coords in: query required: true schema: type: string style: form explode: false</pre>
B	<p>The <code>coords</code> string value will be a Well Known Text of representation geometry as defined in Simple Feature Access - Part 1: Common Architecture. The representation type will depend on the queryType of the API</p>

Requirement 31	/req/edr/coords-response
A	<p>Only those resources that have a spatial geometry that intersects the area defined by the</p>

	coords parameter SHALL be part of the result set.
B	The coordinates SHALL consist of a Well Known Text (WKT) geometry string
C	<p>The coordinate reference system of the values SHALL be interpreted as WGS84 longitude/latitude</p> <pre>WKT: GEOGCS["WGS 84",DATUM["WGS_1984",SPHEROID["WGS 84",6378137,298.257223563,AUTHORITY["EPSG","7030"]],AUTHORITY["EPSG","6326"]],PRIMEM["Greenwich",0,AUTHORITY["EPSG","31433"]],UNIT["metre",1,AUTHORITY["EPSG","9001"]]]</pre> <pre>EPSG: http://www.opengis.net/def/crs/OGC/1.3/CRS84</pre> <p>unless a different coordinate reference system is specified in a parameter crs .</p>

The point query supports two types of Well Known Text geometries, Point for as single location and Multipoint for a list of locations. The point query only supports 2D geometries

Example 7. Point

retrieve data for a single location 51.2 N, 3.2 W

```
coords=POINT(-3.2 51.2)
```

Example 8. Multipoint

retrieve data for a list of locations : 38.9N 77W, 48.85N 2.35E, 39.92N 116.38E, 35.29S 149.1E, 51.5N 0.1W

```
coords=MULTIPOINT((38.9 -77),(48.85 2.35),(39.92 116.38),(-35.29 149.1),(51.5 -0.1))
```

9.5.4. Parameter interpolation

Requirement 32	/req/edr/interpolation-definition
A	<p>Each resource collection operation MAY support a parameter `interpolation` with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: interpolation in: query required: false schema: type: string style: form explode: false </pre>

Requirement 33	/req/edr/interpolation-response
A	If the <code>interpolation</code> parameter is defined the result set SHALL to data point that is the best match based on the chosen algorithm.
B	<p>The interpolation information is an interpolation method. The available interpolation methods should be part of the collection response:</p> <pre>interpolation = interpolation-method</pre>

If not specified the query will use the default interpolation method for the chosen collection. If the interpolation method does not match an entry in the defined list of valid interpolation methods for the collection a 403 message SHOULD be returned.

Example 9. An interpolation

Use the defined nearest neighbour algorithm to get the best data match for the requested locations

```
interpolation=nearest-neighbour
```

Example 10. An interpolation

Use the defined nearest neighbour algorithm to get the best data match for the requested locations

```
interpolation=nearest-neighbour
```

9.5.5. Parameter within

Requirement 34	/req/edr/within-definition
A	<p>Each resource collection operation MAY support a parameter `within` with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: within in: query required: false schema: type: string style: form explode: false </pre>

Requirement 35	/req/edr/within-response
A	If the <code>within</code> parameter is provided, all selected information within the specified radius SHALL be part of the result set.
B	If a <code>withinUnits</code> parameter is not provided, the distance units will default to the requested CRS default units.

If not specified the query will return the information for the location defined by the `coords` parameter.

9.5.6. Parameter `withinUnits`

Unresolved directive in requirements/edr/query_type/point.adoc - include::../REQ_rc-withinunits-definition.adoc[]

Unresolved directive in requirements/edr/query_type/point.adoc - include::../REQ_rc-withinunits-response.adoc[]

9.5.7. Polygon

9.5.8. Parameters

9.5.9. Parameter `coords`

Requirement 36	/req/edr/coords-definition
A	<p>Each resource collection operation SHALL support a parameter <code>coords</code> with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: coords in: query required: true schema: type: string style: form explode: false </pre>
B	<p>The <code>coords</code> string value will be a Well Known Text of representation geometry as defined in Simple Feature Access - Part 1: Common Architecture. The representation type will depend on the queryType of the API</p>
Requirement 37	/req/edr/coords-response
A	<p>Only those resources that have a spatial geometry that intersects the area defined by the</p>

	coords parameter SHALL be part of the result set.
B	The coordinates SHALL consist of a Well Known Text (WKT) geometry string
C	<p>The coordinate reference system of the values SHALL be interpreted as WGS84 longitude/latitude</p> <pre>WKT: GEOGCS["WGS 84",DATUM["WGS_1984",SPHEROID["WGS 84",6378137,298.257223563,AUTHORITY["EPSG","7030"]],AUTHORITY["EPSG","6326"]],PRIMEM["Greenwich",0,AUTHORITY["EPSG","9108"]],UNIT["metre",1,AUTHORITY["EPSG","9001"]]]</pre> <pre>EPSG: http://www.opengis.net/def/crs/OGC/1.3/CRS84</pre> <p>unless a different coordinate reference system is specified in a parameter crs .</p>

"Intersects" means that the rectangular area specified in the parameter `coords` includes a coordinate that is part of the (spatial) geometry of the resource. This includes the boundaries of the geometries (e.g. for curves the start and end position and for surfaces the outer and inner rings).

The polygon query supports two Well Know Text geometry types Polygon and Multipolygon, the polygon query SHOULD support 3D queries allowing the definition of a vertical level value (z) therefore coordinates for geometries may be 2D (x, y) or 3D (x, y, z). If a height level is not specified all available levels SHOULD be returned.

All polygons in a MULTIPOLYGON request must either by 2D or 3D a request MUST not contain a mix a 2D and 3D definitions.

Example 11. A polygon covering the UK

An area covering the UK in WGS84 (from 15°W to 5°E and from 60.95°S to 48.8°S)

```
coords=POLYGON((-15 48.8,-15 60.95,5 60.85,5 48.8,-15 48.8))
```

Example 12. A polygon covering the UK for a specific vertical level

An area covering the UK in WGS84 (from 15°W to 5°E and from 60.95°S to 48.8°S) at 500hPa

```
coords=POLYGON((-15 48.8 500,-15 60.95 500,5 60.85 500,5 48.8 500,-15 48.8 500))
```

Example 13. A polygon covering the UK multiple heights

An area covering the UK in WGS84 (from 15°W to 5°E and from 60.95°S to 48.8°S) at 10m and 80m

```
coords=MULTIPOLYGON((-15 48.8 10,-15 60.95 10,5 60.85 10,5 48.8 10,-15 48.8 10),(-15 48.8 80,-15 60.95 80,5 60.85 80,5 48.8 80,-15 48.8 80))
```

Example 14. Multiple areas

Selecting data for two different regions

```
coords=MULTIPOLYGON((-15 48.8,-15 60.95,5 60.85,5 48.8,-15 48.8),(-6.1 50.3,-4.35 51.4,-2.6 51.6,-2.8 50.6,-5.3 49.9,-6.1,50.3))
```

9.5.10. Parameter interpolationX

Requirement 38	/req/edr/interpolationX-definition
A	<p>Each resource collection operation MAY support a parameter `interpolationX` with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre>name: interpolationX in: query required: false schema: type: string style: form explode: false</pre>

Requirement 39	/req/edr/interpolationX-response
A	<p>If the <code>interpolationX</code> parameter is defined the result set SHALL contain values derieved based on the chosen interpolation algorithm at the number of specifed x intervals.</p>
B	<p>The interpolationX information is an interpolation method and an interval. The available interpolation methods should be part of the collection response and the interval is a number :</p> <pre>interpolationX = "R"interval "/" interpolation-method</pre>

If not specified the query will not perform any interpolation of data along the X axis. If the interpolationX method does not match an entry in the defined list of valid interpolationX methods for the collection a 403 message SHOULD be returned.

Example 15. An interpolationX

Use the defined linear algorithm to return 10 values between the minimum X value and the maximum X value

```
interpolationX=R10/linear
```

9.5.11. Parameter interpolationY

Requirement 40	/req/edr/interpolationY-definition
A	<p>Each resource collection operation MAY support a parameter `interpolationY` with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: interpolationY in: query required: false schema: type: string style: form explode: false </pre>

Requirement 41	/req/edr/interpolationY-response
A	<p>If the <code>interpolationY</code> parameter is defined the result set SHALL contain values derieved based on the chosen interpolation algorithm at the number of specied y intervals.</p>
B	<p>The interpolationY information is an interpolation method and an interval. The available interpolation methods should be part of the collection response and the interval is a number :</p> <pre> interpolationY = "R"interval "/" interpolation-method </pre>

If not specified the query will not perform any interpolation of data along the Y axis. If the interpolationY method does not match an entry in the defined list of valid interpolationY methods for the collection a 403 message SHOULD be returned.

Example 16. An interpolationY

Use the defined nearest-neighbour algorithm to return 3 values between the minimum Y value and the maximum Y value

```
interpolationY=R3/nearest-neighbour
```

9.5.12. Cube

Unresolved directive in clause_8_collections.adoc - include::requirements/edr/query_type/cube.adoc[]

9.5.13. Trajectory (corridor)

9.5.14. Parameters

9.5.15. Parameter coords

Requirement 42	/req/edr/coords-definition
A	<p>Each resource collection operation SHALL support a parameter <code>coords</code> with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: coords in: query required: true schema: type: string style: form explode: false </pre>
B	<p>The <code>coords</code> string value will be a Well Known Text of representation geometry as defined in Simple Feature Access - Part 1: Common Architecture. The representation type will depend on the queryType of the API</p>
Requirement 43	/req/edr/coords-response
A	<p>Only those resources that have a spatial geometry that intersects the area defined by the</p>

	coords parameter SHALL be part of the result set.
B	The coordinates SHALL consist of a Well Known Text (WKT) geometry string
C	<p>The coordinate reference system of the values SHALL be interpreted as WGS84 longitude/latitude</p> <pre>WKT: GEOGCS["WGS 84",DATUM["WGS_1984",SPHEROID["WGS 84",6378137,298.257223563,AUTHORITY["EPSG","7030"]],AUTHORITY["EPSG","6326"]],PRIMEM["Greenwich",0,AUTHORITY["EPSG","31433"]],UNIT["metre",1,AUTHORITY["EPSG","9001"]]]</pre> <pre>EPSG: http://www.opengis.net/def/crs/OGC/1.3/CRS84</pre> <p>unless a different coordinate reference system is specified in a parameter crs .</p>

"Intersects" means that the area specified by the parameter coords , includes a coordinate that is part of the (spatial) geometry of the resource. This includes the boundaries of the geometries.

The trajectory query supports the Linestring Well Know Text (WKT) geometry type, the trajectory query SHOULD support 2D, 3D and 4D queries allowing the definition of a vertical level value (z) and an time value (as an epoc time) therefore coordinates for geometries may be 2D (x, y), 3D (x, y, z) or 4D (x, y, z, t).

If the collection has height (z) dimension and the Well Known Text query does does not include a height value a 403 error should be returned

If the collection does not have a height dimension but time values are required in the WKT geometry the z value SHOULD always be 0.

Example 17. A basic surface route

From Bristol to Exeter

```
coords=LINESTRING(51.14 -2.98,51.36 -2.87,51.03 -3.15,50.74 -3.48,50.9 -3.36)
```

Example 18. A basic surface route with defined time intervals

From Bristol to Exeter

```
coords=LINESTRING(51.14 -2.98 0 1560507000,51.36 -2.87 0 1560507600,51.03 -3.15 0 1560508200,50.74 -3.48 0 1560508500,50.9 -3.36 0 1560510240)
```

9.5.16. Parameter interpolation

Requirement 44	/req/edr/interpolation-definition
A	<p>Each resource collection operation MAY support a parameter `interpolation` with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: interpolation in: query required: false schema: type: string style: form explode: false </pre>

Requirement 45	/req/edr/interpolation-response
A	If the <code>interpolation</code> parameter is defined the result set SHALL to data point that is the best match based on the chosen algorithm.
B	<p>The interpolation information is an interpolation method. The available interpolation methods should be part of the collection response:</p> <pre> interpolation = interpolation-method </pre>

If not specified the query will not perform any interpolation of the data points specified in the `coords` query parameter. If the `interpolation` method does not match an entry in the defined list of valid `interpolation` methods for the collection a 403 message SHOULD be returned.

9.5.17. Parameter interpolationZ

Requirement 46	/req/edr/interpolationZ-definition
A	<p>Each resource collection operation MAY support a parameter `interpolationZ` with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: interpolationZ in: query required: false schema: type: string style: form explode: false </pre>

Requirement 47	/req/edr/interpolationZ-response
A	If the interpolationZ parameter is defined the result set SHALL contain values derieved based on the chosen interpolation algorithm at the number of specifed z intervals.
B	<p>The interpolationY information is an interpolation method and an interval. The available interpolation methods should be part of the collection response and the interval is a number :</p> <pre>interpolationZ = "R" intervals "/" intervalinterpolation-method</pre>

If not specified the query will not perform any interpolation of data along the height axis. If the interpolationZ method does not match an entry in the defined list of valid interpolationY methods for the collection a 403 message SHOULD be returned.

9.5.18. Item

9.5.19. Parameters

Due to the concept of Collections in EDR the item query is a powerful and flexible tool, but retains only simple options. It could be used to rerun a previously run query but with a replacement for one or more of the input parameters; this would be achieved by using the id field value from the successful output from a previous query as the input id query parameter of item query, then the API user could override one or more of the original query parameters by just entering the query parameters that they want to change (i.e. a trajectory query where the same route is used every day with the same interpolation options, crs and outputFormat and the user just needs to enter the new time range).

Again this is dependant on the data publisher implementing support for the functionality.

Example 19. id

```
return information for the requested id

id=gfs-query-2020-01-31
```

As in the EDR concept a Collection is a black box it would be possible to overload the id query parameter to perform different actions, as it is the Collection black box that interprets how it handles the parameter; for instance in the Metar collection it could be combined with the parametername query parameter and the time parameter to return all Metars for ICAO id KIAD for the requested time period

```
return information for the requested id

/collections/metar/raw/item?id=KIAD&parametername=icao_id&time=2020-01-31T00:00:00Z/2020-02-01T04:00:00Z
```

This example does have a flaw in that the EDR API provides no mechanism for the user to discover the available icao id's in the metadata (the id's are available in the query results but not in any of the available metadata outputs).

9.6. General Requirements

The following general requirements and recommendations apply to all OGC APIs which host Spatial Resources.

9.6.1. Coordinate Reference Systems

As discussed in Chapter 9 of the W3C/OGC Spatial Data on the Web [Best Practices document](#), how to express and share the location of resources in a consistent way is one of the most fundamental aspects of publishing geographic data and it is important to be clear about the coordinate reference system that coordinates are in.

For the reasons discussed in the Best Practices, OGC APIs use WGS84 longitude and latitude as the default coordinate reference system.

Requirement 48	<code>/req/collections/crs84</code>
A	Unless the client explicitly requests a different coordinate reference system, all spatial geometries SHALL be in the CRS84 (WGS 84 longitude/latitude) coordinate reference system for geometries without height information and CRS84h (WGS 84 longitude/latitude plus ellipsoidal height) for geometries with height information.

The implementations compliant with the Core are not required to support publishing geometries in coordinate reference systems other than <http://www.opengis.net/def/crs/OGC/1.3/CRS84>. The Core also does not specify a capability to request geometries in a different reference system than the native one of the published resource. Such a capability will be specified in other OGC API standards.

10. Requirements classes for encodings

10.1. Overview

This clause specifies two pre-defined requirements classes for encodings to be used by an OGC API implementation. These encodings are commonly used encodings for spatial data on the web:

- [HTML](#)
- [GeoJSON](#)

Neither of these encodings are mandatory and an implementation of the [Core](#) requirements class may implement either, both, or none of them. [Clause 7 \(Overview\)](#) includes a discussion about recommended encodings.

10.2. Requirement Class "HTML"

Geographic information that is only accessible in formats like GeoJSON or GML has two issues:

- The data is not discoverable using the most common mechanism for discovering information, that is the search engines of the Web,
- The data can not be viewed directly in a browser - additional tools are required to view the data.

Therefore, sharing data on the Web should include publication in HTML. To be consistent with the Web, it should be done in a way that enables users and search engines to access all data.

This is discussed in detail in [W3C Best Practice](#). This standard therefore [recommends](#) supporting HTML as an encoding.

Requirements Class	
http://www.opengis.net/spec/ogcapi_common/1.0/req/html	
Target type	Web API
Dependency	Requirements Class "OAPI Core"
Dependency	HTML5
Dependency	Schema.org

Requirement 49	/req/html/definition
A	Every 200 -response of an operation of the API SHALL support the media type <code>text/html</code> .

Requirement 50	/req/html/content
A	Every 200 -response of the API with the media type "text/html" SHALL be a HTML 5 document that includes the following information in the HTML body: <ul style="list-style-type: none">• all information identified in the schemas of the Response Object in the HTML <code><body/></code>, and• all links in HTML <code><a/></code> elements in the HTML <code><body/></code>.

Recommendation 12	/rec/html/schema-org
A	A 200 -response with the media type <code>text/html</code> , SHOULD include Schema.org annotations.

10.3. Requirement Class "GeoJSON"

GeoJSON is a commonly used format that is simple to understand and well supported by tools and software libraries. Since most Web developers are comfortable with using a JSON-based format, supporting GeoJSON is recommended if the resource can be represented in GeoJSON for the intended use.

Requirements Class	
http://www.opengis.net/spec/ogcapi_common/1.0/req/geojson	
Target type	Web API
Dependency	Requirements Class "OAPI Core"
Dependency	GeoJSON

Requirement 51	/req/geojson/definition
A	<p>200 -responses of the server SHALL support the following media types:</p> <ul style="list-style-type: none">• <code>application/geo+json</code> for resources that include feature content, and• <code>application/json</code> for all other resources.

Requirement 52	/req/geojson/content
A	<p>Every 200 -response with the media type <code>application/geo+json</code> SHALL be</p> <ul style="list-style-type: none">• a GeoJSON FeatureCollection Object for feature collections, and• a GeoJSON Feature Object for features.
B	<p>The schema of all responses with the media type <code>application/json</code> SHALL conform with the JSON Schema specified for that resource.</p>

NOTE | The following schema names are from API-Features and need to be updated.

Templates for the definition of the schemas for the GeoJSON responses in JSON Schema definitions are available at [collections.yaml](#) and [collectionInfo.yaml](#).

These are generic schemas that do not include any application schema information about specific resource types or their properties.

11. Requirements class "OpenAPI 3.0"

11.1. Basic requirements

APIs conforming to this requirements class document themselves by an [OpenAPI Document](#).

Requirements Class	
http://www.opengis.net/spec/ogcapi_common/1.0/req/oas30	
Target type	Web API
Dependency	Requirements Class "OAPI Core"
Dependency	OpenAPI Specification 3.0.2

Requirement 53	/req/oas30/oas-definition-1
A	An OpenAPI definition in JSON using the media type <code>application/vnd.oai.openapi+json;version=3.0</code> and a HTML version of the API definition using the media type <code>text/html</code> SHALL be available.

CAUTION | [ISSUE 117](#)

The OpenAPI media type has not been registered yet with IANA and will likely change. We need to update the media type after registration.

Requirement 54	/req/oas30/oas-definition-2
A	The JSON representation SHALL conform to the OpenAPI Specification, version 3.0 .

Two example OpenAPI documents are included in [Annex B](#).

Requirement 55	/req/oas30/oas-impl
A	The API SHALL implement all capabilities specified in the OpenAPI definition.

11.2. Complete definition

Requirement 56	/req/oas30/completeness
A	The OpenAPI definition SHALL specify for each operation all HTTP Status Codes and Response Objects that the API uses in responses.
B	This includes the successful execution of an operation as well as all error situations that originate from the server.

Note that APIs that, for example, are access-controlled (see [Security](#)), support web cache validation, CORS or that use HTTP redirection will make use of additional HTTP status codes beyond regular codes such as 200 for successful GET requests and 400, 404 or 500 for error situations. See [HTTP Status Codes](#).

Clients have to be prepared to receive responses not documented in the OpenAPI definition. For example, additional errors may occur in the transport layer outside of the server.

11.3. Exceptions

Requirement 57	/req/oas30/exceptions-codes
A	For error situations that originate from an API server, the API definition SHALL cover all applicable HTTP Status Codes.

Example 20. An exception response object definition

```

description: An error occurred.
content:
  application/json:
    schema:
      $ref:
        https://raw.githubusercontent.com/opengeospatial/OAPI/openapi/schemas/exception.yaml
  text/html:
    schema:
      type: string

```

11.4. Security

Requirement 58	/req/oas30/security
A	For cases, where the operations of the API are access-controlled, the security scheme(s) and requirements SHALL be documented in the OpenAPI definition.

The OpenAPI specification currently supports the following [security schemes](#):

- HTTP authentication,
 - an API key (either as a header or as a query parameter),
 - OAuth2's common flows (implicit, password, application and access code) as defined in RFC6749, and
 - OpenID Connect Discovery.
-

12. Media Types

JSON media types that would typically be used in on OGC API that supports JSON are

- `application/geo+json` for feature collections and features, and
- `application/json` for all other resources.

XML media types that would typically occur in on OGC API that supports XML are

- `application/gml+xml;version=3.2` for any GML 3.2 feature collections and features,
- `application/gml+xml;version=3.2;profile=http://www.opengis.net/def/profile/ogc/2.0/gml-sf0` for GML 3.2 feature collections and features conforming to the GML Simple Feature Level 0 profile,
- `application/gml+xml;version=3.2;profile=http://www.opengis.net/def/profile/ogc/2.0/gml-sf2` for GML 3.2 feature collections and features conforming to the GML Simple Feature Level 2 profile, and
- `application/xml` for all other resources.

The typical HTML media type for all "web pages" in an OGC API would be `text/html`.

The media types for an OpenAPI definition are `vnd.oai.openapi+json;version=3.0` (JSON) and `application/vnd.oai.openapi;version=3.0` (YAML).

NOTE

The OpenAPI media type has not been registered yet with IANA and may change.

Annex A: Abstract Test Suite (Normative)

A.1. Introduction

OGC Web APIs are not a Web Services in the traditional sense. Rather, they define the behavior and content of a set of Resources exposed through a Web Application Programming Interface (Web API). Therefore, an API may expose resources in addition to those defined by the standard. A test engine must be able to traverse the API, identify and validate test points, and ignore resource paths which are not to be tested.

A.2. Conformance Class Core

Conformance Class	
http://www.opengis.net/spec/ogcapi-common/1.0/conf/core	
Target type	Web API
Requirements Class	http://www.opengis.net/spec/ogcapi-common/1.0/req/core

A.2.1. General Tests

HTTP

Abstract Test 1	/ats/core/http
Test Purpose	Validate that the resource paths advertised through the API conform with HTTP 1.1 and, where appropriate, TLS.
Requirement	/req/core/http
Test Method	<ol style="list-style-type: none"> 1. All compliance tests shall be configured to use the HTTP 1.1 protocol exclusively. 2. For APIs which support HTTPS, all compliance tests shall be configured to use HTTP over TLS (RFC 2818) with their HTTP 1.1 protocol.

A.2.2. Landing Page {root}/

Abstract Test 2	/ats/core/root-op
Test Purpose	Validate that a landing page can be retrieved from the expected location.
Requirement	/req/core/root-op
Test Method	<ol style="list-style-type: none"> 1. Issue an HTTP GET request to the URL {root}/ 2. Validate that a document was returned with a status code 200 3. Validate the contents of the returned document using test /ats/core/root-success.

Abstract Test 3	/ats/core/root-success
Test Purpose	Validate that the landing page complies with the require structure and contents.
Requirement	/req/core/root-success
Test Method	<p>Validate the landing page for all supported media types using the resources and tests identified in Table 7</p> <p>For formats that require manual inspection, perform the following:</p> <ol style="list-style-type: none"> Validate that the landing page includes a "service-desc" and/or "service-doc" link to an API Definition Validate that the landing page includes a "conformance" link to the conformance class declaration Validate that the landing page includes a "data" link to the Feature contents.

The landing page may be retrieved in a number of different formats. The following table identifies the applicable schema document for each format and the test to be used to validate the landing page against that schema. All supported formats should be exercised.

Table 7. Schema and Tests for Landing Pages

Format	Schema Document	Test ID
HTML	landingPage.json	/ats/html/content
JSON	landingPage.json	/ats/geojson/content

A.2.3. API Definition Path {root}/api (link)

Abstract Test 4	/ats/core/api-definition-op
Test Purpose	Validate that the API Definition document can be retrieved from the expected location.
Requirement	/req/core/api-definition-op
Test Purpose	Validate that the API Definition document can be retrieved from the expected location.
Test Method	<ol style="list-style-type: none"> 1. Construct a path for each API Definition link on the landing page 2. Issue a HTTP GET request on each path 3. Validate that a document was returned with a status code 200 4. Validate the contents of the returned document using test /ats/core/api-definition-success.

Abstract Test 5	/ats/core/api-definition-success
Test Purpose	Validate that the API Definition complies with the required structure and contents.
Requirement	/req/core/api-definition-success
Test Method	Validate the API Definition document against an appropriate schema document.

A.2.4. Conformance Path {root}/conformance

Abstract Test 6	/ats/core/conformance-op
Test Purpose	Validate that a Conformance Declaration can be retrieved from the expected location.
Requirement	/req/core/conformance-op
Test Method	<ol style="list-style-type: none"> 1. Construct a path for each "conformance" link on the landing page as well as for the {root}/conformance path. 2. Issue an HTTP GET request on each path 3. Validate that a document was returned with a status code 200 4. Validate the contents of the returned document using test /ats/core/conformance-success.

Abstract Test 7	/ats/core/conformance-success
Test Purpose	Validate that the Conformance Declaration response complies with the required structure and contents.
Requirement	/req/core/conformance-success
Test Method	<ol style="list-style-type: none"> 1. Validate the response document against OpenAPI 3.0 schema confClasses.yaml 2. Validate that the document includes the conformance class "http://www.opengis.net/spec/ogcapi-features-1/1.0/conf/core" 3. Validate that the document list all OGC API conformance classes that the API implements.

A.3. Conformance Class Collections

Conformance Class	
http://www.opengis.net/spec/ogcapi-common/1.0/conf/collections	
Target type	Web API
Requirements Class	http://www.opengis.net/spec/ogcapi_common/1.0/req/collections
Dependency	Conformance Class "OAPI Core"

A.3.1. General Tests

Abstract Test 8	/ats/collections/crs84
Test Purpose	Validate that all spatial geometries provided through the API are in the CRS84 spatial reference system unless otherwise requested by the client.
Requirement	/req/collections/crs84
Test Method	<ol style="list-style-type: none"> 1. Do not specify a coordinate reference system in any request. All spatial data should be in the CRS84 reference system. 2. Validate retrieved spatial data using the CRS84 reference system.

A.3.2. Feature Collections **{root}/collections**

Abstract Test 9	/ats/collections/rc-md-op
Test Purpose	Validate that information about the Collections can be retrieved from the expected location.
Requirement	/req/collections/rc-md-op
Test Method	<ol style="list-style-type: none"> 1. Issue an HTTP GET request to the URL {root}/collections 2. Validate that a document was returned with a status code 200 3. Validate the contents of the returned document using test /ats/collections/rc-md-success.

Abstract Test 10	/ats/collections_rc-md-success
Test Purpose	Validate that the Collections content complies with the required structure and contents.
Requirement	/req/collections/rc-md-success , /req/collections/crs84
Test Method	<ol style="list-style-type: none"> 1. Validate that all response documents comply with /ats/collections/rc-md-links 2. In case the response includes a "crs" property, validate that the first value is either "http://www.opengis.net/def/crs/OGC/1.3/CRS84" or "http://www.opengis.net/def/crs/OGC/0/CRS84h" 3. Validate the collections content for all supported media types using the resources and tests identified in Table 8

The Collections content may be retrieved in a number of different formats. The following table identifies the applicable schema document for each format and the test to be used to validate the against that schema. All supported formats should be exercised.

Table 8. Schema and Tests for Collections content

Format	Schema Document	Test ID
HTML	collections.json	/ats/html/content
JSON	collections.json	/ats/geojson/content

A.3.3. Feature Collection {root}/collections/{collectionId}

Abstract Test 11	/ats/collections/src-md-op
Test Purpose	Validate that the Collection content can be retrieved from the expected location.
Requirement	/req/collections/src-md-op
Test Method	For every Feature Collection described in the Collections content, issue an HTTP GET request to the URL /collections/{collectionId} where {collectionId} is the id property for the collection. . Validate that a Collection was returned with a status code 200 . Validate the contents of the returned document using test /ats/collections/src-md-success .

Abstract Test 12	/ats/collections/src-md-success
Test Purpose	Validate that the Collection content complies with the required structure and contents.
Requirement	/req/collections/src-md-success
Test Method	Verify that the content of the response is consistent with the content for this Resource Collection in the <code>/collections</code> response. That is, the values for <code>id</code> , <code>title</code> , <code>description</code> and <code>extent</code> are identical.

A.3.4. Features `{root}/collections/{collectionId}/items`

NOTE | This test is too Feature centric. Will need to be greatly reduced in scope.

Abstract Test 13	/ats/collections/rc-op
Test Purpose	Validate that resources can be identified and extracted from a Collection using query parameters.
Requirement	/req/collections/rc-op
Test Method	<ol style="list-style-type: none"> 1. For every resource collection identified in Collections, issue an HTTP GET request to the URL <code>/collections/{collectionId}/items</code> where <code>{collectionId}</code> is the <code>id</code> property for a Collection described in the Collections content. 2. Validate that a document was returned with a status code 200. <p>Repeat these tests using the following parameter tests:</p> <p>Bounding Box:</p> <ul style="list-style-type: none"> • Parameter /ats/collections/rc-bbox-definition • Response /ats/collections/rc-bbox-response <p>DateTime:</p> <ul style="list-style-type: none"> • Parameter /ats/collections/rc-time-definition • Response /ats/collections/rc-time-response <p>Execute requests with combinations of the "bbox" and "datetime" query parameters and verify that only features are returned that match both selection criteria.</p>

Abstract Test 14	/ats/collections/rc-bbox-definition
Test Purpose	Validate that the bounding box query parameters are constructed correctly.
Requirement	/req/collections/rc-bbox-definition
Test Method	<p>Verify that the <code>bbox</code> query parameter complies with the following definition (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: bbox in: query required: false schema: type: array minItems: 4 maxItems: 6 items: type: number style: form explode: false </pre> <p>Use a bounding box with four numbers in all requests:</p> <ul style="list-style-type: none"> • Lower left corner, WGS 84 longitude • Lower left corner, WGS 84 latitude • Upper right corner, WGS 84 longitude • Upper right corner, WGS 84 latitude

Abstract Test 15	/ats/collections/rc-bbox-response
Test Purpose	Validate that the bounding box query parameters are processed correctly.
Requirement	/req/collections/rc-bbox-response
Test Method	<ol style="list-style-type: none"> 1. Verify that only resources that have a spatial geometry that intersects the bounding box are returned as part of the result set. 2. Verify that the <code>bbox</code> parameter matched all resources in the collection that were not associated with a spatial geometry (this is only applicable for datasets that include resources without a spatial geometry). 3. Verify that the coordinate reference system of the geometries is WGS 84 longitude/latitude ("http://www.opengis.net/def/crs/OGC/1.3/CRS84" or "http://www.opengis.net/def/crs/OGC/0/CRS84h") since no parameter <code>bbox-crs</code> was specified in the request.

Abstract Test 16	/ats/collections/rc-time-definition
Test Purpose	Validate that the dateTime query parameters are constructed correctly.
Requirement	/req/collections/rc-time-definition
Test Method	<p>Verify that the <code>datetime</code> query parameter complies with the following definition (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: datetime in: query required: false schema: type: string style: form explode: false </pre>

Abstract Test 17	/ats/collections/rc-time-response
Test Purpose	Validate that the dateTime query parameters are processed correctly.
Requirement	/req/collections/rc-time-response
Test Method	<ol style="list-style-type: none"> 1. Verify that only resources that have a temporal geometry that intersects the temporal information in the <code>datetime</code> parameter were included in the result set 2. Verify that all resources in the collection that are not associated with a temporal geometry are included in the result set 3. Validate that the datetime parameter complies with the syntax described in /req/collections/rc-time-response.

Abstract Test 18	/ats/collections/rc-response
Test Purpose	Validate that the Resource Collection complies with the require structure and contents.
Requirement	/req/collections/rc-response
Test Method	The test method is specific to the resource type returned.

A.3.5. Second Tier Tests

These tests are invoked by other tests.

Extent

Abstract Test 19	/ats/collections/rc-md-extent
Test Purpose	Validate that the <code>extent</code> property if it is present
Requirement	/req/collections/rc-md-extent
Test Method	<ol style="list-style-type: none"> 1. Verify that the <code>extent</code> provides bounding boxes that include all spatial geometries 2. Verify that if the <code>extent</code> provides time intervals that include all temporal geometries in this collection. 3. A temporal extent of <code>null</code> indicates an open time interval.

Items

Abstract Test 20	/ats/collections/rc-md-items
Test Purpose	Validate that each collection provided by the server is described in the Collections Metadata.
Requirement	/req/collections/rc-md-items
Test Method	<ol style="list-style-type: none">1. Verify that there is an entry in the <code>collections</code> array of the Collections Metadata for each feature collection provided by the API.2. Verify that each collection entry includes an identifier.3. Verify that each collection entry includes links in accordance with /collections/rc-md-items-links.4. Verify that if the collection entry includes an extent property, that that property complies with /collections/rc-md-extent5. Validate each collection entry for all supported media types using the resources and tests identified in Table 9

The collection entries may be encoded in a number of different formats. The following table identifies the applicable schema document for each format and the test to be used to validate the against that schema. All supported formats should be exercised.

Table 9. Schema and Tests for Collection Entries

Format	Schema Document	Test ID
HTML	collectionInfo.json	/ats/html/content
JSON	collectionInfo.json	/ats/geojson/content

Abstract Test 21	/ats/collections/rc-md-items-links
Test Purpose	Validate that each Feature Collection metadata entry in the Collections Metadata document includes all required links.
Requirement	/req/collections/rc-md-items-links
Test Method	<ol style="list-style-type: none"> 1. Verify that each Collection item in the Collections Metadata document includes a <code>link</code> property for each supported encoding. 2. Verify that the <code>links</code> properties of the collection includes an item for each supported encoding with a link to the features resource (relation: <code>items</code>). 3. Verify that all links include the <code>rel</code> and <code>type</code> link parameters.

Links

Abstract Test 22	/ats/collections/rc-md-links
Test Purpose	Validate that the required links are included in the Collections Metadata document.
Requirement	/req/collections/rc-md-links
Test Method	<p>Verify that the response document includes:</p> <ol style="list-style-type: none"> 1. a link to this response document (relation: <code>self</code>), 2. a link to the response document in every other media type supported by the server (relation: <code>alternate</code>). <p>Verify that all links include the <code>rel</code> and <code>type</code> link parameters.</p>

A.4. Conformance Class GeoJSON

Conformance Class	
http://www.opengis.net/spec/ogcapi-common/1.0/conf/geojson	
Target type	Web API
Requirements Class	http://www.opengis.net/spec/ogcapi-common/1.0/req/geojson
Dependency	Conformance Class "OAPI Core"

A.4.1. GeoJSON Definition

Abstract Test 23	/ats/geojson/definition
Test Purpose	Verify support for JSON and GeoJSON
Requirement	/req/geojson/definition
Test Method	<ol style="list-style-type: none"> 1. A resource is requested with response media type of <code>application/geo+json</code> 2. All 200-responses SHALL support the following media types: <ul style="list-style-type: none"> ◦ <code>application/geo+json</code> for resources that include feature content, and ◦ <code>application/json</code> for all other resources.

A.4.2. GeoJSON Content

Abstract Test 24	/ats/geojson/content
Test Purpose	Verify the content of a GeoJSON document given an input document and schema.
Requirement	/req/geojson/content
Test Method	<ol style="list-style-type: none"> 1. Validate that the document is a GeoJSON document. 2. Validate the document against the schema using an JSON Schema validator.

A.5. Conformance Class HTML

Conformance Class	
http://www.opengis.net/spec/ogcapi-common/1.0/conf/html	
Target type	Web API
Requirements Class	http://www.opengis.net/spec/ogcapi_common/1.0/req/html
Dependency	Conformance Class "OAPI Core"

A.5.1. HTML Definition

Abstract Test 25	/ats/html/definition
Test Purpose	Verify support for HTML
Requirement	/req/html/definition
Test Method	Verify that every 200 -response of every operation of the API where HTML was requested is of media type <code>text/html</code>

A.5.2. HTML Content

Abstract Test 26	/ats/html/content
Test Purpose	Verify the content of an HTML document given an input document and schema.
Requirement	/req/html/content
Test Method	<ol style="list-style-type: none"> 1. Validate that the document is an HTML 5 document 2. Manually inspect the document against the schema.

A.6. Conformance Class OpenAPI 3.0

Conformance Class	
http://www.opengis.net/spec/ogcapi-common/1.0/conf/oas3	
Target type	Web API
Requirements Class	http://www.opengis.net/spec/ogcapi_common/1.0/req/oas3
Dependency	Conformance Class "OAPI Core"

Abstract Test 27	/ats/oas30/completeness
Test Purpose	Verify the completeness of an OpenAPI document.
Requirement	/req/oas30/completeness
Test Method	Verify that for each operation, the OpenAPI document describes all HTTP Status Codes and Response Objects that the API uses in responses.

Abstract Test 28	/ats/oas30/exceptions-codes
Test Purpose	Verify that the OpenAPI document fully describes potential exception codes.
Requirement	/req/oas30/exceptions-codes
Test Method	Verify that for each operation, the OpenAPI document describes all HTTP Status Codes that may be generated.

Abstract Test 29	/ats/oas30/oas-definition-1
Test Purpose	Verify that JSON and HTML versions of the OpenAPI document are available.
Requirement	/req/oas30/oas-definition-1
Test Method	<ol style="list-style-type: none"> 1. Verify that an OpenAPI definition in JSON is available using the media type <code>application/vnd.oai.openapi+json;version=3.0</code> and link relation <code>service-desc</code> 2. Verify that an HTML version of the API definition is available using the media type <code>text/html</code> and link relation <code>service-doc</code>.

Abstract Test 30	/ats/oas30/oas-definition-2
Test Purpose	Verify that the OpenAPI document is valid JSON.
Requirement	/req/oas30/oas-definition-2
Test Method	Verify that the JSON representation conforms to the OpenAPI Specification, version 3.0 .

Abstract Test 31	/ats/oas30/oas-impl
Test Purpose	Verify that all capabilities specified in the OpenAPI definition are implemented by the API.
Requirement	/req/oas30/oas-impl
Test Method	<ol style="list-style-type: none"> 1. Construct a path from each URL template including all server URL options and all enumerated path parameters. 2. For each path defined in the OpenAPI document, validate that the path performs in accordance with the API definition and the API-Features standard.

Abstract Test 32	/ats/oas30/security
Test Purpose	Verify that any authentication protocols implemented by the API are documented in the OpenAPI document.
Requirement	/req/oas30/security
Test Method	<ol style="list-style-type: none"> 1. Identify all authentication protocols supported by the API. 2. Validate that each authentication protocol is described in the OpenAPI document by a Security Schema Object and its' use specified by a Security Requirement Object.

Annex B: Examples (Informative)

B.1. Example Landing Pages

Example 21. JSON Landing Page

```
{
  "links": [
    { "href": "http://data.example.org/",
      "rel": "self", "type": "application/json", "title": "this document" },
    { "href": "http://data.example.org/api",
      "rel": "service", "type": "application/openapi+json;version=3.0", "title":
        "the API definition" },
    { "href": "http://data.example.org/conformance",
      "rel": "conformance", "type": "application/json", "title": "OGC conformance
        classes implemented by this API" },
    { "href": "http://data.example.org/collections",
      "rel": "data", "type": "application/json", "title": "Metadata about the
        resource collections" }
  ]
}
```

B.2. API Description Examples

NOTE | include::examples/tbd.adoc[]

B.3. Conformance Examples

Example 22. Conformance Response

This example response in JSON is for an OGC API Features that supports OpenAPI 3.0 for the API definition and HTML and GeoJSON as encodings for resources.

```
{
  "conformsTo": [
    "http://www.opengis.net/spec/ogcapi-features-1/1.0/req/core",
    "http://www.opengis.net/spec/ogcapi-features-1/1.0/req/oas30",
    "http://www.opengis.net/spec/ogcapi-features-1/1.0/req/html",
    "http://www.opengis.net/spec/ogcapi-features-1/1.0/req/geojson"
  ]
}
```

B.4. Collections Metadata Examples

Example 23. Collection metadata response document

This collection metadata example response in JSON is for a service with collections "Metar", "GFS height above ground parameters" and "DEM". It includes links to the collection resource in all formats that are supported by the API ([link relation type](#): "items").

There is a link to the feature collections response itself ([link relation type](#): "self").

Representations of this resource in other formats are referenced using [link relation type](#) "alternate".

An additional link is to a GML application schema for the dataset - using: <https://www.iana.org/assignments/link-relations/link-relations.xhtml>[link relation type] "describedBy".

A bulk download of all the features in the dataset is referenced using [link relation type](#) "enclosure"

Finally there are also links to the license information for the building data (using: <https://www.iana.org/assignments/link-relations/link-relations.xhtml>[link relation type] "license").

Reference system information is not provided as the service provides geometries only in the default system (spatial: WGS 84 longitude/latitude; temporal: Gregorian calendar).

```

{
  "links": [
    { "href": "http://data.example.org/collections.json",
      "rel": "self", "type": "application/json", "title": "this document" },
    { "href": "http://data.example.org/collections.html",
      "rel": "alternate", "type": "text/html", "title": "this document as HTML" },
    { "href": "http://schemas.example.org/1.0/foobar.xsd",
      "rel": "describedBy", "type": "application/xml", "title": "XML schema for
Acme Corporation data" }
  ],
  "collections": [
    {
      "id": "metar",
      "title": "Metars",
      "description": "Metar observations",
      "extent": {
        "spatial": [ -180.0, -89.9, 180, 89.9 ],
        "temporal": [ "2020-01-30T12:00:00Z/2020-01-13T11:00:00Z" ]
      },
      "dataDetails": {
        "@context": {
          "@version": 1.1,
          "xsd": "http://www.w3.org/2001/XMLSchema#",
          "dc": "http://purl.org/dc/terms/",
          "dcam": "http://purl.org/dc/dcam/"
        },
        "dc:accessRights": {
          },
        "dc:source": {
          "dc:title": "datasource name",
          "dc:identifier" : "https://data.example.org/collection/metar/link-
for-more-details"
        },
        "dc:publisher" : "contact@example.org",
        "dcam:domainIncludes":
["temperature","wind_speed","wind_direction","maximum_wind_gust_speed","speci_visi-
bility","pressure","pressure_msl","raw_observation","id"]
      },
      "supportedQueryTypes": {"point"}
    },
    "links": [
      { "href": "http://data.example.org/collections/metars",
        "rel": "instances", "type": "application/json",
        "title": "Instances of the Metar collection" },
      { "href": "http://data.example.org/collections/metars?outputFormat=html",
        "rel": "instances", "type": "text/html",
        "title": "Instances of the Metar collection" }
      { "href": "https://data.example.org/collection/metar/licence-doc",
        "rel": "licence", "type": "text/html",
        "title": "Licence for the Metar collection" }
    ]
  ]
}

```

```

},
{
  "id": "gfs_time-height_above_ground-lat-lon",
  "title": "GFS time, height_above_ground lat-lon",
  "description": "GFS parameters based on heights above ground level",
  "extent": {
    "spatial": [ -180.0, -89.9, 180, 89.9 ],
    "temporal": [ "2020-02-01T00:00:00Z/2020-02-12T00:00:00Z" ],
    "vertical": [ "2.0", "10.0", "80.0" ]
  },
  "dataDetails": {
    "@context": {
      "@version": 1.1,
      "xsd": "http://www.w3.org/2001/XMLSchema#",
      "dc": "http://purl.org/dc/terms/",
      "dcam": "http://purl.org/dc/dcam/"
    },
    "dc:accessRights": {},
    "dc:source": {
      "dc:title": "datasource name",
      "dc:identifier" : "https://data.example.org/collection/gfs_time-
height_above_ground-lat-lon/link-for-more-details"
    },
    "dc:publisher" : "contact@example.org",
    "dcam:domainIncludes":
["apparent_temperature_height_above_ground", "dewpoint_temperature_height_above_gr
ound", "relative_humidity_height_above_ground"]

  },
  "supportedQueryTypes": {"point", "polygon", "cube", "trajectory"}
  "links": [
    { "href": "http://data.example.org/collections/gfs_time-
height_above_ground-lat-lon",
      "rel": "instances", "type": "application/json",
      "title": "Instances of the gfs_time-height_above_ground-lat-lon
collection" },
    { "href": "http://data.example.org/collections/gfs_time-
height_above_ground-lat-lon?outputFormat=html",
      "rel": "instances", "type": "text/html",
      "title": "Instances of the gfs_time-height_above_ground-lat-lon
collection" },
    { "href": "https://data.example.org/collection/gfs_time-
height_above_ground-lat-lon/licence-doc",
      "rel": "licence", "type": "text/html",
      "title": "Licence for the gfs_time-height_above_ground-lat-lon
collection" }
  ]
},
{
  "id": "dem",
  "title": "DEM",
  "description": "Global Digital Elevation Model height data",
  "extent": {
    "spatial": [ -180.0, -89.9, 180, 89.9 ]
  }
}

```

```

    },
    "dataDetails": {
      "@context": {
        "@version": 1.1,
        "xsd": "http://www.w3.org/2001/XMLSchema#",
        "dc": "http://purl.org/dc/terms/",
        "dcam": "http://purl.org/dc/dcam/"
      },
      "dc:accessRights": {},
      "dc:source": {
        "dc:title": "datasource name",
        "dc:identifier" : "https://data.example.org/collection/dem/link-for-
more-details"
      },
      "dc:publisher" : "contact@example.org",
      "dcam:domainIncludes": ["height"]
    },
    "supportedQueryTypes": {"point", "polygon", "trajectory"}
    "links": [
      { "href": "http://data.example.org/collections/dem",
        "rel": "instances", "type": "application/json",
        "title": "Instances of the dem collection" },
      { "href": "http://data.example.org/collections/dem?outputFormat=html",
        "rel": "instances", "type": "text/html",
        "title": "Instances of the dem collection" },
      { "href": "https://data.example.org/collection/dem/licence-doc",
        "rel": "licence", "type": "text/html",
        "title": "Licence for the dem collection" }
    ]
  }
}

```

B.5. Collection Instance Metadata Examples

Example 24. Collection instance metadata response document

This collection metadata example response in JSON lists the available instances for the `gfs_time-height_above_ground-lat-lon` gfs collection. It includes links to the collection resource in all formats that are supported by the API ([link relation type](#): "items").

There is a link to the feature collections response itself ([link relation type](#): "self").

Representations of this resource in other formats are referenced using [link relation type](#) "alternate".

An additional link is to a GML application schema for the dataset - `using:https://www.iana.org/assignments/link-relations/link-relations.xhtml` [[link relation type](#) "describedBy"].

A bulk download of all the features in the dataset is referenced using [link relation type](#) "enclosure"

Finally there are also links to the license information for the building data (using: <https://www.iana.org/assignments/link-relations/link-relations.xhtml> [link relation type] "license").

Reference system information is not provided as the service provides geometries only in the default system (spatial: WGS 84 longitude/latitude; temporal: Gregorian calendar).

```

{
  "links": [
    { "href": "http://data.example.org/collections.json",
      "rel": "self", "type": "application/json", "title": "this document" },
    { "href": "http://data.example.org/collections.html",
      "rel": "alternate", "type": "text/html", "title": "this document as HTML" },
    { "href": "http://schemas.example.org/1.0/foobar.xsd",
      "rel": "describedBy", "type": "application/xml", "title": "XML schema for
Acme Corporation data" }
  ],
  "instances": [
    {
      "id": "latest",
      "title": "Latest",
      "description": "GFS parameters based on heights above ground level from the
latest model run",
      "extent": {
        "spatial": [ -180.0, -89.9, 180, 89.9 ],
        "temporal": [ "2020-02-01T12:00:00Z/2020-02-12T00:00:00Z" ],
        "vertical": ["2.0","10.0","80.0"]
      },
      "dataDetails": {
        "@context": {
          "@version": 1.1,
          "xsd": "http://www.w3.org/2001/XMLSchema#",
          "dc": "http://purl.org/dc/terms/",
          "dcam": "http://purl.org/dc/dcam/"
        },
        "dc:accessRights": {},
        "dc:source": {
          "dc:title": "datasource name",
          "dc:identifier" : "https://data.example.org/collection/gfs_time-
height_above_ground-lat-lon/link-for-more-details"
        },
        "dc:publisher" : "contact@example.org",
        "dcam:domainIncludes":
["apparent_temperature_height_above_ground","dewpoint_temperature_height_above_g-
round","relative_humidity_height_above_ground"]
      },
      "itemType": "Grid",
      "supportedQueryTypes": {"point","polygon","cube","trajectory"},
      "links": [
        { "href": "http://data.example.org/collections/gfs_time-
height_above_ground-lat-lon/latest",
          "rel": "metadata", "type": "application/json",
          "title": "Metadata for the latest run" },
        { "href": "http://data.example.org/collections/gfs_time-
height_above_ground-lat-lon/latest?outputFormat=html",
          "rel": "metadata", "type": "text/html",
          "title": "Metadata for the latest run" },
        { "href": "https://data.example.org/collection/gfs_time-
height_above_ground-lat-lon/licence-doc",

```



```

"rel": "licence", "type": "text/html",
  "title": "Licence for the latest run" }
]
},
{
  "id": "2020-02-01T12:00:00Z",
  "title": "2020-02-01T12:00:00Z",
  "description": "GFS parameters based on heights above ground level from the
2020-02-01T12:00:00Z run",
  "extent": {
    "spatial": [ -180.0, -89.9, 180, 89.9 ],
    "temporal": [ "2020-02-01T12:00:00Z/2020-02-12T00:00:00Z" ],
    "vertical": ["2.0","10.0","80.0"]
  },
  "dataDetails": {
    "@context": {
      "@version": 1.1,
      "xsd": "http://www.w3.org/2001/XMLSchema#",
      "dc": "http://purl.org/dc/terms/",
      "dcam": "http://purl.org/dc/dcam/"
    },
    "dc:accessRights": {},
    "dc:source": {
      "dc:title": "datasource name",
      "dc:identifier" : "https://data.example.org/collection/gfs_time-
height_above_ground-lat-lon/link-for-more-details"
    },
    "dc:publisher" : "contact@example.org",
    "dcam:domainIncludes":
["apparent_temperature_height_above_ground","dewpoint_temperature_height_above_gr
ound","relative_humidity_height_above_ground"]

  },
  "supportedQueryTypes": {"point","polygon","cube","trajectory"}
  "links": [
    { "href": "http://data.example.org/collections/gfs_time-
height_above_ground-lat-lon/2020-02-01T12:00:00Z",
      "rel": "Metadata", "type": "application/json",
      "title": "Metadata for the 2020-02-01T12:00:00Z run" },
    { "href": "http://data.example.org/collections/gfs_time-
height_above_ground-lat-lon/2020-02-01T12:00:00Z?outputFormat=html",
      "rel": "instances", "type": "text/html",
      "title": "Metadata for the 2020-02-01T12:00:00Z run" },
    { "href": "https://data.example.org/collection/gfs_time-
height_above_ground-lat-lon/licence-doc",
      "rel": "licence", "type": "text/html",
      "title": "Licence for the 2020-02-01T12:00:00Z run" }
  ]
},
{
  "id": "2020-02-01T00:00:00Z",
  "title": "2020-02-01T00:00:00Z",
  "description": "GFS parameters based on heights above ground level from the
2020-02-01T00:00:00Z run",
  "extent": {

```

```

"spatial": [ -180.0, -89.9, 180, 89.9 ],
"temporal": [ "2020-02-01T00:00:00Z/2020-02-11T12:00:00Z" ],
"vertical": ["2.0","10.0","80.0"]
},
"dataDetails": {
  "@context": {
    "@version": 1.1,
    "xsd": "http://www.w3.org/2001/XMLSchema#",
    "dc": "http://purl.org/dc/terms/",
    "dcam": "http://purl.org/dc/dcam/"
  },

  "dc:accessRights": {},
  "dc:source": {
    "dc:title": "datasource name",
    "dc:identifier" : "https://data.example.org/collection/gfs_time-
height_above_ground-lat-lon/link-for-more-details"
  },
  "dc:publisher" : "contact@example.org",
  "dcam:domainIncludes":
["apparent_temperature_height_above_ground","dewpoint_temperature_height_above_gr
ound","relative_humidity_height_above_ground"]

},
"supportedQueryTypes": {"point","polygon","cube","trajectory"}
"links": [
  { "href": "http://data.example.org/collections/gfs_time-
height_above_ground-lat-lon/2020-02-01T00:00:00Z",
    "rel": "instances", "type": "application/json",
    "title": "Metadata for the 2020-02-01T00:00:00Z run" },
  { "href": "http://data.example.org/collections/gfs_time-
height_above_ground-lat-lon/2020-02-01T00:00:00Z?outputFormat=html",
    "rel": "instances", "type": "text/html",
    "title": "Metadata for the 2020-02-01T00:00:00Z run" },
  { "href": "https://data.example.org/collection/gfs_time-
height_above_ground-lat-lon/licence-doc",
    "rel": "licence", "type": "text/html",
    "title": "Licence for the 2020-02-01T00:00:00Z run" }
]
}
]
}

```

Example 25. Collection instance metadata response document

This collection metadata example response in JSON lists the available instances for the Metar collection. It includes links to the collection resource in all formats that are supported by the API ([link relation type](#): "items").

There is a link to the feature collections response itself ([link relation type](#): "self").

Representations of this resource in other formats are referenced using [link relation type](#) "alternate".

An additional link is to a GML application schema for the dataset - using: <https://www.iana.org/assignments/link-relations/link-relations.xhtml>[link relation type] "describedBy".

A bulk download of all the features in the dataset is referenced using [link relation type](#) "enclosure"

Finally there are also links to the license information for the building data (using: <https://www.iana.org/assignments/link-relations/link-relations.xhtml>[link relation type] "license").

Reference system information is not provided as the service provides geometries only in the default system (spatial: WGS 84 longitude/latitude; temporal: Gregorian calendar).

```

{
  "links": [
    { "href": "http://data.example.org/collections.json",
      "rel": "self", "type": "application/json", "title": "this document" },
    { "href": "http://data.example.org/collections.html",
      "rel": "alternate", "type": "text/html", "title": "this document as HTML" },
    { "href": "http://schemas.example.org/1.0/foobar.xsd",
      "rel": "describedBy", "type": "application/xml", "title": "XML schema for
Acme Corporation data" }
  ],
  "instances": [
    {
      "id": "raw",
      "title": "Raw",
      "description": "Raw Metar observations",
      "extent": {
        "spatial": [ -180.0, -89.9, 180, 89.9 ],
        "temporal": [ "2020-01-30T12:00:00Z/2020-01-13T11:00:00Z" ]
      },
      "dataDetails": {
        "@context": {
          "@version": 1.1,
          "xsd": "http://www.w3.org/2001/XMLSchema#",
          "dc": "http://purl.org/dc/terms/",
          "dcam": "http://purl.org/dc/dcam/"
        },
        "dc:accessRights": {},
        "dc:source": {
          "dc:title": "datasource name",
          "dc:identifier" : "https://data.example.org/collection/metar/link-
for-more-details"
        },
        "dc:publisher" : "contact@example.org",
        "dcam:domainIncludes":
["temperature","wind_speed","wind_direction","maximum_wind_gust_speed","speci_visi
bility","pressure","pressure_msl","raw_observation","id"]

      },
      "supportedQueryTypes": {"point"}
      "links": [
        { "href": "http://data.example.org/collections/metars/raw",
          "rel": "metadata", "type": "application/json",
          "title": "Metadata for Raw Metar data" },
          { "href": "http://data.example.org/collections/metars/raw?
outputFormat=html",
            "rel": "instances", "type": "text/html",
            "title": "Metadata for Raw Metar data" },
        { "href": "https://data.example.org/collection/metar/licence-doc",
          "rel": "licence", "type": "text/html",
          "title": "Licence for Raw Metar data" }
      ]
    },
    {

```

```

    "id": "initial_qc",
    "title": "Intial QC",
    "description": "First pass of Quality Control processed Metar observations",
    "extent": {
      "spatial": [ -180.0, -89.9, 180, 89.9 ],
      "temporal": [ "2020-01-30T12:00:00Z/2020-01-13T11:00:00Z" ]
    },
    "dataDetails": {
      "@context": {
        "@version": 1.1,
        "xsd": "http://www.w3.org/2001/XMLSchema#",
        "dc": "http://purl.org/dc/terms/",
        "dcam": "http://purl.org/dc/dcam/"
      },
      "dc:accessRights": {},
      "dc:license": "https://data.example.org/collection/metar/licence-doc",
      "dc:source": {
        "dc:title": "datasource name",
        "dc:identifier" : "https://data.example.org/collection/metar/link-
for-more-details"
      },
      "dc:publisher" : "contact@example.org",
      "dcam:domainIncludes":
["temperature", "wind_speed", "wind_direction", "maximum_wind_gust_speed", "speci_visi
bility", "pressure", "pressure_msl", "raw_observation", "id"]

    },
    "itemType": "PointSeries",
    "supportedQueryTypes": {"point"},
    "links": [
      { "href": "http://data.example.org/collections/metars/initial_qc",
        "rel": "metadata", "type": "application/json",
        "title": "Metadata for QC'd Metar data" },
      { "href": "http://data.example.org/collections/metars/initial_qc?
outputFormat=html",
        "rel": "instances", "type": "text/html",
        "title": "Metadata for Qc'd Metar data" }
    ]
  }
]
}

```

Example 26. Collection metadata response document

This collection metadata example response in JSON lists the available instances of the DEM collection. It includes links to the collection resource in all formats that are supported by the API ([link relation type](#): "items").

There is a link to the feature collections response itself ([link relation type](#): "self").

Representations of this resource in other formats are referenced using [link relation type](#) "alternate".

An additional link is to a GML application schema for the dataset - using: <https://www.iana.org/assignments/link-relations/link-relations.xhtml> [link relation type] "describedBy".

A bulk download of all the features in the dataset is referenced using [link relation type](#) "enclosure"

Finally there are also links to the license information for the building data (using: <https://www.iana.org/assignments/link-relations/link-relations.xhtml> [link relation type] "license").

Reference system information is not provided as the service provides geometries only in the default system (spatial: WGS 84 longitude/latitude; temporal: Gregorian calendar).

```

{
  "links": [
    { "href": "http://data.example.org/collections.json",
      "rel": "self", "type": "application/json", "title": "this document" },
    { "href": "http://data.example.org/collections.html",
      "rel": "alternate", "type": "text/html", "title": "this document as HTML" },
    { "href": "http://schemas.example.org/1.0/foobar.xsd",
      "rel": "describedBy", "type": "application/xml", "title": "XML schema for
Acme Corporation data" }
  ],
  "instances": [
    {
      "id": "data",
      "title": "data",
      "description": "Global Digital Elevation Model height data",
      "extent": {
        "spatial": [ -180.0, -89.9, 180, 89.9 ]
      },
      "dataDetails": {
        "@context": {
          "@version": 1.1,
          "xsd": "http://www.w3.org/2001/XMLSchema#",
          "dc": "http://purl.org/dc/terms/",
          "dcam": "http://purl.org/dc/dcam/"
        },

        "dc:accessRights": {},
        "dc:source": {
          "dc:title": "datasource name",
          "dc:identifier" : "https://data.example.org/collection/dem/link-for-
more-details"
        },
        "dc:publisher" : "contact@example.org",
        "dcam:domainIncludes": ["height"]
      },

      "itemType": "Grid",
      "supportedQueryTypes": {"point", "polygon", "trajectory"},
      "links": [
        { "href": "http://data.example.org/collections/dem/data",
          "rel": "metadata", "type": "application/json",
          "title": "Metadata for the dem collection" },
          { "href": "http://data.example.org/collections/dem/data?
outputFormat=html",
            "rel": "metadata", "type": "text/html",
            "title": "Metadata for the dem collection" },
        { "href": "https://data.example.org/collection/dem/licence-doc",
          "rel": "licence", "type": "text/html",
          "title": "Licence for the dem collection" }
      ]
    }
  ]
}

```

B.6. Collection Query Metadata Examples

Example 27. Collection instance metadata response document

This metadata example response in JSON is for a the latest instance of the fs_time-height_above_ground-lat-lon collection. It includes links to the collection resource in all formats that are supported by the API ([link relation type: "items"](#)).

There is a link to the feature collections response itself ([link relation type: "self"](#)).

Representations of this resource in other formats are referenced using [link relation type "alternate"](#).

An additional link is to a GML application schema for the dataset - using: <https://www.iana.org/assignments/link-relations/link-relations.xhtml> [[link relation type "describedBy"](#)].

A bulk download of all the features in the dataset is referenced using [link relation type "enclosure"](#)

Finally there are also links to the license information for the building data (using: <https://www.iana.org/assignments/link-relations/link-relations.xhtml> [[link relation type "license"](#)]).

Reference system information is not provided as the service provides geometries only in the default system (spatial: WGS 84 longitude/latitude; temporal: Gregorian calendar).


```

{
  "links": [
    {
      "href": "http://data.example.org/collections/gfs_025_time-
height_above_ground-lat-lon/latest?outputFormat=application%2Fjson",
      "rel": "self",
      "type": "application/json",
      "title": "latest document as json"
    },
    {
      "href": "http://data.example.org/collections/gfs_025_time-
height_above_ground-lat-lon/latest?outputFormat=application%2Fyaml",
      "rel": "alternate",
      "type": "application/x-yaml",
      "title": "latest document as yaml"
    },
    {
      "href": "http://data.example.org/collections/gfs_025_time-
height_above_ground-lat-lon/latest?outputFormat=text%2Fxml",
      "rel": "alternate",
      "type": "text/xml",
      "title": "latest document as xml"
    },
    {
      "href": "http://data.example.org/collections/gfs_025_time-
height_above_ground-lat-lon/latest?outputFormat=text%2Fhtml",
      "rel": "alternate",
      "type": "text/html",
      "title": "latest document as html"
    },
    {
      "href": "http://data.example.org/collections/gfs_025_time-
height_above_ground-lat-lon/latest/point",
      "rel": "self",
      "type": "point",
      "title": "Point query",
      "self": "Point"
    },
    {
      "href": "http://data.example.org/collections/gfs_025_time-
height_above_ground-lat-lon/latest/polygon",
      "rel": "self",
      "type": "polygon",
      "title": "Polygon query",
      "self": "Polygon"
    }
  ],
  "id": "gfs_time-height_above_ground-lat-lon-latest",
  "title": "Latest Global Forecast System (GFS) time height_above_ground lat lon",
  "description": "Lates Global Forecast System (GFS) Model Global 0.25 degree Data
time height_above_ground lat lon",
  "parameters": {
    "Apparent_temperature_height_above_ground": {
      "description": {
        "en": "Apparent_temperature_height_above_ground"
      }
    }
  },

```

```

"unit": {
  "label": {
    "en": "kelvin"
  },
  "symbol": {
    "value": "K",
    "type": "http://data.example.org/metadata/uom/UCUM/K"
  }
},
"observedProperty": {
  "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-21",
  "label": {
    "en": "Apparent_temperature_height_above_ground"
  }
},
"measurementType": {
  "method": "instantaneous"
},
"extent": {
  "horizontal": {
    "name": [
      "longitude",
      "latitude"
    ],
    "coordinates": [
      "x",
      "y"
    ],
    "geographic": "BBOX[359.875,90.125,-0.125,-90.125]"
  },
  "vertical": {
    "name": [
      "height_above_ground"
    ],
    "coordinates": [
      "z"
    ],
    "range": [
      "2.0"
    ]
  },
  "temporal": {
    "name": [
      "time"
    ],
    "coordinates": [
      "time"
    ],
    "range": [
      "2020-02-02T00:00:00Z",
      "2020-02-02T03:00:00Z",
      "2020-02-02T06:00:00Z",
      "2020-02-02T09:00:00Z",
      "2020-02-02T12:00:00Z",
      "2020-02-02T15:00:00Z",
      "2020-02-02T18:00:00Z",

```

"2020-02-02T21:00:00Z",
"2020-02-03T00:00:00Z",
"2020-02-03T03:00:00Z",
"2020-02-03T06:00:00Z",
"2020-02-03T09:00:00Z",
"2020-02-03T12:00:00Z",
"2020-02-03T15:00:00Z",
"2020-02-03T18:00:00Z",
"2020-02-03T21:00:00Z",
"2020-02-04T00:00:00Z",
"2020-02-04T03:00:00Z",
"2020-02-04T06:00:00Z",
"2020-02-04T09:00:00Z",
"2020-02-04T12:00:00Z",
"2020-02-04T15:00:00Z",
"2020-02-04T18:00:00Z",
"2020-02-04T21:00:00Z",
"2020-02-05T00:00:00Z",
"2020-02-05T03:00:00Z",
"2020-02-05T06:00:00Z",
"2020-02-05T09:00:00Z",
"2020-02-05T12:00:00Z",
"2020-02-05T15:00:00Z",
"2020-02-05T18:00:00Z",
"2020-02-05T21:00:00Z",
"2020-02-06T00:00:00Z",
"2020-02-06T03:00:00Z",
"2020-02-06T06:00:00Z",
"2020-02-06T09:00:00Z",
"2020-02-06T12:00:00Z",
"2020-02-06T15:00:00Z",
"2020-02-06T18:00:00Z",
"2020-02-06T21:00:00Z",
"2020-02-07T00:00:00Z",
"2020-02-07T03:00:00Z",
"2020-02-07T06:00:00Z",
"2020-02-07T09:00:00Z",
"2020-02-07T12:00:00Z",
"2020-02-07T15:00:00Z",
"2020-02-07T18:00:00Z",
"2020-02-07T21:00:00Z",
"2020-02-08T00:00:00Z",
"2020-02-08T03:00:00Z",
"2020-02-08T06:00:00Z",
"2020-02-08T09:00:00Z",
"2020-02-08T12:00:00Z",
"2020-02-08T15:00:00Z",
"2020-02-08T18:00:00Z",
"2020-02-08T21:00:00Z",
"2020-02-09T00:00:00Z",
"2020-02-09T03:00:00Z",
"2020-02-09T06:00:00Z",
"2020-02-09T09:00:00Z",
"2020-02-09T12:00:00Z",
"2020-02-09T15:00:00Z",
"2020-02-09T18:00:00Z",
"2020-02-09T21:00:00Z",

```

"2020-02-10T00:00:00Z",
    "2020-02-10T03:00:00Z",
    "2020-02-10T06:00:00Z",
    "2020-02-10T09:00:00Z",
    "2020-02-10T12:00:00Z",
    "2020-02-10T15:00:00Z",
    "2020-02-10T18:00:00Z",
    "2020-02-10T21:00:00Z",
    "2020-02-11T00:00:00Z",
    "2020-02-11T03:00:00Z",
    "2020-02-11T06:00:00Z",
    "2020-02-11T09:00:00Z",
    "2020-02-11T12:00:00Z",
    "2020-02-11T15:00:00Z",
    "2020-02-11T18:00:00Z",
    "2020-02-11T21:00:00Z",
    "2020-02-12T00:00:00Z",
    "2020-02-12T12:00:00Z",
    "2020-02-13T00:00:00Z",
    "2020-02-13T12:00:00Z",
    "2020-02-14T00:00:00Z",
    "2020-02-14T12:00:00Z",
    "2020-02-15T00:00:00Z",
    "2020-02-15T12:00:00Z",
    "2020-02-16T00:00:00Z",
    "2020-02-16T12:00:00Z",
    "2020-02-17T00:00:00Z",
    "2020-02-17T12:00:00Z",
    "2020-02-18T00:00:00Z"
  ]
}
}
},
"Dewpoint_temperature_height_above_ground": {
  "description": {
    "en": "Dewpoint_temperature_height_above_ground"
  },
  "unit": {
    "label": {
      "en": "kelvin"
    },
    "symbol": {
      "value": "K",
      "type": "http://data.example.org/metadata/uom/UCUM/K"
    }
  },
  "observedProperty": {
    "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-6",
    "label": {
      "en": "Dewpoint_temperature_height_above_ground"
    }
  },
  "measurementType": {
    "method": "instantaneous"
  },
  "extent": {

```

```

"horizontal": {
  "name": [
    "longitude",
    "latutude"
  ],
  "coordinates": [
    "x",
    "y"
  ],
  "geographic": "BB0X[359.875,90.125,-0.125,-90.125]"
},
"vertical": {
  "name": [
    "height_above_ground"
  ],
  "coordinates": [
    "z"
  ],
  "range": [
    "2.0"
  ]
},
"temporal": {
  "name": [
    "time"
  ],
  "coordinates": [
    "time"
  ],
  "range": [
    "2020-02-02T00:00:00Z",
    "2020-02-02T03:00:00Z",
    "2020-02-02T06:00:00Z",
    "2020-02-02T09:00:00Z",
    "2020-02-02T12:00:00Z",
    "2020-02-02T15:00:00Z",
    "2020-02-02T18:00:00Z",
    "2020-02-02T21:00:00Z",
    "2020-02-03T00:00:00Z",
    "2020-02-03T03:00:00Z",
    "2020-02-03T06:00:00Z",
    "2020-02-03T09:00:00Z",
    "2020-02-03T12:00:00Z",
    "2020-02-03T15:00:00Z",
    "2020-02-03T18:00:00Z",
    "2020-02-03T21:00:00Z",
    "2020-02-04T00:00:00Z",
    "2020-02-04T03:00:00Z",
    "2020-02-04T06:00:00Z",
    "2020-02-04T09:00:00Z",
    "2020-02-04T12:00:00Z",
    "2020-02-04T15:00:00Z",
    "2020-02-04T18:00:00Z",
    "2020-02-04T21:00:00Z",
    "2020-02-05T00:00:00Z",
    "2020-02-05T03:00:00Z",
    "2020-02-05T06:00:00Z",

```

"2020-02-05T09:00:00Z",
"2020-02-05T12:00:00Z",
"2020-02-05T15:00:00Z",
"2020-02-05T18:00:00Z",
"2020-02-05T21:00:00Z",
"2020-02-06T00:00:00Z",
"2020-02-06T03:00:00Z",
"2020-02-06T06:00:00Z",
"2020-02-06T09:00:00Z",
"2020-02-06T12:00:00Z",
"2020-02-06T15:00:00Z",
"2020-02-06T18:00:00Z",
"2020-02-06T21:00:00Z",
"2020-02-07T00:00:00Z",
"2020-02-07T03:00:00Z",
"2020-02-07T06:00:00Z",
"2020-02-07T09:00:00Z",
"2020-02-07T12:00:00Z",
"2020-02-07T15:00:00Z",
"2020-02-07T18:00:00Z",
"2020-02-07T21:00:00Z",
"2020-02-08T00:00:00Z",
"2020-02-08T03:00:00Z",
"2020-02-08T06:00:00Z",
"2020-02-08T09:00:00Z",
"2020-02-08T12:00:00Z",
"2020-02-08T15:00:00Z",
"2020-02-08T18:00:00Z",
"2020-02-08T21:00:00Z",
"2020-02-09T00:00:00Z",
"2020-02-09T03:00:00Z",
"2020-02-09T06:00:00Z",
"2020-02-09T09:00:00Z",
"2020-02-09T12:00:00Z",
"2020-02-09T15:00:00Z",
"2020-02-09T18:00:00Z",
"2020-02-09T21:00:00Z",
"2020-02-10T00:00:00Z",
"2020-02-10T03:00:00Z",
"2020-02-10T06:00:00Z",
"2020-02-10T09:00:00Z",
"2020-02-10T12:00:00Z",
"2020-02-10T15:00:00Z",
"2020-02-10T18:00:00Z",
"2020-02-10T21:00:00Z",
"2020-02-11T00:00:00Z",
"2020-02-11T03:00:00Z",
"2020-02-11T06:00:00Z",
"2020-02-11T09:00:00Z",
"2020-02-11T12:00:00Z",
"2020-02-11T15:00:00Z",
"2020-02-11T18:00:00Z",
"2020-02-11T21:00:00Z",
"2020-02-12T00:00:00Z",
"2020-02-12T12:00:00Z",
"2020-02-13T00:00:00Z",
"2020-02-13T12:00:00Z",

```

"2020-02-14T00:00:00Z",
    "2020-02-14T12:00:00Z",
    "2020-02-15T00:00:00Z",
    "2020-02-15T12:00:00Z",
    "2020-02-16T00:00:00Z",
    "2020-02-16T12:00:00Z",
    "2020-02-17T00:00:00Z",
    "2020-02-17T12:00:00Z",
    "2020-02-18T00:00:00Z"
  ]
}
},
"Dewpoint_temperature_height_above_ground": {
  "description": {
    "en": "Dewpoint_temperature_height_above_ground"
  },
  "unit": {
    "label": {
      "en": "kelvin"
    },
    "symbol": {
      "value": "K",
      "type": "http://data.example.org/metadata/uom/UCUM/K"
    }
  },
  "observedProperty": {
    "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-6",
    "label": {
      "en": "Dewpoint_temperature_height_above_ground"
    }
  },
  "measurementType": {
    "method": "instantaneous"
  },
  "extent": {
    "horizontal": {
      "name": [
        "longitude",
        "latitude"
      ],
      "coordinates": [
        "x",
        "y"
      ],
      "geographic": "BBOX[359.875,90.125,-0.125,-90.125]"
    },
    "vertical": {
      "name": [
        "height_above_ground"
      ],
      "coordinates": [
        "z"
      ],
      "range": [
        "2.0"
      ]
    }
  }
}

```

```

]
},
"temporal": {
  "name": [
    "time"
  ],
  "coordinates": [
    "time"
  ],
  "range": [
    "2020-02-02T00:00:00Z",
    "2020-02-02T03:00:00Z",
    "2020-02-02T06:00:00Z",
    "2020-02-02T09:00:00Z",
    "2020-02-02T12:00:00Z",
    "2020-02-02T15:00:00Z",
    "2020-02-02T18:00:00Z",
    "2020-02-02T21:00:00Z",
    "2020-02-03T00:00:00Z",
    "2020-02-03T03:00:00Z",
    "2020-02-03T06:00:00Z",
    "2020-02-03T09:00:00Z",
    "2020-02-03T12:00:00Z",
    "2020-02-03T15:00:00Z",
    "2020-02-03T18:00:00Z",
    "2020-02-03T21:00:00Z",
    "2020-02-04T00:00:00Z",
    "2020-02-04T03:00:00Z",
    "2020-02-04T06:00:00Z",
    "2020-02-04T09:00:00Z",
    "2020-02-04T12:00:00Z",
    "2020-02-04T15:00:00Z",
    "2020-02-04T18:00:00Z",
    "2020-02-04T21:00:00Z",
    "2020-02-05T00:00:00Z",
    "2020-02-05T03:00:00Z",
    "2020-02-05T06:00:00Z",
    "2020-02-05T09:00:00Z",
    "2020-02-05T12:00:00Z",
    "2020-02-05T15:00:00Z",
    "2020-02-05T18:00:00Z",
    "2020-02-05T21:00:00Z",
    "2020-02-06T00:00:00Z",
    "2020-02-06T03:00:00Z",
    "2020-02-06T06:00:00Z",
    "2020-02-06T09:00:00Z",
    "2020-02-06T12:00:00Z",
    "2020-02-06T15:00:00Z",
    "2020-02-06T18:00:00Z",
    "2020-02-06T21:00:00Z",
    "2020-02-07T00:00:00Z",
    "2020-02-07T03:00:00Z",
    "2020-02-07T06:00:00Z",
    "2020-02-07T09:00:00Z",
    "2020-02-07T12:00:00Z",
    "2020-02-07T15:00:00Z",
    "2020-02-07T18:00:00Z",

```



```

"2020-02-07T21:00:00Z",
  "2020-02-08T00:00:00Z",
  "2020-02-08T03:00:00Z",
  "2020-02-08T06:00:00Z",
  "2020-02-08T09:00:00Z",
  "2020-02-08T12:00:00Z",
  "2020-02-08T15:00:00Z",
  "2020-02-08T18:00:00Z",
  "2020-02-08T21:00:00Z",
  "2020-02-09T00:00:00Z",
  "2020-02-09T03:00:00Z",
  "2020-02-09T06:00:00Z",
  "2020-02-09T09:00:00Z",
  "2020-02-09T12:00:00Z",
  "2020-02-09T15:00:00Z",
  "2020-02-09T18:00:00Z",
  "2020-02-09T21:00:00Z",
  "2020-02-10T00:00:00Z",
  "2020-02-10T03:00:00Z",
  "2020-02-10T06:00:00Z",
  "2020-02-10T09:00:00Z",
  "2020-02-10T12:00:00Z",
  "2020-02-10T15:00:00Z",
  "2020-02-10T18:00:00Z",
  "2020-02-10T21:00:00Z",
  "2020-02-11T00:00:00Z",
  "2020-02-11T03:00:00Z",
  "2020-02-11T06:00:00Z",
  "2020-02-11T09:00:00Z",
  "2020-02-11T12:00:00Z",
  "2020-02-11T15:00:00Z",
  "2020-02-11T18:00:00Z",
  "2020-02-11T21:00:00Z",
  "2020-02-12T00:00:00Z",
  "2020-02-12T12:00:00Z",
  "2020-02-13T00:00:00Z",
  "2020-02-13T12:00:00Z",
  "2020-02-14T00:00:00Z",
  "2020-02-14T12:00:00Z",
  "2020-02-15T00:00:00Z",
  "2020-02-15T12:00:00Z",
  "2020-02-16T00:00:00Z",
  "2020-02-16T12:00:00Z",
  "2020-02-17T00:00:00Z",
  "2020-02-17T12:00:00Z",
  "2020-02-18T00:00:00Z"
]
}
},
"Dewpoint_temperature_height_above_ground": {
  "description": {
    "en": "Dewpoint_temperature_height_above_ground"
  },
  "unit": {
    "label": {
      "en": "kelvin"
    }
  }
}

```

```

},
  "symbol": {
    "value": "K",
    "type": "http://data.example.org/metadata/uom/UCUM/K"
  }
},
"observedProperty": {
  "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-6",
  "label": {
    "en": "Dewpoint_temperature_height_above_ground"
  }
},
},
"measurementType": {
  "method": "instantaneous"
},
},
"extent": {
  "horizontal": {
    "name": [
      "longitude",
      "latitude"
    ],
    "coordinates": [
      "x",
      "y"
    ],
    "geographic": "BB0X[359.875,90.125,-0.125,-90.125]"
  },
  "vertical": {
    "name": [
      "height_above_ground"
    ],
    "coordinates": [
      "z"
    ],
    "range": [
      "2.0"
    ]
  },
},
"temporal": {
  "name": [
    "time"
  ],
  "coordinates": [
    "time"
  ],
  "range": [
    "2020-02-02T00:00:00Z",
    "2020-02-02T03:00:00Z",
    "2020-02-02T06:00:00Z",
    "2020-02-02T09:00:00Z",
    "2020-02-02T12:00:00Z",
    "2020-02-02T15:00:00Z",
    "2020-02-02T18:00:00Z",
    "2020-02-02T21:00:00Z",
    "2020-02-03T00:00:00Z",
    "2020-02-03T03:00:00Z",
  ]
}

```

"2020-02-03T06:00:00Z",
"2020-02-03T09:00:00Z",
"2020-02-03T12:00:00Z",
"2020-02-03T15:00:00Z",
"2020-02-03T18:00:00Z",
"2020-02-03T21:00:00Z",
"2020-02-04T00:00:00Z",
"2020-02-04T03:00:00Z",
"2020-02-04T06:00:00Z",
"2020-02-04T09:00:00Z",
"2020-02-04T12:00:00Z",
"2020-02-04T15:00:00Z",
"2020-02-04T18:00:00Z",
"2020-02-04T21:00:00Z",
"2020-02-05T00:00:00Z",
"2020-02-05T03:00:00Z",
"2020-02-05T06:00:00Z",
"2020-02-05T09:00:00Z",
"2020-02-05T12:00:00Z",
"2020-02-05T15:00:00Z",
"2020-02-05T18:00:00Z",
"2020-02-05T21:00:00Z",
"2020-02-06T00:00:00Z",
"2020-02-06T03:00:00Z",
"2020-02-06T06:00:00Z",
"2020-02-06T09:00:00Z",
"2020-02-06T12:00:00Z",
"2020-02-06T15:00:00Z",
"2020-02-06T18:00:00Z",
"2020-02-06T21:00:00Z",
"2020-02-07T00:00:00Z",
"2020-02-07T03:00:00Z",
"2020-02-07T06:00:00Z",
"2020-02-07T09:00:00Z",
"2020-02-07T12:00:00Z",
"2020-02-07T15:00:00Z",
"2020-02-07T18:00:00Z",
"2020-02-07T21:00:00Z",
"2020-02-08T00:00:00Z",
"2020-02-08T03:00:00Z",
"2020-02-08T06:00:00Z",
"2020-02-08T09:00:00Z",
"2020-02-08T12:00:00Z",
"2020-02-08T15:00:00Z",
"2020-02-08T18:00:00Z",
"2020-02-08T21:00:00Z",
"2020-02-09T00:00:00Z",
"2020-02-09T03:00:00Z",
"2020-02-09T06:00:00Z",
"2020-02-09T09:00:00Z",
"2020-02-09T12:00:00Z",
"2020-02-09T15:00:00Z",
"2020-02-09T18:00:00Z",
"2020-02-09T21:00:00Z",
"2020-02-10T00:00:00Z",
"2020-02-10T03:00:00Z",
"2020-02-10T06:00:00Z",

```

"2020-02-10T09:00:00Z",
    "2020-02-10T12:00:00Z",
    "2020-02-10T15:00:00Z",
    "2020-02-10T18:00:00Z",
    "2020-02-10T21:00:00Z",
    "2020-02-11T00:00:00Z",
    "2020-02-11T03:00:00Z",
    "2020-02-11T06:00:00Z",
    "2020-02-11T09:00:00Z",
    "2020-02-11T12:00:00Z",
    "2020-02-11T15:00:00Z",
    "2020-02-11T18:00:00Z",
    "2020-02-11T21:00:00Z",
    "2020-02-12T00:00:00Z",
    "2020-02-12T12:00:00Z",
    "2020-02-13T00:00:00Z",
    "2020-02-13T12:00:00Z",
    "2020-02-14T00:00:00Z",
    "2020-02-14T12:00:00Z",
    "2020-02-15T00:00:00Z",
    "2020-02-15T12:00:00Z",
    "2020-02-16T00:00:00Z",
    "2020-02-16T12:00:00Z",
    "2020-02-17T00:00:00Z",
    "2020-02-17T12:00:00Z",
    "2020-02-18T00:00:00Z"
  ]
}
}
},
"Dewpoint_temperature_height_above_ground": {
  "description": {
    "en": "Dewpoint_temperature_height_above_ground"
  },
  "unit": {
    "label": {
      "en": "kelvin"
    },
    "symbol": {
      "value": "K",
      "type": "http://data.example.org/metadata/uom/UCUM/K"
    }
  },
  "observedProperty": {
    "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-6",
    "label": {
      "en": "Dewpoint_temperature_height_above_ground"
    }
  },
  "measurementType": {
    "method": "instantaneous"
  },
  "extent": {
    "horizontal": {
      "name": [
        "longitude",

```

```

"latitude"
],
"coordinates": [
  "x",
  "y"
],
"geographic": "BB0X[359.875,90.125,-0.125,-90.125]"
},
"vertical": {
  "name": [
    "height_above_ground"
  ],
  "coordinates": [
    "z"
  ],
  "range": [
    "2.0"
  ]
},
"temporal": {
  "name": [
    "time"
  ],
  "coordinates": [
    "time"
  ],
  "range": [
    "2020-02-02T00:00:00Z",
    "2020-02-02T03:00:00Z",
    "2020-02-02T06:00:00Z",
    "2020-02-02T09:00:00Z",
    "2020-02-02T12:00:00Z",
    "2020-02-02T15:00:00Z",
    "2020-02-02T18:00:00Z",
    "2020-02-02T21:00:00Z",
    "2020-02-03T00:00:00Z",
    "2020-02-03T03:00:00Z",
    "2020-02-03T06:00:00Z",
    "2020-02-03T09:00:00Z",
    "2020-02-03T12:00:00Z",
    "2020-02-03T15:00:00Z",
    "2020-02-03T18:00:00Z",
    "2020-02-03T21:00:00Z",
    "2020-02-04T00:00:00Z",
    "2020-02-04T03:00:00Z",
    "2020-02-04T06:00:00Z",
    "2020-02-04T09:00:00Z",
    "2020-02-04T12:00:00Z",
    "2020-02-04T15:00:00Z",
    "2020-02-04T18:00:00Z",
    "2020-02-04T21:00:00Z",
    "2020-02-05T00:00:00Z",
    "2020-02-05T03:00:00Z",
    "2020-02-05T06:00:00Z",
    "2020-02-05T09:00:00Z",
    "2020-02-05T12:00:00Z",
    "2020-02-05T15:00:00Z",

```

"2020-02-05T18:00:00Z",
"2020-02-05T21:00:00Z",
"2020-02-06T00:00:00Z",
"2020-02-06T03:00:00Z",
"2020-02-06T06:00:00Z",
"2020-02-06T09:00:00Z",
"2020-02-06T12:00:00Z",
"2020-02-06T15:00:00Z",
"2020-02-06T18:00:00Z",
"2020-02-06T21:00:00Z",
"2020-02-07T00:00:00Z",
"2020-02-07T03:00:00Z",
"2020-02-07T06:00:00Z",
"2020-02-07T09:00:00Z",
"2020-02-07T12:00:00Z",
"2020-02-07T15:00:00Z",
"2020-02-07T18:00:00Z",
"2020-02-07T21:00:00Z",
"2020-02-08T00:00:00Z",
"2020-02-08T03:00:00Z",
"2020-02-08T06:00:00Z",
"2020-02-08T09:00:00Z",
"2020-02-08T12:00:00Z",
"2020-02-08T15:00:00Z",
"2020-02-08T18:00:00Z",
"2020-02-08T21:00:00Z",
"2020-02-09T00:00:00Z",
"2020-02-09T03:00:00Z",
"2020-02-09T06:00:00Z",
"2020-02-09T09:00:00Z",
"2020-02-09T12:00:00Z",
"2020-02-09T15:00:00Z",
"2020-02-09T18:00:00Z",
"2020-02-09T21:00:00Z",
"2020-02-10T00:00:00Z",
"2020-02-10T03:00:00Z",
"2020-02-10T06:00:00Z",
"2020-02-10T09:00:00Z",
"2020-02-10T12:00:00Z",
"2020-02-10T15:00:00Z",
"2020-02-10T18:00:00Z",
"2020-02-10T21:00:00Z",
"2020-02-11T00:00:00Z",
"2020-02-11T03:00:00Z",
"2020-02-11T06:00:00Z",
"2020-02-11T09:00:00Z",
"2020-02-11T12:00:00Z",
"2020-02-11T15:00:00Z",
"2020-02-11T18:00:00Z",
"2020-02-11T21:00:00Z",
"2020-02-12T00:00:00Z",
"2020-02-12T12:00:00Z",
"2020-02-13T00:00:00Z",
"2020-02-13T12:00:00Z",
"2020-02-14T00:00:00Z",
"2020-02-14T12:00:00Z",
"2020-02-15T00:00:00Z",

```

"2020-02-15T12:00:00Z",
    "2020-02-16T00:00:00Z",
    "2020-02-16T12:00:00Z",
    "2020-02-17T00:00:00Z",
    "2020-02-17T12:00:00Z",
    "2020-02-18T00:00:00Z"
  ]
}
},
"Dewpoint_temperature_height_above_ground": {
  "description": {
    "en": "Dewpoint_temperature_height_above_ground"
  },
  "unit": {
    "label": {
      "en": "kelvin"
    },
    "symbol": {
      "value": "K",
      "type": "http://data.example.org/metadata/uom/UCUM/K"
    }
  },
  "observedProperty": {
    "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-6",
    "label": {
      "en": "Dewpoint_temperature_height_above_ground"
    }
  },
  "measurementType": {
    "method": "instantaneous"
  },
  "extent": {
    "horizontal": {
      "name": [
        "longitude",
        "latitude"
      ],
      "coordinates": [
        "x",
        "y"
      ],
      "geographic": "BBOX[359.875,90.125,-0.125,-90.125]"
    },
    "vertical": {
      "name": [
        "height_above_ground"
      ],
      "coordinates": [
        "z"
      ],
      "range": [
        "2.0"
      ]
    }
  },
  "temporal": {

```

```

"name": [
  "time"
],
"coordinates": [
  "time"
],
"range": [
  "2020-02-02T00:00:00Z",
  "2020-02-02T03:00:00Z",
  "2020-02-02T06:00:00Z",
  "2020-02-02T09:00:00Z",
  "2020-02-02T12:00:00Z",
  "2020-02-02T15:00:00Z",
  "2020-02-02T18:00:00Z",
  "2020-02-02T21:00:00Z",
  "2020-02-03T00:00:00Z",
  "2020-02-03T03:00:00Z",
  "2020-02-03T06:00:00Z",
  "2020-02-03T09:00:00Z",
  "2020-02-03T12:00:00Z",
  "2020-02-03T15:00:00Z",
  "2020-02-03T18:00:00Z",
  "2020-02-03T21:00:00Z",
  "2020-02-04T00:00:00Z",
  "2020-02-04T03:00:00Z",
  "2020-02-04T06:00:00Z",
  "2020-02-04T09:00:00Z",
  "2020-02-04T12:00:00Z",
  "2020-02-04T15:00:00Z",
  "2020-02-04T18:00:00Z",
  "2020-02-04T21:00:00Z",
  "2020-02-05T00:00:00Z",
  "2020-02-05T03:00:00Z",
  "2020-02-05T06:00:00Z",
  "2020-02-05T09:00:00Z",
  "2020-02-05T12:00:00Z",
  "2020-02-05T15:00:00Z",
  "2020-02-05T18:00:00Z",
  "2020-02-05T21:00:00Z",
  "2020-02-06T00:00:00Z",
  "2020-02-06T03:00:00Z",
  "2020-02-06T06:00:00Z",
  "2020-02-06T09:00:00Z",
  "2020-02-06T12:00:00Z",
  "2020-02-06T15:00:00Z",
  "2020-02-06T18:00:00Z",
  "2020-02-06T21:00:00Z",
  "2020-02-07T00:00:00Z",
  "2020-02-07T03:00:00Z",
  "2020-02-07T06:00:00Z",
  "2020-02-07T09:00:00Z",
  "2020-02-07T12:00:00Z",
  "2020-02-07T15:00:00Z",
  "2020-02-07T18:00:00Z",
  "2020-02-07T21:00:00Z",
  "2020-02-08T00:00:00Z",
  "2020-02-08T03:00:00Z",

```



```

"2020-02-08T06:00:00Z",
    "2020-02-08T09:00:00Z",
    "2020-02-08T12:00:00Z",
    "2020-02-08T15:00:00Z",
    "2020-02-08T18:00:00Z",
    "2020-02-08T21:00:00Z",
    "2020-02-09T00:00:00Z",
    "2020-02-09T03:00:00Z",
    "2020-02-09T06:00:00Z",
    "2020-02-09T09:00:00Z",
    "2020-02-09T12:00:00Z",
    "2020-02-09T15:00:00Z",
    "2020-02-09T18:00:00Z",
    "2020-02-09T21:00:00Z",
    "2020-02-10T00:00:00Z",
    "2020-02-10T03:00:00Z",
    "2020-02-10T06:00:00Z",
    "2020-02-10T09:00:00Z",
    "2020-02-10T12:00:00Z",
    "2020-02-10T15:00:00Z",
    "2020-02-10T18:00:00Z",
    "2020-02-10T21:00:00Z",
    "2020-02-11T00:00:00Z",
    "2020-02-11T03:00:00Z",
    "2020-02-11T06:00:00Z",
    "2020-02-11T09:00:00Z",
    "2020-02-11T12:00:00Z",
    "2020-02-11T15:00:00Z",
    "2020-02-11T18:00:00Z",
    "2020-02-11T21:00:00Z",
    "2020-02-12T00:00:00Z",
    "2020-02-12T12:00:00Z",
    "2020-02-13T00:00:00Z",
    "2020-02-13T12:00:00Z",
    "2020-02-14T00:00:00Z",
    "2020-02-14T12:00:00Z",
    "2020-02-15T00:00:00Z",
    "2020-02-15T12:00:00Z",
    "2020-02-16T00:00:00Z",
    "2020-02-16T12:00:00Z",
    "2020-02-17T00:00:00Z",
    "2020-02-17T12:00:00Z",
    "2020-02-18T00:00:00Z"
  ]
}
}
},
"Dewpoint_temperature_height_above_ground": {
  "description": {
    "en": "Dewpoint_temperature_height_above_ground"
  },
  "unit": {
    "label": {
      "en": "kelvin"
    },
    "symbol": {
      "value": "K",

```

```

"type": "http://data.example.org/metadata/uom/UCUM/K"
  }
},
"observedProperty": {
  "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-6",
  "label": {
    "en": "Dewpoint_temperature_height_above_ground"
  }
},
"measurementType": {
  "method": "instantaneous"
},
"extent": {
  "horizontal": {
    "name": [
      "longitude",
      "latitude"
    ],
    "coordinates": [
      "x",
      "y"
    ],
    "geographic": "BB0X[359.875,90.125,-0.125,-90.125]"
  },
  "vertical": {
    "name": [
      "height_above_ground"
    ],
    "coordinates": [
      "z"
    ],
    "range": [
      "2.0"
    ]
  },
  "temporal": {
    "name": [
      "time"
    ],
    "coordinates": [
      "time"
    ],
    "range": [
      "2020-02-02T00:00:00Z",
      "2020-02-02T03:00:00Z",
      "2020-02-02T06:00:00Z",
      "2020-02-02T09:00:00Z",
      "2020-02-02T12:00:00Z",
      "2020-02-02T15:00:00Z",
      "2020-02-02T18:00:00Z",
      "2020-02-02T21:00:00Z",
      "2020-02-03T00:00:00Z",
      "2020-02-03T03:00:00Z",
      "2020-02-03T06:00:00Z",
      "2020-02-03T09:00:00Z",
      "2020-02-03T12:00:00Z",

```

"2020-02-03T15:00:00Z",
"2020-02-03T18:00:00Z",
"2020-02-03T21:00:00Z",
"2020-02-04T00:00:00Z",
"2020-02-04T03:00:00Z",
"2020-02-04T06:00:00Z",
"2020-02-04T09:00:00Z",
"2020-02-04T12:00:00Z",
"2020-02-04T15:00:00Z",
"2020-02-04T18:00:00Z",
"2020-02-04T21:00:00Z",
"2020-02-05T00:00:00Z",
"2020-02-05T03:00:00Z",
"2020-02-05T06:00:00Z",
"2020-02-05T09:00:00Z",
"2020-02-05T12:00:00Z",
"2020-02-05T15:00:00Z",
"2020-02-05T18:00:00Z",
"2020-02-05T21:00:00Z",
"2020-02-06T00:00:00Z",
"2020-02-06T03:00:00Z",
"2020-02-06T06:00:00Z",
"2020-02-06T09:00:00Z",
"2020-02-06T12:00:00Z",
"2020-02-06T15:00:00Z",
"2020-02-06T18:00:00Z",
"2020-02-06T21:00:00Z",
"2020-02-07T00:00:00Z",
"2020-02-07T03:00:00Z",
"2020-02-07T06:00:00Z",
"2020-02-07T09:00:00Z",
"2020-02-07T12:00:00Z",
"2020-02-07T15:00:00Z",
"2020-02-07T18:00:00Z",
"2020-02-07T21:00:00Z",
"2020-02-08T00:00:00Z",
"2020-02-08T03:00:00Z",
"2020-02-08T06:00:00Z",
"2020-02-08T09:00:00Z",
"2020-02-08T12:00:00Z",
"2020-02-08T15:00:00Z",
"2020-02-08T18:00:00Z",
"2020-02-08T21:00:00Z",
"2020-02-09T00:00:00Z",
"2020-02-09T03:00:00Z",
"2020-02-09T06:00:00Z",
"2020-02-09T09:00:00Z",
"2020-02-09T12:00:00Z",
"2020-02-09T15:00:00Z",
"2020-02-09T18:00:00Z",
"2020-02-09T21:00:00Z",
"2020-02-10T00:00:00Z",
"2020-02-10T03:00:00Z",
"2020-02-10T06:00:00Z",
"2020-02-10T09:00:00Z",
"2020-02-10T12:00:00Z",
"2020-02-10T15:00:00Z",

```

"2020-02-10T18:00:00Z",
    "2020-02-10T21:00:00Z",
    "2020-02-11T00:00:00Z",
    "2020-02-11T03:00:00Z",
    "2020-02-11T06:00:00Z",
    "2020-02-11T09:00:00Z",
    "2020-02-11T12:00:00Z",
    "2020-02-11T15:00:00Z",
    "2020-02-11T18:00:00Z",
    "2020-02-11T21:00:00Z",
    "2020-02-12T00:00:00Z",
    "2020-02-12T12:00:00Z",
    "2020-02-13T00:00:00Z",
    "2020-02-13T12:00:00Z",
    "2020-02-14T00:00:00Z",
    "2020-02-14T12:00:00Z",
    "2020-02-15T00:00:00Z",
    "2020-02-15T12:00:00Z",
    "2020-02-16T00:00:00Z",
    "2020-02-16T12:00:00Z",
    "2020-02-17T00:00:00Z",
    "2020-02-17T12:00:00Z",
    "2020-02-18T00:00:00Z"
  ]
}
},
"Dewpoint_temperature_height_above_ground": {
  "description": {
    "en": "Dewpoint_temperature_height_above_ground"
  },
  "unit": {
    "label": {
      "en": "kelvin"
    },
    "symbol": {
      "value": "K",
      "type": "http://data.example.org/metadata/uom/UCUM/K"
    }
  },
  "observedProperty": {
    "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-6",
    "label": {
      "en": "Dewpoint_temperature_height_above_ground"
    }
  },
  "measurementType": {
    "method": "instantaneous"
  },
  "extent": {
    "horizontal": {
      "name": [
        "longitude",
        "latitude"
      ],
      "coordinates": [

```

```

"x",
    "y"
  ],
  "geographic": "BB0X[359.875,90.125,-0.125,-90.125]"
},
"vertical": {
  "name": [
    "height_above_ground"
  ],
  "coordinates": [
    "z"
  ],
  "range": [
    "2.0"
  ]
},
"temporal": {
  "name": [
    "time"
  ],
  "coordinates": [
    "time"
  ],
  "range": [
    "2020-02-02T00:00:00Z",
    "2020-02-02T03:00:00Z",
    "2020-02-02T06:00:00Z",
    "2020-02-02T09:00:00Z",
    "2020-02-02T12:00:00Z",
    "2020-02-02T15:00:00Z",
    "2020-02-02T18:00:00Z",
    "2020-02-02T21:00:00Z",
    "2020-02-03T00:00:00Z",
    "2020-02-03T03:00:00Z",
    "2020-02-03T06:00:00Z",
    "2020-02-03T09:00:00Z",
    "2020-02-03T12:00:00Z",
    "2020-02-03T15:00:00Z",
    "2020-02-03T18:00:00Z",
    "2020-02-03T21:00:00Z",
    "2020-02-04T00:00:00Z",
    "2020-02-04T03:00:00Z",
    "2020-02-04T06:00:00Z",
    "2020-02-04T09:00:00Z",
    "2020-02-04T12:00:00Z",
    "2020-02-04T15:00:00Z",
    "2020-02-04T18:00:00Z",
    "2020-02-04T21:00:00Z",
    "2020-02-05T00:00:00Z",
    "2020-02-05T03:00:00Z",
    "2020-02-05T06:00:00Z",
    "2020-02-05T09:00:00Z",
    "2020-02-05T12:00:00Z",
    "2020-02-05T15:00:00Z",
    "2020-02-05T18:00:00Z",
    "2020-02-05T21:00:00Z",
    "2020-02-06T00:00:00Z",

```

"2020-02-06T03:00:00Z",
"2020-02-06T06:00:00Z",
"2020-02-06T09:00:00Z",
"2020-02-06T12:00:00Z",
"2020-02-06T15:00:00Z",
"2020-02-06T18:00:00Z",
"2020-02-06T21:00:00Z",
"2020-02-07T00:00:00Z",
"2020-02-07T03:00:00Z",
"2020-02-07T06:00:00Z",
"2020-02-07T09:00:00Z",
"2020-02-07T12:00:00Z",
"2020-02-07T15:00:00Z",
"2020-02-07T18:00:00Z",
"2020-02-07T21:00:00Z",
"2020-02-08T00:00:00Z",
"2020-02-08T03:00:00Z",
"2020-02-08T06:00:00Z",
"2020-02-08T09:00:00Z",
"2020-02-08T12:00:00Z",
"2020-02-08T15:00:00Z",
"2020-02-08T18:00:00Z",
"2020-02-08T21:00:00Z",
"2020-02-09T00:00:00Z",
"2020-02-09T03:00:00Z",
"2020-02-09T06:00:00Z",
"2020-02-09T09:00:00Z",
"2020-02-09T12:00:00Z",
"2020-02-09T15:00:00Z",
"2020-02-09T18:00:00Z",
"2020-02-09T21:00:00Z",
"2020-02-10T00:00:00Z",
"2020-02-10T03:00:00Z",
"2020-02-10T06:00:00Z",
"2020-02-10T09:00:00Z",
"2020-02-10T12:00:00Z",
"2020-02-10T15:00:00Z",
"2020-02-10T18:00:00Z",
"2020-02-10T21:00:00Z",
"2020-02-11T00:00:00Z",
"2020-02-11T03:00:00Z",
"2020-02-11T06:00:00Z",
"2020-02-11T09:00:00Z",
"2020-02-11T12:00:00Z",
"2020-02-11T15:00:00Z",
"2020-02-11T18:00:00Z",
"2020-02-11T21:00:00Z",
"2020-02-12T00:00:00Z",
"2020-02-12T12:00:00Z",
"2020-02-13T00:00:00Z",
"2020-02-13T12:00:00Z",
"2020-02-14T00:00:00Z",
"2020-02-14T12:00:00Z",
"2020-02-15T00:00:00Z",
"2020-02-15T12:00:00Z",
"2020-02-16T00:00:00Z",
"2020-02-16T12:00:00Z",

```

"2020-02-17T00:00:00Z",
    "2020-02-17T12:00:00Z",
    "2020-02-18T00:00:00Z"
  ]
}
},
"Dewpoint_temperature_height_above_ground": {
  "description": {
    "en": "Dewpoint_temperature_height_above_ground"
  },
  "unit": {
    "label": {
      "en": "kelvin"
    },
    "symbol": {
      "value": "K",
      "type": "http://data.example.org/metadata/uom/UCUM/K"
    }
  },
  "observedProperty": {
    "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-6",
    "label": {
      "en": "Dewpoint_temperature_height_above_ground"
    }
  },
  "measurementType": {
    "method": "instantaneous"
  },
  "extent": {
    "horizontal": {
      "name": [
        "longitude",
        "latitude"
      ],
      "coordinates": [
        "x",
        "y"
      ],
      "geographic": "BBBOX[359.875,90.125,-0.125,-90.125]"
    },
    "vertical": {
      "name": [
        "height_above_ground"
      ],
      "coordinates": [
        "z"
      ],
      "range": [
        "2.0"
      ]
    },
    "temporal": {
      "name": [
        "time"
      ],

```

```
"coordinates": [  
  "time"  
],  
"range": [  
  "2020-02-02T00:00:00Z",  
  "2020-02-02T03:00:00Z",  
  "2020-02-02T06:00:00Z",  
  "2020-02-02T09:00:00Z",  
  "2020-02-02T12:00:00Z",  
  "2020-02-02T15:00:00Z",  
  "2020-02-02T18:00:00Z",  
  "2020-02-02T21:00:00Z",  
  "2020-02-03T00:00:00Z",  
  "2020-02-03T03:00:00Z",  
  "2020-02-03T06:00:00Z",  
  "2020-02-03T09:00:00Z",  
  "2020-02-03T12:00:00Z",  
  "2020-02-03T15:00:00Z",  
  "2020-02-03T18:00:00Z",  
  "2020-02-03T21:00:00Z",  
  "2020-02-04T00:00:00Z",  
  "2020-02-04T03:00:00Z",  
  "2020-02-04T06:00:00Z",  
  "2020-02-04T09:00:00Z",  
  "2020-02-04T12:00:00Z",  
  "2020-02-04T15:00:00Z",  
  "2020-02-04T18:00:00Z",  
  "2020-02-04T21:00:00Z",  
  "2020-02-05T00:00:00Z",  
  "2020-02-05T03:00:00Z",  
  "2020-02-05T06:00:00Z",  
  "2020-02-05T09:00:00Z",  
  "2020-02-05T12:00:00Z",  
  "2020-02-05T15:00:00Z",  
  "2020-02-05T18:00:00Z",  
  "2020-02-05T21:00:00Z",  
  "2020-02-06T00:00:00Z",  
  "2020-02-06T03:00:00Z",  
  "2020-02-06T06:00:00Z",  
  "2020-02-06T09:00:00Z",  
  "2020-02-06T12:00:00Z",  
  "2020-02-06T15:00:00Z",  
  "2020-02-06T18:00:00Z",  
  "2020-02-06T21:00:00Z",  
  "2020-02-07T00:00:00Z",  
  "2020-02-07T03:00:00Z",  
  "2020-02-07T06:00:00Z",  
  "2020-02-07T09:00:00Z",  
  "2020-02-07T12:00:00Z",  
  "2020-02-07T15:00:00Z",  
  "2020-02-07T18:00:00Z",  
  "2020-02-07T21:00:00Z",  
  "2020-02-08T00:00:00Z",  
  "2020-02-08T03:00:00Z",  
  "2020-02-08T06:00:00Z",  
  "2020-02-08T09:00:00Z",  
  "2020-02-08T12:00:00Z",  
]
```



```

"2020-02-08T15:00:00Z",
  "2020-02-08T18:00:00Z",
  "2020-02-08T21:00:00Z",
  "2020-02-09T00:00:00Z",
  "2020-02-09T03:00:00Z",
  "2020-02-09T06:00:00Z",
  "2020-02-09T09:00:00Z",
  "2020-02-09T12:00:00Z",
  "2020-02-09T15:00:00Z",
  "2020-02-09T18:00:00Z",
  "2020-02-09T21:00:00Z",
  "2020-02-10T00:00:00Z",
  "2020-02-10T03:00:00Z",
  "2020-02-10T06:00:00Z",
  "2020-02-10T09:00:00Z",
  "2020-02-10T12:00:00Z",
  "2020-02-10T15:00:00Z",
  "2020-02-10T18:00:00Z",
  "2020-02-10T21:00:00Z",
  "2020-02-11T00:00:00Z",
  "2020-02-11T03:00:00Z",
  "2020-02-11T06:00:00Z",
  "2020-02-11T09:00:00Z",
  "2020-02-11T12:00:00Z",
  "2020-02-11T15:00:00Z",
  "2020-02-11T18:00:00Z",
  "2020-02-11T21:00:00Z",
  "2020-02-12T00:00:00Z",
  "2020-02-12T12:00:00Z",
  "2020-02-13T00:00:00Z",
  "2020-02-13T12:00:00Z",
  "2020-02-14T00:00:00Z",
  "2020-02-14T12:00:00Z",
  "2020-02-15T00:00:00Z",
  "2020-02-15T12:00:00Z",
  "2020-02-16T00:00:00Z",
  "2020-02-16T12:00:00Z",
  "2020-02-17T00:00:00Z",
  "2020-02-17T12:00:00Z",
  "2020-02-18T00:00:00Z"
]
}
}
},
"Dewpoint_temperature_height_above_ground": {
  "description": {
    "en": "Dewpoint_temperature_height_above_ground"
  },
  "unit": {
    "label": {
      "en": "kelvin"
    },
    "symbol": {
      "value": "K",
      "type": "http://data.example.org/metadata/uom/UCUM/K"
    }
  }
},

```

```

"observedProperty": {
  "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-6",
  "label": {
    "en": "Dewpoint_temperature_height_above_ground"
  }
},
"measurementType": {
  "method": "instantaneous"
},
"extent": {
  "horizontal": {
    "name": [
      "longitude",
      "latitude"
    ],
    "coordinates": [
      "x",
      "y"
    ],
    "geographic": "BB0X[359.875,90.125,-0.125,-90.125]"
  },
  "vertical": {
    "name": [
      "height_above_ground"
    ],
    "coordinates": [
      "z"
    ],
    "range": [
      "2.0"
    ]
  },
  "temporal": {
    "name": [
      "time"
    ],
    "coordinates": [
      "time"
    ],
    "range": [
      "2020-02-02T00:00:00Z",
      "2020-02-02T03:00:00Z",
      "2020-02-02T06:00:00Z",
      "2020-02-02T09:00:00Z",
      "2020-02-02T12:00:00Z",
      "2020-02-02T15:00:00Z",
      "2020-02-02T18:00:00Z",
      "2020-02-02T21:00:00Z",
      "2020-02-03T00:00:00Z",
      "2020-02-03T03:00:00Z",
      "2020-02-03T06:00:00Z",
      "2020-02-03T09:00:00Z",
      "2020-02-03T12:00:00Z",
      "2020-02-03T15:00:00Z",
      "2020-02-03T18:00:00Z",
      "2020-02-03T21:00:00Z",
    ]
  }
}

```

"2020-02-04T00:00:00Z",
"2020-02-04T03:00:00Z",
"2020-02-04T06:00:00Z",
"2020-02-04T09:00:00Z",
"2020-02-04T12:00:00Z",
"2020-02-04T15:00:00Z",
"2020-02-04T18:00:00Z",
"2020-02-04T21:00:00Z",
"2020-02-05T00:00:00Z",
"2020-02-05T03:00:00Z",
"2020-02-05T06:00:00Z",
"2020-02-05T09:00:00Z",
"2020-02-05T12:00:00Z",
"2020-02-05T15:00:00Z",
"2020-02-05T18:00:00Z",
"2020-02-05T21:00:00Z",
"2020-02-06T00:00:00Z",
"2020-02-06T03:00:00Z",
"2020-02-06T06:00:00Z",
"2020-02-06T09:00:00Z",
"2020-02-06T12:00:00Z",
"2020-02-06T15:00:00Z",
"2020-02-06T18:00:00Z",
"2020-02-06T21:00:00Z",
"2020-02-07T00:00:00Z",
"2020-02-07T03:00:00Z",
"2020-02-07T06:00:00Z",
"2020-02-07T09:00:00Z",
"2020-02-07T12:00:00Z",
"2020-02-07T15:00:00Z",
"2020-02-07T18:00:00Z",
"2020-02-07T21:00:00Z",
"2020-02-08T00:00:00Z",
"2020-02-08T03:00:00Z",
"2020-02-08T06:00:00Z",
"2020-02-08T09:00:00Z",
"2020-02-08T12:00:00Z",
"2020-02-08T15:00:00Z",
"2020-02-08T18:00:00Z",
"2020-02-08T21:00:00Z",
"2020-02-09T00:00:00Z",
"2020-02-09T03:00:00Z",
"2020-02-09T06:00:00Z",
"2020-02-09T09:00:00Z",
"2020-02-09T12:00:00Z",
"2020-02-09T15:00:00Z",
"2020-02-09T18:00:00Z",
"2020-02-09T21:00:00Z",
"2020-02-10T00:00:00Z",
"2020-02-10T03:00:00Z",
"2020-02-10T06:00:00Z",
"2020-02-10T09:00:00Z",
"2020-02-10T12:00:00Z",
"2020-02-10T15:00:00Z",
"2020-02-10T18:00:00Z",
"2020-02-10T21:00:00Z",
"2020-02-11T00:00:00Z",

```

"2020-02-11T03:00:00Z",
    "2020-02-11T06:00:00Z",
    "2020-02-11T09:00:00Z",
    "2020-02-11T12:00:00Z",
    "2020-02-11T15:00:00Z",
    "2020-02-11T18:00:00Z",
    "2020-02-11T21:00:00Z",
    "2020-02-12T00:00:00Z",
    "2020-02-12T12:00:00Z",
    "2020-02-13T00:00:00Z",
    "2020-02-13T12:00:00Z",
    "2020-02-14T00:00:00Z",
    "2020-02-14T12:00:00Z",
    "2020-02-15T00:00:00Z",
    "2020-02-15T12:00:00Z",
    "2020-02-16T00:00:00Z",
    "2020-02-16T12:00:00Z",
    "2020-02-17T00:00:00Z",
    "2020-02-17T12:00:00Z",
    "2020-02-18T00:00:00Z"
  ]
}
}
},
"Dewpoint_temperature_height_above_ground": {
  "description": {
    "en": "Dewpoint_temperature_height_above_ground"
  },
  "unit": {
    "label": {
      "en": "kelvin"
    },
    "symbol": {
      "value": "K",
      "type": "http://data.example.org/metadata/uom/UCUM/K"
    }
  },
  "observedProperty": {
    "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-6",
    "label": {
      "en": "Dewpoint_temperature_height_above_ground"
    }
  },
  "measurementType": {
    "method": "instantaneous"
  },
  "extent": {
    "horizontal": {
      "name": [
        "longitude",
        "latitude"
      ],
      "coordinates": [
        "x",
        "y"
      ],
    },
  },

```

```

"geographic": "BBOX[359.875,90.125,-0.125,-90.125]"
},
"vertical": {
  "name": [
    "height_above_ground"
  ],
  "coordinates": [
    "z"
  ],
  "range": [
    "2.0"
  ]
},
"temporal": {
  "name": [
    "time"
  ],
  "coordinates": [
    "time"
  ],
  "range": [
    "2020-02-02T00:00:00Z",
    "2020-02-02T03:00:00Z",
    "2020-02-02T06:00:00Z",
    "2020-02-02T09:00:00Z",
    "2020-02-02T12:00:00Z",
    "2020-02-02T15:00:00Z",
    "2020-02-02T18:00:00Z",
    "2020-02-02T21:00:00Z",
    "2020-02-03T00:00:00Z",
    "2020-02-03T03:00:00Z",
    "2020-02-03T06:00:00Z",
    "2020-02-03T09:00:00Z",
    "2020-02-03T12:00:00Z",
    "2020-02-03T15:00:00Z",
    "2020-02-03T18:00:00Z",
    "2020-02-03T21:00:00Z",
    "2020-02-04T00:00:00Z",
    "2020-02-04T03:00:00Z",
    "2020-02-04T06:00:00Z",
    "2020-02-04T09:00:00Z",
    "2020-02-04T12:00:00Z",
    "2020-02-04T15:00:00Z",
    "2020-02-04T18:00:00Z",
    "2020-02-04T21:00:00Z",
    "2020-02-05T00:00:00Z",
    "2020-02-05T03:00:00Z",
    "2020-02-05T06:00:00Z",
    "2020-02-05T09:00:00Z",
    "2020-02-05T12:00:00Z",
    "2020-02-05T15:00:00Z",
    "2020-02-05T18:00:00Z",
    "2020-02-05T21:00:00Z",
    "2020-02-06T00:00:00Z",
    "2020-02-06T03:00:00Z",
    "2020-02-06T06:00:00Z",
    "2020-02-06T09:00:00Z",

```

"2020-02-06T12:00:00Z",
"2020-02-06T15:00:00Z",
"2020-02-06T18:00:00Z",
"2020-02-06T21:00:00Z",
"2020-02-07T00:00:00Z",
"2020-02-07T03:00:00Z",
"2020-02-07T06:00:00Z",
"2020-02-07T09:00:00Z",
"2020-02-07T12:00:00Z",
"2020-02-07T15:00:00Z",
"2020-02-07T18:00:00Z",
"2020-02-07T21:00:00Z",
"2020-02-08T00:00:00Z",
"2020-02-08T03:00:00Z",
"2020-02-08T06:00:00Z",
"2020-02-08T09:00:00Z",
"2020-02-08T12:00:00Z",
"2020-02-08T15:00:00Z",
"2020-02-08T18:00:00Z",
"2020-02-08T21:00:00Z",
"2020-02-09T00:00:00Z",
"2020-02-09T03:00:00Z",
"2020-02-09T06:00:00Z",
"2020-02-09T09:00:00Z",
"2020-02-09T12:00:00Z",
"2020-02-09T15:00:00Z",
"2020-02-09T18:00:00Z",
"2020-02-09T21:00:00Z",
"2020-02-10T00:00:00Z",
"2020-02-10T03:00:00Z",
"2020-02-10T06:00:00Z",
"2020-02-10T09:00:00Z",
"2020-02-10T12:00:00Z",
"2020-02-10T15:00:00Z",
"2020-02-10T18:00:00Z",
"2020-02-10T21:00:00Z",
"2020-02-11T00:00:00Z",
"2020-02-11T03:00:00Z",
"2020-02-11T06:00:00Z",
"2020-02-11T09:00:00Z",
"2020-02-11T12:00:00Z",
"2020-02-11T15:00:00Z",
"2020-02-11T18:00:00Z",
"2020-02-11T21:00:00Z",
"2020-02-12T00:00:00Z",
"2020-02-12T12:00:00Z",
"2020-02-13T00:00:00Z",
"2020-02-13T12:00:00Z",
"2020-02-14T00:00:00Z",
"2020-02-14T12:00:00Z",
"2020-02-15T00:00:00Z",
"2020-02-15T12:00:00Z",
"2020-02-16T00:00:00Z",
"2020-02-16T12:00:00Z",
"2020-02-17T00:00:00Z",
"2020-02-17T12:00:00Z",
"2020-02-18T00:00:00Z"

```

    ]
    }
  }
},
"Dewpoint_temperature_height_above_ground": {
  "description": {
    "en": "Dewpoint_temperature_height_above_ground"
  },
  "unit": {
    "label": {
      "en": "kelvin"
    },
    "symbol": {
      "value": "K",
      "type": "http://data.example.org/metadata/uom/UCUM/K"
    }
  },
  "observedProperty": {
    "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-6",
    "label": {
      "en": "Dewpoint_temperature_height_above_ground"
    }
  },
  "measurementType": {
    "method": "instantaneous"
  },
  "extent": {
    "horizontal": {
      "name": [
        "longitude",
        "latitude"
      ],
      "coordinates": [
        "x",
        "y"
      ],
      "geographic": "BBBOX[359.875,90.125,-0.125,-90.125]"
    },
    "vertical": {
      "name": [
        "height_above_ground"
      ],
      "coordinates": [
        "z"
      ],
      "range": [
        "2.0"
      ]
    },
    "temporal": {
      "name": [
        "time"
      ],
      "coordinates": [
        "time"
      ]
    }
  }
}

```

"range": [

"2020-02-02T00:00:00Z",
"2020-02-02T03:00:00Z",
"2020-02-02T06:00:00Z",
"2020-02-02T09:00:00Z",
"2020-02-02T12:00:00Z",
"2020-02-02T15:00:00Z",
"2020-02-02T18:00:00Z",
"2020-02-02T21:00:00Z",
"2020-02-03T00:00:00Z",
"2020-02-03T03:00:00Z",
"2020-02-03T06:00:00Z",
"2020-02-03T09:00:00Z",
"2020-02-03T12:00:00Z",
"2020-02-03T15:00:00Z",
"2020-02-03T18:00:00Z",
"2020-02-03T21:00:00Z",
"2020-02-04T00:00:00Z",
"2020-02-04T03:00:00Z",
"2020-02-04T06:00:00Z",
"2020-02-04T09:00:00Z",
"2020-02-04T12:00:00Z",
"2020-02-04T15:00:00Z",
"2020-02-04T18:00:00Z",
"2020-02-04T21:00:00Z",
"2020-02-05T00:00:00Z",
"2020-02-05T03:00:00Z",
"2020-02-05T06:00:00Z",
"2020-02-05T09:00:00Z",
"2020-02-05T12:00:00Z",
"2020-02-05T15:00:00Z",
"2020-02-05T18:00:00Z",
"2020-02-05T21:00:00Z",
"2020-02-06T00:00:00Z",
"2020-02-06T03:00:00Z",
"2020-02-06T06:00:00Z",
"2020-02-06T09:00:00Z",
"2020-02-06T12:00:00Z",
"2020-02-06T15:00:00Z",
"2020-02-06T18:00:00Z",
"2020-02-06T21:00:00Z",
"2020-02-07T00:00:00Z",
"2020-02-07T03:00:00Z",
"2020-02-07T06:00:00Z",
"2020-02-07T09:00:00Z",
"2020-02-07T12:00:00Z",
"2020-02-07T15:00:00Z",
"2020-02-07T18:00:00Z",
"2020-02-07T21:00:00Z",
"2020-02-08T00:00:00Z",
"2020-02-08T03:00:00Z",
"2020-02-08T06:00:00Z",
"2020-02-08T09:00:00Z",
"2020-02-08T12:00:00Z",
"2020-02-08T15:00:00Z",
"2020-02-08T18:00:00Z",
"2020-02-08T21:00:00Z",


```

"2020-02-09T00:00:00Z",
  "2020-02-09T03:00:00Z",
  "2020-02-09T06:00:00Z",
  "2020-02-09T09:00:00Z",
  "2020-02-09T12:00:00Z",
  "2020-02-09T15:00:00Z",
  "2020-02-09T18:00:00Z",
  "2020-02-09T21:00:00Z",
  "2020-02-10T00:00:00Z",
  "2020-02-10T03:00:00Z",
  "2020-02-10T06:00:00Z",
  "2020-02-10T09:00:00Z",
  "2020-02-10T12:00:00Z",
  "2020-02-10T15:00:00Z",
  "2020-02-10T18:00:00Z",
  "2020-02-10T21:00:00Z",
  "2020-02-11T00:00:00Z",
  "2020-02-11T03:00:00Z",
  "2020-02-11T06:00:00Z",
  "2020-02-11T09:00:00Z",
  "2020-02-11T12:00:00Z",
  "2020-02-11T15:00:00Z",
  "2020-02-11T18:00:00Z",
  "2020-02-11T21:00:00Z",
  "2020-02-12T00:00:00Z",
  "2020-02-12T12:00:00Z",
  "2020-02-13T00:00:00Z",
  "2020-02-13T12:00:00Z",
  "2020-02-14T00:00:00Z",
  "2020-02-14T12:00:00Z",
  "2020-02-15T00:00:00Z",
  "2020-02-15T12:00:00Z",
  "2020-02-16T00:00:00Z",
  "2020-02-16T12:00:00Z",
  "2020-02-17T00:00:00Z",
  "2020-02-17T12:00:00Z",
  "2020-02-18T00:00:00Z"
]
}
}
},
"Dewpoint_temperature_height_above_ground": {
  "description": {
    "en": "Dewpoint_temperature_height_above_ground"
  },
  "unit": {
    "label": {
      "en": "kelvin"
    },
    "symbol": {
      "value": "K",
      "type": "http://data.example.org/metadata/uom/UCUM/K"
    }
  },
  "observedProperty": {
    "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-6",

```

```

"label": {
  "en": "Dewpoint_temperature_height_above_ground"
},
"measurementType": {
  "method": "instantaneous"
},
"extent": {
  "horizontal": {
    "name": [
      "longitude",
      "latutude"
    ],
    "coordinates": [
      "x",
      "y"
    ],
    "geographic": "BB0X[359.875,90.125,-0.125,-90.125]"
  },
  "vertical": {
    "name": [
      "height_above_ground"
    ],
    "coordinates": [
      "z"
    ],
    "range": [
      "2.0"
    ]
  },
  "temporal": {
    "name": [
      "time"
    ],
    "coordinates": [
      "time"
    ],
    "range": [
      "2020-02-02T00:00:00Z",
      "2020-02-02T03:00:00Z",
      "2020-02-02T06:00:00Z",
      "2020-02-02T09:00:00Z",
      "2020-02-02T12:00:00Z",
      "2020-02-02T15:00:00Z",
      "2020-02-02T18:00:00Z",
      "2020-02-02T21:00:00Z",
      "2020-02-03T00:00:00Z",
      "2020-02-03T03:00:00Z",
      "2020-02-03T06:00:00Z",
      "2020-02-03T09:00:00Z",
      "2020-02-03T12:00:00Z",
      "2020-02-03T15:00:00Z",
      "2020-02-03T18:00:00Z",
      "2020-02-03T21:00:00Z",
      "2020-02-04T00:00:00Z",
      "2020-02-04T03:00:00Z",
      "2020-02-04T06:00:00Z",

```

"2020-02-04T09:00:00Z",
"2020-02-04T12:00:00Z",
"2020-02-04T15:00:00Z",
"2020-02-04T18:00:00Z",
"2020-02-04T21:00:00Z",
"2020-02-05T00:00:00Z",
"2020-02-05T03:00:00Z",
"2020-02-05T06:00:00Z",
"2020-02-05T09:00:00Z",
"2020-02-05T12:00:00Z",
"2020-02-05T15:00:00Z",
"2020-02-05T18:00:00Z",
"2020-02-05T21:00:00Z",
"2020-02-06T00:00:00Z",
"2020-02-06T03:00:00Z",
"2020-02-06T06:00:00Z",
"2020-02-06T09:00:00Z",
"2020-02-06T12:00:00Z",
"2020-02-06T15:00:00Z",
"2020-02-06T18:00:00Z",
"2020-02-06T21:00:00Z",
"2020-02-07T00:00:00Z",
"2020-02-07T03:00:00Z",
"2020-02-07T06:00:00Z",
"2020-02-07T09:00:00Z",
"2020-02-07T12:00:00Z",
"2020-02-07T15:00:00Z",
"2020-02-07T18:00:00Z",
"2020-02-07T21:00:00Z",
"2020-02-08T00:00:00Z",
"2020-02-08T03:00:00Z",
"2020-02-08T06:00:00Z",
"2020-02-08T09:00:00Z",
"2020-02-08T12:00:00Z",
"2020-02-08T15:00:00Z",
"2020-02-08T18:00:00Z",
"2020-02-08T21:00:00Z",
"2020-02-09T00:00:00Z",
"2020-02-09T03:00:00Z",
"2020-02-09T06:00:00Z",
"2020-02-09T09:00:00Z",
"2020-02-09T12:00:00Z",
"2020-02-09T15:00:00Z",
"2020-02-09T18:00:00Z",
"2020-02-09T21:00:00Z",
"2020-02-10T00:00:00Z",
"2020-02-10T03:00:00Z",
"2020-02-10T06:00:00Z",
"2020-02-10T09:00:00Z",
"2020-02-10T12:00:00Z",
"2020-02-10T15:00:00Z",
"2020-02-10T18:00:00Z",
"2020-02-10T21:00:00Z",
"2020-02-11T00:00:00Z",
"2020-02-11T03:00:00Z",
"2020-02-11T06:00:00Z",
"2020-02-11T09:00:00Z",

```

"2020-02-11T12:00:00Z",
    "2020-02-11T15:00:00Z",
    "2020-02-11T18:00:00Z",
    "2020-02-11T21:00:00Z",
    "2020-02-12T00:00:00Z",
    "2020-02-12T12:00:00Z",
    "2020-02-13T00:00:00Z",
    "2020-02-13T12:00:00Z",
    "2020-02-14T00:00:00Z",
    "2020-02-14T12:00:00Z",
    "2020-02-15T00:00:00Z",
    "2020-02-15T12:00:00Z",
    "2020-02-16T00:00:00Z",
    "2020-02-16T12:00:00Z",
    "2020-02-17T00:00:00Z",
    "2020-02-17T12:00:00Z",
    "2020-02-18T00:00:00Z"
  ]
}
},
"Dewpoint_temperature_height_above_ground": {
  "description": {
    "en": "Dewpoint_temperature_height_above_ground"
  },
  "unit": {
    "label": {
      "en": "kelvin"
    },
    "symbol": {
      "value": "K",
      "type": "http://data.example.org/metadata/uom/UCUM/K"
    }
  },
  "observedProperty": {
    "id": "http://data.example.org/metadata/grib2/codeflag/4.2-0-0-6",
    "label": {
      "en": "Dewpoint_temperature_height_above_ground"
    }
  },
  "measurementType": {
    "method": "instantaneous"
  },
  "extent": {
    "horizontal": {
      "name": [
        "longitude",
        "latitude"
      ],
      "coordinates": [
        "x",
        "y"
      ],
      "geographic": "BB0X[359.875,90.125,-0.125,-90.125]"
    },
    "vertical": {

```