## **CS546 Parallel and distributed Processing**

## **Programming Assignment**

## Design

In this assignment, we have to implement a simple MPI-IO program. The homework has two parts.

1. One is to simply gain some familiarity with MPI-IO. MPI-IO will likely be part of whatever I/O stack you will be using in an HPC environment. We want each MPI process to write its rank to a common file using The MPI-IO interface.

Basically a parallel I/O system for distributed memory architectures will need a mechanism to specify collective operations and specify noncontiguous data layout in memory and file .Reading and writing in parallel is like receiving and sending messages. Hence, an MPI-like machinery is a good setting for Parallel I/O

In the first part, we want each MPI process to write its rank to a common file. In command line line argument, it will read N (number of processes), Output file name to print rank of each process. Here, each process participates in writing a portion of a common file.

Initially we have declare file pointer using :MPI\_File fh.I used the MPI functions for writing must be

Preceded by a call to MPI\_File\_open to open a file.

int MPI\_File\_open(MPI\_Comm comm, char \*filename,int amode, MPI\_Info info, MPI\_File \*fh).

Then, While opening the file in the write mode, use the appropriate flag/s in MPI\_File\_open: MPI MODE WRONLY for writing.

To write the rank to a common file, we need to calculate the displacement i.e. number of bytes to skip from the start of the file. I've taken size of buffer is 4. and calculated offset for each rank and stored offset, rank into buffer as follows.

```
buf[0] =offset;
buf[1] =rank;
buf[2] =0;
buf[3] =0;
```

I've used MPI\_File\_write\_at to writedata as int MPI\_File\_write\_at(MPI\_File fh, MPI\_Offset offset,void \*buf, int count, MPI\_Datatype datatype,MPI\_Status \*status). And Close the file using: MPI\_File\_close(MPI\_File fh). Moreover, I added error handling to all the MPI Functions. If error occurs,it will throw an error.

Sample output : od	d -td -v abc	.txt		
0000000	0	0	0	0
0000020	16	1	0	0
0000040	32	2	0	0
0000060	48	3	0	0
0000100	64	4	0	0
0000120	80	5	0	0

0000140	96	6	0	0
0000160	112	7	0	0
0000200	128	8	0	0
0000220	144	9	0	0
0000240	160	10	0	0
0000260	176	11	0	0
0000300	192	12	0	0
0000320	208	13	0	0
0000340	224	14	0	0
0000360	240	15	0	0
0000400				

2. The second part is to build a parallel I/O benchmark using MPI-IO. In this Benchmark, we will open a temporary file, write random data to a file, and close the file. Then we will open it again, read the data from the file and close it again. All operations are performed by each rank to a common file.

Basically a parallel I/O system for distributed memory architectures will need a mechanism to specify collective operations and specify noncontiguous data layout in memory and file .Reading and writing in parallel is like receiving and sending messages. Hence, an MPI-like machinery is a good setting for Parallel I/O

In the second part, we have to build a parallel I/O benchmark using MPI-IO. we will open a temporary file, write random data to a file, and close the file. Then we will open it again, read the data from the file and close it again. All operations are performed by each rank to a common file. At the end, we have delete the file.

Initially read the arguments number of processes, outputfile to print timings, print ranks and MB for each rank. we need to open the file and write random data as follows: Firstly, we have declare file pointer using :MPI\_File fh.I used the MPI functions for writing must be preceded by a call to MPI\_File\_open to open a file.

int MPI File open(MPI Comm comm, char \*filename, int amode, MPI Info info, MPI File \*fh).

Then, While opening the file in the write mode, use the appropriate flag/s in MPI\_File\_open: MPI\_MODE\_WRONLY for writing.

I've assigned 1MB(long N=5152\*512/2) and calculated total size for each rank as follows: N=N\*p.where p is Mb for each rank. Based on I have written random data of size in to buffer and calculated offset to displacement.

Then,I've used MPI\_File\_write\_at to writedata as int MPI\_File\_write\_at(MPI\_File fh, MPI\_Offset offset,void \*buf, int count, MPI\_Datatype datatype,MPI\_Status \*status). And Close the file using: MPI\_File\_close(MPI\_File fh). Moreover, I added error handling to all the MPI Functions. If error occurs,it will throw an error.

Now,I have to open the file and read the data form a file which we written data. I used the MPI functions for writing must be preceded by a call to MPI\_File\_open to open a file.

int MPI\_File\_open(MPI\_Comm comm, char \*filename,int amode, MPI\_Info info, MPI\_File \*fh).

Then, While opening the file in the read mode, use the appropriate flag/s in MPI\_File\_open: MPI\_MODE\_RDONLY for Reading.

I've assigned 1MB(long N=5152\*512/2) and calculated the buffer size to read data based on displacement from a file as follows.

```
bufsize= N/size;
nints= bufsize/sizeof(long);
long buf1[nints];
```

Then,I've used MPI\_File\_read\_at to read data as int MPI\_File\_read\_at(fh, rank\*bufsize, buf, nints, MPI\_LONG, &status1);And Close the file using: MPI\_File\_close(MPI\_File fh). Moreover, I added error handling to all the MPI Functions. If error occurs, it will throw an error. And deleted temporary file.

And using MPI\_Wtime(),I've calculated the reading, writing timings for each rank.