

## Quiz 5

Name: \_\_\_\_\_

**Question 1. (10pt)** Given:

```
void fFunc(int *ptr, int size);    // ptr to an array with size
void gFunc(int array[], int size); // array with size
void hFunc(int);
void jFunc(int&);
void kFunc(int*);

int main() {
    int myArray[5] = {1, 2, 3, 4, 5};
    int *ptr;

    // Your code comes here
}
```

- a. (1pt) Please show how to call fFunc() with myArray as argument.

**fFunc(myArray, 5)**

- b. (1pt) Please show how to call gFunc() with myArray as argument.

**gFunc(myArray, 5)**

- c. (2pt) Please show how to call hFunc() with index-0 element of myArray as argument.

**hFunc(myArray[0])**

- d. (3pt) Please show how to call jFunc() with index-1 element of myArray as argument.

**jFunc(myArray[1])**

- e. (3pt) Please show how to call kFunc() with index-2 element of myArray as argument.

**kFunc( &(myArray[2]) )**

**Question 3. (20pt)**

- a. (2pt) Write a C++ function to receive an integer and return a boolean indicating if the integer is an even number.

```
bool IsEven(int n) {  
    return ((n % 2) == 0);  
}
```

- b. (4pt) Please show the implementation of the following function:

```
int ExtractEven(int input[], int size, int output[])  
    // Function goes through input[], copy and return even numbers in output[]  
    // size: size of the input array  
    // returns: size of the output array  
    // Pre-condition: output[] is allocated with size-number of elements  
    // For example:  
    //     input = {1, 2, 2, 3, 4, 5}    size=6  
    // When return:  
    //     output = {2, 2, 4}, return value 3
```

```
int ReturnEven(int input[], int size, int output[]) {  
    int out_size = 0;  
    for (int i = 0; i < size; i++) {  
        if (IsEven(input[i])) {  
            output[out_size++] = input[i];  
        }  
    }  
    return out_size;  
}
```

c. (6pt) Please show the implementation of the following function:

```
int KeepEvenAndCompact(int input[], int size)
// Function goes through input[], remove odd numbers, the resulting input[]
// must be contain only even numbers found in the same order as the input[]
// size: size of the input array
// returns: size of the resulting array
// For example:
//      input = {1, 2, 2, 3, 4, 5}    size=6
// When return:
//      input = {2, 2, 4}, return value 3
```

```
int KeepEvenAndCompact(int input[], int size) {
    int returnSize = 0;
    for (int i = 0; i < size; i++) {
        if (IsEven(input[i])) {
            input[returnSize] = input[i];
            returnSize++;
        }
    }
    return returnSize;
}
```

d. (8pt) Please show the implementation of the following function:

```
int KeepEvenCompactAndUnique(int input[], int size)
// Function goes through input[], remove odd numbers and any duplicates,
// the resulting input[] contains only unique even numbers found in the
// same order as the input[]
// size: size of the input array
// returns: size of the resulting array
// For example:
//     input = {1, 2, 2, 3, 4, 5}    size=6
// When return:
//     input = {2, 4}, return value 2

int RemoveCompactAndUnique(int input[], int size) {
    int returnSize = 1;
    for (int i = 1; i < size; i++) {
        if (IsEven(input[i])) {
            bool dup = false;
            int check = 0;
            while ((!dup) && (check < returnSize)) {
                dup = (input[check] == input[i]);
                check++;
            }
            if (!dup) { // unique odd number ...
                input[returnSize] = input[i];
                returnSize++;
            }
        }
    }
    return returnSize;
}
```