

Infrastructure as Code

CSSE6400

Brae Webb

March 21, 2022

Infrastructure as Code

How did we get here?

Pre-2000

The *Iron Age*

Iron Age



Iron Age



Introducing...

The *Cloud Age*

The Cloud Age



When faced with complexity

Automate it!

The larger story

Server Config Config Management

The larger story

Server Config Config Management
Application Config Config Files

The larger story

Server Config Config Management
Application Config Config Files
Provisioning Infrastructure Code

The larger story

Server Config Config Management
Application Config Config Files
Provisioning Infrastructure Code
Building Continuous Integration

The larger story

Server Config	Config Management
Application Config	Config Files
Provisioning	Infrastructure Code
Building	Continuous Integration
Deployment	Continuous Deployment

The larger story

Server Config	Config Management
Application Config	Config Files
Provisioning	Infrastructure Code
Building	Continuous Integration
Deployment	Continuous Deployment
Testing	Automated Tests

The larger story

Server Config Config Management

Application Config Config Files

Provisioning Infrastructure Code

Building Continuous Integration

Deployment Continuous Deployment

Testing Automated Tests

Database Administration Schema Migration

The larger story

Server Config Config Management

Application Config Config Files

Provisioning Infrastructure Code

Building Continuous Integration

Deployment Continuous Deployment

Testing Automated Tests

Database Administration Schema Migration

Specifications Behaviour Driven Development

Definition 1. Infrastructure Code

Code that provisions *infrastructure resources*.

Definition 2. Infrastructure Code

Code that provisions *infrastructure resources*.

Definition 3. Infrastructure Resources

Compute resources, networking resources, and storage resources.

Infrastructure Code



```
1  #!/bin/bash

3  SG=$(aws ec2 create-security-group ...)

5  aws ec2 authorize-security-group-ingress --group-id "$SG"

7  INST=$(aws ec2 run-instances --security-group-ids "$SG" \
8      --instance-type t2.micro)
```

```
1 import boto3

3 def create_instance():
4     ec2_client = boto3.client("ec2", region_name="us-east-1")
5     response = ec2.create_security_group(...)
6     security_group_id = response['GroupId']

8     data = ec2.authorize_security_group_ingress(...)

10     instance = ec2_client.run_instances(
11         SecurityGroups=[security_group_id],
12         InstanceType="t2.micro",
13         ...
14     )
```

```
1 resource "aws_instance" "hextris-server" {
2     instance_type = "t2.micro"
3     security_groups = [aws_security_group.hextris-server.name]
4     ...
5 }

7 resource "aws_security_group" "hextris-server" {
8     ingress {
9         from_port = 80
10        to_port = 80
11        ...
12    }
13    ...
14 }
```

Question

Notice anything different?

The *main* difference

Imperative vs. Declarative

Infrastructure Code

- Provisions and manages *infrastructure resources*.

Infrastructure Code

- Provisions and manages *infrastructure resources*.
- Only one part of the movement to *automate* the complexities of development.

Infrastructure Code

- Provisions and manages *infrastructure resources*.
- Only one part of the movement to *automate* the complexities of development.
- Ranges from simple shell scripts up to...?

Infrastructure Code

- Provisions and manages *infrastructure resources*.
- Only one part of the movement to *automate* the complexities of development.
- Ranges from simple shell scripts up to...?
- Tendancy to be *declaritive*.

Typo?

Infrastructure Code \neq Infrastructure *as* Code

Definition 4. Infrastructure as Code

Following the same *good coding practices* to manage Infrastructure Code as standard code.

Warning!

Infrastructure as Code still *early* and quite *bad*.

Question

What are *coding practices*?

Good Coding Practice #1

Everything as code

```
1 #!/bin/bash
3 ./download-dependencies
4 ./build-resources
5 cp -r output/* artifacts/
```

```
1 #!/bin/bash
3 ./download-dependencies
4 ./build-resources
5 cp -r output/* artifacts/
```

```
$ cp: directory artifacts does not exist
```

```
1 resource "aws_instance" "hextris-server" {  
2     instance_type = "t2.micro"  
3     security_groups = ["sg-6400"]  
4     ...  
5 }
```

```
1 resource "aws_instance" "hextris-server" {
2     instance_type = "t2.micro"
3     security_groups = [aws_security_group.hextris-server.name]
4     ...
5 }

7 resource "aws_security_group" "hextris-server" {
8     ingress {
9         from_port = 80
10        to_port = 80
11        ...
12    }
13    ...
14 }
```

Good Coding Practice #2

Version control

Benefits

1. Reproducible.
2. Restorable.
3. Accountable.

Good Coding Practice #3

Automation

Good Coding Practice #4

Re-use Code

Good Coding Practice #5

Testing