

Coffee Shop

Software Architecture

April 4, 2022

Brae Webb

1 Brief

This week we have introduced the concept of event-driven architectures. In this tutorial, we will explore and document a project which implements this type of architecture.

<https://github.com/CSSE6400/scalable-coffee-shop>

The project is an implementation of a coffee shop, implemented by [Sebastian Daschner](#). The coffee shop exposes a HTTP API which can be used to stock beans and place drink orders.

Our goal is to run the software locally, begin exploring the implementation, and create a C4 diagram to serve as documentation.

2 Installation and Running

For the first 15 to 20 minutes of the tutorial, we will install the application. To install, we recommend that you use Docker Compose. The project has a `docker-compose.yml` configuration in the top-level folder.

```
1 $ git clone https://github.com/CSSE6400/scalable-coffee-shop
2 $ cd scalable-coffee-shop
3 $ docker-compose up
```

Ideally this command will execute without error and start servicing requests as shown in the examples below.

Info

The `docker-compose up` command produces a lot of interleaving output. If you need to debug why one particular service, e.g. the beans service, is not working, you can use the `logs` command to inspect it.

```
1 $ docker-compose logs -f beans
```

```
1 $ curl http://localhost:8002/beans/resources/beans -i -XPOST \
2   -H 'content-type: application/json' \
3   -d '{"beanOrigin": "Colombia", "amount": 10}'
4
5 HTTP/1.1 204 No Content
6 X-Powered-By: Undertow/1
7 Server: WildFly/10
8 Date: Fri, 17 Nov 2017 20:49:26 GMT
```

```
10 $ curl http://localhost:8002/beans/resources/beans
11 {"Colombia":10}
```

```
1 $ curl http://localhost:8001/orders/resources/orders/ -i -XPOST \
2   -H 'Content-type: application/json' \
3   -d '{"beanOrigin": "Colombia", "coffeeType": "Espresso"}'

5 HTTP/1.1 202 Accepted
6 Connection: keep-alive
7 X-Powered-By: Undertow/1
8 Server: WildFly/10
9 Location: http://localhost:8001/orders/resources/orders/c099c158-b748-4115-bed3-7
   b5dfff70771
10 Content-Length: 0
11 Date: Fri, 17 Nov 2017 20:51:16 GMT

13 $ curl http://localhost:8001/orders/resources/orders/c099c158-b748-4115-bed3-7
   b5dfff70771
14 {"status":"started","type":"espresso","beanOrigin":"Colombia"}
```

3 Documentation

In the documentation assignment, you will have gained some experience with creating diagrams of software architecture. In the tutorial today, we will be using those skills to create documentation for the coffee shop application using diagrams. You can use your favourite diagram software for this task. For the tutorial, you should produce:

1. A context diagram for the system.
2. A container diagram of the system.
3. A component diagram for at least the Kafka server.

For reference on how event-driven architectures should look in C4, please refer to the Event Driven Architecture handout [1].

Info

You do not need an in-depth understanding of Kafka to document the architecture. For a simple introduction to the concepts of Kafka see the Hortonworks documentation [2]. For a more in-depth look at how Kafka actually works, read the article by Stopford [3].

References

- [1] R. Thomas, “Event-driven architecture,” April 2022. <https://csse6400.uqcloud.net/handouts/event.pdf>.
- [2] H. D. Platform, “Basic kafka concepts.” https://docs.cloudera.com/HDPDocuments/HDP2/HDP-2.2.4/bk_storm-user-guide/content/basic-kafka-concepts.html.
- [3] B. Stopford, “Apache kafka as an event-driven backbone for service architectures.” <https://www.confluent.io/blog/apache-kafka-for-service-architectures/>, July 2017.