Serverless Architecture

Software Architecture

Richard Thomas

May 12, 2025

Oxymoron 1. Serverless

Logic running on someone else's server.

Developers can focus on logic, not infrastructure to deliver it.

Definition 0. Backend as a Service (BaaS)


Cloud-hosted applications or services that deliver functionality used by an application front-end.

• Front-end may be a SPA or mobile app.


application's functionality.

- Back-end provides sophisticated functionality (e.g. database,
- machine learning, location services, authentication, ...).Front-end ties back-end services together to deliver the

BaaS Iceberg [Brunko, 2019]



BaaS Example



- Example of simple system with back-end functionality delivered *entirely* via BaaS.
- Feature-rich front-ends coordinate behaviour delivered by BaaS.
- Consequence: Front-ends are tightly coupled to BaaS.
- Consequence: Front-ends have both UI and functional behaviour logic.
- Front-end could have a layered design, though many SPAs don't.


Definition 0. Functions as a Service (FaaS)

Application logic that is triggered by an event and runs in a *transient*, *stateless* compute node.


- Node may only exist for duration of function call.
- Server infrastructure (e.g. type of node, lifespan, scaling, ...) are managed by hosting provider.
- e.g. AWS Lambda, Google App Engine, Azure Automation,

. . . .

FaaS Iceberg [Brunko, 2019]



FaaS Example




- Example of simple system with back-end functionality delivered by FaaS.
 - Some services delivered via BaaS.
 (e.g. Authentication not shown on diagram for simplicity.)
- Feature-rich front-ends coordinate behaviour delivered by FaaS.
- Front-ends invoke functions via an API.
- API Gateway provides some separation between front-end and functions.
- Allows a bit more separation between UI and logic.

Definition 0. Serverless Architecture Software system delivering functionality

Software system delivering functionality through BaaS or FaaS.

- Many people focus on FaaS when considering Serverless.
- Mobile App or Single Page Web App (SPA) coordinate services.
- Front-end ties back-end services together to deliver application's functionality.

Sahara Browse & Order — Serverless



- Only browse, search and purchase are shown.
- Uses both BaaS & FaaS.
- Shopping cart is implemented within the web and mobile app for this architecture.
- Order Scenario 1: Customer checks out their shopping cart in the web or mobile app.
- Order Scenario 2: App calls Purchase Products function via API Gateway.
- Order Scenario 3: Purchase Products stores order in DB and sends a payment request to Payment Provider.
- Order Scenario 4: We provide Payment Provider with API end point to call to report payment result.
- Order Scenario 5-9: Notes continue on next slide.

Sahara Fulfilment — Serverless **Email Service** AWS API Gateway. oordinates fulflime Requests Lambda Service **Order Status** Sahara Web Application Order Status Order Database Fulfill Order Order Picking Order Database

[REST API JSON/HTTPS

- Only fulfilment functions are shown.
- Shows Lambda Service polling Queue, demonstrating how Lambda Functions are invoked via events in a message queue.
- Fulfilment Scenario 1: Lambda Service monitors Queue for 'ship order' messages.
- Fulfilment Scenario 2: Lambda Service batches groups of 'ship order' messages and sends them to Fulfill Order function.
- Fulfilment Scenario 3: Fulfil Order gets order details from DB and sends pick list to Fulfilment App.
- Fulfilment Scenario 4: When order is shipped, Fulfilment App calls Order Shipped function via API Gateway.
- Fulfilment Scenario 5-8: Notes continue on next slide.

- Automatic scaling
 - Multiple instances of function

- Automatic scaling
- Multiple instances of function
- Reduced cost for dynamic loads
- No server idle time

- Automatic scaling
 - Multiple instances of function
- Reduced cost for dynamic loads
 - No server idle time
- Reduced server management

- Automatic scaling
 - Multiple instances of function
- Reduced cost for dynamic loads
 - No server idle time
- Reduced server management
- Easier to run closer to client
 - Launch in same zone as client

BaaS Tradeoffs

- Front-end accesses database directly
 - Front-end needs to sanitise inputs
 - Easy to spoof messages from front-end
 - Hope DB provider is secure

Spoofing messages is an issue for all BaaS services.

BaaS Tradeoffs

- Front-end accesses database directly
 - Front-end needs to sanitise inputs
 - Easy to spoof messages from front-end
 - Hope DB provider is secure
- Application logic is in front-end
 - Less modularisation
 - Duplication of logic with multiple front-ends
 - Web, mobile, ...

- Modern expectations are that almost all systems will have multiple front-ends.
- Duplication of front-end logic is a smaller, but still partial, concern for FaaS.

BaaS Tradeoffs

- Front-end accesses database directly
 - Front-end needs to sanitise inputs
 - Easy to spoof messages from front-end
 - Hope DB provider is secure
- Application logic is in front-end
 - Less modularisation
 - Duplication of logic with multiple front-ends

• Web, mobile, ...

- No control over server optimisation

• No server state

FaaS Tradeoffs

- All state needs to be saved (e.g. Redis, S3, ...)
 - Not just persistent state

- Server running function can be killed when function is not running.
- Can occasionally send messages to functions to keep them alive — Not ideal.

FaaS Tradeoffs • No server state

- - All state needs to be saved (e.g. Redis, S3, ...)
 - Not just persistent state

• AWS Lambda – up to 15 minutes

- Execution duration
 - Can't be long running process

• No server state • All state needs to be saved (e.g. Redis, S3, ...)

FaaS Tradeoffs

- Not just persistent state
- Execution duration
 - Can't be long running process
- AWS Lambda up to 15 minutes
- Startup latency • Functions take time to start

 - Some languages worse than others (e.g. Java)

Java has concurrency benefits over other languages.

FaaS Tradeoffs • No server state • All state needs to be saved (e.g. Redis, S3, ...) • Not just persistent state • Execution duration • Can't be long running process • AWS Lambda – up to 15 minutes • Startup latency • Functions take time to start • Some languages worse than others (e.g. Java) • Proliferation of functions • Loss of encapsulation

When is serverless appropriate?

When is serverless appropriate?

- Rich client apps with common backend
 - BaaS

When is serverless appropriate?

- Rich client apps with common backend
 - BaaS
- High latency processing
 - Within function duration constraints

When is serverless appropriate?

- Rich client apps with common backend
 - BaaS
- High latency processing
 - Within function duration constraints
- Apps with variable load
 - Take advantage of auto-scaling

When is serverless *not* appropriate?

When is serverless not appropriate?

- Quick response required
 - Can't wait for FaaS to start

When is serverless not appropriate?

- Quick response required
 - Can't wait for FaaS to start
- Compute intensive processing

When is serverless not appropriate?

- Quick response required
 - Can't wait for FaaS to start
- Compute intensive processing
- Apps with steady load
 - Server-based approaches are cheaper

Self-Study Exercise

- Redesign your scalability assignment to be serverless.
 - What parts of your design would benefit from being serverless?
- Implement your revised design.

Pros & Cons • Modularity: Deployed functions are naturally modular. Extensibility • Modularity: Higher-level abstractions to group deployed 000 Reliability functions is difficult. Interoperability • Testability: Unit testing FaaS functions is easy. • Testability: Integration testing is harder. Scalability • Maintainability: Backend modularity and independence 00 Deployability should facilitate its maintenance. Modularity • Maintainability: Frontend contains UI and application logic. Testability • Security BaaS: Front-end access database directly. No server-side protection of db. Maintainability • Security FaaS: Every function needs its own security policy Security (e.g. IAM), which is easy to get wrong.

Simplicity

References

[Brunko, 2019] Brunko, P. (2019).

Serverless architecture: When to use this approach and what benefits it gives.

https://apiko.com/blog/serverless-architecture-benefits/.