

Application Programming Interfaces (APIs)

Software Architecture

March 28, 2022

Brae Webb




Figure 1: A map of communication techniques from Designing Data-Intensive Applications [1].

1 This Week

This week our goal is to:

- explore the various techniques developers use to communicate between distributed systems;
- deploy a static website on an S3 bucket; and
- configure the static website to communicate with the EC2 backend.

2 Communication

This week we have started to explore the world of distributed systems. The world relies (heavily) on distributed systems, there is no machine in the world powerful enough to process the requests Google receives every second. We need to have many hundreds of machines working seamlessly together. This inter-machine teamwork requires machines to know how to talk to each other. For the practical this week we will look at APIs as a mechanism for communication.

3 Data Formats

When engaging in communication we wish to exchange information. On computer systems information is stored at runtime in memory as primitive data which your programming language can interpret; bytes, integers, strings, etc. In object-oriented languages, primitive data is wrapped up into useful packages: objects. If we want this information to escape the confines of our programming language runtime, we need to package it up in a language-independent format. For a format to be language-independent we just need many languages to implement an encoding and decoding mechanism for the format. We have a number of language-independent formats available but a few defacto standards.

3.1 XML

Extensible Markup Language (XML) is one of the most widely used language-independent formats. The use cases of XML are extensive, it's the [foundation for many popular utilities¹](#), such as SVG file formats, SAML authentication, RSS feeds, and ePub books.

```
» cat csse6400.xml
1 <root>
2   <item>
3     <key>Course Code</key>
4     <value>CSSE6400</value>
5   </item>
6   <item>
7     <key>Course Title</key>
8     <value>Software Architecture</value>
9   </item>
10 </root>
```

XML is designed as a markup language, similar to HTML, it is not designed as a data exchange format. Developers have come to point out that the verbosity and complexity of XML, compared to alternatives such as JSON, are deal breakers. While XML can be used as a data exchange format it is not designed for it, and as a result APIs built around XML as a data format are becoming less common.

3.2 JSON

JavaScript Object Notation (JSON) is quickly replacing XML as the data format used in APIs. As you will note, it is more succinct and communicates the important points to a human reader better. Although the

¹https://en.wikipedia.org/wiki/List_of_XML_markup_languages

popularity of JSON is largely due to the compatibility with JavaScript which has taken over web development. JSON is the map-esque data type in JavaScript. Detractors of JSON claim that its main disadvantage over XML is that it lacks a schema. However, [schemas are possible in JSON²](#), they are optional, just as in XML but much less used than XML.

```
» cat csse6400.json
1 {
2   "Course Code": "CSSE6400",
3   "Course Title": "Software Architecture"
4 }
```

3.3 MessagePack

It should not be a surprise that the JSON and XML formats are not resource efficient. Nowadays, we are less concerned with squeezing data into a tiny amount of data on the hard drive as our hard drives are massive. However, we are often concerned with how much data is being transmitted via network communication.

In the example JSON snippet above, we use 78 bytes to encode the message. [MessagePack³](#) is a standard for encoding and decoding JSON. When encoding our original JSON snippet with MessagePack we shrink to just 57 bytes. At our scale, a negligible difference, but at the scale of terrabytes or petabytes, a significant consideration.

```
» cat csse6400.msgpack
1 82 ab 43 6f 75 72 73 65 20 43 6f 64 65 a8 43 53 53 45 36 34 30 30 ac 43 6f 75 72 73
   65 20 54 69 74 6c 65 b5 53 6f 66 74 77 61 72 65 20 41 72 63 68 69 74 65 63 74 75
   72 65
```

Info

For those interested, 0x82 specifies a map type (0x80) with two fields (0x02). Followed by a string type (0xa0) of size eleven (0x0b). The rest is left as an exercise: <https://github.com/msgpack/msgpack/blob/master/spec.md>.

3.4 Protobuf

Protocol Buffers (protobuf) is another type of binary encoding. However, unlike MessagePack, the format was designed from scratch, allowing a more compact and better designed format. Protobufs require all data to be defined by a schema. For example:

```
» cat csse6400.proto
```

²<https://json-schema.org/>

³<https://msgpack.org/>

```
1 message Course {  
2     required string code = 1;  
3     required string name = 2;  
4 }
```

Protobufs differ from XML, JSON, and MessagePack via their method of integration. In all other examples, your language would have a library to encode and decode the data format into and out of your language's type system. With protobuf, an external tool, *protoc*, takes the schema and generates a model of the schema in your target language. This gives every language a native method to interact with the data format; it often means that developers don't need to be aware of the underlying encoding.

```
» cat csse6400.java  
  
1 Course softarch = Course.newBuilder()  
2     .setCode("CSSE6400")  
3     .setName("Software Architecture")  
4     .build();  
5 output = new FileOutputStream(args[0]);  
6 softarch.writeTo(output);
```

4 Application Programming Interfaces

- XML-RPC
- SOAP
- REST
- JSON-RPC
- Maybe OData?
- GraphQL
- gRPC

References

- [1] M. Kleppmann, *Designing Data-Intensive Applications: The big ideas behind reliable, scalable, and maintainable systems*. O'Reilly Media, Inc., March 2017.