

# Scaling Stateless Components

Software Architecture

March 29, 2023

Evan Hughes &amp; Anna Truffet &amp; Brae Webb



## 1 This Week

Our goal is to scale out the stateless component of our TaskOverflow application across multiple compute instances. Specifically we will need to:

- Route traffic to our deployed TaskOverflow application with a load balancer.
- Scale out TaskOverflow instances with autoscaling.
- Check the status of our instances with a healthcheck.
- Dynamically scale our application based on load.

## 2 Load Balancers

Load balancing distributes a load over a set of resources. For example, balancing network traffic across several servers. Load balancing is crucial to the scalability of modern systems, as often, one physical device cannot handle the volume of requests or the processing demand (e.g. the large amount of network traffic for a large website).

A service which load balances, is called a **Load Balancer**.

### 2.1 Routing Algorithms

A load balancer can implement many techniques to select which resource to route incoming requests toward, these techniques are the load balancer's routing algorithm.

Below are several common routing techniques. There are many other generic and bespoke routing algorithms that are not listed.

**Round Robin** allocates requests to the next available server regardless of where the last request was sent. It is simple, and in practice, works effectively.

**Least Connections** sends the next request to the node with the fewest current connections. The load balancer is responsible for tracking how many connections exist to each node.

**Weighted Least Connections** sends the next request to the node with the least weighted connections. This is similar to the above least connections method, however, each node has an associated weight. This allows certain nodes to be preferred over others. This is useful if we have an unequal distribution of compute power. We would want to give smaller nodes a reduced load in comparison to other more powerful nodes.

**Consistent Hashing** In some cases we may want a user to consistently be routed to a specific node. This is useful for multiple transactions that need to be done in a consistent order or if the data is stored/-cached on the node. This can be done by hashing the information in the request payload or headers and then routing the request to the node that handles hashes in the range of the computed hash.

### 2.2 Health Checks

When load balancing, it is important to ensure that the nodes to which we route requests are able to service the request. A good health check can save or break your service. Consider the two following examples from UQ's Information Technology Services (ITS):

**Example 1** Early in my career, I, Evan Hughes, setup a multi-node Directory Server at UQ under the hostname of `ldap.uq.edu.au`. This server was a NoSQL database which implemented the LDAP protocol and supported UQ Authenticate, UQ's Single Sign-On service.

The service had a load balancer which checked that port 389 was open and reachable. This worked well most of the time. However, the health check was too weak. When

1. a data-center outage occurred; and
2. the storage running the service disappeared; but
3. the service was still running in memory.

The health check passed, but in reality, the service was talking to dead nodes, causing upstream services to have intermittent failures.

**Example 2** During the rollout of a new prompt for UQ Authenticate, which required users to go to my.UQ to provide verified contact details – the Blackboard (learn.uq.edu.au) service went completely offline. The health check for Blackboard at the time completed a full authentication as a test user to ensure everything was functioning as expected. Once this user was enrolled into the new rollout, the health checks started reporting failures and within a matter of minutes the entire pool of nodes were shutdown. This health check was too broad and was not isolated enough to the service that it was checking.

A lot of services will provide a health check endpoint or a metrics endpoint which can help the engineer setup a proper level of health check. We want a health check that is specific enough for the service that it is checking but not so specific that it is too brittle. For the TaskOverflow application that we have been building so far, a reasonable health check would be that the health endpoint ensures the database is available and that the application is able to connect to it.

## 3 Load Balancers in AWS

### 3.1 Types of AWS Load Balancers

Not all load balancers are the same. Some load balancers inspect the transmitted packets to correctly route the packet. We will cover two types of load balancers provided by AWS:

**Application Load Balancer** is an OSI layer 7<sup>1</sup> load balancer which routes traffic based on the request's content. This is useful for services using HTTP, HTTPS, or any other supported protocol.

**Network Load Balancer** is an OSI layer 4<sup>2</sup> load balancer which routes traffic based on the source and destination IP addresses and ports. This is useful for services that are using TCP or UDP.

### 3.2 AWS Load Balancer Design

An AWS Elastic<sup>3</sup> Load Balancer has three distinct components.

**Listeners** allows traffic to enter the Elastic Load Balancer. Each listener has a port (e.g. port 80) and a protocol (e.g. HTTP) associated with it.

**Target Groups** are groups of nodes which the load balancer can route to. Each target group has a protocol and a port associated with it, allowing us (the programmer) to switch ports on the way through the load balancer. This is useful if the targets are using a different port to the ports we want to expose.

**Load Balancer** is the actual load balancer that routes the traffic to the target groups based on rules that we setup. The load balancer has a DNS name that we can use to route traffic to it. The load balancer also has a security group that we can use to control what traffic can enter the load balancer.


---

<sup>1</sup>OSI layer 7: Application, in this case HTTP/HTTPS/etc

<sup>2</sup>OSI layer 4: Transport, in this case TCP/UDP

<sup>3</sup>Elastic, in a cloud computing context, refers to the system's ability to adapt to workload by starting and stopping infrastructure services to meet demand.

## AWS Application Load Balancer Components



### 3.3 Autoscaling in AWS

Instead of creating the maximum amount of services we predict we will need, we can automatically scale the number of nodes we need to minimise resources. When the load is low, we operate with minimal nodes. When the load is high, we increase the number of nodes available to cope.

To compute the resources needed, AWS relies on triggers from CloudWatch and scaling policies. Some premade triggers are based around a node's

- CPU usage,
- memory usage, or
- network usage.

We create custom triggers based on our application's metrics.

## 4 Load Balancing TaskOverflow

This week we are going to explore load balancing the TaskOverflow service that we have been working with. The aim is to have a service that when given a lot of requests will be able to scale out the webservice nodes to handle it. This will not be a full solution to the scaling issue as our database is still a single node, but it will be a good start. Other methods could also be employed to help deal with the load like caching but we will leave that for another day.


Start with the github repository provided in class and install Terraform as it will be required this week. You will also need to start your learner lab and copy the credentials into a credentials file into the root of

the repository. In the repository you will also see two different folders, one is the starter for the EC2 path and the other is the starter for the ECS path. Once you have chosen which path you wish to take, copy the contents of the folder into the root of the repository.

As per last week, we encourage that you take Path B first and then peruse Path A, if you have time. This week Path A shows an alternative method to autoscaling.

## 4.1 [Path A] EC2

Congratulations! You have chosen to go down the EC2 path. This week we need to create an AutoScaling Group and a Load Balancer to handle the scaling of our service. Our goal is to implement the deployment diagram below.



To get started, we need to modify how we create our EC2 instances. Instead of manually creating them we are going to have to tell AWS how to deploy them for us. We can do this by converting our EC2 instance into a Launch Template. Our launch template is going to look very similar to the instance we had last week, with a few variables changing. This includes that `user_data` must be stored as a base64 encoded string. Some of these changes have been highlighted below. Copy this code into a file called `ec2.tf`.

```
» cat ec2.tf

resource "aws_launch_template" "todo" {
  name          = "todo-launch-template"
  image_id      = "ami-005f9685cb30f234b"
  instance_type = "t2.micro"
  key_name      = "vockey"
  user_data     = base64encode(<<-EOT
  #!/bin/bash
```

```

yum update -y
yum install -y docker
service docker start
systemctl enable docker
usermod -a -G docker ec2-user
docker run --restart always -e SQLALCHEMY_DATABASE_URI=postgresql://${local.
database_username}:${local.database_password}@${aws_db_instance.database.address
}:5432/todo -p 6400:6400 ${local.image}
EOT
)

vpc_security_group_ids = [aws_security_group.todo.id]
}

resource "aws_security_group" "todo" {
  name      = "todo"
  description = "TaskOverflow Security Group"

  ingress {
    from_port  = 6400
    to_port    = 6400
    protocol   = "tcp"
    cidr_blocks = ["0.0.0.0/0"]
  }


  ingress {
    from_port  = 22
    to_port    = 22
    protocol   = "tcp"
    cidr_blocks = ["0.0.0.0/0"]
  }

  egress {
    from_port  = 0
    to_port    = 0
    protocol   = "-1"
    cidr_blocks = ["0.0.0.0/0"]
  }
}

```

Now that we have a template and a security group, we can create the AutoScaling Group. This block defines the limits of how many instances we want to have and the template we want it to use. Copy this code into a file called `autoscaling.tf`.

## Building a AWS Load Balancer



```
» cat autoscaling.tf
```

```
resource "aws_autoscaling_group" "todo" {
    name          = "todo"
    availability_zones = ["us-east-1a"]
    desired_capacity  = 1
    max_size        = 4
    min_size        = 1

    launch_template {
        id      = aws_launch_template.todo.id
        version = "$Latest"
    }
}
```

If we deployed this now, we would get one initial instance created for us, due to the `desired_capacity` and `min_size` values. Now that we have instances we have the ability for traffic to be routed to them. Let's create a target group which will be on the internal facing side of our load balancer. This is the side that lets traffic leave the load balancer and hit the instances. Copy this code into a file called `lb.tf`.

## Building a AWS Load Balancer



```
> cat lb.tf

resource "aws_lb_target_group" "todo" {
  name      = "todo"
  port      = 6400
  protocol = "HTTP"
  vpc_id    = aws_security_group.todo.vpc_id
}
```

When the target\_group is created, we need to attach it to the autoscaling group. This is done by via the code below. Copy this into lb.tf.

```
> cat lb.tf

resource "aws_autoscaling_attachment" "todo" {
  autoscaling_group_name = aws_autoscaling_group.todo.id
  alb_target_group_arn   = aws_lb_target_group.todo.arn
}
```

With a target\_group created, we now need to attach it to a load balancer, copy this code into lb.tf. You will notice that there is also a security group attached to the load balancer. This is the firewall that sits on the front of the load balancer and allows traffic to enter the load balancer.

## Building a AWS Load Balancer



```
» cat lb.tf
```

```
resource "aws_lb" "taskoverflow" {
  name          = "taskoverflow"
  internal      = false
  load_balancer_type = "application"
  subnets       = data.aws_subnets.private.ids
  security_groups = [aws_security_group.taskoverflow.id]
}


resource "aws_security_group" "taskoverflow" {
  name          = "taskoverflow"
  description   = "TaskOverflow Security Group"

  ingress {
    from_port    = 80
    to_port      = 80
    protocol     = "tcp"
    cidr_blocks = ["0.0.0.0/0"]
  }

  egress {
    from_port    = 0
    to_port      = 0
    protocol     = "-1"
    cidr_blocks = ["0.0.0.0/0"]
  }
}
```

Now we are on the external side of the load balancer. We need to create a listener which actually creates the rules for how traffic is routed to the instances. Copy this code into lb.tf.

## Building a AWS Load Balancer



```
» cat lb.tf

resource "aws_lb_listener" "taskoverflow" {
  load_balancer_arn = aws_lb.taskoverflow.arn
  port            = "80"
  protocol        = "HTTP"

  default_action {
    type      = "forward"
    target_group_arn = aws_lb_target_group.todo.arn
  }
}
```

Deploying this, we now have achieved the architecture as requested with a dynamically scaling group of EC2s with an Application Load Balancer sitting in front which is listening on port 80 instead of 6400.

To make our autoscaling group perform dynamic scaling, we need to give it some rules about when to scale up and when to scale down. The policies below are what does this function for us. They listen to the average CPU usage of the group of instances. If the usage is above 20 percent it will scale up by 1 instance, and if it is below 10 percent it will scale down by 1 instance. We apply a cooldown period so that we do not act too aggressively to changes in CPU usage, as instances will take time to start and handle load. Copy this code into autoscaling.tf.

```
» cat autoscaling.tf
```

```

resource "aws_autoscaling_policy" "todo_scale_down" {
  name          = "todo_scale_down"
  autoscaling_group_name = aws_autoscaling_group.todo.name
  adjustment_type      = "ChangeInCapacity"
  scaling_adjustment    = -1
  cooldown           = 120
}

resource "aws_cloudwatch_metric_alarm" "todo_scale_down" {
  alarm_description  = "Monitors CPU utilization for Todo"
  alarm_actions       = [aws_autoscaling_policy.todo_scale_down.arn]
  alarm_name          = "todo_scale_down"
  comparison_operator = "LessThanOrEqualToThreshold"
  namespace            = "AWS/EC2"
  metric_name          = "CPUUtilization"
  threshold             = "10"
  evaluation_periods   = "2"
  period                = "120"
  statistic              = "Average"

  dimensions          = {
    AutoScalingGroupName = aws_autoscaling_group.todo.name
  }
}

resource "aws_autoscaling_policy" "todo_scale_up" {
  name          = "todo_scale_up"
  autoscaling_group_name = aws_autoscaling_group.todo.name
  adjustment_type      = "ChangeInCapacity"
  scaling_adjustment    = 1
  cooldown           = 120
}

resource "aws_cloudwatch_metric_alarm" "todo_scale_up" {
  alarm_description  = "Monitors CPU utilization for Todo"
  alarm_actions       = [aws_autoscaling_policy.todo_scale_up.arn]
  alarm_name          = "todo_scale_up"
  comparison_operator = "GreaterThanOrEqualToThreshold"
  namespace            = "AWS/EC2"
  metric_name          = "CPUUtilization"
  threshold             = "20"
  evaluation_periods   = "2"
  period                = "120"
  statistic              = "Average"


  dimensions          = {
    AutoScalingGroupName = aws_autoscaling_group.todo.name
  }
}

```

Head to section 4.3 to see how we can send multiple requests to our service so that the load balancer has to scale up.

## 4.2 [Path B] ECS

Congratulations! You have chosen to go down the ECS path. This week we need to create an Application Scaling Policy for our ECS service and a Load Balancer to handle the routing of our service. Our goal is to implement the deployment diagram below.



Last week, when we setup the ECS service, we noticed that we could not get an endpoint because the instance would only be provisioned after our Terraform code had run. This is because it is already a dynamic service and it wants a load balancer to service its traffic. To get started we need to create a target group which is on the internal side of the load balancer and defines where traffic can be routed to. Copy this code into `1b.tf`.

## Building a AWS Load Balancer



```
» cat lb.tf

resource "aws_lb_target_group" "todo" {
  name        = "todo"
  port        = 6400
  protocol    = "HTTP"
  vpc_id      = aws_security_group.todo.vpc_id
  target_type = "ip"

  health_check {
    path          = "/api/v1/health"
    port          = "6400"
    protocol     = "HTTP"
    healthy_threshold = 2
    unhealthy_threshold = 2
    timeout       = 5
    interval      = 10
  }
}
```


Now that we have the target group we can add it to the ECS service. Copy this code into `ecs.tf` inside the service block.

```
» cat ecs.tf

load_balancer {
  target_group_arn = aws_lb_target_group.todo.arn
  container_name   = "todo"
  container_port   = 6400
}
```

With the internal side of the load balancer done, we can create it and a firewall for the external side. This firewall allows us to restrict what traffic will be allowed to flow through the load balancer. Copy this code into lb.tf.

### Building a AWS Load Balancer



```

>> cat lb.tf

resource "aws_lb" "taskoverflow" {
  name          = "taskoverflow"
  internal      = false
  load_balancer_type = "application"
  subnets       = data.aws_subnets.private.ids
  security_groups = [aws_security_group.taskoverflow.id]
}


resource "aws_security_group" "taskoverflow" {
  name      = "taskoverflow"
  description = "TaskOverflow Security Group"

  ingress {
    from_port      = 80
    to_port        = 80
    protocol       = "tcp"
    cidr_blocks   = ["0.0.0.0/0"]
  }

  egress {
    from_port      = 0
    to_port        = 0
    protocol       = "-1"
    cidr_blocks   = ["0.0.0.0/0"]
  }
}

```

Now over to the external side of the load balancer. We need to create a listener which is the entry point for the load balancer. Copy this code into `lb.tf`.



```

» cat lb.tf

resource "aws_lb_listener" "todo" {
  load_balancer_arn    = aws_lb.taskoverflow.arn
  port                  = "80"
  protocol              = "HTTP"

  default_action {
    type      = "forward"
    target_group_arn = aws_lb_target_group.todo.arn
  }
}

```

If we deployed now, we would have implemented the deployment diagram above. However, we want to add autoscaling to our service so that it can scale up and down based on the load. Copy this code into `autoscaling.tf`.

```

» cat autoscaling.tf

resource "aws_appautoscaling_target" "todo" {
  max_capacity      = 4
  min_capacity      = 1
}

```

```

resource_id          = "service/taskoverflow/taskoverflow"
scalable_dimension  = "ecs:service:DesiredCount"
service_namespace   = "ecs"
}

resource "aws_appautoscaling_policy" "todo-cpu" {
  name              = "todo-cpu"
  policy_type       = "TargetTrackingScaling"
  resource_id        = aws_appautoscaling_target.todo.resource_id
  scalable_dimension = aws_appautoscaling_target.todo.scalable_dimension
  service_namespace  = aws_appautoscaling_target.todo.service_namespace

  target_tracking_scaling_policy_configuration {
    predefined_metric_specification {
      predefined_metric_type = "ECSServiceAverageCPUUtilization"
    }

    target_value          = 20
  }
}

```

This auto scaling policy looks at the average CPU utilization of the service and scales up if it is above 20% and scales down if it is below 20%. This is a very simple policy but it is a good starting point. We can now deploy our service and see it scale up and down. Continue onto the next section to see how to send multiple requests to our service to generate a heavy load.

### 4.3 Producing Load with K6

We have a service but us visiting it in our web browser is not going to be enough load for our policies to trigger. To do this we will employ the help of a tool called K6, which is a relatively new load testing tool. To install K6 visit <https://k6.io/docs/get-started/installation/>. It can be installed in the code spaces environment or locally.

We have provided an example K6 file, which is JavaScript code that creates 1000 to 5000 users to call the list endpoint of our service. Copy this code into a file called `k6.js`.

```

» cat k6.js

import http from 'k6/http';
import { sleep, check } from 'k6';

export const options = {
  stages: [
    { target: 1000, duration: '1m' },
    { target: 5000, duration: '10m' },
  ],
};

export default function () {

```

```
const res = http.get('http://your-loadBalancer-url-here/api/v1/todos');
check(res, { 'status was 200': (r) => r.status == 200 });
sleep(1);
}
```

We can then run this file using the following command.

```
>> k6 run k6.js
```

```
execution: local
script: load.js
output: -

scenarios: (100.00%) 1 scenario, 5000 max VUs, 11m30s max duration (incl. graceful
stop):
  * default: Up to 5000 looping VUs for 11m0s over 2 stages (gracefulRampDown:
  30s, gracefulStop: 30s)

running (00m05.4s), 0091/5000 VUs, 140 complete and 0 interrupted iterations
default  [-----] 0091/5000 VUs 00m05.4s/11m00.0s
```

#### 4.3.1 EC2 Auto Scaling

With all the pieces together we can now see if our efforts have paid off. While the above K6 code is running, let's check the EC2 console and see what actions our autoscaling policy has taken. In the EC2 console scroll down the left hand menu and select Auto Scaling Groups.

The screenshot shows the AWS EC2 Home page. The left sidebar contains a navigation menu with the following items:

- Dedicated Hosts
- Scheduled Instances
- Capacity Reservations
- Images** (selected)
- AMIs
- AMI Catalog
- Elastic Block Store**
- Volumes
- Snapshots
- Lifecycle Manager
- Network & Security**
- Security Groups
- Elastic IPs
- Placement Groups
- Key Pairs
- Network Interfaces
- Load Balancing**
- Load Balancers
- Target Groups
- Auto Scaling** (selected)
- Launch Configurations
- Auto Scaling Groups

The main content area displays the following information:

## Resources

You are using the following Amazon EC2 resources in the US

Instances (running)	0	Auto Scaling Group
Elastic IPs	0	Instances
Load balancers	1	Placement groups
Snapshots	0	Volumes

**Tip:** Easily size, configure, and deploy Microsoft SQL Server AWS Launch Wizard for SQL Server. [Learn more](#)

## Launch instance

To get started, launch an Amazon EC2 instance, which is a virtual server in the cloud.

**Launch instance** ▾

Migrate a server ↗

Note: Your instances will launch in the US East (N. Virginia) Region

## Scheduled events

You will be presented with our todo group, which states the current instances and the desired minimum and maximum number of instances. Select the name of the group.

The screenshot shows the AWS Auto Scaling groups page. The top navigation bar includes links for EC2 and Auto Scaling groups. The main content area displays the following information:

### Auto Scaling groups (1) [Info](#)

**Create an Auto Scaling group**

**Search your Auto Scaling groups**

<input type="checkbox"/>	Name	Launch template/configuration	Instances	Status	Desired capacity	Min
<input type="checkbox"/>	todo	todo-launch-template   Version Latest	1	-	1	1

In this panel we are presented with much of the same information, but what we want is the Automatic scaling tab.

## todo

Details    Activity    Automatic scaling    Instance management    Monitoring    Instance refresh

### Group details

Edit

Auto Scaling group name todo	Desired capacity 1	Status -	Amazon Resource Name (ARN) <code>arn:aws:autoscaling:us-east-1:245177958106:autoScalingGroup:91e8402c-a8be-4c4f-ad6f-0c02b19607fc:autoScalingGroupName/todo</code>
Date created Mon Mar 27 2023 16:32:28 GMT+1000 (Australian Eastern Standard Time)	Minimum capacity 1	Maximum capacity 4	

In this tab our two policies are displayed and we can see the configuration of both.

## todo

Details    Activity    **Automatic scaling**    Instance management    Monitoring    Instance refresh

Scaling policies resize your Auto Scaling group to meet changes in demand. With reactive dynamic scaling policies, you can track specific CloudWatch metrics and take action when the CloudWatch alarm threshold is met. Use predictive scaling policies along with dynamic scaling policies in the following situations: when your application demand changes quickly, but with a recurring pattern, or when your EC2 instances require more time to initialize.

### Dynamic scaling policies (2) Info



Actions ▾

Create dynamic scaling policy

< 1 >

#### todo\_scale\_down



Simple scaling

Enabled

#### todo\_scale\_down

breaches the alarm threshold: CPUUtilization <= 10 for 2 consecutive periods of 120 seconds for the metric dimensions:

AutoScalingGroupName = todo

Remove 1 capacity units

120 seconds before allowing another scaling activity

#### todo\_scale\_up



Simple scaling

Enabled

#### todo\_scale\_up

breaches the alarm threshold: CPUUtilization > 20 for 2 consecutive periods of 120 seconds for the metric dimensions:

AutoScalingGroupName = todo

Add 1 capacity units

120 seconds before allowing another scaling activity

In the Activity tab we can see the actions performed by our policies, whether it be a scale up or a scale down.

## todo

Details	Activity	Automatic scaling	Instance management	Monitoring	Instance refresh
<b>Activity notifications (0)</b>					
<input type="text"/> Filter notifications	<input type="button"/>	<input type="button"/> Actions ▾	<input type="button"/> Create notification	< 1 >	<input type="button"/>
<input type="checkbox"/> Send to	▼	On instance action			▼
<b>Activity history (2)</b>					
<input type="text"/> Filter activity history	<input type="button"/>	< 1 >	<input type="button"/>		
Status	Description	▼	Cause	▼	Start time
Successful	Updating load balancers/target groups: Successful. Status Reason: Added: arn:aws:elasticloadbalancing:us-east-1:245177958106:targetgroup/todo/ebcbca97edb519ec (Target Group).				2023 March 27, 04:33:20 PM +10:00
Successful	Launching a new EC2 instance: i-05bf864d60fa54dbe		At 2023-03-27T06:32:28Z a user request created an AutoScalingGroup changing the desired capacity from 0 to 1. At 2023-03-27T06:32:31Z an instance was started in response to a difference between desired and actual capacity, increasing the capacity from 0 to 1.		2023 March 27, 04:32:33 PM +10:00

If we head over to CloudWatch alarms, we can see the alarms that are the triggers for our policies.



### 4.3.2 ECS Auto Scaling

With all the pieces together we can now see if our efforts have paid off. While the k6 code from above is running, let's go to the ECS console and see if we can see any scaling events. Navigate to ECS -> Clusters -> taskoverflow -> Services -> taskoverflow -> Configuration and tasks.

## taskoverflow Info



Health and metrics

Logs

Configuration and tasks

Deployments and events

Networking

Tags

In this panel we can see our Auto Scaling configuration which lists the desired, minimum and maximum number of tasks. The policies are listed further down and we can view the alarm which is a graphical representation of the CPU utilization vs the target value.

### Auto Scaling

Desired tasks 1	Min tasks 1	Max tasks 4
--------------------	----------------	----------------

### Policies (1)

Policy name	Policy type	Scale-in	Alarm
todo-cpu: Tracking ECSServiceAverageCPUUtilization at 20	Target tracking	On	TargetTracking-service/taskoverflow /taskoverflow-AlarmHigh-a56c53cb-c376-4ff6-a18a-64adaec37997

### Tasks (1/2)

Task	Last status	Desired st...	Tas...	Revision	Health sta...	Started at	Container insta...
<span>●</span> <a href="#">132a0...</a>	<span>⌚</span> <a href="#">Running</a>	<span>⌚</span> <a href="#">Running</a>	todo	6	<span> ⓘ Unknown</span>	40 seconds ago	-

In the Cloudwatch Alarm panel you will notice that we have two different alarms, these are for the scaling up and down of the service. Selecting the alarm you can view the status where an "in alert" alarm is when the auto scaling configuration needs to action increasing/decreasing the number of instances.

