

Serverless Architecture

Software Architecture

Richard Thomas

April 13, 2026

Oxymoron 1. Serverless

Logic running on someone else's server.


Developers can focus on logic, not infrastructure to deliver it

Definition 0. Backend as a Service (BaaS)


Cloud-hosted applications or services that deliver functionality used by an application front-end.

- Front-end may be a SPA or mobile app
- Back-end provides sophisticated functionality (e.g. database, machine learning, location services, authentication, ...)
- Front-end ties back-end services together to deliver the application's functionality

BaaS Iceberg *[Brunko, 2019]*



BaaS Example




- Simple system with back-end functionality delivered *entirely* via BaaS
- Feature-rich front-ends coordinate behaviour delivered by BaaS
- Consequence for Front-ends
 - Tightly coupled to BAAS
 - Contains both UI and functional behaviour logic – Poor Cohesion
- Front-end could have a layered design – many SPAs don't

Definition 0. Functions as a Service (FaaS)


Application logic that is triggered by an event and runs in a *transient*, *stateless* compute node.

- Node may only exist for duration of function call
- Server infrastructure (e.g. type of node, lifespan, scaling, ...) are managed by hosting provider
- e.g. AWS Lambda, Google App Engine, Azure Automation, ...

FaaS Iceberg *[Brunko, 2019]*



FaaS Example




- Simple system — back-end functionality delivered by FaaS
 - Some services delivered via BaaS (e.g. Authentication – not shown on diagram for simplicity)
- Feature-rich front-ends coordinate behaviour delivered by FaaS
- Front-ends invoke functions via an API
- API Gateway provides some separation between front-end and functions
- Allows a bit more separation between UI and logic

Definition 0. Serverless Architecture

Software system delivering functionality through BaaS or FaaS.


- Many people focus on FaaS when considering Serverless
- Mobile App or Single Page Web App (SPA) coordinate services
- Front-end ties back-end services together to deliver application's functionality

Sahara Browse & Order — Serverless




- Only browse, search and purchase are shown
- Uses both BaaS & FaaS
- Shopping cart is implemented within the web and mobile app for this architecture
- Order Step 1: Customer checks out their shopping cart in the web or mobile app
- Order Step 2: App calls Purchase Products function via API Gateway
- Order Step 3: Purchase Products stores order in DB and sends a payment request to Payment Provider
- Order Step 4: Provide Payment Provider with API endpoint to call to report payment result
- Order Steps 5-9: Notes continue on *next slide*

Sahara Browse & Order — Serverless




- Order Step 5: Payment success causes Payment Confirmed function to be invoked
- Order Step 6: Payment Confirmed updates order in DB with payment status
- Order Step 7: Payment Confirmed adds Payment Confirmation message to the Queue
- Order Step 8: Payment Confirmation message is picked up by a fulfilment function to pack & send order
- Order Step 9: Once order is shipped, another message would trigger an 'order sent' function

Sahara Fulfilment — Serverless



- Only fulfilment functions are shown
- Shows Lambda Service polling Queue, demonstrating how Lambda Functions are invoked via events in a message queue
- Fulfilment Step 1: Lambda Service monitors Queue for 'ship order' messages
- Fulfilment Step 2: Lambda Service batches groups of 'ship order' messages and sends them to Fulfil Order function
- Fulfilment Step 3: Fulfil Order gets order details from DB and sends pick list to Fulfilment App
- Fulfilment Step 4: When order is shipped, Fulfilment App calls Order Shipped function via API Gateway
- Fulfilment Steps 5-8: Notes continue on *next slide*

Sahara Fulfilment — Serverless



- Fulfilment Step 5: Order Shipped sends email to customer and updates order status in DB
- Fulfilment Step 5a: Simplification of order picking, packing and shipping steps
- Fulfilment Step 5b: Each step sends messages to Queue to trigger other functions
- Fulfilment Step 6: Customer queries order status in the web or mobile app
- Fulfilment Step 7: App calls Order Status function via API Gateway
- Fulfilment Step 8: Order Status queries Order DB and sends status back to customer via App

Serverless Benefits

- Automatic scaling
 - Multiple instances of function

Serverless Benefits

- Automatic scaling
 - Multiple instances of function
- Reduced cost for dynamic loads
 - No server idle time

Serverless Benefits

- Automatic scaling
 - Multiple instances of function
- Reduced cost for dynamic loads
 - No server idle time
- Reduced server management

Serverless Benefits

- Automatic scaling
 - Multiple instances of function
- Reduced cost for dynamic loads
 - No server idle time
- Reduced server management
- Easier to run closer to client
 - Launch in same zone as client

BaaS Tradeoffs

- Front-end accesses database directly
 - Front-end needs to sanitise inputs
 - Easy to spoof messages from front-end
 - Hope DB provider is secure

Spoofing messages is an issue for all BaaS services

BaaS Tradeoffs

- Front-end accesses database directly
 - Front-end needs to sanitise inputs
 - Easy to spoof messages from front-end
 - Hope DB provider is secure
- Application logic is in front-end
 - Less modularisation
 - Duplication of logic with multiple front-ends
 - Web, mobile, ...
- Modern expectations are that almost all systems will have multiple front-ends
- Duplication of front-end logic is a smaller, but still partial, concern for FaaS

BaaS Tradeoffs

- Front-end accesses database directly
 - Front-end needs to sanitise inputs
 - Easy to spoof messages from front-end
 - Hope DB provider is secure
- Application logic is in front-end
 - Less modularisation
 - Duplication of logic with multiple front-ends
 - Web, mobile, ...
- No control over server optimisation

FaaS Tradeoffs

- No server state
 - All state needs to be saved (e.g. Redis, S3, ...)
 - Not just persistent state
- Server running function can be killed when function is not running
- Can occasionally send messages to functions to keep them alive — Not ideal

FaaS Tradeoffs

- No server state
 - All state needs to be saved (e.g. Redis, S3, ...)
 - Not just persistent state
- Execution duration
 - Can't be long running process
 - AWS Lambda – up to 15 minutes

FaaS Tradeoffs

- No server state
 - All state needs to be saved (e.g. Redis, S3, ...)
 - Not just persistent state
- Execution duration
 - Can't be long running process
 - AWS Lambda – up to 15 minutes
- Startup latency
 - Functions take time to start
 - Some languages worse than others (e.g. Java)

Java has concurrency benefits over other languages

FaaS Tradeoffs

- No server state
 - All state needs to be saved (e.g. Redis, S3, ...)
 - Not just persistent state
- Execution duration
 - Can't be long running process
 - AWS Lambda – up to 15 minutes
- Startup latency
 - Functions take time to start
 - Some languages worse than others (e.g. Java)
- Proliferation of functions
 - Loss of encapsulation

Question

When is serverless appropriate?

Question

When is serverless appropriate?

Answer

- Rich client apps with common backend
 - BaaS

Question

When is serverless appropriate?

Answer

- Rich client apps with common backend
 - BaaS
- High latency processing
 - Within function duration constraints

Question

When is serverless appropriate?

Answer

- Rich client apps with common backend
 - BaaS
- High latency processing
 - Within function duration constraints
- Apps with variable load
 - Take advantage of auto-scaling

Question

When is serverless *not* appropriate?

Question

When is serverless *not* appropriate?

Answer

- Quick response required
 - Can't wait for FaaS to start

Question

When is serverless *not* appropriate?

Answer

- Quick response required
 - Can't wait for FaaS to start
- Compute intensive processing

Question

When is serverless *not* appropriate?

Answer

- Quick response required
 - Can't wait for FaaS to start
- Compute intensive processing
- Apps with steady load
 - Server-based approaches are cheaper

Self-Study Exercise

- Redesign your scalability assignment to be serverless
 - What parts of your design would benefit from being serverless?
 - Implement your revised design
- Not for your assignment submission
 - Learner Labs limits number of concurrently executing Lambdas

Pros & Cons

Extensibility



Reliability



Interoperability



Scalability



Deployability



Modularity



Testability



Maintainability



Security



Simplicity



- Modularity: Deployed functions are naturally modular
- Modularity: Higher-level abstractions to group deployed functions is difficult
- Testability: Unit testing FaaS functions is easy
- Testability: Integration testing is harder
- Maintainability: Backend modularity and independence should facilitate its maintenance
- Maintainability: Frontend contains UI and application logic
- Security BaaS: Front-end accesses back-end directly — No server-side protection of db or other resources
- Security FaaS: Every function needs its own security policy (e.g. IAM), — easy to get wrong

References

- [Brunko, 2019] Brunko, P. (2019).
Serverless architecture: When to use this approach and what benefits it gives.
<https://apiko.com/blog/serverless-architecture-benefits/>.