

A Syntactic Criterion for Injectivity of Authentication Protocols

Cas Cremers

joint work with Sjouke Mauw and Erik de Vink

ccremers@win.tue.nl

Eindhoven Computer Science Security (ECSS) group

Goal:

To study the design and analysis of secure systems from a fundamental point of view

Topics:

- Security protocol analysis
- Multi-party protocols
- Ad-hoc/sensor networks
- Smartcard security
- Attack trees
- Digital Rights Management
- RFID security
- Privacy

Overview

Motivation

Problem statement

Security model

Main theorem

Conclusions

- Motivation
- Problem statement
- Main theorem
- Necessity of preconditions
- Conclusions

Example: unilateral authentication protocol

Overview

Motivation

● Example

● Replay attack

● Injectivity

● Fixed protocol


● Nonces

Problem statement

Security model

Main theorem

Conclusions



Example: unilateral authentication protocol

Overview

Motivation

● Example


- Replay attack
- Injectivity
- Fixed protocol
- Nonces

Problem statement

Security model

Main theorem

Conclusions



Question: Does this protocol satisfy agreement?

A replay attack

Overview

Motivation

- Example

- **Replay attack**

- Injectivity

- Fixed protocol


- Nonces

Problem statement

Security model

Main theorem

Conclusions



A replay attack

Overview

Motivation


- Example
- Injectivity
- Fixed protocol
- Nonces

Problem statement

Security model

Main theorem

Conclusions



Question: How to fix this protocol?

Overview

Motivation

- Example
- Replay attack
- **Injectivity**
- Fixed protocol
- Nonces

Problem statement

Security model

Main theorem

Conclusions

Each instance of an agent executing the authenticating role corresponds to a *unique* instance of its communication partner running the responder role.

Overview

Motivation


- Example
- Replay attack
- Injectivity
- Fixed protocol
- Nonces

Problem statement

Security model


Main theorem

Conclusions



- Nonces

Conclusions



Overview

Motivation


- Example
- Replay attack
- Injectivity
- Fixed protocol
- Nonces

Problem statement

Security model

Main theorem

Conclusions




Motivation

- ## Problem statement

Security model

Main theorem

Conclusions



Fixing the injectivity problem

Overview

Motivation


- Example
- Replay attack
- Injectivity
- Fixed protocol
- Nonces

Problem statement

Security model

Main theorem

Conclusions



Fixing the injectivity problem

Overview

Motivation


- Example
- Replay attack
- Injectivity
- Fixed protocol
- Nonces

Problem statement

Security model

Main theorem

Conclusions



Question: What's the general idea behind this fix?

Fixing the injectivity problem

Overview

Motivation


- Example
- Replay attack
- Injectivity
- Fixed protocol
- Nonces

Problem statement

Security model

Main theorem

Conclusions




Question: What's the general idea behind this fix?

Answer 1: By letting I control the nonce.

Answer 2: By introducing a challenge-response mechanism from I via R back to I . (add a loop)

Doesn't a nonce suffice?

Adding nonces does not trivially lead to injectivity.



Here, injectivity depends on the properties of the function g .

Overview

Motivation

- Example
- Replay attack
- Injectivity
- Fixed protocol
- Nonces

Problem statement


Security model

Main theorem

Conclusions

Agreement over what?

Sometimes roles have no shared value to determine injectivity from (I and S ?)



Overview

Motivation

- Example
- Replay attack
- Injectivity
- Fixed protocol
- Nonces

Problem statement

Security model

Main theorem

Conclusions

Overview

Motivation

Problem statement

● Authentication

● Problem statement

Security model

Main theorem

Conclusions

Agreement

Upon successfully finishing a protocol session, parties agree on the values of (common) variables.

(G. Lowe)

Synchronization

Upon successfully finishing a protocol session, all messages have been executed in intended order, with intended contents.

(Similar to Intensional Specifications, A.W. Roscoe)

Synchronization is strictly stronger than agreement, but the differences are subtle.

Both available in injective (*i-synch*, *i-agree*) and non-injective (*ni-synch*) variants.

Claim: well-designed protocols satisfy both properties.

Overview

Motivation

Problem statement

● Authentication

● Problem statement

Security model

Main theorem

Conclusions

Find a *generic* and *easy* way to validate injectivity for synchronizing protocols.

Generic:

As few assumptions on the security model as possible.

Easy:

Statically decidable.

We require that the following two properties hold:

Intruder Model:

Intruder must have the ability to duplicate messages

- Satisfied by the standard Dolev-Yao model.
- No need to encrypt/decrypt.

Agent/Execution Model:

We require that the following two properties hold:

Intruder Model:

Intruder must have the ability to duplicate messages

- Satisfied by the standard Dolev-Yao model.
- No need to encrypt/decrypt.

Agent/Execution Model:


Role instances must be independent: can be executed in any order

- Satisfied by Strand Spaces, Operational Semantics.
- No shared memory. (buffers/time)

[Overview](#)[Motivation](#)[Problem statement](#)[Security model](#)[Main theorem](#)[● Loop property](#)[● Main Theorem](#)[● Loop](#)[● Synchronization](#)[● Indep. instances](#)[Conclusions](#)

After the start of the authenticating role, but before it ends, each involved role must have a read action and a send action.


(As prescribed by the partial order on the protocol)



This protocol satisfies *LOOP*

After the start of the authenticating role, but before it ends, each involved role must have a read action and a send action.


(As prescribed by the partial order on the protocol)



This protocol satisfies *LOOP*

After the start of the authenticating role, but before it ends, each involved role must have a read action and a send action.

(As prescribed by the partial order on the protocol)



This protocol does *not* satisfy *LOOP*

[Overview](#)[Motivation](#)[Problem statement](#)[Security model](#)[Main theorem](#)

● Loop property

● **Main Theorem**

● Loop

● Synchronization

● Indep. instances

[Conclusions](#)

Preconditions:

- duplicating intruder
- independent role instances

$$ni\text{-}synch \wedge LOOP \Rightarrow i\text{-}synch$$


So, for synchronizing protocols, injectivity follows from the *LOOP* property.

No reference is made to the data model (operators, etc.) or the contents of the messages (e.g. nonces)

- Loop property
- Main Theorem
- **Loop**
- Synchronization
- Indep. instances

Given a duplicating intruder and independent role instances:


$$ni\text{-}synch \Rightarrow i\text{-}synch?$$



Do we need a loop?

Given a duplicating intruder and independent role instances:

$$ni\text{-}synch \Rightarrow i\text{-}synch?$$



Overview

Motivation

Problem statement

Security model

Main theorem


- Loop property
- Main Theorem
- **Loop**
- Synchronization
- Indep. instances

Conclusions

Do we need Synchronization?

Given a duplicating intruder and independent role instances:

$$ni\text{-}agree \wedge LOOP \Rightarrow i\text{-}agree?$$



Overview

Motivation

Problem statement

Security model

Main theorem

● Loop property

● Main Theorem

● Loop

● Synchronization


● Indep. instances

Conclusions

Do we need Synchronization?

Given a duplicating intruder and independent role instances:

$$ni\text{-}agree \wedge LOOP \Rightarrow i\text{-}agree?$$



Overview

Motivation

Problem statement

Security model

Main theorem


- Loop property
- Main Theorem
- Loop
- Synchronization
- Indep. instances

Conclusions

Do we need independent role instances?

Given a duplicating intruder:

$$ni\text{-}synch \wedge LOOP \Rightarrow i\text{-}synch?$$



Overview

Motivation

Problem statement

Security model

Main theorem


- Loop property
- Main Theorem
- Loop
- Synchronization
- Indep. instances

Conclusions

Do we need independent role instances?

Given a duplicating intruder:

$$ni\text{-}synch \wedge LOOP \Rightarrow i\text{-}synch?$$



Overview

Motivation

Problem statement

Security model

Main theorem

- Loop property
- Main Theorem
- Loop
- Synchronization
- Indep. instances

Conclusions

Given a duplicating intruder and independent role instances:

$$ni\text{-}synch \wedge LOOP \Rightarrow i\text{-}synch$$

- *LOOP*-property can be checked easily.
- Generic: Sufficient condition for large class of security protocol semantics.
- *LOOP* plus agreement not sufficient to imply injective agreement.
Extra structure in synchronization is helpful.
- Generalizes easily to multi-party protocols with multiple claims.

Overview

Motivation

Problem statement

Security model

Main theorem

Conclusions

- Challenge: Is there a similar condition for agreement?
 - statically checkable
 - generic
- Use in model checker/theorem prover.
- Analyze other security properties for statically decidable subproperties.

Overview

Motivation

Problem statement

Security model

Main theorem

Conclusions

Any Questions?

E-mail: `ccremers@win.tue.nl`

model-checking approach

Counting: $\#(I\text{-runs}) \leq \#(\text{corresponding } R\text{-runs})$

other approaches (logics, term rewriting)

- Strand spaces: solicited authentication tests (Guttman, Theyer 2002)
- π -calculus: injective correspondence (Gordon, Jeffrey 2002)
- Logic: e-commerce protocol logic (Adi, Debbabi, Mejri 2003)
- Further: Ad-hoc reasoning, informal reasoning, or simply not.

For all $e \prec_p \text{claim}$, such that $\text{role}(e) \neq \text{role}(\text{claim})$ there exist e' and e'' such that

$$\begin{aligned} e' \prec_p e'' \prec_p \text{claim} \wedge \\ \text{role}(e') = \text{role}(\text{claim}) \wedge \\ \text{role}(e'') = \text{role}(e) \end{aligned}$$

This property can be easily verified on the syntactic description of the protocol.