

# LAU10-By-Shantal-Cruz.R

CS

2023-09-24

```
library(readr)
data <- readr::read_csv("4063Midterm.csv")
```

```
## Rows: 1000 Columns: 13
## -- Column specification -----
## Delimiter: ","
## chr (4): Fname, Lname, gender, City
## dbl (9): ID, FamilyIncome, EdYears, FamilySize, Grocery, Cosmetics, MF, Boug...
##
## i Use 'spec()' to retrieve the full column specification for this data.
## i Specify the column types or set 'show_col_types = FALSE' to quiet this message.
```

```
# City Toronto only
myCity <- data[data$City == "Toronto", c("EdYears", "Cosmetics")]
# View(myCity)
```


```
# 1) Use a function such as factoextra::fviz_nbclust with silhouette method to identify the optimum num
# install.packages("factoextra")
```

```
library(factoextra)
```

```
## Loading required package: ggplot2
## Welcome! Want to learn more? See two factoextra-related books at https://goo.gl/ve3WBa
```

```
library(cluster)

# silhouette method
hc_s <- factoextra::fviz_nbclust(myCity, FUNcluster = hcut, method = "silhouette")
print(hc_s)
```



```
hc_optimal_k <- 2
# 2) Use a function such as stats::hclust to build your hierarchical cluster model and use factoextra::
# Hierarchical Clustering
hc <- stats::hclust(dist(myCity))
hc
```

```
##
## Call:
## stats::hclust(d = dist(myCity))
##
## Cluster method      : complete
## Distance            : euclidean
## Number of objects: 255
```


```
cut_tree <- cutree(hc, k = hc_optimal_k)
cut_tree
```

```
##      [1] 1 2 2 1 2 2 2 2 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 1 2 2 1 1
##     [38] 1 2 2 1 2 1 2 1 2 2 1 2 2 2 2 2 2 2 1 2 2 1 2 2 1 1 2 1 2 2 2 1 2 2 2 1
##     [75] 2 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 1 2 2 2 2 2 2 2 1 2 1 1 2 2 2 2 2 2
##    [112] 1 2 2 1 2 2 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 1 2 2 2 2 2 2 1
##    [149] 2 2 2 2 2 2 2 2 2 2 2 1 1 1 2 2 2 2 2 2 2 2 2 2 1 2 1 2 2 1 2 2 2 2 2 1 2 2
##    [186] 2 2 2 2 2 2 2 2 2 1 2 2 1 2 2 2 2 2 2 2 1 2 2 2 2 2 1 2 2 2 1 2 2 2 2 2 2 2
##    [223] 2 2 1 2 2 2 2 2 2 2 2 1 2 2 2 2 2 1 2 2 2 1 2 1 1 1 1 2 2 1 2 2 2
```

```
# Visualize the dendrogram
dend <- as.dendrogram(hc)
dend
```


```
## 'dendrogram' with 2 branches and 255 members total, at height 488.1168
```

```
# Create a clustering object using cut_tree
hc_cluster <- factoextra::fviz_cluster(list(data = myCity, cluster = cut_tree))
hc_cluster
```



```
# Plot the clustering object
print(hc_cluster)
```


## Cluster plot



# 3) Use a function such as `factoextra::fviz_nbclust` with silhouette method to identify the optimum number of clusters

```
# silhouette method
```

```
km_s <- factoextra::fviz_nbclust(myCity, FUNcluster = kmeans, method = "silhouette")
print(km_s)
```



```
km_optimal_k <- 2
```

*# 4) Use a function such as stats::Kmeans to build your Kmeans cluster model and use factoextra::fviz\_c*

*# K-Means Clustering*

```
km <- stats::kmeans(myCity, centers = km_optimal_k)
km
```

```
## K-means clustering with 2 clusters of sizes 156, 99
```

```
##
```

```
## Cluster means:
```

```
##      EdYears Cosmetics
```

```
## 1 13.48718  413.6987
```

```
## 2 17.39394  536.4444
```

```
##
```

```
## Clustering vector:
```

```
##  [1] 2 2 1 2 1 1 2 1 1 2 1 1 1 1 2 1 1 2 1 2 2 2 1 2 1 1 1 1 1 1 1 2 1 1 2 2
```

```
## [38] 2 1 2 2 1 2 2 2 1 1 2 2 1 1 1 1 1 2 2 1 2 1 1 2 2 1 2 1 2 1 1 2 1 2
```

```
## [75] 2 2 2 1 1 1 2 1 1 1 1 2 1 2 2 1 1 1 2 2 1 1 1 2 2 2 2 1 2 1 1 1 1
```

```
## [112] 2 1 1 2 2 1 1 2 1 2 1 1 2 1 1 1 1 2 1 1 1 1 1 1 1 1 1 2 1 1 1 1 1 2
```

```
## [149] 2 1 2 1 1 1 1 2 1 1 2 2 2 1 1 2 1 2 1 1 1 1 2 1 1 2 1 1 2 2 1 2 1 1
```

```
## [186] 1 1 2 2 1 1 2 1 2 2 2 2 2 1 1 1 1 1 2 1 1 1 1 2 2 2 1 2 1 2 1 1 1 1
```

```
## [223] 2 1 2 1 1 1 1 1 2 1 1 2 1 1 1 1 1 2 1 1 1 2 1 2 2 2 2 2 2 2 1 1
```

```
##
```


```
## Within cluster sum of squares by cluster:
```

```
## [1] 259771.8 264838.1
```

```
## (between_SS / total_SS = 63.5 %)
##
## Available components:
##
## [1] "cluster"      "centers"      "totss"        "withinss"     "tot.withinss"
## [6] "betweenss"   "size"         "iter"         "ifault"       "
```


```
# Visualize the clustering object
```

```
km_cluster <- factoextra::fviz_cluster(list(data = myCity, cluster = km$cluster))
km_cluster
```



```
# Plot the clustering object
```

```
print(km_cluster)
```



```
# 5) Compare and contrast the visualizations of the clusters detected by two Machine Learning models. W
# put the two plots side by side
library(gridExtra)
grid.arrange(hc_cluster, km_cluster, ncol = 2, nrow = 1, top = "Hierarchical Clustering vs. K-Means Clu
```

## Hierarchical Clustering vs. K-Means Clustering



```
print("To determine what clustering is better will depend on many factors. We can quantitatively use di
```

```
## [1] "To determine what clustering is better will depend on many factors. We can quantitatively use d
```