SCHEDULED MAINTENANCE CHECK SHEET (all models with 6,000 mile (10,000 km) service intervals)



Customer Name	Registration Number	Model	Date	
Date of Registration	VIN	Odometer Reading	Job Number	
Bike Under Warranty? ☐ Yes ☐ No	Service Book Stamped? ☐Yes☐No	Technician Name	Technician Signature	

Carry out all the operations specified below at the required intervals. Additional operations must be carried out at the specified time/distance interval, whichever comes first. IMPORTANT: Under severe operating conditions, certain items require more frequent servicing. Refer to the Owner's Handbook for further information.

Annual Service - Every year First Service - First 500 miles/800 km/1 Month (whichever comes first) First Service Tick Box when Item Complete Annual Service Not Applicable to this Model NA 6,000 and 18,000 miles (10,000 and 30,000 km) 12,000 miles (20,000 km) 24,000 miles (40,000 km) # [Lubrication Engine and oil cooler - check for leaks 2. Engine oil - renew 3. Engine oil filter - renew Fuel System and Engine Management Autoscan - carry out a full Autoscan using the Triumph diagnostic tool (print a customer copy) 2. Fuel system - check for leaks Fuel system - check fuel hoses for chafing, cracks or damage. Replace if necessary 4. Air cleaner - renew 5. Fuel filter - renew (if fitted) 6. Throttle body plate (butterfly) - check/clean Throttle cables - check cable for chafing, cracks or damage/ adjust (models with a cable operated throttle only) Throttle linkage - check/clean/lubricate (Tiger 800, Tiger 800XC only) Exhaust butterfly valve cables - check cable for chafing, cracks or damage/adjust (Daytona 675, Thunderbird Commander and Thunderbird LT only) 10. Exhaust butterfly valve actuator - check/clean/grease electrical connector (Daytona 675 up to VIN 564947 only) 11. Secondary air injection system - check/clean 12. Secondary exhaust clamp bolts - check/adjust torque (if fitted) 13. Throttle bodies/carburettors - balance 14. Idle CO level - check/adjust (carburettor and open loop EFI models only) 15. Fuel hoses - renew - every 4 years, regardless of mileage † 16. Evaporative hoses - renew (if fitted) - every 4 years, regardless of mileage † Ignition System Spark plugs - check Spark plugs - renew Cooling System (liquid cooled models only) Cooling system - check for leaks Cooling system - check coolant hoses for chafing, cracks or damage. Replace if necessary Coolant level - check/adjust Coolant - renew - every 3 years, regardless of mileage † **Engine** 1. Clutch cable - check cable for chafing, cracks or damage/adjust Valve clearances - check/adjust † Wheels and Tyres 1. Wheels - inspect for damage Wheel bearings - check for wear/smooth operation Wheels - check for broken or damaged spokes and check spoke tightness (not alloy wheels) 4. Tyre wear/tyre damage - check 5. Tyre pressures - check/adjust

- Every year	Additional items at specified mileage/date only, as indicated below	
12,000 miles (Tick Box when Item Complete WA Not Applicable to this Model	
	Steering and Suspension	
1.	Steering - check for free operation	
2.	Forks - check for damage/leaks/smooth operation	
3.	Fork oil - renew	
4.	Headstock bearings - check/adjust - except first service	
	Headstock bearings - lubricate	
	Rear wheel bearings - lubricate (single-sided swinging arm models only)	
7.	Rear suspension unit and linkage - check/lubricate (single rear suspension unit models only)	
	Brakes	
1.	Brake pads - check wear levels ‡	
2.	Brake master cylinders - check for fluid leaks	
	Brake calipers - check for fluid leaks and seized pistons	
	Brake fluid levels - check	
	Brake fluid - renew - every 2 years, regardless of mileage †	
J	Drive Chain and Drive Belt	
	·	
	Drive belt - inspect for wear, chafing, cracks or damage Drive belt tension - check and adjust annually or every 2,500 miles (4,000 km) whichever comes first	
3.	Drive flange bearings - check for wear/smooth operation (drive belt models only)	
4	Drive flange assembly - renew (drive belt models only) 1	
	Drive chain slack - check/adjust	
	Drive chain - wear check [‡]	
	Drive chain - lubricate	
	Drive chain rubbing strip - check for wear, cracks or damage [‡]	
9.	Drive chain rubbing strip - renew §	
	Electrical	
1.		
	General	
1.	Bank angle indicators - check for wear [‡]	
2.	Fasteners - inspect visually for security	
	Accessory rack sliding carriage - check for correct operation - except first service	
4.	Accessory pannier link mechanism - check for correct operation and adjustment	
5.	Centre and/or side stand - check for wear/smooth operation	
6.	Centre stand flanged sleeves (if fitted) clean/grease	
7.	Carry out all outstanding Service Bulletin and warranty work	
8.	Carry out road test	
9.	Complete the service record book and reset the service indicator (if fitted)	

Note:

The following notes must be referred to as necessary during scheduled servicing:

‡ Renew checked items if worn beyond the service limit.

§ Tiger models with a 800 cc engine only.

Additional items are subject to additional labour charge, above the cost and time allowance for the basic service, which includes time to check only.

For Thunderbird motorcycles up to VIN 454618 only: Renew the drive flange assembly

(part number T2010461) at the first 24,000 miles (40,000 km) service only. At subsequent services, check the drive flange bearings for wear/smooth operation.

Daily checks must also be carried out as specified in the Owner's Handbook.

Issue 16 01. 2016 1 of 1