



Scheduled Maintenance

Model: ☐ Monster 1200 ☐ Monster 821 ☐ Diavel MY15-16 ☐ Hypermotard / Hyperstrada MY13-15 and MY16

Plate Number: _____ Current km/mi: _____

Customer Name: _____ Date of Registration: _____

Scheduled Maintenance intervention Check List for motorcycle equipped with Testastretta 11° 821, Testastretta 11° 939 and Testastretta 11° DS 1200 engine	km. x 1.000	1	15	30	45	60	Time (months)
	mi. x 1.000	0,6	9	18	27	36	
<input type="checkbox"/> Reading of the error memory with DDS 2.0 and check of Software version update on control units		•	•	•	•	•	12
<input type="checkbox"/> Check the presence of any technical updates and recall campaigns		•	•	•	•	•	12
<input type="checkbox"/> Change engine oil and filter		•	•	•	•	•	12
<input type="checkbox"/> Clean engine oil intake filter		•					
<input type="checkbox"/> Clean engine oil intake filter (only Monster 821, Hypermotard and Hyperstrada)		•		•		•	
<input type="checkbox"/> Check and/or adjust valve clearance				•		•	
<input type="checkbox"/> Change timing belts				•		•	60
<input type="checkbox"/> Change the spark plugs				•		•	
<input type="checkbox"/> Change the spark plugs (only Monster 821, Hypermotard and Hyperstrada)			•	•	•	•	
<input type="checkbox"/> Clean air filter			•		•		
<input type="checkbox"/> Change air filter				•		•	
<input type="checkbox"/> Check brake and clutch fluid level (only brake fluid for Monster 821, Hypermotard and Hyperstrada)		•	•	•	•	•	12
<input type="checkbox"/> Change brake and clutch fluid (only brake fluid for Monster 821, Hypermotard and Hyperstrada)							36
<input type="checkbox"/> Check brake discs and pad wear. Change, if necessary		•	•	•	•	•	12
<input type="checkbox"/> Check tightening torque of front and rear brake calliper screws and front brake disc screws		•	•	•	•	•	12
<input type="checkbox"/> Check of tightening of phonic wheel and rear brake disc screws (with removal of the rear wheel shaft, only Diavel)			•	•	•	•	
<input type="checkbox"/> Check front and rear wheel nuts tightening		•	•	•	•	•	12
<input type="checkbox"/> Check frame-to-engine fasteners tightening			•	•	•	•	
<input type="checkbox"/> Check wheel hub bearings				•		•	
<input type="checkbox"/> Check and lubricate the rear wheel shaft				•		•	
<input type="checkbox"/> Check the cush drive damper on rear sprocket				•		•	
<input type="checkbox"/> Check the proper tightening of final drive front and rear sprocket nuts		•	•	•	•	•	12
<input type="checkbox"/> Check final drive wear (chain, front and rear sprockets) and chain sliding shoes			•	•	•	•	12
<input type="checkbox"/> Check the final drive chain tension and lubrication		•	•	•	•	•	12
<input type="checkbox"/> Check steering bearings and lubricate, if necessary				•		•	
<input type="checkbox"/> Change front fork fluid				•		•	
<input type="checkbox"/> Change front fork fluid (only Hypermotard and Hyperstrada)					•		
<input type="checkbox"/> Visual check of front fork and rear shock absorber seals		•	•	•	•	•	12
<input type="checkbox"/> Check the freedom of movement and tightening of the side stand (if installed)		•	•	•	•	•	12
<input type="checkbox"/> Visual check of the fuel lines			•	•	•	•	12
<input type="checkbox"/> Check rubbing points, clearance, freedom of movement and positioning of hoses and electric wiring in view		•	•	•	•	•	12
<input type="checkbox"/> Lubricate the levers at the handlebar and pedal controls			•	•	•	•	12
<input type="checkbox"/> Change coolant					•		48
<input type="checkbox"/> Check coolant level and circuit for damage		•	•	•	•	•	12
<input type="checkbox"/> Check tyres pressure and wear		•	•	•	•	•	12
<input type="checkbox"/> Check the battery charge level		•	•	•	•	•	12
<input type="checkbox"/> Check the operation of the safety electrical devices (side stand sensor, front and rear brake switches, engine stop switch, gear/neutral sensor)		•	•	•	•	•	12
<input type="checkbox"/> Check lights, turn indicators, horn and controls		•	•	•	•	•	12
<input type="checkbox"/> Reset Service indication through DDS 2.0		•	•	•	•	•	
<input type="checkbox"/> Final test and road test of the motorcycle, testing safety devices (ex. ABS and DTC), electric fans and idling		•	•	•	•	•	12
<input type="checkbox"/> Softly clean the motorcycle		•	•	•	•	•	12
<input type="checkbox"/> Fill out that the service was performed in on-board documentation (Service Booklet)		•	•	•	•	•	12

☒ Tick the box next to the interventions carried out during Scheduled Maintenance

Thank you! Your Ducati Technician:

Current Date: