

Northstar systems and API reference

SYSTEMS REFERENCE

SYS-CATALOG-001

Owner: IT Manager | Interface version: 2026-09 | Environment: isolated project workspace.

Operations workspace

Northstar Operations is the coordinator team's working application. It combines email and portal requests, saves workflow progress and records the customer response. Coordinators still check evidence across several records before they act.

Authentication

Use the private assessment token as a bearer token. Keep it in an environment variable and never commit it.

```
Authorization: Bearer $NORTHSTAR_ACCESS_TOKEN  
Base URL: https://hiring.celecolabs.com/api/assessment
```

Available services

- GET ?route=requests - requests and saved workflow state.
- POST ?route=request-workflow - triage, notes and customer reply draft.
- GET ?route=customers&q=Aster - customer, site and asset lookup.
- GET ?route=agreements&q=CON-012-A2 - service agreement and amendment lookup.
- GET ?route=technicians - qualifications and current availability.
- GET ?route=work-order-history&q=AST-101 - searchable service history.
- GET or POST ?route=work-orders - active work orders and creation.

Work-order creation

```
{  
  "externalEventId": "evt-1042",  
  "requestId": "REQ-1042",  
  "assetId": "AST-101",  
  "technicianId": "TECH-01",  
  "safetyRisk": false  
}
```

The API validates authentication, required fields, referenced record IDs and idempotency. It behaves like the current CRM and does not decide whether a dispatch is safe, covered or operationally sound. Your system owns that judgement. Repeating an accepted externalEventId returns the original work order.

Known limitations

- Records may be incomplete and a request may not contain an asset identifier.
- Dependencies can time out, so callers should validate responses and retry safe reads.
- Technician availability can change between selection and dispatch.

Request and response behaviour

Successful list calls return {results:[...]}. Successful creation returns {workOrder, duplicate}. Validation errors return HTTP 400 or 422 with an error and reasons. A dependency timeout returns 504. Treat a timeout after a write as an uncertain outcome: reconcile by request or external event reference before retrying.

Workflow record

```
{
  "requestId": "REQ-1042",
  "status": "awaiting_approval",
  "customerId": "CUS-012",
  "siteId": "SITE-008",
  "assetId": "AST-101",
  "safetyOutcome": "clear",
  "coverageOutcome": "needs_review",
  "technicianId": null,
  "coordinatorNotes": "Later amendment needs review",
  "customerReplyDraft": "We are checking the account record."
}
```

Security and isolation

The Northstar key is valid only for Northstar Operations and the business APIs. It will not authenticate to the Celeco model gateway or the assessment submission service. Do not place it in source control, browser logs or model prompts.