One-Shot Domain Calibration of MoE Routers via Gradient Bias Steering

Evgeny Bessonnitsyn, Konstantin Pakulnevich, Marina Frolova, Ivan Shchukin,
Timur Gabbasov, Aleksandr Ustinov, Sergey Muravyov

ITMO University

August 9–13, 2026
KDD 2026
Jeju, Korea
RelKD Workshop @ KDD 2026

Main idea: calibrate the router, not the experts.

One forward/backward pass over 100 domain examples produces a tiny bias that steers borderline Top-K choices, while the frozen MoE and its standard inference path remain intact.

Abstract

Sparse Mixture-of-Experts models are pretrained on broad data mixtures, so their routers may underuse experts that are useful for a narrow deployment domain. We introduce **Domain-Calibrated Router Bias (DCRB)**, a one-shot post-training method for a fully frozen MoE. A 100-example labeled calibration set provides answer-token gradients with respect to router bias; the resulting per-expert importance is normalized, scaled by the layer's own logit dispersion, and folded into the standard gate bias. DCRB improves mathematics, chemistry, and history accuracy while storing only a few kilobytes per domain and adding no custom routing logic at inference.

Motivation and contributions

- Domain knowledge may already exist in the frozen experts, but the general-purpose router may not expose it consistently.
- Full fine-tuning is expensive; dynamic routing rules can add per-token control logic and latency.
- DCRB changes only one scalar per expert per MoE layer and keeps the number of active experts fixed.

Contributions

- Answer-token gradient importance for each router bias.
- Automatic layer-wise scaling from router-logit statistics.
- Subject-level, resource, and routing-behavior evaluation on two Qwen MoE models.

Method: one-shot gradient bias steering

A. DCRB calibration and deployment pipeline

1. **Collect 100 domain examples** — Use a labeled calibration set disjoint from evaluation.
2. **Run one gradient pass** — Teacher forcing; the loss mask includes answer tokens only.
3. **Score routed experts** — Test whether a larger gate bias lowers answer loss.
4. **Normalize and scale** — Center each layer and use $4\,\mathrm{Std}(z_\ell)/N_\ell$.
5. **Write into the gate bias** — Store $\Delta b^{(d)}$ in the standard router linear layer and deploy.

No iterative optimization. Calibration uses no optimizer state, learning-rate schedule, repeated epochs, trainable adapter, or expert-weight update.

B. Gradient score for each routed expert

For active expert i in layer ℓ, differentiating the routed mixture through the selected-expert softmax gives

$$\frac{\partial o_{\ell,t}}{\partial z_{\ell,t,i}} = w_{\ell,t,i}\big(e_{\ell,i}(h_{\ell,t}) - o_{\ell,t}\big).$$

With $g_{\ell,t} = \partial L/\partial o_{\ell,t}$, DCRB accumulates only answer tokens ($m_t = 1$):

$$S_{\ell,i} = -\sum_{t:m_t=1} g_{\ell,t}^{\top} w_{\ell,t,i}\big(e_{\ell,i}(h_{\ell,t}) - o_{\ell,t}\big).$$

Interpretation. Positive $S_{\ell,i}$ means that a small increase of expert i's router bias is locally aligned with lower answer-token loss.

answer-token loss L → MoE output $o_{\ell,t}$ → router logit $z_{\ell,t,i}$ → gate bias $b^r_{\ell,i}$

backpropagation reaches the additive bias directly because $\partial z/\partial b = 1$

C. Normalize, scale, and steer only borderline routing decisions

Layer-wise normalization removes score-scale differences:

$$\hat{S}_{\ell,i} = \frac{S_{\ell,i} - \bar{S}_\ell}{\max_j |S_{\ell,j} - \bar{S}_\ell| + \epsilon}, \qquad \Delta b^{(d)}_{\ell,i} = \frac{4\,\mathrm{Std}(z_\ell)}{N_\ell}\hat{S}_{\ell,i}.$$



schematic: domain expert promoted, one generic expert suppressed

Why this scale. $4\,\mathrm{Std}(z_\ell)/N_\ell$ follows each router's natural dynamic range and remains conservative. IQR-, margin-, and squared-score scales were explored as ablations; the 4σ rule was selected for stability.

D. Deployment invariants: a domain adapter measured in kilobytes

- **All pretrained weights frozen** — No expert, attention, embedding, or router matrix is updated.
- **Standard forward path** — The offset is the ordinary bias of the router linear layer.
- **Inference sparsity unchanged** — Top-K, activated experts, and expert computation stay fixed.
- **One scalar per expert** — Many domains can be stored as tiny bias deltas, not full checkpoints.

Practical interpretation. DCRB does not teach the model new knowledge. It changes how a frozen MoE allocates already learned expert capacity to a target domain.

Experiments

1. Evaluation setup

- **Models:** Qwen1.5-MoE-A2.7B (24 layers, 60 routed experts, top-4) and Qwen3-30B-A3B (48 layers, 128 experts, top-8)
- **Calibration:** 100 labeled, non-test examples per domain; teacher forcing; answer-token loss only
- **Evaluation:** MMLU mathematics, chemistry, and history subsets; `all_part` is a held-out 300-example general subset
- **Hardware:** one NVIDIA A800 GPU with 80GB VRAM; all pretrained weights frozen

2. Results at a glance – Qwen1.5-MoE-A2.7B

+5.00 pp College mathematics 35.00 → 40.00

+3.00 pp College chemistry 45.00 → 48.00

+2.45 pp High-school U.S. history 69.12 → 71.57

General behavior is preserved. The held-out `all_part` subset is unchanged after mathematics and chemistry calibration; history calibration changes it by +0.33 pp.

3. Mathematics – one fixed DCRB configuration

Bias calibrated on 100 non-test `college_mathematics` examples. Accuracies are percentages.

Evaluation subset	Base	DCRB	Δ pp
Qwen1.5-MoE-A2.7B			
College mathematics	35.00	**40.00**	**+5.00**
Abstract algebra	38.00	**39.00**	+1.00
Elementary mathematics	40.21	**41.53**	+1.32
High-school mathematics	30.37	**31.11**	+0.74
all_part	55.67	55.67	+0.00
Qwen3-30B-A3B			
College mathematics	73.00	**74.00**	+1.00
Abstract algebra	73.00	**74.00**	+1.00
Elementary mathematics	85.19	85.19	+0.00
High-school mathematics	65.93	**66.30**	+0.37
all_part	85.00	85.00	+0.00

Cross-model pattern. Qwen1.5 improves on all four mathematics subsets. The stronger Qwen3 baseline improves or remains unchanged on every mathematics subset and on `all_part`.

4. Chemistry and history – Qwen1.5-MoE-A2.7B

Each bias is calibrated on 100 non-test examples from its named calibration subject.

Evaluation subset	Base	DCRB	Δ pp
Chemistry – calibrated on college chemistry			
College chemistry	45.00	**48.00**	**+3.00**
High-school chemistry	44.83	**45.81**	+0.98
all_part	55.67	55.67	+0.00
History – calibrated on high-school world history			
High-school world history	70.89	**72.15**	+1.26
High-school European history	68.48	67.88	−0.60
High-school U.S. history	69.12	**71.57**	**+2.45**
all_part	55.67	**56.00**	+0.33

Nuance. Chemistry improves on both target subsets. History improves on two of three target subsets; high-school European history decreases by 0.60 pp.

5. Resource accounting and router behavior

- **<1 min** — 100 examples on one A800 80GB
- **2.8KB** — Qwen1.5: 1,440 FP16 scalars
- **12.0KB** — Qwen3: 6,144 FP16 scalars
- **same Top-K** — No extra expert computation

Local rerouting. In the most affected Qwen1.5 layers, exact Top-K matches remain around 40%, while partial overlap stays high. Qwen3 reroutes more conservatively.

No collapse. Expert-activation entropy decreases, concentrating mass on a narrower domain-relevant subset, but never falls to zero.

Uncertainty. MMLU subject subsets are small. Changes below one percentage point should not be overinterpreted; the paper emphasizes repeated directionality and preservation of `all_part`, not significance of every individual cell.

Conclusion

DCRB shows that some domain adaptation of MoE LLMs can be achieved by calibrating expert selection instead of expert weights. A single small gradient pass yields a deployable router bias that improves several related subjects while preserving the original sparse computation path.

Scope and limitations

DCRB requires gradient access and cannot be used with black-box API-only models. It cannot add missing knowledge. The current study covers two MoE architectures and MMLU-style multiple-choice tasks; generation, larger calibration pools, multi-domain bias composition, and paired significance tests remain open.

Acknowledgment

This work supported by the Ministry of Economic Development of the Russian Federation (IGK 000000C313925P4C0002), agreement No139-15-2025-010.

GitHub

Github repository
github.com/CTLab-ITMO/

Contact

Telegram
@Turukmokto