

Application: **Configurable Place Finder – HTML5**  
Version: **1.1**  
Document: **Readme**  
Date: **July 31, 2013**  
Author: **CyberTech Systems and Software Ltd.**



## Description

Configurable Place Finder is a configuration of ArcGIS Server and a HTML5 application that allows citizens to locate facilities in their community. This application is typically used by citizens to locate a facility in their community that offers a recreation activity they are interested in, but can also be used by visitors to locate a facility in a community they are visiting.

## Package Contents

**Configurable Place Finder:** Folder containing web application and configuration file

**Readme.pdf:** Deployment and configuration guide

## Minimum System Requirements

- **Application Web Server**
  - P-IV with 1 GB RAM and 40 GB Hard Disk
  - IIS 5.0 or higher
  - Win 2K Server or above
- **GIS Server**
  - P-IV with 1 GB RAM and 40 GB Hard Disk
  - IIS 5.0 or higher
  - ArcGIS Desktop 10.1, ArcGIS Server 10.1 and ArcSDE 10.1
  - .NET framework 3.5 with Service Pack 1
- **Network Requirements**
  - LAN connectivity
  - Broadband internet connection
- **Client Requirements**
  - Web browser with JavaScript enabled
- **Screen Resolution**
  - 1024 x 768 high color, 32-bit or higher

## Configuration

You can configure Configurable Place Finder Template in your environment. To complete the configuration, you will need experience with Microsoft's Internet Information Server (IIS). If you are new to JavaScript Viewers, this template will demonstrate a pattern you can use to deploy your own HTML application.

1. Copy the "Configurable Place Finder" directory onto your web server so that it can be accessed as a website or virtual directory.

Example: Copy the "Configurable Place Finder" directory under C:\inetpub\wwwroot for Microsoft IIS web servers.

2. This application uses a proxy file provided by ESRI. The proxy file is available in three different languages (ASP.NET, PHP and JSP). Current application uses ASP.NET proxy file. If you wish to use a different proxy file please click [here](#). For ASP.NET proxy file, change the REST end point to the ArcGIS REST service URL in the proxy.config file.
3. Go to IIS, right-click on the parent directory of the copied files, select "Convert to Application" and set the application pool to ASP.NET v4.0.

**Note:** If you want to use a different version of ASP.NET, please follow the steps below.

- Open the source folder as a website in Visual Studio
  - Right-click on website, go to properties and change the .NET target framework to desired version
  - Publish the website
4. The "Configurable Place Finder" directory contains Config.js which is the main configuration file. To modify any configuration values, open Config.js file using a text editor like Notepad. Make necessary changes to the JSON objects. See the "Description of Configuration Tags" section below for more information.
  5. Test the application in a browser by entering the URL to the default.htm page. Example: `http://<server>/ConfigurablePlaceFinder/default.htm`  
Substitute "<server>" tag with name of your server.

Please note: "default.htm" may not be defined as a default document on your web server.

### Description of Configuration Tags (Config.js)

ApplicationName: Set application title

[ApplicationName](#): "Configurable Place Finder",

ApplicationIcon: Set application icon path

[ApplicationIcon](#): "images/i\_hydro.png",

ApplicationFavicon: Set application Favicon path

[ApplicationFavicon](#): "images/i\_hydro.ico",

ApplicationTheme: Set application theme

[ApplicationTheme](#): "styles/blueTheme.css",

SplashScreen: Set splash window content - Message that appears when the application starts

- Message: message to be displayed in splash screen
- isVisible: set visibility of splash screen to true or false

[SplashScreen](#): {

Message: "Lorem ipsum dolor sit er elit lamet, consectetur cillum adipisicing pecu, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum. Nam liber te conscient to factor tum poen legum odioque civiuda.",

```
    isVisible: true  
  },
```

HelpURL: Set URL of help page/portal

HelpURL: "help.htm",

BaseMapLayers: Set baseMap layers

Please note: All base-maps need to use the same spatial reference. By default, on application start the first base-map will be loaded

- Key: Key for every map. This has to be unique in this collection.
- ThumbnailSource: Source path of the image.
- Name: Name of the layer.
- MapURL: URL of the Map layer.

```
BaseMapLayers: [{  
  Key: "topoMap",  
  ThumbnailSource: "images/topographic.jpg",  
  Name: "Topographic Map",  
  MapURL: "http://services.arcgisonline.com/ArcGIS/rest/services/World_Topo_Map/MapServer"  
}, {  
  Key: "streets",  
  ThumbnailSource: "images/streets.png",  
  Name: "Street Map",  
  MapURL: "http://services.arcgisonline.com/ArcGIS/rest/services/World_Street_Map/MapServer"  
}],
```

DefaultExtent: Initial map extent. Use comma (,) to separate values and don't delete the last comma

DefaultExtent: " -9991781.18961914, 4083344.0852194074, -9160146.321876464, 4494881.045506775",

FacilityLayer: URL used for doing query task on the feature layer,

For facilities photos, recommended image format is PNG and each image size should be maximum up to 700 KB.

FacilityLayer: "http://50.18.115.76:6080/arcgis/rest/services/WaterAccess/FeatureServer/0",

PrimaryKeyForFeatures: Set the primary key attribute for features

PrimaryKeyForFeatures: "\${OBJECTID}",

CommentsLayer:

- Visibility: Set to true if comments need to be displayed , or false if not required
- URL: URL used for doing query task on the comments layer

CommentsLayer: {

Visibility: true,

URL: "http://50.18.115.76:6080/arcgis/rest/services/WaterAccess/FeatureServer/1"

},

PrimaryKeyForComments: Set the primary key attribute for comments

PrimaryKeyForComments: "\${id}",

FeatureName: Set the name attribute for features

FeatureName: "\${Name}",

ReferenceOverlayLayer: Set the URL for the overlay layer

- ServiceUrl: ServiceUrl is the REST end point for the reference overlay layer
- DisplayOnLoad: DisplayOnLoad setting is used to show or hide the reference overlay layer. Reference overlay will be shown when it is set to true

ReferenceOverlayLayer:

{

ServiceUrl: " http://50.18.115.76:6080/arcgis/rest/services/HuntableLands/MapServer/0",

DisplayOnLoad: true

},

InfoWindowHeader : Set Info-window title. Configure this with text/fields

InfoWindowHeader: [{

FieldName: "\${Name}",

Alias: "Facility Name",

InfoWindowHeaderText: "Facility Info"

}],

InfoWindowContent: Choose content/fields for the infowindow

InfoWindowContent: [{

FieldName: "\${Region}",

Alias: "Region"

}],

InfoPopupFieldsCollection: Set the content to be displayed on the info-Popup. Define labels, field values, field types and field formats

- DisplayText: Field used for displaying the Text instead of alias names
- FieldName: Field used for getting the details of the particular service feature

InfoPopupFieldsCollection: [{

DisplayText: "Region:",

FieldName: "\${Region}"

```

}, {
  DisplayText: "Hours Open For:",
  FieldName: "${Hours_Open}"
}, {
  DisplayText: "Owner:",
  FieldName: "${Owner}"
}, {
  DisplayText: "Facility Type:",
  FieldName: "${Type}"
}
],

```

Activities: Activities to be displayed in info window for a feature

- FieldName: Field used for getting the details of the particular service feature
- Alias: Alias name of that particular field
- Image: Image used to represent that particular field
- Name: field used to show the name of the Activity

```

Activities: [{
  FieldName: "${FourWheel}",
  Alias: "FourWheel",
  Image: "images/fourwheel.png",
  isSelected: true
}, {
  FieldName: "${HandicapPark}",
  Alias: "Handicap Parking Available",
  Image: "images/handicapparks.png"
}, {
  FieldName: "${LightedPark}",
  Alias: "Lighted Park",
  Image: "images/lightedpark.png"
}, {
  FieldName: "${OpenYearRound}",
  Alias: "Open Year Round",
  Image: "images/openyearround.png"
}, {
  FieldName: "${SunriseSunset}",
  Alias: "Sunrise Sunset",
  Image: "images/sunrisesunset.png"
}, {
  FieldName: "${ElectricHookup}",
  Alias: "Electric Hookup",
  Image: "images/electrichookup.png"
}, {
  FieldName: "${WaterHookup}",
  Alias: "Water Hookup",
  Image: "images/waterhookup.png"
}
]

```

```

}, {
  FieldName: "${Restrooms}",
  Alias: "Restrooms Available",
  Image: "images/restrooms.png"
}, {
  FieldName: "${FishingPier}",
  Alias: "Fishing Pier",
  Image: "images/fishingpier.png"
}, {
  FieldName: "${CanoeLanding}",
  Alias: "Canoe Landing",
  Image: "images/canoelanding.png"
}, {
  FieldName: "${WinterPool}",
  Alias: "Winter Pool",
  Image: "images/winterpool.png"
}, {
  FieldName: "${CourtesyDock}",
  Alias: "Courtesy Dock",
  Image: "images/courtesydock.png"
}, {
  FieldName: "${RentalAvail}",
  Alias: "Rental Available",
  Image: "images/rentavail.png"
}, {
  FieldName: "${BoatRamp}",
  Alias: "Boat Ramp",
  Image: "images/boatramp.png"
}, {
  FieldName: "${Marina}",
  Alias: "Marina",
  Image: "images/marina.png"
}, {
  FieldName: "${Fishing}",
  Alias: "Fishing",
  Image: "images/fishing.png"
}
],

```

Set size of the info-Popup - select maximum height and width in pixels (not applicable for tabbed info-Popup)

InfoPopupHeight: 270,

InfoPopupWidth: 330,

ShowNullValueAs: Set string value to be shown for null or blank values

ShowNullValueAs: "N/A",

FormatDateAs : Set date format

FormatDateAs: "MMM dd, yyyy",

BufferDistance: set distance in miles for drawing the buffer

BufferDistance: "2",

LocatorRippleSize: Set the locator ripple size

LocatorRippleSize: 40,

GetDirectionsMobile: Set this variable to true/false to enable/disable directions for Mobile/tablet

GetDirectionsMobile: true,

GetDirectionsDesktop: Set this variable to true/false to enable/disable directions for desktop

GetDirectionsDesktop: true,

GetDirections: Set this variable to true/false to enable/disable directions

Note: if this master variable is set to false directions cannot be enabled for any of the devices

GetDirections: true,

ApproximateValue: Set this value to display text besides calculated distances in search results

ApproximateValue: "approx",

LocatorSettings: Set locator settings such as locator symbol, size, display fields, match score

LocatorSettings: {

DefaultLocatorSymbol: "images/RedPushpin.png",

MarkupSymbolSize: {

width: 35,

height: 35

},

Locators: [{

DisplayText: "Location",

LocatorDefaultAddress: "Lake Echo Rd, Tracy City, TN, 37387",

LocatorParameters: { SearchField: "text", SearchResultField: "outFields", SearchCountField: "maxLocations", SearchBoundaryField: "bbox", SpatialReferenceField: "outSR" },

LocatorURL: "http://geocode.arcgis.com/arcgis/rest/services/World/GeocodeServer/find",

CandidateFields: "Addr\_type,Type,Score, Match\_addr",

DisplayField: "\${Match\_addr}",

AddressMatchScore: { Field: "Score", Value: 80 },

LocatorFieldName: 'Addr\_type',

LocatorFieldValues: ["StreetAddress", "StreetName", "PointAddress"],

CountyFields: { LocatorFieldValue: 'POI', FieldName: 'Type', Value: 'county', countySearch: true },

MaxResults: 200

},{

DisplayText: "Name",

LocatorDefaultFeature: "Shelby Park"

},{

DisplayText: "Activity"

}

```
    ]  
  },  
  ZoomLevel: Set the Zoom Level  
  ZoomLevel: 12,
```

DatabaseFields: Define the database field names, DateFieldName refers to a date database field. All other attributes refer to text database fields.

```
DatabaseFields: {  
  FeatureIdFieldName: "id",  
  CommentsFieldName: "COMMENTS",  
  DateFieldName: "SUBMITDT",  
  RankFieldName: "RANK"  
},
```

CommentsInfoPopupFieldsCollection: Set info-pop fields for adding and displaying comment

```
CommentsInfoPopupFieldsCollection: {  
  Rank: "${RANK}",  
  SubmitDate: "${SUBMITDT}",  
  Comments: "${COMMENTS}"  
},
```

GeometryService : Set geometry service URL

```
GeometryService: "http://tasks.arcgisonline.com/ArcGIS/rest/services/Geometry/GeometryServer",
```

RouteServiceURL : Set URL for routing service

```
RouteServiceURL:  
"http://tasks.arcgisonline.com/ArcGIS/rest/services/NetworkAnalysis/ESRI_Route_NA/NAserver/Route,
```

RouteColor: Set color for the route symbol

```
RouteColor: "#7F7FFE",
```

RouteWidth: Set width of the route

```
RouteWidth: 6,
```

InfoBoxWidth: Set width of the boxes in the bottom panel

```
InfoBoxWidth: 422,
```

MapSharingOptions: Set URL for TinyURL service, and URLs for social media.

- TinyURLServiceURL: used for converting the long URL to short URL
- TinyURLResponseAttribute: It is a response for the URL for converting long URL to short URL and it behaves as a key for that URL.
- FacebookShareURL: Social networking site URL

```
MapSharingOptions: {  
  TinyURLServiceURL:
```

```
"http://api.bit.ly/v3/shorten?login=esri&apiKey=R_65fd9891cd882e2a96b99d4bda1be00e&uri=${0}&format=json",
```



```
TinyURLResponseAttribute: "data.url",
```

```
FacebookShareURL:
```

```
"http://www.facebook.com/sharer.php?u=${0}&t=Configurable%20Place%20Finder",
```

```
TwitterShareURL: "http://mobile.twitter.com/compose/tweet?status= Configurable  
%20Place%20Finder ${0}",
```

```
ShareByMailLink: "mailto:%20?subject=Check%20out%20this%20map!&body=${0}"
```

```
},
```

Order: Set sequence for info pods in the bottom panel

```
Order: ["search", "facility", "directions", "photogallery", "comments"]
```

```
});
```