

2. Internal functions

Ada (body)

driverspace_workspace/formal/ds-spark-core/src/ds_buddy_math.adb (line 6)

[function] function Power_Of_Two (Exponent : Block_Size) return Phys_Addr is

driverspace_workspace/formal/ds-spark-core/src/ds_buddy_math.adb (line 11)

[function] function Is_Aligned (Addr : Phys_Addr; Size_Exp : Block_Size) return Boolean is

driverspace_workspace/formal/ds-spark-core/src/ds_buddy_math.adb (line 18)

[function] function Get_Buddy_Address (

driverspace_workspace/formal/ds-spark-core/src/ds_buddy_math.adb (line 31)

[function] function Get_Left_Child_Address (

driverspace_workspace/formal/ds-spark-core/src/ds_buddy_math.adb (line 40)

[function] function Get_Right_Child_Address (

driverspace_workspace/formal/ds-spark-core/src/ds_buddy_math.adb (line 50)

[function] function Safe_Calculate_DMA_End (

kernel_Workspace/kernel/src/policy/ada/policy.adb (line 5)

[function] function Evaluate (Ring : Ring_Id;

kernel_Workspace/kernel/src/policy/ada/policy_c.adb (line 5)

[function] function To_Ring (V : Unsigned_8) return Ring_Id is

kernel_Workspace/kernel/src/policy/ada/policy_c.adb (line 11)

[function] function To_Class (V : Unsigned_8) return Call_Class is

kernel_Workspace/kernel/src/policy/ada/policy_c.adb (line 20)

[function] function policy_evaluate (ring : Unsigned_8;

Assembly

comgrub/src/boot.asm (line 10)

[label] mboot_header_start:

comgrub/src/boot.asm (line 19)

[label] mboot_header_end:

comgrub/src/boot.asm (line 23)

[label] stack_bottom:

comgrub/src/boot.asm (line 25)

[label] stack_top:

comgrub/src/boot.asm (line 33)

[label] _start:

kernel_Workspace/kernel-bin/src/boot.asm (line 8)

[label] kernel_bin_entry:

kernel_Workspace/kernel/src/cpu/trampoline.s (line 13)

[label] trampoline_start:

kernel_Workspace/kernel/src/cpu/trampoline.s (line 31)

[label] trampoline_32:

kernel_Workspace/kernel/src/cpu/trampoline.s (line 59)

[label] trampoline_64:

kernel_Workspace/kernel/src/cpu/trampoline.s (line 81)

[label] trampoline_gdt:

kernel_Workspace/kernel/src/cpu/trampoline.s (line 87)

[label] trampoline_gdt_end:

kernel_workspace/kernel/src/cpu/trampoline.s (line 90)
[label] trampoline_gdtr:
kernel_workspace/kernel/src/cpu/trampoline.s (line 95)
[label] trampoline_cr3: .quad 0
kernel_workspace/kernel/src/cpu/trampoline.s (line 96)
[label] trampoline_entry: .quad 0
kernel_workspace/kernel/src/cpu/trampoline.s (line 97)
[label] trampoline_stack: .quad 0
kernel_workspace/kernel/src/cpu/trampoline.s (line 98)
[label] trampoline_arg: .quad 0
kernel_workspace/kernel/src/cpu/trampoline.s (line 101)
[label] trampoline_end:
kernel_workspace/kernel/src/mm/arch/x86_64/tlb_asm.s (line 5)
[label] tlb_asm_invlpg:
kernel_workspace/kernel/src/mm/arch/x86_64/tlb_asm.s (line 11)
[label] tlb_asm_read_cr3:
kernel_workspace/kernel/src/mm/arch/x86_64/tlb_asm.s (line 17)
[label] tlb_asm_write_cr3:
kernel_workspace/kernel/src/mm/arch/x86_64/tlb_asm.s (line 23)
[label] tlb_asm_read_cr4:
kernel_workspace/kernel/src/mm/arch/x86_64/tlb_asm.s (line 29)
[label] tlb_asm_write_cr4:
kernel_workspace/kernel/src/mm/arch/x86_64/tlb_asm.s (line 36)
[label] tlb_asm_invpaid:
kernel_workspace/kernel/src/mm/arch/x86_64/tlb_asm.s (line 42)
[label] tlb_asm_wbinvd:
kernel_workspace/kernel/src/mm/arch/x86_64/tlb_asm.s (line 48)
[label] tlb_asm_clflush:
kernel_workspace/kernel/src/trampoline_rings/arch/aarch64/trampoline_rings.s (line 4)
[label] vector_table:
kernel_workspace/kernel/src/trampoline_rings/arch/aarch64/trampoline_rings.s (line 41)
[label] vector_default:
kernel_workspace/kernel/src/trampoline_rings/arch/aarch64/trampoline_rings.s (line 44)
[label] vector_hyper:
kernel_workspace/kernel/src/trampoline_rings/arch/aarch64/trampoline_rings.s (line 104)
[label] tr_init:
kernel_workspace/kernel/src/trampoline_rings/arch/aarch64/trampoline_rings.s (line 113)
[label] tr_restore_ctx:
kernel_workspace/kernel/src/trampoline_rings/arch/risc-v/trampoline_rings.s (line 3)
[label] kstack_top:
kernel_workspace/kernel/src/trampoline_rings/arch/risc-v/trampoline_rings.s (line 10)
[label] trap_entry:
kernel_workspace/kernel/src/trampoline_rings/arch/risc-v/trampoline_rings.s (line 100)
[label] tr_init:
kernel_workspace/kernel/src/trampoline_rings/arch/risc-v/trampoline_rings.s (line 116)
[label] tr_restore_ctx:
kernel_workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.s (line 4)
[label] tr_gdt:

```

kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.s (line 13)
[label] tr_tss_desc:
kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.s (line 16)
[label] gdt_ptr:
kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.s (line 22)
[label] tr_tss:
kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.s (line 29)
[label] tr_init:
kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.s (line 56)
[label] isr_hypercall:
kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.s (line 96)
[label] isr_default:
kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.s (line 101)
[label] tr_restore_ctx:
triang-lang/out/x86_64/prog.asm (line 4)
[label] buffer: resb 16
triang-lang/out/x86_64/prog.asm (line 8)
[label] main:
triang-lang/out/x86_64/prog.asm (line 9)
[label] fn_main:
triang-lang/out/x86_64/prog.asm (line 17)
[label] fill_1:
triang-lang/out/x86_64/prog.asm (line 24)
[label] fill_end_2:
triang-lang/out/x86_64/prog.asm (line 41)
[label] else_1:
triang-lang/out/x86_64/prog.asm (line 43)
[label] end_2:
triang-lang/out/x86_64/prog.asm (line 44)
[label] loop_3:
triang-lang/out/x86_64/prog.asm (line 51)
[label] loop_end_4:

```

C

```

kernel_Workspace/kernel/src/core-lang/native_x86.c (line 30)
[function] static void push_rax(nb_t *d) { nb_u8(d, 0x50); }
kernel_Workspace/kernel/src/core-lang/native_x86.c (line 31)
[function] static void pop_rax(nb_t *d) { nb_u8(d, 0x58); }
kernel_Workspace/kernel/src/core-lang/native_x86.c (line 32)
[function] static void pop_rcx(nb_t *d) { nb_u8(d, 0x59); }
kernel_Workspace/kernel/src/core-lang/native_x86.c (line 33)
[function] static void push_rcx(nb_t *d) { nb_u8(d, 0x51); }
kernel_Workspace/kernel/src/mm/alloc/api/alloc.c (line 10)
[function] static void k_memset(const void *dst, const uint8 value, const size_t n) {
kernel_Workspace/kernel/src/mm/alloc/api/alloc.c (line 15)
[function] static void k_memcpy(const void *dst, const void *src, const size_t n) {
kernel_Workspace/kernel/src/mm/alloc/api/alloc.c (line 21)
[function] static size_t k_strlen(const char *s) {

```

```

kernel_Workspace/kernel/src/mm/alloc/api/alloc.c (line 27)
[function] static size_t k_usable_size(void *ptr) {
kernel_Workspace/kernel/src/mm/alloc/debug/alloc_debug.c (line 25)
[function] static uint64_t dbg_tail_canary(size_t size) { return ~((uint64_t)size) ^
DBG_MAGIC; }
kernel_Workspace/kernel/src/mm/alloc/heap/buddy.c (line 25)
[function] static inline uint64_t order_size(size_t o) { return ARCH_PAGE_SIZE << o;
}
kernel_Workspace/kernel/src/mm/alloc/heap/buddy.c (line 26)
[function] static size_t page_of(uint64_t va) { return (size_t)((va - buddy_base) /
ARCH_PAGE_SIZE); }
kernel_Workspace/kernel/src/mm/alloc/heap/buddy.c (line 27)
[function] static uint64_t va_of(size_t page) { return buddy_base + (uint64_t)page *
ARCH_PAGE_SIZE; }
kernel_Workspace/kernel/src/mm/alloc/heap/buddy.c (line 28)
[function] static size_t size_to_order(size_t size) {
kernel_Workspace/kernel/src/mm/alloc/heap/buddy.c (line 36)
[function] static void fl_push(size_t o, size_t idx) {
kernel_Workspace/kernel/src/mm/alloc/heap/buddy.c (line 40)
[function] static size_t fl_pop(size_t o) {
kernel_Workspace/kernel/src/mm/alloc/heap/buddy.c (line 46)
[function] static void fl_remove(size_t o, size_t idx) {

```

Nim

```

kernel_Workspace/kernel/src/nimcore/banner.nim (line 13)
[proc] proc nim_banner(buf: ptr uint8, cap: uint32): uint32 {.exportc, cdecl.} =
kernel_Workspace/kernel/src/nimcore/format.nim (line 1)
[proc] proc nim_u64_to_str(v: uint64, base: uint8, buf: ptr uint8, cap: uint32):
uint32
kernel_Workspace/kernel/src/nimcore/format.nim (line 29)
[proc] proc nim_hex_dump(src: ptr uint8, len: uint32, buf: ptr uint8, cap: uint32):
uint32
kernel_Workspace/kernel/src/nimcore/parse.nim (line 1)
[proc] proc nim_parse_u64(s: ptr uint8, len: uint32, base: uint8, out_v: ptr
uint64): uint8
kernel_Workspace/kernel/src/nimcore/ringbuf.nim (line 1)
[type] type Rb = object
kernel_Workspace/kernel/src/nimcore/ringbuf.nim (line 8)
[proc] proc nim_rb_push(b: uint8): uint8 {.exportc, cdecl.} =
kernel_Workspace/kernel/src/nimcore/ringbuf.nim (line 15)
[proc] proc nim_rb_pop(): int32 {.exportc, cdecl.} =
kernel_Workspace/kernel/src/nimcore/ringbuf.nim (line 21)
[proc] proc nim_rb_len(): uint32 {.exportc, cdecl.} =
kernel_Workspace/kernel/src/nimcore/shell.nim (line 1)
[type] type Handler = proc(arg: ptr uint8, len: uint32): int32 {.cdecl.}
kernel_Workspace/kernel/src/nimcore/shell.nim (line 3)
[type] type Cmd = object
kernel_Workspace/kernel/src/nimcore/shell.nim (line 11)
[proc] proc nim_shell_register(name: ptr uint8, nlen: uint32, h: Handler): uint8

```

```

kernel_Workspace/kernel/src/nimcore/shell.nim (line 28)
[proc] proc eq_name(c: var Cmd, line: ptr uint8, nlen: uint32): bool =
kernel_Workspace/kernel/src/nimcore/shell.nim (line 36)
[proc] proc nim_shell_run(line: ptr uint8, len: uint32): int32
kernel_Workspace/kernel/src/policy/nim/policynim.nim (line 10)
[proc] proc nim_policy_log(ring, cls, op, dec: uint8) {.exportc, cdecl.} =
kernel_Workspace/kernel/src/policy/nim/policynim.nim (line 17)
[proc] proc nim_policy_denies(): uint64 {.exportc, cdecl.} =
kernel_Workspace/kernel/src/policy/nim/policynim.nim (line 20)
[proc] proc nim_policy_get(idx: uint32,

```

Python

```

doc.py (line 298)
[function] def _rules_js_ts():
doc.py (line 313)
[function] def _rules_java_cs():
doc.py (line 322)
[function] def _rules_go():
doc.py (line 331)
[function] def _rules_rust():
doc.py (line 342)
[function] def _rules_c_cpp():
doc.py (line 350)
[function] def _rules_php():
doc.py (line 359)
[function] def _rules_ruby():
doc.py (line 367)
[function] def _rules_kotlin_swift():
doc.py (line 378)
[function] def _rules_d():
doc.py (line 387)
[function] def _rules_nim():
doc.py (line 399)
[function] def _rules_odin():
doc.py (line 410)
[function] def _rules_ada_spec():
doc.py (line 420)
[function] def _rules_ada_body():
doc.py (line 428)
[function] def _rules_asm():
doc.py (line 660)
[function] def _new_doc(path: str):
doc.py (line 667)
[function] def _summary_paragraph(styles, root, public_defs, internal_defs,
md_files):
driverspace_workspace/drivers/iommu-TrangorgeOS/tools/pci_ids.py (line 63)
[function] def _pascal_tokens(tokens: list[str], max_tokens: int | None = None) ->
str:

```

driverspace_workspace/drivers/iommu-TrangorgeOS/tools/pci_ids.py (line 179)

```
[method] def __init__(self) -> None:
```

Rust

c.rs (line 57)

```
[struct] struct BlockHeader* next; /* Wskaźnik do następnego bloku */
```

c.rs (line 58)

```
[struct] struct BlockHeader* prev; /* Wskaźnik do poprzedniego bloku */
```

comgrub/build.rs (line 1)

```
[function] fn main() {
```

comgrub/src/main.rs (line 11)

```
[function] fn kernel_main(magic: u32, info: *const u8) -> !;
```

comgrub/src/main.rs (line 15)

```
[function] fn panic(_info: &PanicInfo) -> ! {
```

comlimine/build.rs (line 1)

```
[function] fn main() {
```

comlimine/src/main.rs (line 1)

```
[function] fn main() {}
```

drivers/amdgpu_driver/src/main.rs (line 1)

```
[function] fn main() {
```

drivers/audiodriver/build.rs (line 12)

```
[function] fn main() {
```

drivers/audiodriver/src/lib.rs (line 7)

```
[function] fn ad_init(nam_va: u64, bm_va: u64) -> i32;
```

drivers/audiodriver/src/lib.rs (line 8)

```
[function] fn ad_play(data_phys: u64, len: u32, bdl_va: u64, bdl_phys: u64) -> i32;
```

drivers/audiodriver/src/lib.rs (line 9)

```
[function] fn ad_capture(data_phys: u64, len: u32, bdl_va: u64, bdl_phys: u64) -> i32;
```

drivers/audiodriver/src/lib.rs (line 10)

```
[function] fn ad_stop() -> i32;
```

drivers/audiodriver/src/lib.rs (line 11)

```
[function] fn ad_jack_present() -> i32;
```

drivers/audiodriver/src/lib.rs (line 12)

```
[function] fn ad_set_amp(on: i32) -> i32;
```

drivers/audiodriver/src/lib.rs (line 13)

```
[function] fn ad_position() -> u32;
```

drivers/audiodriver/src/main.rs (line 8)

```
[function] fn main() {
```

drivers/intelgpu_driver/src/main.rs (line 1)

```
[function] fn main() {
```

drivers/netcam_driver/src/main.rs (line 1)

```
[function] fn main() {
```

drivers/wacomgraphic_driver/src/main.rs (line 1)

```
[function] fn main() {
```

driverspace/src/drivers/storage.rs (line 20)

```
[function] fn init(&mut self, _info: &DeviceInfo) -> Result<(), DsError> {
```

driverspace/src/main.rs (line 32)

```
[function] fn panic(_info: &core::panic::PanicInfo) -> ! {
```

```

driverspace_workspace/crates/ds-manager/src/main.rs (line 1)
[function] fn main() {
driverspace_workspace/drivers/amdgpu-driver/src/main.rs (line 1)
[function] fn main() {
driverspace_workspace/drivers/audiodriver/src/main.rs (line 1)
[function] fn main() {
driverspace_workspace/drivers/intelgpu-driver/src/main.rs (line 1)
[function] fn main() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 12)
[function] fn checked_add(self, offset: usize) -> Option<Self>;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 19)
[function] fn checked_add(self, offset: usize) -> Option<Self> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 28)
[function] fn checked_add(self, offset: usize) -> Option<Self> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 37)
[function] fn checked_add(self, offset: usize) -> Option<Self> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 91)
[function] fn into(self) -> usize {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 98)
[function] fn from(value: usize) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 134)
[function] fn fmt(&self, f: &mut fmt::Formatter<'>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 140)
[function] fn fmt(&self, f: &mut fmt::Formatter<'>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 146)
[function] fn fmt(&self, f: &mut fmt::Formatter<'>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 152)
[function] fn fmt(&self, f: &mut fmt::Formatter<'>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 181)
[function] fn from_start_size(start: MmioAddr<T>, size: usize) -> Option<Self>;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 182)
[function] fn from_phys_range(range: PhysAddrRange) -> Self;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 183)
[function] fn from_phys_start_size(start: PhysAddr, size: usize) -> Option<Self>;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 184)
[function] fn to_phys_range(self) -> PhysAddrRange;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 185)
[function] fn as_phys_range(self) -> PhysAddrRange {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 188)
[function] fn reg<const W: usize>(self, offset: usize) -> Option<MmioAddr<T>>;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 189)
[function] fn reg8(self, offset: usize) -> Option<MmioAddr<T>>;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 190)
[function] fn reg16(self, offset: usize) -> Option<MmioAddr<T>>;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 191)
[function] fn reg32(self, offset: usize) -> Option<MmioAddr<T>>;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 192)
[function] fn reg64(self, offset: usize) -> Option<MmioAddr<T>>;

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 193)
[function] fn reg16_aligned(self, offset: usize) -> Option<MmioAddr<T>>;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 194)
[function] fn reg32_aligned(self, offset: usize) -> Option<MmioAddr<T>>;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 195)
[function] fn reg64_aligned(self, offset: usize) -> Option<MmioAddr<T>>;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 200)
[function] fn from_start_size(start: MmioAddr<T>, size: usize) -> Option<Self> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 205)
[function] fn from_phys_range(range: PhysAddrRange) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 213)
[function] fn from_phys_start_size(start: PhysAddr, size: usize) -> Option<Self> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 218)
[function] fn to_phys_range(self) -> PhysAddrRange {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 226)
[function] fn reg<const W: usize>(self, offset: usize) -> Option<MmioAddr<T>> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 233)
[function] fn reg8(self, offset: usize) -> Option<MmioAddr<T>> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 238)
[function] fn reg16(self, offset: usize) -> Option<MmioAddr<T>> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 243)
[function] fn reg32(self, offset: usize) -> Option<MmioAddr<T>> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 248)
[function] fn reg64(self, offset: usize) -> Option<MmioAddr<T>> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 253)
[function] fn reg16_aligned(self, offset: usize) -> Option<MmioAddr<T>> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 259)
[function] fn reg32_aligned(self, offset: usize) -> Option<MmioAddr<T>> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 265)
[function] fn reg64_aligned(self, offset: usize) -> Option<MmioAddr<T>> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 291)
[function] fn from(port: u16) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 298)
[function] fn from(port: IoPort) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 336)
[function] fn fmt(&self, f: &mut fmt::Formatter<'>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 342)
[function] fn fmt(&self, f: &mut fmt::Formatter<'>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 348)
[function] fn fmt(&self, f: &mut fmt::Formatter<'>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 354)
[function] fn fmt(&self, f: &mut fmt::Formatter<'>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 417)
[function] fn fmt(&self, f: &mut fmt::Formatter<'>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 426)
[function] fn assert_mmio_round_trips<T: Unsigned>(samples: &[usize]) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 438)
[function] fn assert_iovi_round_trips<T: Unsigned>(samples: &[usize]) {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 446)
[function] fn mmio_value<T: Unsigned>(addr: MmioAddr<T>) -> usize {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 451)
[function] fn mmio_addr_u32_round_trips_representable_values() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 456)
[function] fn mmio_addr_u64_round_trips_representable_values() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 461)
[function] fn iovi_addr_u32_round_trips_representable_values() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 466)
[function] fn iovi_addr_u64_round_trips_representable_values() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 473)
[function] fn mmio_addr_u32_rejects_out_of_range_values() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 480)
[function] fn mmio_addr_u32_checked_add_and_mul_reject_overflows() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 489)
[function] fn iovi_addr_u32_rejects_out_of_range_values() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/addr.rs (line 494)
[function] fn mmio_range_register_helpers_respect_bounds_and_alignment() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 55)
[function] fn from(value: AcpiError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 62)
[function] fn from(value: BdfRangeSetError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 69)
[function] fn from(value: PagingError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 75)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 85)
[function] fn checked_offset(base: usize, offset: usize) -> Result<usize, IortError>
{
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 90)
[function] fn mmio_address(base: u64) -> Result<MmioAddr, IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 96)
[function] fn mmio_range_from_start_size(start: u64, size: u64) ->
Result<MmioAddrRange, IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 107)
[function] fn phys_range_from_start_size(start: u64, size: u64) ->
Result<PhysAddrRange, IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 129)
[function] fn header(&self) -> &SdtHeader {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 134)
[function] fn table_bytes<'a, T: AcpiTable>(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 169)
[function] fn read_array<const N: usize>(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 186)
[function] fn read_u8(bytes: &[u8], offset: usize) -> Result<u8, IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 194)
[function] fn read_u16(bytes: &[u8], offset: usize) -> Result<u16, IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 203)
[function] fn read_u32(bytes: &[u8], offset: usize) -> Result<u32, IortError> {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 212)
[function] fn read_u64(bytes: &[u8], offset: usize) -> Result<u64, IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 226)
[function] fn parse(bytes: &'a [u8]) -> Result<Self, IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 584)
[function] fn for_each_node<F>(self, mut f: F) -> Result<(), IortError>
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 594)
[function] fn translate_once(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 624)
[function] fn parse_node(self, offset: usize) -> Result<IortNode<'a>, IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 644)
[function] fn parse_node_header(self, offset: usize) -> Result<IortNodeHeader,
IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 667)
[function] fn parse_its_group(self, header: IortNodeHeader) -> Result<IortItsGroup,
IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 679)
[function] fn parse_named_component(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 709)
[function] fn parse_root_complex(self, header: IortNodeHeader) ->
Result<IortRootComplex, IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 725)
[function] fn parse_smmu(self, header: IortNodeHeader) -> Result<IortSmmu,
IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 745)
[function] fn parse_smmu_v3(self, header: IortNodeHeader) -> Result<IortSmmuV3,
IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 771)
[function] fn parse_pmcg(self, header: IortNodeHeader) -> Result<IortPmcg,
IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 789)
[function] fn parse_reserved_memory(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 804)
[function] fn id_mappings_for_header(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 836)
[function] fn smmu_interrupts(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 870)
[function] fn read_memory_access(self, offset: usize) -> Result<IortMemoryAccess,
IortError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 888)
[function] fn next(&mut self) -> Option<Self::Item> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1018)
[struct] struct IortSingleStepTranslation {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1077)
[function] fn translate_for_node_kind(self, kind: IortNodeKind, input_id: u32) ->
Option<u32> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1110)
[function] fn next(&mut self) -> Option<Self::Item> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1152)
[function] fn next(&mut self) -> Option<Self::Item> {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1247)
[function] fn next(&mut self) -> Option<Self::Item> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1342)
[function] fn next(&mut self) -> Option<Self::Item> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1371)
[struct] struct TestEntry;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1376)
[function] fn new_leaf(_paddr: PhysAddr, _flags: Self::Flags, _size: PageSize) ->
Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1380)
[function] fn new_table(_paddr: PhysAddr, _level: u8) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1384)
[function] fn paddr(&self) -> PhysAddr {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1388)
[function] fn flags(&self) -> Self::Flags {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1390)
[function] fn is_present(&self) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1394)
[function] fn entry_kind(&self, _level: u8) -> PageTableEntryKind {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1398)
[function] fn clear(&mut self) {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1400)
[function] fn bits(&self) -> u64 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1404)
[function] fn from_bits(_bits: u64) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1409)
[function] fn write_sdt_header(bytes: &mut [u8], signature: Signature, length:
usize) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1415)
[function] fn finish_sdt_checksum(bytes: &mut [u8]) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1424)
[function] fn table_mapping(bytes: &[u8]) -> Mapping<TestEntry, VirtAddr> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1433)
[function] fn write_node_header(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1449)
[function] fn write_id_mapping(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1466)
[function] fn parses_root_complex_smmuv3_and_id_mapping() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/iort.rs (line 1586)
[function] fn parses_its_group_and_reserved_memory_descriptors() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/smmu3/mod.rs (line 26)
[function] fn level_shift(level: u8) -> u32 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/smmu3/mod.rs (line 31)
[function] fn level_index_bits(level: u8) -> u32 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/smmu3/mod.rs (line 40)
[function] fn level_supports_leaf(level: u8, size: PageSize) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/smmu3/mod.rs (line 66)
[function] fn level_shift(level: u8) -> u32 {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/smmu3/mod.rs (line 71)
[function] fn level_index_bits(level: u8) -> u32 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/smmu3/mod.rs (line 76)
[function] fn level_supports_leaf(level: u8, size: PageSize) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/smmu3/mod.rs (line 102)
[function] fn level_shift(level: u8) -> u32 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/smmu3/mod.rs (line 107)
[function] fn level_index_bits(level: u8) -> u32 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/smmu3/mod.rs (line 112)
[function] fn level_supports_leaf(level: u8, size: PageSize) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/smmu3/mod.rs (line 145)
[function] fn smmu_vmsa_uses_iova_addresses() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/aarch64/smmu3/mod.rs (line 151)
[function] fn root_index_widths_match_granule_and_va_width() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/riscv64/riscv/paging.rs (line 24)
[function] fn level_shift(level: u8) -> u32 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/riscv64/riscv/paging.rs (line 29)
[function] fn level_supports_leaf(level: u8, size: PageSize) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/riscv64/riscv/paging.rs (line 59)
[function] fn riscv_iommu_uses_iova_addresses() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/riscv64/riscv/paging.rs (line 65)
[function] fn sv_widths_match_expected_levels() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 80)
[function] fn from(value: AcpiError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 87)
[function] fn from(value: BdfRangeSetError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 94)
[function] fn from(value: PagingError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 100)
[function] fn fmt(&self, f: &mut fmt::Formatter<'>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 110)
[function] fn mmio_register_window(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 121)
[function] fn phys_range_from_start_size(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 146)
[function] fn header(&self) -> &SdtHeader {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 151)
[function] fn table_bytes<'a, T: AcpiTable>(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 186)
[function] fn read_array<const N: usize>(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 203)
[function] fn read_u8(bytes: &[u8], offset: usize) -> Result<u8, IvrsError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 211)
[function] fn read_u16(bytes: &[u8], offset: usize) -> Result<u16, IvrsError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 220)
[function] fn read_u32(bytes: &[u8], offset: usize) -> Result<u32, IvrsError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 229)
[function] fn read_u64(bytes: &[u8], offset: usize) -> Result<u64, IvrsError> {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 243)
[function] fn parse(bytes: &'a [u8]) -> Result<Self, IvrsError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 370)
[function] fn for_each_block<F>(self, mut f: F) -> Result<(), IvrsError>
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 380)
[function] fn parse_block(self, offset: usize, length: usize, kind: u8) ->
Result<IvrsBlock, IvrsError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 396)
[function] fn parse_ivhd(self, offset: usize, length: usize, block_type: u8) ->
Result<Ivhd, IvrsError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 461)
[function] fn parse_ivmd(self, offset: usize, length: usize, block_type: u8) ->
Result<Ivmd, IvrsError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 479)
[function] fn walk_device_entries<F>(<
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 629)
[function] fn next(&mut self) -> Option<Self::Item> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 766)
[struct] struct PendingIvhdRange {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 850)
[struct] struct TestEntry;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 855)
[function] fn new_leaf(_paddr: PhysAddr, _flags: Self::Flags, _size: PageSize) ->
Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 859)
[function] fn new_table(_paddr: PhysAddr, _level: u8) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 863)
[function] fn paddr(&self) -> PhysAddr {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 867)
[function] fn flags(&self) -> Self::Flags {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 869)
[function] fn is_present(&self) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 873)
[function] fn entry_kind(&self, _level: u8) -> PageTableEntryKind {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 877)
[function] fn clear(&mut self) {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 879)
[function] fn bits(&self) -> u64 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 883)
[function] fn from_bits(_bits: u64) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 888)
[function] fn registers(base: usize) -> MmioAddrRange {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 896)
[function] fn write_sdt_header(bytes: &mut [u8], signature: Signature, length:
usize) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 902)
[function] fn finish_sdt_checksum(bytes: &mut [u8]) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 911)
[function] fn table_mapping(bytes: &[u8]) -> Mapping<TestEntry, VirtAddr> {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 921)
[function] fn parses_ivhd_and_bdf_ranges() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 963)
[function] fn parses_ivmd_reserved_memory() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/ivrs.rs (line 991)
[function] fn parses_extended_and_acpi_named_ivhd_entries() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 63)
[function] fn to_leaf_bits(self, size: PageSize) -> u64 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 78)
[function] fn from_bits(bits: u64) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 99)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 110)
[function] fn new_leaf(paddr: PhysAddr, flags: Self::Flags, size: PageSize) -> Self
{
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 115)
[function] fn new_table(paddr: PhysAddr, level: u8) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 127)
[function] fn paddr(&self) -> PhysAddr {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 132)
[function] fn flags(&self) -> Self::Flags {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 137)
[function] fn is_present(&self) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 142)
[function] fn entry_kind(&self, level: u8) -> PageTableEntryKind {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 160)
[function] fn clear(&mut self) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 165)
[function] fn bits(&self) -> u64 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 170)
[function] fn from_bits(bits: u64) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 188)
[function] fn level_shift(level: u8) -> u32 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 193)
[function] fn level_supports_leaf(level: u8, size: PageSize) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 216)
[function] fn table_entry_encodes_child_level() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/amd/paging.rs (line 224)
[function] fn large_leaf_uses_large_level_marker() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/caps.rs (line 188)
[function] fn from(value: u64) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/caps.rs (line 195)
[function] fn from(value: VtdCapability) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/caps.rs (line 365)
[function] fn from(value: u64) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/caps.rs (line 372)
[function] fn from(value: VtdExtendedCapability) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/caps.rs (line 382)
[function] fn cap_decodes_address_widths_and_superpages() {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/caps.rs (line 402)
[function] fn ecap_lifts_common_flags() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 215)
[function] fn entry_vaddr(self, bus: u8) -> Result<VirtAddr> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 280)
[function] fn entry_vaddr(self, index: u8) -> Result<VirtAddr> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 285)
[function] fn client_entry_vaddr(self, client: PciDevice) -> Result<VirtAddr> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 518)
[function] fn irta_size(self) -> u64 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 523)
[function] fn entry_vaddr(self, entry: VtdInterruptEntry) -> Result<VirtAddr> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 565)
[function] fn from(value: VtdRemappedMsi) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 803)
[function] fn write64_shared(&self, offset: usize, value: u64) -> Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 876)
[function] fn poll_transition() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1399)
[function] fn validate_client(&self, client: PciDevice) -> Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1412)
[function] fn context_table_for_client(&self, client: PciDevice) ->
Result<VtdContextTableBacking> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1417)
[function] fn submit_queued_invalidation(&self, descriptor:
VtdQueuedInvalidationDescriptor) -> Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1429)
[function] fn invalidate_context_device(&self, client: PciDevice) -> Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1434)
[function] fn invalidate_iotlb_domain(&self, domain: VtdIoDomain) -> Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1442)
[function] fn invalidate_iotlb_global(&self) -> Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1448)
[function] fn invalidate_iotlb_page(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1467)
[function] fn invalidate_iotlb_range(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1525)
[function] fn bind_context(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1552)
[function] fn unbind_context(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1581)
[function] fn clear_fault_status(&mut self, status: u32) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1589)
[function] fn poll_primary_fault(&mut self, status: u32) -> Result<Option<VtdFault>>
{
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1660)
[function] fn unit(&self) -> &VtdUnit<Entry, QN> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1696)
[function] fn flush_tlb_local(&self, vaddr: IoviAddr<u64>) {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1701)
[function] fn flush_tlb_all_local(&self) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1706)
[function] fn flush_tlb_range_local(&self, start: IoviAddr<u64>, page_size:
PageSize, count_pages: usize) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1711)
[function] fn prefer_full_flush(&self, pending_count: usize) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1723)
[function] fn flush_iotlb(&self, iova: IoviAddr<u64>) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1728)
[function] fn flush_iotlb_all(&self) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1733)
[function] fn flush_iotlb_range(&self, start: IoviAddr<u64>, page_size: PageSize,
count_pages: usize) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1738)
[function] fn flush_device_tlb(&self, _client: PciDevice, _iova: IoviAddr<u64>) {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1741)
[function] fn flush_device_tlb_all(&self, _client: PciDevice) {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1744)
[function] fn prefer_full_iotlb_flush(&self, pending_count: usize) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1808)
[function] fn root(&self) -> PhysAddr {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1813)
[function] fn query(&self, vaddr: IoviAddr<u64>) ->
PagingResult<Mapping<Self::Entry, IoviAddr<u64>>> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1818)
[function] fn map<'a, B, F, Tlb>(<
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1834)
[function] fn remap<Tlb>(<
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1848)
[function] fn protect<Tlb>(<
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1861)
[function] fn unmap<Tlb>(<
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1873)
[function] fn split_at<Tlb>(<
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1885)
[function] fn merge_at<Tlb>(<
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1910)
[function] fn info(&self) -> &Self::Info {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1915)
[function] fn domain(&self) -> Self::Domain {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1920)
[function] fn stage(&self) -> crate::TranslationStage {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1925)
[function] fn enable(&mut self) -> Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1930)
[function] fn bind(&mut self, binding: Binding<Self::Client, Self::Domain>) ->
Result {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1935)
[function] fn unbind(&mut self, client: Self::Client, selector: BindingSelector) ->
Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1940)
[function] fn invalidator(&self) -> &Self::Invalidator {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1944)
[function] fn invalidate(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1969)
[function] fn configure_fault_event(&mut self, route: InterruptRoute) -> Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 1974)
[function] fn poll_fault(&mut self) -> Result<Option<Self::Fault>> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2139)
[function] fn queued_invalidation_table_address(backing: CommandQueueBacking) ->
Result<u64> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2174)
[function] fn decode_fault_status(status: u32) -> Option<VtdFault> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2209)
[function] fn decode_primary_fault(segment: u16, index: u16, low: u64, high: u64) ->
VtdFault {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2242)
[struct] struct VtdIotlbRangeBlock {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2248)
[struct] struct VtdIotlbRangePlan {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2257)
[function] fn new(start_page: usize, page_count: usize, min_mask: u8, max_mask: u8)
-> Result<Self> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2285)
[function] fn descriptor_count(self) -> usize {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2295)
[function] fn next_block(&mut self) -> Option<VtdIotlbRangeBlock> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2312)
[function] fn next_address_mask(self) -> u8 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2343)
[function] fn write_128(vaddr: VirtAddr, low: u64, high: u64) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2352)
[function] fn read_128(vaddr: VirtAddr) -> (u64, u64) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2363)
[function] fn write_root_entry(table: VtdRootTableBacking, bus: u8, entry:
VtdRootEntry) -> Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2370)
[function] fn read_root_entry(table: VtdRootTableBacking, bus: u8) ->
Result<VtdRootEntry> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2377)
[function] fn write_context_entry(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2388)
[function] fn read_context_entry(table: VtdContextTableBacking, client: PciDevice)
-> Result<VtdContextEntry> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2395)
[function] fn write_interrupt_remap_entry(

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2428)
[function] fn mmio_range(base: usize, size: usize) -> MmioAddrRange {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2433)
[function] fn table_range(buffer: &mut [u8], phys_base: usize) -> (PhysAddrRange,
VirtAddrRange) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2443)
[function] fn queue_backing(buffer: &mut [u8], phys_base: usize, entries: usize) ->
CommandQueueBacking {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2448)
[function] fn register_window(buffer: &mut [u8]) ->
VtdRegisterWindow<VtdSecondLevelPte> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2460)
[function] fn unit_info(segment: Option<u16>, cap: u64, ecap: u64) -> VtdInfo {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2472)
[function] fn root_table(buffer: &mut [u8]) -> VtdRootTableBacking {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2477)
[function] fn context_table(buffer: &mut [u8]) -> VtdContextTableBacking {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2483)
[function] fn root_entry_points_at_context_table() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2501)
[function] fn context_entry_encodes_domain_root_width_and_id() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2521)
[function] fn context_table_writes_device_function_slot() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2536)
[function] fn queued_invalidation_table_address_encodes_queue_size() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2549)
[function] fn queued_invalidation_table_address_rejects_invalid_backing() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2582)
[function] fn unit_installs_context_table_for_bus() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2601)
[function] fn bind_validation_rejects_unsupported_or_wrong_contexts() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2668)
[function] fn page_invalidation_falls_back_to_domain_without_psi() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2697)
[function] fn range_invalidation_coalesces_to_largest_supported_address_mask() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2734)
[function] fn range_invalidation_uses_domain_when_descriptor_count_is_too_high() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2765)
[function] fn range_plan_splits_by_alignment_and_capability() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2786)
[function] fn fault_decoders_preserve_primary_record_details() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2812)
[function] fn binding_context_rejects_non_default_selector_for_legacy_contexts() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2827)
[function] fn binding_context_checks_pass_through_capability() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2847)
[function] fn context_device_uses_pci_source_id() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2855)
[function] fn page_iotlb_descriptor_encodes_address_mask() {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2871)
[function] fn interrupt_remap_entry_encodes_x86_delivery_and_source() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2892)
[function] fn interrupt_remap_entry_keeps_delivery_mode_bits() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2910)
[function] fn interrupt_remap_target_preserves_extended_destination_id() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2926)
[function] fn remapped_msi_message_encodes_index_and_subhandle() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2934)
[function] fn interrupt_remap_table_writes_128_bit_entry() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/ctrl.rs (line 2951)
[function] fn queued_invalidation_descriptor_submits_to_command_queue() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 59)
[function] fn from(value: AcpiError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 66)
[function] fn from(value: BdfRangeSetError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 73)
[function] fn from(value: PagingError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 79)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 89)
[function] fn mmio_register_window(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 100)
[function] fn inclusive_phys_range(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 127)
[function] fn header(&self) -> &SdtHeader {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 132)
[function] fn table_bytes<'a, T: AcpiTable>(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 167)
[function] fn read_array<const N: usize>(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 184)
[function] fn read_u8(bytes: &[u8], offset: usize) -> Result<u8, DmarError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 192)
[function] fn read_u16(bytes: &[u8], offset: usize) -> Result<u16, DmarError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 201)
[function] fn read_u32(bytes: &[u8], offset: usize) -> Result<u32, DmarError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 210)
[function] fn read_u64(bytes: &[u8], offset: usize) -> Result<u64, DmarError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 224)
[function] fn parse(bytes: &'a [u8]) -> Result<Self, DmarError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 604)
[function] fn for_each_structure<F>(self, mut f: F) -> Result<(), DmarError>
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 614)
[function] fn parse_structure(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 636)
[function] fn parse_drhd(self, offset: usize, length: usize) -> Result<DmarDrhd,
DmarError> {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 659)
[function] fn parse_andd(self, offset: usize, length: usize) -> Result<DmarAndd<'a>,
DmarError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 671)
[function] fn parse_rmrr(self, offset: usize, length: usize) -> Result<DmarRmrr,
DmarError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 696)
[function] fn parse_atrs(self, offset: usize, length: usize) -> Result<DmarAtsr,
DmarError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 713)
[function] fn parse_rhsa(self, offset: usize, length: usize) -> Result<DmarRhsa,
DmarError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 730)
[function] fn parse_satc(self, offset: usize, length: usize) -> Result<DmarSatc,
DmarError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 747)
[function] fn parse_sidp(self, offset: usize, length: usize) -> Result<DmarSidp,
DmarError> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 761)
[function] fn walk_device_scopes<F>(<
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 830)
[function] fn next(&mut self) -> Option<Self::Item> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1052)
[struct] struct TestEntry;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1057)
[function] fn new_leaf(_paddr: PhysAddr, _flags: Self::Flags, _size: PageSize) ->
Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1061)
[function] fn new_table(_paddr: PhysAddr, _level: u8) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1065)
[function] fn paddr(&self) -> PhysAddr {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1069)
[function] fn flags(&self) -> Self::Flags {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1071)
[function] fn is_present(&self) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1075)
[function] fn entry_kind(&self, _level: u8) -> PageTableEntryKind {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1079)
[function] fn clear(&mut self) {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1081)
[function] fn bits(&self) -> u64 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1085)
[function] fn from_bits(_bits: u64) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1090)
[function] fn registers(base: usize) -> MmioAddrRange {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1098)
[function] fn write_sdt_header(bytes: &mut [u8], signature: Signature, length:
usize) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1104)
[function] fn finish_sdt_checksum(bytes: &mut [u8]) {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1113)
[function] fn table_mapping(bytes: &[u8]) -> Mapping<TestEntry, VirtAddr> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1123)
[function] fn parses_drhd_and_exact_bdf_ranges() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1174)
[function] fn parses_reserved_memory_affinity_and_satc() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1225)
[function] fn parses_andd_and_preserves_multi_hop_scope_path() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/dmar.rs (line 1284)
[function] fn parses_sidp_and_ignores_satc_policy_when_present() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/error.rs (line 19)
[function] fn from(value: VtdError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/info.rs (line 98)
[function] fn from(value: VtdDomainToken) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/info.rs (line 173)
[function] fn root(self) -> PhysAddr {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/info.rs (line 191)
[function] fn install(&self, root: PhysAddr, controls: Self::Controls) ->
PagingResult<Self::Token> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/info.rs (line 311)
[function] fn version_splits_major_and_minor() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/info.rs (line 318)
[function] fn vtd_domain_is_the_common_domain_value() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/info.rs (line 327)
[function] fn domain_activation_installs_second_level_root_token() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/info.rs (line 345)
[function] fn domain_activation_rejects_unaligned_roots() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/info.rs (line 357)
[function] fn stateless_domain_activation_does_not_publish_to_hardware() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 110)
[function] fn to_leaf_bits(self, size: PageSize) -> u64 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 125)
[function] fn from_bits(bits: u64) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 142)
[function] fn from(value: DmaAttrs) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 149)
[function] fn from(value: VtdSecondLevelFlags) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 160)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 171)
[function] fn new_leaf(paddr: PhysAddr, flags: Self::Flags, size: PageSize) -> Self
{
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 176)
[function] fn new_table(paddr: PhysAddr, _level: u8) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 181)
[function] fn paddr(&self) -> PhysAddr {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 186)
[function] fn flags(&self) -> Self::Flags {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 191)
[function] fn is_present(&self) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 196)
[function] fn entry_kind(&self, level: u8) -> PageTableEntryKind {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 207)
[function] fn clear(&mut self) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 212)
[function] fn bits(&self) -> u64 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 217)
[function] fn from_bits(bits: u64) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 235)
[function] fn level_shift(level: u8) -> u32 {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 240)
[function] fn level_supports_leaf(level: u8, size: PageSize) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 266)
[function] fn leaf_2m_sets_super_bit() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 279)
[function] fn table_entry_is_intermediate() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/intel/paging.rs (line 286)
[function] fn address_widths_match_vtd_agaw_shapes() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/interrupt.rs (line 200)
[function] fn from(value: X86MsiDelivery) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/interrupt.rs (line 210)
[function] fn rejects_exception_vectors_for_msi_delivery() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/interrupt.rs (line 216)
[function] fn fixed_physical_delivery_encodes_apic_msi_message() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/arch/x86_64/interrupt.rs (line 228)
[function] fn logical_lowest_priority_delivery_sets_route_bits() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/caps.rs (line 152)
[function] fn bitor(self, rhs: Self) -> Self::Output {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/caps.rs (line 159)
[function] fn bitor_assign(&mut self, rhs: Self) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/caps.rs (line 168)
[function] fn bitand(self, rhs: Self) -> Self::Output {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/caps.rs (line 175)
[function] fn bitand_assign(&mut self, rhs: Self) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 67)
[function] fn from(value: MsiMessage) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 148)
[function] fn entry_vaddr(self, slot: usize) -> Result<VirtAddr> {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 363)
[function] fn wait_for_capacity(&self, ticket: usize, entry_count: usize) -> Result
{
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 375)
[function] fn wait_for_empty(&self, slot: usize) -> Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 386)
[function] fn wait_to_publish(&self, ticket: usize) -> Result {

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 397)
[function] fn wait_for_consumed<RH>(&self, slot: usize, entry_bytes: usize, mut
read_head: RH) -> Result
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 412)
[function] fn advance_retired(&self, next: usize) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 428)
[function] fn write_slot<const W: usize>(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 448)
[function] fn default() -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 462)
[function] fn flush_iotlb(&self, iova: V);
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 463)
[function] fn flush_iotlb_all(&self);
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 465)
[function] fn flush_iotlb_range(&self, start: V, page_size: PageSize, count_pages:
usize) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 474)
[function] fn flush_device_tlb(&self, client: Self::Client, iova: V);
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 475)
[function] fn flush_device_tlb_all(&self, client: Self::Client);
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 477)
[function] fn flush_device_tlb_range(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 492)
[function] fn prefer_full_iotlb_flush(&self, pending_count: usize) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 518)
[function] fn flush_tlb_local(&self, _vaddr: V) {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 521)
[function] fn flush_tlb_all_local(&self) {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 524)
[function] fn flush_tlb_range_local(&self, _start: V, _page_size: PageSize,
_count_pages: usize) {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 527)
[function] fn prefer_full_flush(&self, _pending_count: usize) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 540)
[function] fn flush_iotlb(&self, _iova: V) {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 543)
[function] fn flush_iotlb_all(&self) {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 546)
[function] fn flush_iotlb_range(&self, _start: V, _page_size: PageSize,
_count_pages: usize) {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 549)
[function] fn flush_device_tlb(&self, _client: Client, _iova: V) {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 552)
[function] fn flush_device_tlb_all(&self, _client: Client) {}
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 555)
[function] fn flush_device_tlb_range(
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 565)
[function] fn prefer_full_iotlb_flush(&self, _pending_count: usize) -> bool {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 636)
[function] fn info(&self) -> &Self::Info;

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 637)
[function] fn domain(&self) -> Self::Domain;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 638)
[function] fn stage(&self) -> TranslationStage;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 639)
[function] fn enable(&mut self) -> Result;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 640)
[function] fn bind(&mut self, binding: Binding<Self::Client, Self::Domain>) ->
Result;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 641)
[function] fn unbind(&mut self, client: Self::Client, selector: BindingSelector) ->
Result;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 642)
[function] fn invalidator(&self) -> &Self::Invalidator;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 643)
[function] fn invalidate(&mut self, request: Invalidate<Self::Client, V>) ->
Result<InvalidateOutcome>;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 644)
[function] fn configure_fault_event(&mut self, route: InterruptRoute) -> Result;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 645)
[function] fn poll_fault(&mut self) -> Result<Option<Self::Fault>>;
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 660)
[function] fn test_queue() -> (CommandQueue<ENTRIES>, std::vec::Vec<u8>,
AtomicUsize) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 677)
[function] fn read_slot(buffer: &[u8], slot: usize) -> (u64, u64) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 685)
[function] fn interrupt_route_tracks_msi_delivery_state() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 695)
[function] fn command_queue_backing_rejects_non_power_of_two_entries() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 711)
[function] fn command_queue_submit_writes_entry_and_advances_tail() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/ctrl.rs (line 737)
[function] fn command_queue_sequential_submits_wrap_slots() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/error.rs (line 28)
[function] fn from(value: PagingError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/error.rs (line 36)
[function] fn from(value: crate::arch::x86_64::intel::dmar::DmarError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/error.rs (line 49)
[function] fn from(value: crate::arch::x86_64::amd::ivrs::IvrsError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/error.rs (line 62)
[function] fn from(value: crate::arch::aarch64::iort::IortError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/firm/pcie.rs (line 79)
[function] fn from(value: u16) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/firm/pcie.rs (line 86)
[function] fn from(value: Bdf) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/firm/pcie.rs (line 317)
[function] fn insert_at<E>(&mut self, index: usize, range: BdfRange) -> Result<(),
E>

```

```

driverspace_workspace/drivers/iommu-TrangorgeOS/src/firm/pcie.rs (line 335)
[function] fn merge_around<E>(&mut self, mut index: usize) -> Result<(), E>
driverspace_workspace/drivers/iommu-TrangorgeOS/src/firm/pcie.rs (line 355)
[function] fn merge_pair<E>(&mut self, left: usize, right: usize) -> Result<bool, E>
driverspace_workspace/drivers/iommu-TrangorgeOS/src/firm/pcie.rs (line 375)
[function] fn remove(&mut self, index: usize) {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/firm/pcie.rs (line 388)
[function] fn default() -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/firm/pcie.rs (line 402)
[function] fn from(value: BdfRangeError) -> Self {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/firm/pcie.rs (line 414)
[function] fn fmt(&self, f: &mut fmt::Formatter<'>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/firm/pcie.rs (line 424)
[function] fn fmt(&self, f: &mut fmt::Formatter<'>) -> fmt::Result {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/firm/pcie.rs (line 437)
[function] fn bdf_encodes_requester_id() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/firm/pcie.rs (line 446)
[function] fn bdf_range_set_sorts_and_merges_adjacent_ranges() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/info.rs (line 174)
[function] fn io_domain_keeps_asid_and_generation_separate() {
driverspace_workspace/drivers/iommu-TrangorgeOS/src/info.rs (line 184)
[function] fn io_domain_rejects_ids_outside_mask() {
driverspace_workspace/drivers/netcam_driver/src/main.rs (line 1)
[function] fn main() {
driverspace_workspace/drivers/vgpu/src/main.rs (line 42)
[struct] struct VgpuInfo {
driverspace_workspace/drivers/vgpu/src/main.rs (line 67)
[function] fn vgpu_init(w: u32, h: u32) -> bool {
driverspace_workspace/drivers/vgpu/src/main.rs (line 138)
[function] fn find_vga_device() -> Option<u64> {
driverspace_workspace/drivers/vgpu/src/main.rs (line 151)
[function] fn read_pci_config(bdf: u64, offset: u32) -> u32 {
driverspace_workspace/drivers/vgpu/src/main.rs (line 161)
[function] fn read_pci_bar(bdf: u64, bar: u32) -> u64 {
driverspace_workspace/drivers/vgpu/src/main.rs (line 172)
[function] fn enable_pci_device(bdf: u64) {
driverspace_workspace/drivers/vgpu/src/main.rs (line 185)
[function] fn vbe_write(idx: u16, val: u16) {
driverspace_workspace/drivers/vgpu/src/main.rs (line 192)
[function] fn vgpu_clear(color: u32) {
driverspace_workspace/drivers/vgpu/src/main.rs (line 207)
[function] fn vgpu_pixel(x: u32, y: u32, color: u32) {
driverspace_workspace/drivers/vgpu/src/main.rs (line 219)
[function] fn panic(_info: &core::panic::PanicInfo) -> ! {
driverspace_workspace/drivers/wacomgraphic_driver/src/main.rs (line 1)
[function] fn main() {
driverspace_workspace/lib/ds-formal-ffi/build.rs (line 10)
[function] fn main() {

```

```

driverspace_workspace/lib/ds-fw-audio/src/lib.rs (line 10)
[function] fn it_works() {
driverspace_workspace/lib/ds-fw-block/src/traits.rs (line 18)
[function] fn read_blocks(&mut self, lba: u64, block_count: u32, buffer: &mut [u8])
-> Result<(), DsError>;
driverspace_workspace/lib/ds-fw-block/src/traits.rs (line 21)
[function] fn write_blocks(&mut self, lba: u64, block_count: u32, buffer: &[u8]) ->
Result<(), DsError>;
driverspace_workspace/lib/ds-fw-block/src/traits.rs (line 24)
[function] fn flush(&mut self) -> Result<(), DsError>;
driverspace_workspace/lib/ds-fw-block/src/traits.rs (line 27)
[function] fn geometry(&self) -> BlockGeometry;
driverspace_workspace/lib/ds-fw-block/src/traits.rs (line 30)
[function] fn supports_trim(&self) -> bool { false }
driverspace_workspace/lib/ds-fw-block/src/traits.rs (line 33)
[function] fn submit_request(&mut self, _req: BlockRequest) -> Result<(), DsError> {
driverspace_workspace/lib/ds-fw-gpu/src/lib.rs (line 10)
[function] fn it_works() {
driverspace_workspace/lib/ds-fw-input/src/lib.rs (line 10)
[function] fn it_works() {
driverspace_workspace/lib/ds-ipc/src/channel.rs (line 33)
[function] fn next_id(&self) -> u64 {
driverspace_workspace/lib/ds-log/src/formatter.rs (line 30)
[function] fn write_str(&mut self, s: &str) -> fmt::Result {
driverspace_workspace/lib/ds-log/src/transport.rs (line 8)
[function] fn uart_putchar(c: u8) {
driverspace_workspace/lib/ds-mem/src/dma/buffer.rs (line 34)
[function] fn drop(&mut self) {
driverspace_workspace/lib/ds-mem/src/dma/mapping.rs (line 25)
[function] fn drop(&mut self) {
driverspace_workspace/lib/kapi-abi/build.rs (line 9)
[function] fn main() {
driverspace_workspace/lib/kapi-abi/src/wire/mod.rs (line 28)
[function] fn default() -> Self {
driverspace_workspace/lib/kapi-syscall/src/channel.rs (line 17)
[function] fn slot_ptr(&self, index: u64) -> *mut DsMsg {
driverspace_workspace/src/self_test.rs (line 21)
[function] fn test_ipc_ring() -> Result<(), Status> {
driverspace_workspace/src/self_test.rs (line 39)
[function] fn test_memory_alloc() -> Result<(), Status> {
driverspace_workspace/src/self_test.rs (line 62)
[function] fn test_capability_check() -> Result<(), Status> {
driverspacelib/src/abi.rs (line 133)
[function] fn from(v: i32) -> Self {
driverspacelib/src/driver.rs (line 15)
[function] fn init(&mut self, info: &DeviceInfo) -> Result<(), DsError>;
gfx_protocol_workspace/crates/gfx-api/src/lib.rs (line 42)
[function] fn send_ipc(&self, msg: GfxIpcMsg) -> GfxIpcMsg {

```

gfx_protocol_workspace/crates/gfx-server/src/compositor.rs (line 4)

```
[struct] struct Surface {
```

gfx_protocol_workspace/crates/gfx-server/src/main.rs (line 49)

```
[function] fn wait_for_ipc() -> GfxIpcMsg {
```

gfx_protocol_workspace/crates/gfx-server/src/main.rs (line 54)

```
[function] fn reply(cmd: u32, status: i32, data: u64) {
```

kernel-drivers/audio/src/lib.rs (line 9)

```
[function] fn ad_init(base: u32) -> bool;
```

kernel-drivers/audio/src/lib.rs (line 10)

```
[function] fn ad_jack_present() -> bool;
```

kernel-drivers/audio/src/lib.rs (line 11)

```
[function] fn ad_set_amp(on: bool);
```

kernel-drivers/audio/src/lib.rs (line 12)

```
[function] fn ad_play_phys(phys: u64, len: u32) -> bool;
```

kernel-drivers/audio/src/lib.rs (line 13)

```
[function] fn ad_stop();
```

kernel-drivers/battery/src/lib.rs (line 6)

```
[function] fn battery_init() -> bool;
```

kernel-drivers/bluetooth/src/lib.rs (line 7)

```
[function] fn bt_init() -> bool;
```

kernel-drivers/bluetooth/src/lib.rs (line 8)

```
[function] fn bt_ready() -> bool;
```

kernel-drivers/camera/src/lib.rs (line 6)

```
[function] fn camera_init() -> bool;
```

kernel-drivers/displayport/src/lib.rs (line 6)

```
[function] fn dp_init() -> bool;
```

kernel-drivers/displayport/src/lib.rs (line 7)

```
[function] fn dp_ready() -> bool;
```

kernel-drivers/hdmi/src/lib.rs (line 6)

```
[function] fn hdmi_init_with(fb_phys: u64, w: u32, h: u32, stride: u32) -> bool;
```

kernel-drivers/hdmi/src/lib.rs (line 7)

```
[function] fn hdmi_ready() -> bool;
```

kernel-drivers/pcie/src/lib.rs (line 54)

```
[function] fn cfg_addr(bus: u32, dev: u32, func: u32, off: u32) -> u32 {
```

kernel-drivers/pcie/src/lib.rs (line 152)

```
[function] fn probe(bus: u8, dev: u8, func: u8) -> Option<PciDevice> {
```

kernel-drivers/usb/src/class/hid/mod.rs (line 26)

```
[function] fn submit(x: &mut Xhci, kb: &mut HidKeyboard) {
```

kernel-drivers/usb/src/class/mass/blockdev.rs (line 11)

```
[function] fn name(&self) -> &'static str;
```

kernel-drivers/usb/src/class/mass/blockdev.rs (line 12)

```
[function] fn block_size(&self) -> usize;
```

kernel-drivers/usb/src/class/mass/blockdev.rs (line 13)

```
[function] fn block_count(&self) -> u64;
```

kernel-drivers/usb/src/class/mass/blockdev.rs (line 14)

```
[function] fn read_block(&self, block: u64, buf: &mut [u8]) -> Result<(),  
DriverError>;
```

kernel-drivers/usb/src/class/mass/blockdev.rs (line 15)

```
[function] fn write_block(&self, block: u64, buf: &[u8]) -> Result<(), DriverError>;
```

```

kernel-drivers/usb/src/class/mass/blockdev.rs (line 19)
[function] fn name(&self) -> &'static str {
kernel-drivers/usb/src/class/mass/blockdev.rs (line 23)
[function] fn block_size(&self) -> usize {
kernel-drivers/usb/src/class/mass/blockdev.rs (line 27)
[function] fn block_count(&self) -> u64 {
kernel-drivers/usb/src/class/mass/blockdev.rs (line 31)
[function] fn read_block(&self, block: u64, buf: &mut [u8]) -> Result<(),
DriverError> {
kernel-drivers/usb/src/class/mass/blockdev.rs (line 46)
[function] fn write_block(&self, block: u64, buf: &[u8]) -> Result<(), DriverError>
{
kernel-drivers/usb/src/class/mod.rs (line 7)
[function] fn probe(&self, dev: &UsbDevice) -> bool;
kernel-drivers/usb/src/dma.rs (line 30)
[function] fn drop(&mut self) {
kernel-drivers/usb/src/host/xhci/context.rs (line 80)
[function] fn in_add_drop(&mut self, add: u32, drop: u32) {
kernel-drivers/usb/src/host/xhci/context.rs (line 89)
[function] fn slot_ptr(&mut self) -> *mut u32 {
kernel-drivers/usb/src/host/xhci/context.rs (line 93)
[function] fn ep0_ptr(&mut self) -> *mut u32 {
kernel-drivers/usb/src/host/xhci/init.rs (line 24)
[function] fn spin_wait<F: Fn() -> bool>(f: F) -> Result<(), UsbError> {
kernel-drivers/usb/src/host/xhci/init.rs (line 36)
[function] fn op_write64(regs: &XhciRegs, off: usize, v: u64) {
kernel-drivers/usb/src/host/xhci/init.rs (line 170)
[function] fn attach_port(&mut self, p: u32) {
kernel-drivers/usb/src/host/xhci/regs.rs (line 90)
[function] fn op(&self) -> *mut u8 {
kernel-drivers/usb/src/host/xhci/regs.rs (line 94)
[function] fn rt(&self) -> *mut u8 {
kernel-drivers/usb/src/host/xhci/regs.rs (line 98)
[function] fn db(&self) -> *mut u8 {
kernel_Workspace/C_base/kc-abi-menager/src/main.rs (line 2)
[function] fn main() {
kernel_Workspace/C_base/kc-abi/src/lib.rs (line 11)
[function] fn it_works() {
kernel_Workspace/Odin_base/odin-abi-bridge/src/lib.rs (line 11)
[function] fn it_works() {
kernel_Workspace/Odin_base/odin-abi/src/lib.rs (line 11)
[function] fn it_works() {
kernel_Workspace/Odin_base/odin-bin-loader/src/main.rs (line 2)
[function] fn main() {
kernel_Workspace/base/kw-C-abi/src/lib.rs (line 11)
[function] fn it_works() {
kernel_Workspace/base/kw-base/src/api/net_ops.rs (line 4)
[function] fn k_net_socket(domain: u32, sock_type: u32, proto: u32) -> i32;

```

```

kernel_Workspace/base/kw-base/src/api/net_ops.rs (line 5)
[function] fn k_net_bind(fd: i32, addr: *const u8, len: u32) -> i32;
kernel_Workspace/base/kw-base/src/api/net_ops.rs (line 6)
[function] fn k_net_send(fd: i32, buf: *const u8, len: u32, flags: u32) -> i32;
kernel_Workspace/base/kw-base/src/api/net_ops.rs (line 7)
[function] fn k_net_recv(fd: i32, buf: *mut u8, len: u32, flags: u32) -> i32;
kernel_Workspace/base/kw-base/src/api/process.rs (line 4)
[function] fn k_proc_spawn(world_id: u32, entry: u64, stack: u64) -> i64;
kernel_Workspace/base/kw-base/src/api/process.rs (line 5)
[function] fn k_proc_exit(code: i32);
kernel_Workspace/base/kw-base/src/api/process.rs (line 6)
[function] fn k_proc_yield();
kernel_Workspace/base/kw-base/src/api/process.rs (line 7)
[function] fn k_proc_get_pid() -> u32;
kernel_Workspace/base/kw-base/src/arch/interrupts.rs (line 45)
[function] fn drop(&mut self) {
kernel_Workspace/base/kw-base/src/boot/early_print.rs (line 17)
[function] fn is_transmitter_empty() -> bool {
kernel_Workspace/base/kw-base/src/core/error.rs (line 65)
[function] fn from(s: kstd_base::Status) -> Self {
kernel_Workspace/base/kw-base/src/core/error.rs (line 84)
[function] fn fmt(&self, f: &mut fmt::Formatter<'>) -> fmt::Result {
kernel_Workspace/base/kw-base/src/core/result.rs (line 6)
[function] fn into_kresult(self) -> KResult<T>;
kernel_Workspace/base/kw-base/src/core/result.rs (line 10)
[function] fn into_kresult(self) -> KResult<T> {
kernel_Workspace/base/kw-base/src/core/result.rs (line 16)
[function] fn into_kresult(self) -> KResult<T> {
kernel_Workspace/base/kw-base/src/core/traits.rs (line 5)
[function] fn read_block(&self, block: u64, buf: &mut [u8]) -> Result<(),
KernelError>;
kernel_Workspace/base/kw-base/src/core/traits.rs (line 6)
[function] fn write_block(&self, block: u64, buf: &[u8]) -> Result<(), KernelError>;
kernel_Workspace/base/kw-base/src/core/traits.rs (line 7)
[function] fn block_size(&self) -> usize;
kernel_Workspace/base/kw-base/src/core/traits.rs (line 8)
[function] fn block_count(&self) -> u64;
kernel_Workspace/base/kw-base/src/core/traits.rs (line 12)
[function] fn read(&self, buf: &mut [u8]) -> Result<usize, KernelError>;
kernel_Workspace/base/kw-base/src/core/traits.rs (line 13)
[function] fn write(&self, buf: &[u8]) -> Result<usize, KernelError>;
kernel_Workspace/base/kw-base/src/core/traits.rs (line 17)
[function] fn send(&self, frame: &[u8]) -> Result<(), KernelError>;
kernel_Workspace/base/kw-base/src/core/traits.rs (line 18)
[function] fn recv(&self, buf: &mut [u8]) -> Result<usize, KernelError>;
kernel_Workspace/base/kw-base/src/core/traits.rs (line 19)
[function] fn mac_address(&self) -> [u8; 6];
kernel_Workspace/base/kw-base/src/core/traits.rs (line 23)
[function] fn open(&self, path: &str, flags: u32) -> Result<Handle, KernelError>;

```

```

kernel_Workspace/base/kw-base/src/core/traits.rs (line 24)
[function] fn close(&self, handle: Handle) -> Result<(), KernelError>;
kernel_Workspace/base/kw-base/src/core/traits.rs (line 25)
[function] fn read(&self, handle: Handle, buf: &mut [u8], offset: u64) ->
Result<usize, KernelError>;
kernel_Workspace/base/kw-base/src/core/traits.rs (line 26)
[function] fn write(&self, handle: Handle, buf: &[u8], offset: u64) -> Result<usize,
KernelError>;
kernel_Workspace/base/kw-base/src/core/traits.rs (line 27)
[function] fn stat(&self, path: &str) -> Result<FileStat, KernelError>;
kernel_Workspace/base/kw-base/src/core/traits.rs (line 43)
[function] fn schedule(&mut self) -> Option<TaskId>;
kernel_Workspace/base/kw-base/src/core/traits.rs (line 44)
[function] fn enqueue(&mut self, task: TaskId);
kernel_Workspace/base/kw-base/src/core/traits.rs (line 45)
[function] fn dequeue(&mut self, task: TaskId);
kernel_Workspace/base/kw-base/src/core/traits.rs (line 46)
[function] fn yield_current(&mut self);
kernel_Workspace/base/kw-base/src/core/traits.rs (line 50)
[function] fn enable_irq(&self, irq: u32);
kernel_Workspace/base/kw-base/src/core/traits.rs (line 51)
[function] fn disable_irq(&self, irq: u32);
kernel_Workspace/base/kw-base/src/core/traits.rs (line 52)
[function] fn ack_irq(&self, irq: u32);
kernel_Workspace/base/kw-base/src/core/traits.rs (line 53)
[function] fn end_of_interrupt(&self);
kernel_Workspace/base/kw-base/src/crypto/ciphers.rs (line 4)
[function] fn k_aes256_enc(key: *const u8, iv: *const u8, data: *mut u8, len: usize)
-> bool;
kernel_Workspace/base/kw-base/src/crypto/ciphers.rs (line 5)
[function] fn k_aes256_dec(key: *const u8, iv: *const u8, data: *mut u8, len: usize)
-> bool;
kernel_Workspace/base/kw-base/src/crypto/ciphers.rs (line 13)
[function] fn encrypt(key: &[u8], iv: &[u8], data: &mut [u8]) -> KResult<()>;
kernel_Workspace/base/kw-base/src/crypto/ciphers.rs (line 14)
[function] fn decrypt(key: &[u8], iv: &[u8], data: &mut [u8]) -> KResult<()>;
kernel_Workspace/base/kw-base/src/crypto/ciphers.rs (line 23)
[function] fn encrypt(key: &[u8], iv: &[u8], data: &mut [u8]) -> KResult<()> {
kernel_Workspace/base/kw-base/src/crypto/ciphers.rs (line 37)
[function] fn decrypt(key: &[u8], iv: &[u8], data: &mut [u8]) -> KResult<()> {
kernel_Workspace/base/kw-base/src/crypto/ hashes.rs (line 4)
[function] fn k_sha256(data: *const u8, len: usize, out: *mut u8) -> bool;
kernel_Workspace/base/kw-base/src/crypto/ hashes.rs (line 5)
[function] fn k_sha512(data: *const u8, len: usize, out: *mut u8) -> bool;
kernel_Workspace/base/kw-base/src/crypto/ hashes.rs (line 10)
[function] fn hash(data: &[u8], out: &mut [u8]) -> KResult<()>;
kernel_Workspace/base/kw-base/src/crypto/ hashes.rs (line 16)
[function] fn hash(data: &[u8], out: &mut [u8]) -> KResult<()> {
kernel_Workspace/base/kw-base/src/crypto/ hashes.rs (line 29)
[function] fn hash(data: &[u8], out: &mut [u8]) -> KResult<()> {

```

```

kernel_Workspace/base/kw-base/src/crypto/random.rs (line 4)
[function] fn k_get_random(buf: *mut u8, len: usize) -> bool;
kernel_Workspace/base/kw-base/src/crypto/random.rs (line 5)
[function] fn k_get_hw_random(buf: *mut u8, len: usize) -> bool;
kernel_Workspace/base/kw-base/src/crypto/secure_mem.rs (line 37)
[function] fn drop(&mut self) {
kernel_Workspace/base/kw-base/src/drivers/uart.rs (line 17)
[function] fn init(&mut self) {
kernel_Workspace/base/kw-base/src/drivers/uart.rs (line 29)
[function] fn is_transmitter_empty(&self) -> bool {
kernel_Workspace/base/kw-base/src/drivers/uart.rs (line 40)
[function] fn write_str(&mut self, s: &str) -> Result<(), ()> {
kernel_Workspace/base/kw-base/src/fs/vfs.rs (line 8)
[function] fn stat(&self) -> KResult<FileStat>;
kernel_Workspace/base/kw-base/src/fs/vfs.rs (line 9)
[function] fn read(&self, offset: u64, buf: &mut [u8]) -> KResult<usize>;
kernel_Workspace/base/kw-base/src/fs/vfs.rs (line 10)
[function] fn write(&self, offset: u64, buf: &[u8]) -> KResult<usize>;
kernel_Workspace/base/kw-base/src/fs/vfs.rs (line 11)
[function] fn lookup(&self, name: &str) -> KResult<Handle>;
kernel_Workspace/base/kw-base/src/fs/vfs.rs (line 15)
[function] fn inode(&self) -> &dyn Inode;
kernel_Workspace/base/kw-base/src/fs/vfs.rs (line 16)
[function] fn flags(&self) -> u32;
kernel_Workspace/base/kw-base/src/fs/vfs.rs (line 20)
[function] fn name(&self) -> &str;
kernel_Workspace/base/kw-base/src/fs/vfs.rs (line 21)
[function] fn root_inode(&self) -> Handle;
kernel_Workspace/base/kw-base/src/fs/vfs.rs (line 22)
[function] fn sync(&self) -> KResult<()>;
kernel_Workspace/base/kw-base/src/hal/acpi.rs (line 4)
[function] fn k_acpi_get_rsdp() -> *const u8;
kernel_Workspace/base/kw-base/src/hal/acpi.rs (line 5)
[function] fn k_acpi_find_table(sig: *const u8, idx: u32) -> *const u8;
kernel_Workspace/base/kw-base/src/hal/pci.rs (line 18)
[function] fn config_addr(self, offset: u8) -> u32 {
kernel_Workspace/base/kw-base/src/hal/timers.rs (line 4)
[function] fn k_timer_get_ticks() -> u64;
kernel_Workspace/base/kw-base/src/hal/timers.rs (line 5)
[function] fn k_timer_get_frequency() -> u64;
kernel_Workspace/base/kw-base/src/hal/timers.rs (line 6)
[function] fn k_timer_sleep_ms(ms: u32);
kernel_Workspace/base/kw-base/src/hal/timers.rs (line 7)
[function] fn k_timer_set_oneshot(ns: u64) -> bool;
kernel_Workspace/base/kw-base/src/hal/usb.rs (line 4)
[function] fn k_usb_init() -> bool;
kernel_Workspace/base/kw-base/src/hal/usb.rs (line 5)
[function] fn k_usb_enum_devices() -> u32;

```

```

kernel_Workspace/base/kw-base/src/hal/usb.rs (line 6)
[function] fn k_usb_get_device_count() -> u32;
kernel_Workspace/base/kw-base/src/ipc/message_queue.rs (line 4)
[function] fn k_ipc_send(dst: u32, a0: u64, a1: u64) -> i32;
kernel_Workspace/base/kw-base/src/ipc/message_queue.rs (line 5)
[function] fn k_ipc_recv(a0: *mut u64, a1: *mut u64) -> i32;
kernel_Workspace/base/kw-base/src/ipc/shared_mem.rs (line 32)
[function] fn drop(&mut self) {
kernel_Workspace/base/kw-base/src/mem/buddy.rs (line 37)
[function] fn drop(&mut self) {
kernel_Workspace/base/kw-base/src/mem/frame.rs (line 35)
[function] fn drop(&mut self) {
kernel_Workspace/base/kw-base/src/mem/paging.rs (line 14)
[function] fn paging_map_page(virt: u64, phys: u64, flags: u64) -> bool;
kernel_Workspace/base/kw-base/src/mem/paging.rs (line 15)
[function] fn paging_unmap_page(virt: u64) -> bool;
kernel_Workspace/base/kw-base/src/mem/slab.rs (line 4)
[function] fn slab_cache_create(name: *const u8, obj_size: usize, align: usize) ->
*mut u8;
kernel_Workspace/base/kw-base/src/mem/slab.rs (line 5)
[function] fn slab_cache_destroy(cache: *mut u8);
kernel_Workspace/base/kw-base/src/mem/slab.rs (line 6)
[function] fn slab_alloc(cache: *mut u8) -> *mut u8;
kernel_Workspace/base/kw-base/src/mem/slab.rs (line 7)
[function] fn slab_free(cache: *mut u8, ptr: *mut u8);
kernel_Workspace/base/kw-base/src/mem/slab.rs (line 45)
[function] fn drop(&mut self) {
kernel_Workspace/base/kw-base/src/sync/futex.rs (line 4)
[function] fn k_futex_wait(uaddr: *const u32, expected_val: u32, timeout_ns: u64) ->
i32;
kernel_Workspace/base/kw-base/src/sync/futex.rs (line 5)
[function] fn k_futex_wake(uaddr: *const u32, wake_count: u32) -> i32;
kernel_Workspace/base/kw-base/src/sync/mutex.rs (line 49)
[function] fn unlock(&self) {
kernel_Workspace/base/kw-base/src/sync/mutex.rs (line 61)
[function] fn deref(&self) -> &T { unsafe { &*self.lock.data.get() } }
kernel_Workspace/base/kw-base/src/sync/mutex.rs (line 65)
[function] fn deref_mut(&mut self) -> &mut T { unsafe { &mut *self.lock.data.get() }
}
kernel_Workspace/base/kw-base/src/sync/mutex.rs (line 69)
[function] fn drop(&mut self) { self.lock.unlock(); }
kernel_Workspace/base/kw-base/src/sync/rwlock.rs (line 48)
[function] fn deref(&self) -> &T { unsafe { &*self.lock.data.get() } }
kernel_Workspace/base/kw-base/src/sync/rwlock.rs (line 51)
[function] fn drop(&mut self) { self.lock.state.fetch_sub(1, Ordering::Release); }
kernel_Workspace/base/kw-base/src/sync/rwlock.rs (line 57)
[function] fn deref(&self) -> &T { unsafe { &*self.lock.data.get() } }
kernel_Workspace/base/kw-base/src/sync/rwlock.rs (line 60)
[function] fn deref_mut(&mut self) -> &mut T { unsafe { &mut *self.lock.data.get() }
}

```

```

kernel_Workspace/base/kw-base/src/sync/rwlock.rs (line 63)
[function] fn drop(&mut self) { self.lock.state.store(0, Ordering::Release); }
kernel_Workspace/base/kw-base/src/task/process.rs (line 48)
[function] fn drop(&mut self) {
kernel_Workspace/base/kw-base/src/utils/bitmap.rs (line 19)
[function] fn word_idx(&self, bit: usize) -> usize {
kernel_Workspace/base/kw-base/src/utils/bitmap.rs (line 24)
[function] fn bit_mask(&self, bit: usize) -> u64 {
kernel_Workspace/base/kw-base/src/utils/btree.rs (line 9)
[struct] struct Node<K, V> {
kernel_Workspace/base/kw-base/src/utils/btree.rs (line 18)
[function] fn new_leaf() -> *mut Self {
kernel_Workspace/base/kw-base/src/utils/btree.rs (line 29)
[function] fn new_internal() -> *mut Self {
kernel_Workspace/base/kw-base/src/utils/btree.rs (line 69)
[function] fn split_child(&mut self, parent: *mut Node<K, V>, i: usize) {
kernel_Workspace/base/kw-base/src/utils/btree.rs (line 102)
[function] fn insert_non_full(&mut self, node: *mut Node<K, V>, key: K, val: V) {
kernel_Workspace/base/kw-base/src/utils/hashmap.rs (line 6)
[struct] struct FnvHasher(u64);
kernel_Workspace/base/kw-base/src/utils/hashmap.rs (line 8)
[function] fn finish(&self) -> u64 { self.0 }
kernel_Workspace/base/kw-base/src/utils/hashmap.rs (line 9)
[function] fn write(&mut self, bytes: &[u8]) {
kernel_Workspace/base/kw-base/src/utils/hashmap.rs (line 17)
[function] fn hash_key<K: Hash>(key: &K) -> usize {
kernel_Workspace/base/kw-base/src/utils/hashmap.rs (line 39)
[function] fn grow(&mut self, new_cap: usize) {
kernel_Workspace/base/kw-base/src/utils/hashmap.rs (line 138)
[function] fn drop(&mut self) {
kernel_Workspace/base/kw-base/src/utils/ring_buffer.rs (line 46)
[function] fn drop(&mut self) {
kernel_Workspace/base/kw-lib/src/mem/allocators/slab.rs (line 8)
[struct] struct SlabPage {
kernel_Workspace/base/kw-lib/src/mem/allocators/slab.rs (line 45)
[function] fn alloc_page(&self) -> KResult<*mut SlabPage> {
kernel_Workspace/base/kw-lib/src/mem/physical/buddy.rs (line 9)
[struct] struct FreeList {
kernel_Workspace/base/kw-lib/src/mem/physical/buddy.rs (line 78)
[function] fn frame_to_phys(&self, frame: usize) -> PhysAddr {
kernel_Workspace/base/kw-lib/src/mem/physical/buddy.rs (line 82)
[function] fn phys_to_frame(&self, phys: PhysAddr) -> usize {
kernel_Workspace/base/kw-lib/src/mem/physical/buddy.rs (line 86)
[function] fn free_block(&mut self, frame: usize, order: usize) {
kernel_Workspace/base/kw-lib/src/mem/virtual/aspace.rs (line 67)
[function] fn drop(&mut self) {
kernel_Workspace/base/kw-odin-abi/src/lib.rs (line 11)
[function] fn it_works() {

```

```

kernel_Workspace/core/gluecore/build.rs (line 1)
[function] fn main() {}
kernel_Workspace/core/gluecore/src/bindings.rs (line 12)
[function] fn from(val: CPhysRange) -> Self {
kernel_Workspace/core/gluecore/src/boot.rs (line 4)
[function] fn boot_get_memory_map(out_ptr: *mut u64, out_size: *mut usize) -> bool;
kernel_Workspace/core/gluecore/src/boot.rs (line 5)
[function] fn boot_get_cmdline(out_ptr: *mut u64, out_len: *mut usize) -> bool;
kernel_Workspace/core/gluecore/src/boot.rs (line 6)
[function] fn boot_get_framebuffer(out_phys: *mut u64, out_w: *mut u32, out_h: *mut
u32, out_pitch: *mut u32) -> bool;
kernel_Workspace/core/gluecore/src/context.rs (line 4)
[function] fn paging_read_cr3() -> u64;
kernel_Workspace/core/gluecore/src/context.rs (line 5)
[function] fn paging_write_cr3(pml4_phys: u64);
kernel_Workspace/core/gluecore/src/context.rs (line 6)
[function] fn paging_flush_tlb_all();
kernel_Workspace/core/gluecore/src/context.rs (line 7)
[function] fn paging_flush_page(addr: u64);
kernel_Workspace/core/gluecore/src/context.rs (line 8)
[function] fn context_switch_save_restore(old_ctx: *mut u8, new_ctx: *mut u8);
kernel_Workspace/core/gluecore/src/interrupts.rs (line 38)
[function] fn drop(&mut self) {
kernel_Workspace/core/gluecore/src/syscalls.rs (line 4)
[function] fn syscall_dispatch(num: u64, arg1: u64, arg2: u64, arg3: u64, arg4: u64)
-> i64;
kernel_Workspace/core/kstd_alloc/src/heap.rs (line 5)
[function] fn kmalloc(size: usize) -> *mut u8;
kernel_Workspace/core/kstd_alloc/src/heap.rs (line 6)
[function] fn kcalloc(size: usize) -> *mut u8;
kernel_Workspace/core/kstd_alloc/src/heap.rs (line 7)
[function] fn kcalloc(n: usize, size: usize) -> *mut u8;
kernel_Workspace/core/kstd_alloc/src/heap.rs (line 8)
[function] fn krealloc(ptr: *mut u8, size: usize) -> *mut u8;
kernel_Workspace/core/kstd_alloc/src/heap.rs (line 9)
[function] fn kfree(ptr: *mut u8);
kernel_Workspace/core/kstd_alloc/src/heap.rs (line 10)
[function] fn kmalloc_aligned(size: usize, align: usize) -> *mut u8;
kernel_Workspace/core/kstd_alloc/src/heap.rs (line 16)
[function] fn alloc(&self, layout: Layout) -> Result<*mut u8, Status> {
kernel_Workspace/core/kstd_alloc/src/heap.rs (line 29)
[function] fn dealloc(&self, ptr: *mut u8, _layout: Layout) {
kernel_Workspace/core/kstd_alloc/src/heap.rs (line 35)
[function] fn realloc(&self, ptr: *mut u8, _old: Layout, new_size: usize) ->
Result<*mut u8, Status> {
kernel_Workspace/core/kstd_alloc/src/lib.rs (line 15)
[function] fn oom() -> ! {
kernel_Workspace/core/kstd_alloc/src/page.rs (line 5)
[function] fn kalloc_pages(order: usize) -> *mut u8;

```

```

kernel_Workspace/core/kstd_alloc/src/page.rs (line 6)
[function] fn kfree_pages(ptr: *mut u8, pages: usize);
kernel_Workspace/core/kstd_alloc/src/slab.rs (line 5)
[function] fn slab_alloc(cache: *mut u8) -> *mut u8;
kernel_Workspace/core/kstd_alloc/src/slab.rs (line 6)
[function] fn slab_free(cache: *mut u8, ptr: *mut u8);
kernel_Workspace/core/kstd_alloc/src/slab.rs (line 7)
[function] fn slab_cache_create(name: *const u8, obj_size: usize, align: usize) ->
*mut u8;
kernel_Workspace/core/kstd_alloc/src/slab.rs (line 8)
[function] fn slab_cache_destroy(cache: *mut u8);
kernel_Workspace/core/kstd_alloc/src/slab.rs (line 31)
[function] fn alloc(&self, _layout: Layout) -> Result<*mut u8, Status> {
kernel_Workspace/core/kstd_alloc/src/slab.rs (line 36)
[function] fn dealloc(&self, ptr: *mut u8, _layout: Layout) {
kernel_Workspace/core/kstd_alloc/src/slab.rs (line 44)
[function] fn drop(&mut self) {
kernel_Workspace/core/kstd_alloc/src/traits.rs (line 4)
[function] fn alloc(&self, layout: Layout) -> Result<*mut u8, Status>;
kernel_Workspace/core/kstd_alloc/src/traits.rs (line 5)
[function] fn dealloc(&self, ptr: *mut u8, layout: Layout);
kernel_Workspace/core/kstd_alloc/src/traits.rs (line 6)
[function] fn realloc(&self, ptr: *mut u8, old: Layout, new_size: usize) ->
Result<*mut u8, Status> {
kernel_Workspace/core/kstd_base/src/errors.rs (line 20)
[function] fn from(val: u32) -> Self {
kernel_Workspace/core/kstd_base/src/errors.rs (line 40)
[function] fn from(val: Status) -> Self {
kernel_Workspace/core/kstd_base/src/primitives.rs (line 39)
[function] fn bitor(self, rhs: Self) -> Self {
kernel_Workspace/core/kstd_base/src/trails.rs (line 4)
[function] fn align_up(self) -> Self;
kernel_Workspace/core/kstd_base/src/trails.rs (line 5)
[function] fn align_down(self) -> Self;
kernel_Workspace/core/kstd_base/src/trails.rs (line 6)
[function] fn is_aligned(self) -> bool;
kernel_Workspace/core/kstd_base/src/trails.rs (line 11)
[function] fn align_up(self) -> Self {
kernel_Workspace/core/kstd_base/src/trails.rs (line 16)
[function] fn align_down(self) -> Self {
kernel_Workspace/core/kstd_base/src/trails.rs (line 21)
[function] fn is_aligned(self) -> bool {
kernel_Workspace/core/kstd_base/src/trails.rs (line 28)
[function] fn align_up(self) -> Self {
kernel_Workspace/core/kstd_base/src/trails.rs (line 33)
[function] fn align_down(self) -> Self {
kernel_Workspace/core/kstd_base/src/trails.rs (line 38)
[function] fn is_aligned(self) -> bool {

```

```

kernel_Workspace/core/kstd_base/src/trails.rs (line 44)
[function] fn read_u8(&self, port: u16) -> u8;
kernel_Workspace/core/kstd_base/src/trails.rs (line 45)
[function] fn write_u8(&self, port: u16, val: u8);
kernel_Workspace/core/kstd_base/src/trails.rs (line 46)
[function] fn read_u16(&self, port: u16) -> u16;
kernel_Workspace/core/kstd_base/src/trails.rs (line 47)
[function] fn write_u16(&self, port: u16, val: u16);
kernel_Workspace/core/kstd_base/src/trails.rs (line 48)
[function] fn read_u32(&self, port: u16) -> u32;
kernel_Workspace/core/kstd_base/src/trails.rs (line 49)
[function] fn write_u32(&self, port: u16, val: u32);
kernel_Workspace/core/kstd_base/src/trails.rs (line 53)
[function] fn read_volatile_u32(&self, offset: usize) -> u32;
kernel_Workspace/core/kstd_base/src/trails.rs (line 54)
[function] fn write_volatile_u32(&self, offset: usize, val: u32);
kernel_Workspace/core/kstd_base/src/trails.rs (line 55)
[function] fn read_volatile_u64(&self, offset: usize) -> u64;
kernel_Workspace/core/kstd_base/src/trails.rs (line 56)
[function] fn write_volatile_u64(&self, offset: usize, val: u64);
kernel_Workspace/core/kstd_base/src/types.rs (line 23)
[function] fn default() -> Self {
kernel_Workspace/core/kstd_core/src/panic.rs (line 5)
[function] fn write_all(serial: &mut kstd_io::Serial, vga: &mut kstd_io::VgaConsole,
s: &str) {
kernel_Workspace/core/kstd_core/src/panic.rs (line 34)
[struct] struct FmtWriter<'a, W: Write>(&'a mut W);
kernel_Workspace/core/kstd_core/src/panic.rs (line 37)
[function] fn write_str(&mut self, s: &str) -> core::fmt::Result {
kernel_Workspace/core/kstd_core/src/panic.rs (line 45)
[function] fn heapless_msg(message: core::panic::PanicMessage) ->
kstd_data::string::String {
kernel_Workspace/core/kstd_core/src/panic.rs (line 52)
[struct] struct FmtMsg<'a>(&'a mut kstd_data::string::String);
kernel_Workspace/core/kstd_core/src/panic.rs (line 55)
[function] fn write_str(&mut self, s: &str) -> core::fmt::Result {
kernel_Workspace/core/kstd_core/src/sync.rs (line 45)
[function] fn deref(&self) -> &T {
kernel_Workspace/core/kstd_core/src/sync.rs (line 51)
[function] fn deref_mut(&mut self) -> &mut T {
kernel_Workspace/core/kstd_core/src/sync.rs (line 57)
[function] fn drop(&mut self) {
kernel_Workspace/core/kstd_core/src/task.rs (line 4)
[function] fn sched_create_task(world_id: u32, flags: u32, out_task_id: *mut u64) ->
bool;
kernel_Workspace/core/kstd_core/src/task.rs (line 5)
[function] fn sched_destroy_task(task_id: u64) -> bool;
kernel_Workspace/core/kstd_core/src/task.rs (line 6)
[function] fn sched_yield() -> bool;

```

```

kernel_Workspace/core/kstd_core/src/task.rs (line 7)
[function] fn sched_get_current_task() -> u64;
kernel_Workspace/core/kstd_core/src/thread.rs (line 4)
[function] fn thread_create(task_id: u64, entry: u64, stack_ptr: u64, arg: u64,
out_tid: *mut u64) -> bool;
kernel_Workspace/core/kstd_core/src/thread.rs (line 5)
[function] fn thread_exit() -> !;
kernel_Workspace/core/kstd_core/src/thread.rs (line 6)
[function] fn thread_get_current_id() -> u64;
kernel_Workspace/core/kstd_core/src/time.rs (line 2)
[function] fn k_tick() -> u64;
kernel_Workspace/core/kstd_data/src/map.rs (line 4)
[struct] struct FnvHasher(u64);
kernel_Workspace/core/kstd_data/src/map.rs (line 6)
[function] fn finish(&self) -> u64 { self.0 }
kernel_Workspace/core/kstd_data/src/map.rs (line 7)
[function] fn write(&mut self, bytes: &[u8]) {
kernel_Workspace/core/kstd_data/src/map.rs (line 27)
[function] fn hash_key(key: &K) -> usize {
kernel_Workspace/core/kstd_data/src/map.rs (line 33)
[function] fn idx(&self, hash: usize) -> usize { hash % self.buckets.len() }
kernel_Workspace/core/kstd_data/src/map.rs (line 91)
[function] fn resize(&mut self, new_cap: usize) {
kernel_Workspace/core/kstd_data/src/string.rs (line 29)
[function] fn deref(&self) -> &str { self.as_str() }
kernel_Workspace/core/kstd_data/src/string.rs (line 33)
[function] fn write_str(&mut self, s: &str) -> fmt::Result {
kernel_Workspace/core/kstd_data/src/tree.rs (line 3)
[struct] struct Node<K, V> {
kernel_Workspace/core/kstd_data/src/tree.rs (line 20)
[function] fn alloc_node(&mut self, key: K, val: V) -> usize {
kernel_Workspace/core/kstd_data/src/tree.rs (line 30)
[function] fn free_node(&mut self, idx: usize) {
kernel_Workspace/core/kstd_data/src/tree.rs (line 34)
[function] fn height(&self, idx: usize) -> i32 {
kernel_Workspace/core/kstd_data/src/tree.rs (line 38)
[function] fn update_height(&mut self, idx: usize) {
kernel_Workspace/core/kstd_data/src/tree.rs (line 44)
[function] fn balance_factor(&self, idx: usize) -> i32 {
kernel_Workspace/core/kstd_data/src/tree.rs (line 49)
[function] fn rotate_right(&mut self, y: usize) -> usize {
kernel_Workspace/core/kstd_data/src/tree.rs (line 59)
[function] fn rotate_left(&mut self, x: usize) -> usize {
kernel_Workspace/core/kstd_data/src/tree.rs (line 69)
[function] fn balance(&mut self, idx: usize) -> usize {
kernel_Workspace/core/kstd_data/src/tree.rs (line 89)
[function] fn insert_rec(&mut self, idx: usize, key: K, val: V) -> usize {
kernel_Workspace/core/kstd_data/src/vec.rs (line 24)
[function] fn grow_to(&mut self, new_cap: usize) {

```

```

kernel_Workspace/core/kstd_data/src/vec.rs (line 87)
[function] fn deref(&self) -> &[T] { self.as_slice() }
kernel_Workspace/core/kstd_data/src/vec.rs (line 91)
[function] fn deref_mut(&mut self) -> &mut [T] { self.as_mut_slice() }
kernel_Workspace/core/kstd_data/src/vec.rs (line 95)
[function] fn drop(&mut self) {
kernel_Workspace/core/kstd_io/src/buffer.rs (line 33)
[function] fn write_str(&mut self, s: &str) -> Result<(), ()> {
kernel_Workspace/core/kstd_io/src/console.rs (line 4)
[function] fn kprintf(fmt: *const u8, ...);
kernel_Workspace/core/kstd_io/src/console.rs (line 5)
[function] fn serial_write_str(s: *const u8);
kernel_Workspace/core/kstd_io/src/console.rs (line 10)
[function] fn write_str(&mut self, s: &str) -> Result<(), ()> {
kernel_Workspace/core/kstd_io/src/console.rs (line 26)
[function] fn write_str(&mut self, s: &str) -> Result<(), ()> {
kernel_Workspace/core/kstd_io/src/input.rs (line 2)
[function] fn k_input_key() -> i32;
kernel_Workspace/core/kstd_io/src/input.rs (line 3)
[function] fn k_input_keycode() -> u32;
kernel_Workspace/core/kstd_io/src/input.rs (line 4)
[function] fn kbuf_pop() -> i32;
kernel_Workspace/core/kstd_io/src/input.rs (line 24)
[function] fn read_byte(&mut self) -> Option<u8> {
kernel_Workspace/core/kstd_io/src/input.rs (line 31)
[function] fn read_byte(&mut self) -> Option<u8> {
kernel_Workspace/core/kstd_io/src/traits.rs (line 2)
[function] fn write_str(&mut self, s: &str) -> Result<(), ()>;
kernel_Workspace/core/kstd_io/src/traits.rs (line 4)
[function] fn write_u64(&mut self, mut val: u64, base: u8) -> Result<(), ()> {
kernel_Workspace/core/kstd_io/src/traits.rs (line 23)
[function] fn read_byte(&mut self) -> Option<u8>;
kernel_Workspace/core/linux_abi_driverspace/src/devmodel.rs (line 11)
[function] fn probe(&mut self, dev: &LinuxDevice) -> Result<(), Status>;
kernel_Workspace/core/linux_abi_driverspace/src/devmodel.rs (line 12)
[function] fn remove(&mut self, dev: &LinuxDevice) -> Result<(), Status>;
kernel_Workspace/core/windows-com/src/lib.rs (line 11)
[function] fn it_works() {
kernel_Workspace/kernel-bin/build.rs (line 13)
[function] fn main() {
kernel_Workspace/kernel-bin/src/main.rs (line 17)
[function] fn kernel_main(boot_info: &'static BootInfo) -> ! {
kernel_Workspace/kernel/build.rs (line 6)
[function] fn collect_c_files(dir: &Path, out: &mut Vec<PathBuf>) {
kernel_Workspace/kernel/build.rs (line 23)
[function] fn clang_target(arch: &str) -> &'static str {
kernel_Workspace/kernel/build.rs (line 33)
[function] fn main() {

```

```

kernel_Workspace/kernel/src/arch/riscv64.rs (line 9)
[struct] struct HeapSpace([u8; HEAP_SIZE]);
kernel_Workspace/kernel/src/arch/riscv64.rs (line 13)
[struct] struct Bump {
kernel_Workspace/kernel/src/arch/riscv64.rs (line 60)
[function] fn riscv_panic(info: &PanicInfo) -> ! {
kernel_Workspace/kernel/src/arch/x86_64.rs (line 5)
[function] fn x86_panic(info: &PanicInfo) -> ! {
kernel_Workspace/kernel/src/battery/bridge.rs (line 5)
[function] fn battery_status_packed(a0: *mut u64, a1: *mut u64, a2: *mut u64) ->
bool;
kernel_Workspace/kernel/src/battery/bridge.rs (line 6)
[function] fn battery_set_threshold(pct: u32) -> bool;
kernel_Workspace/kernel/src/battery/init.rs (line 2)
[function] fn battery_init() -> bool;
kernel_Workspace/kernel/src/bluetooth/bridge.rs (line 7)
[function] fn bt_init() -> bool;
kernel_Workspace/kernel/src/bluetooth/bridge.rs (line 8)
[function] fn bt_ready() -> bool;
kernel_Workspace/kernel/src/bluetooth/bridge.rs (line 9)
[function] fn bt_info(ver: *mut u8, bdaddr: *mut u8);
kernel_Workspace/kernel/src/bluetooth/bridge.rs (line 10)
[function] fn bt_hci_cmd(opcode: u16, params: *const u8, len: u8) -> bool;
kernel_Workspace/kernel/src/bluetooth/bridge.rs (line 11)
[function] fn bt_event_poll(buf: *mut u8, cap: u8, len: *mut u8) -> bool;
kernel_Workspace/kernel/src/bluetooth/bridge.rs (line 12)
[function] fn bt_acl_send(data: *const u8, len: u16) -> bool;
kernel_Workspace/kernel/src/bluetooth/bridge.rs (line 13)
[function] fn bt_acl_recv(data: *mut u8, cap: u16, len: *mut u16) -> bool;
kernel_Workspace/kernel/src/bluetooth/init.rs (line 2)
[function] fn bt_init() -> bool;
kernel_Workspace/kernel/src/bluetooth/init.rs (line 3)
[function] fn bt_ready() -> bool;
kernel_Workspace/kernel/src/camera/bridge.rs (line 5)
[function] fn camera_caps_get(w: *mut u32, h: *mut u32, fmt: *mut u32, fps: *mut
u32) -> bool;
kernel_Workspace/kernel/src/camera/bridge.rs (line 6)
[function] fn camera_start() -> bool;
kernel_Workspace/kernel/src/camera/bridge.rs (line 7)
[function] fn camera_stop() -> bool;
kernel_Workspace/kernel/src/camera/bridge.rs (line 8)
[function] fn camera_frame_to_phys(phys: u64, cap: u32, fid: *mut u64) -> bool;
kernel_Workspace/kernel/src/camera/bridge.rs (line 11)
[function] fn grant_phys(va: u64) -> Option<u64> {
kernel_Workspace/kernel/src/camera/init.rs (line 2)
[function] fn camera_init() -> bool;
kernel_Workspace/kernel/src/caps/audit.rs (line 27)
[struct] struct AuditInner {

```

```

kernel_Workspace/kernel/src/caps/audit.rs (line 52)
[function] fn now_tick() -> u64 {
kernel_Workspace/kernel/src/caps/audit.rs (line 56)
[function] fn push(kind: EventKind, world: u32, target: u32, cap: Capability) {
kernel_Workspace/kernel/src/caps/audit.rs (line 142)
[function] fn test_audit() {
kernel_Workspace/kernel/src/caps/check.rs (line 26)
[function] fn current_world_id() -> u32 {
kernel_Workspace/kernel/src/caps/check.rs (line 147)
[function] fn drop(&mut self) {
kernel_Workspace/kernel/src/caps/check.rs (line 158)
[function] fn test_require() {
kernel_Workspace/kernel/src/caps/export.rs (line 7)
[function] fn cap_from_id(id: u8) -> Option<Capability> {
kernel_Workspace/kernel/src/caps/grant.rs (line 58)
[struct] struct TempGrant {
kernel_Workspace/kernel/src/caps/grant.rs (line 74)
[function] fn now_tick() -> u64 {
kernel_Workspace/kernel/src/caps/grant.rs (line 121)
[function] fn test_inherit() {
kernel_Workspace/kernel/src/caps/hierarchy.rs (line 132)
[function] fn test_hierarchy() {
kernel_Workspace/kernel/src/caps/hierarchy.rs (line 149)
[function] fn test_depth() {
kernel_Workspace/kernel/src/caps/policy.rs (line 14)
[function] fn policy_allows(world: u32, cap: Capability) -> bool {
kernel_Workspace/kernel/src/caps/revoke.rs (line 68)
[function] fn test_revoke() {
kernel_Workspace/kernel/src/caps/sets.rs (line 162)
[function] fn test_presets() {
kernel_Workspace/kernel/src/caps/sets.rs (line 174)
[function] fn test_effective() {
kernel_Workspace/kernel/src/caps/store.rs (line 22)
[struct] struct StoreInner {
kernel_Workspace/kernel/src/caps/store.rs (line 71)
[function] fn find_world_inner(s: &StoreInner, world_id: u32) -> Result<WorldCaps,
&'static str> {
kernel_Workspace/kernel/src/caps/store.rs (line 192)
[function] fn test_world_registration() {
kernel_Workspace/kernel/src/caps/syscalls.rs (line 13)
[function] fn cap_from_id(id: u8) -> Option<Capability> {
kernel_Workspace/kernel/src/caps/tests.rs (line 8)
[function] fn test_full_flow() {
kernel_Workspace/kernel/src/caps/tests.rs (line 29)
[function] fn test_hierarchy_enforcement() {
kernel_Workspace/kernel/src/caps/tests.rs (line 40)
[function] fn test_global_revocation() {
kernel_Workspace/kernel/src/caps/tests.rs (line 54)
[function] fn test_audit_trail() {

```

```

kernel_Workspace/kernel/src/caps/types.rs (line 221)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
kernel_Workspace/kernel/src/caps/types.rs (line 240)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
kernel_Workspace/kernel/src/caps/types.rs (line 256)
[function] fn test_set_operations() {
kernel_Workspace/kernel/src/cpu/acpi.rs (line 43)
[function] fn checksum(bytes: &[u8]) -> bool {
kernel_Workspace/kernel/src/cpu/lapic.rs (line 20)
[function] fn x2apic_msr(reg: u32) -> u32 {
kernel_Workspace/kernel/src/cpu/riscv.rs (line 26)
[function] fn system_reset(reset_type: u32) -> ! {
kernel_Workspace/kernel/src/cpu/scheduler/arch/risc_v/context_swich.rs (line 716)
[function] fn test_fpu_save_area_size() {
kernel_Workspace/kernel/src/cpu/scheduler/arch/risc_v/context_swich.rs (line 722)
[function] fn test_satp_constants() {
kernel_Workspace/kernel/src/cpu/scheduler/arch/risc_v/context_swich.rs (line 730)
[function] fn test_sstatus_fs_mask() {
kernel_Workspace/kernel/src/cpu/scheduler/arch/risc_v/context_swich.rs (line 739)
[function] fn test_satp_mode_name() {
kernel_Workspace/kernel/src/cpu/scheduler/arch/x86_64/context_swich.rs (line 45)
[struct] struct XSaveArea {
kernel_Workspace/kernel/src/cpu/scheduler/arch/x86_64/context_swich.rs (line 56)
[struct] struct ExtendedContext {
kernel_Workspace/kernel/src/cpu/scheduler/arch/x86_64/context_swich.rs (line 458)
[struct] struct TssStruct {
kernel_Workspace/kernel/src/cpu/scheduler/arch/x86_64/context_swich.rs (line 769)
[function] fn test_xsave_area_alignment() {
kernel_Workspace/kernel/src/cpu/scheduler/arch/x86_64/context_swich.rs (line 774)
[function] fn test_msr_constants() {
kernel_Workspace/kernel/src/cpu/scheduler/arch/x86_64/context_swich.rs (line 781)
[function] fn test_cr3_masks() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 69)
[function] fn cpu_to_apic_id(cpu: u32) -> Option<u32> {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 175)
[function] fn ns_from_tsc(tsc_delta: u64, hz: u64) -> u64 {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 217)
[function] fn timer_count_for_hz(hz: u64) -> u32 {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 225)
[function] fn cmp_max_1(v: u32) -> u32 {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 233)
[function] fn default_timer_count() -> u32 {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 369)
[struct] struct IdtDescriptor {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 437)
[function] fn arch_context_switch(prev_ctx: *mut CpuContext, next_ctx: *const CpuContext);
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 462)
[function] fn maybe_balance(cpu: u32, registry: &[*mut RunQueue; MAX_CPUS]) {

```

```

kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 587)
[function] fn registry_defaults_to_null_for_untouched_cpu() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 593)
[function] fn apic_id_table_defaults_to_none_then_roundtrips() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 600)
[function] fn register_runqueue_ignores_out_of_range_cpu() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 605)
[function] fn ns_from_tsc_is_zero_without_calibration() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 610)
[function] fn ns_from_tsc_scales_correctly() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 618)
[function] fn timer_count_for_hz_has_sane_fallback() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 624)
[function] fn timer_count_for_hz_never_returns_zero() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 629)
[function] fn tlb_pending_flag_sets_and_clears() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 637)
[function] fn idt_entry_encodes_and_reports_present() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 645)
[function] fn idt_entry_missing_is_not_present() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 651)
[function] fn cpuid_leaf_zero_reports_a_nonzero_max_leaf() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 660)
[function] fn rdtsc_does_not_go_backwards_across_two_reads() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 670)
[function] fn cpuid_and_rdtsc_are_zero_off_x86_64() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 678)
[function] fn set_and_read_tsc_frequency_is_stable_within_this_test() {
kernel_Workspace/kernel/src/cpu/scheduler/arch_hooks.rs (line 684)
[function] fn booted_cpu_count_starts_at_or_above_zero() {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 514)
[function] fn make_idle(pid: TaskId) -> TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 520)
[function] fn make_task(pid: TaskId, policy: SchedPolicy, nice: i8) -> TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 526)
[function] fn ptr_of(t: &mut TaskStruct) -> *mut TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 531)
[function] fn chain_is_ordered_stop_dl_rt_fair_idle() {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 545)
[function] fn class_of_maps_every_variant_correctly() {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 554)
[function] fn pick_next_walks_the_chain_in_priority_order() {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 596)
[function] fn rt_get_rr_interval_is_nonzero_only_for_round_robin() {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 606)
[function] fn fair_and_deadline_and_idle_have_zero_rr_interval() {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 618)
[function] fn check_preempt_cross_class_ignores_intra_class_ops() {

```

```
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 639)
[function] fn switched_to_reschedules_when_new_class_outranks_current() {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 664)
[function] fn change_task_class_moves_task_between_underlying_queues() {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 688)
[function] fn change_task_class_on_non_queued_task_does_not_touch_queues() {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 706)
[function] fn rt_task_tick_only_requeues_round_robin_on_slice_expiry() {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 727)
[function] fn rt_task_tick_marks_resched_when_round_robin_slice_expires() {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 750)
[function] fn dl_task_tick_dequeues_when_throttled() {
kernel_Workspace/kernel/src/cpu/scheduler/class.rs (line 776)
[function] fn fair_charge_dispatches_to_underlying_rqfair() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 168)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 182)
[function] fn next(&mut self) -> Option<usize> {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 340)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 350)
[function] fn words_for_bits_rounds_up() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 358)
[function] fn set_clear_test_roundtrip() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 369)
[function] fn out_of_range_access_is_a_safe_noop() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 377)
[function] fn weight_counts_set_bits_across_words() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 387)
[function] fn find_first_set_crosses_word_boundary() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 394)
[function] fn find_first_zero_skips_full_words() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 401)
[function] fn find_first_zero_none_when_full() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 408)
[function] fn find_next_set_after_given_bit() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 417)
[function] fn set_range_sets_contiguous_span() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 429)
[function] fn boolean_ops_behave_as_expected() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 446)
[function] fn iter_yields_set_bits_in_order() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 460)
[function] fn slice_bitmap_respects_logical_bit_count_not_word_count() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 472)
[function] fn slice_bitmap_clear_all_resets_backing_storage() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 481)
[function] fn atomic_bitmap_test_and_set_reports_previous_state() {
```

```

kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 489)
[function] fn atomic_bitmap_test_and_clear_reports_previous_state() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 498)
[function] fn atomic_bitmap_find_first_zero_and_set_claims_sequentially() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 507)
[function] fn atomic_bitmap_find_first_zero_and_set_returns_none_when_full() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 517)
[function] fn atomic_bitmap_weight_matches_manual_count() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/bitmap.rs (line 526)
[function] fn atomic_bitmap_out_of_range_set_is_harmless() {
kernel_Workspace/kernel/src/cpu/scheduler/collections/plist.rs (line 20)
[function] fn plist_prio(node: *mut TaskStruct) -> i32 {
kernel_Workspace/kernel/src/cpu/scheduler/collections/rbtree.rs (line 23)
[function] fn rb_parent(node: *mut TaskStruct) -> *mut TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/collections/rbtree.rs (line 29)
[function] fn rb_color(node: *mut TaskStruct) -> usize {
kernel_Workspace/kernel/src/cpu/scheduler/collections/rbtree.rs (line 35)
[function] fn rb_is_red(node: *mut TaskStruct) -> bool {
kernel_Workspace/kernel/src/cpu/scheduler/collections/rbtree.rs (line 40)
[function] fn rb_set_parent_color(node: *mut TaskStruct, parent: *mut TaskStruct,
color: usize) {
kernel_Workspace/kernel/src/cpu/scheduler/collections/rbtree.rs (line 48)
[function] fn rb_set_parent(node: *mut TaskStruct, parent: *mut TaskStruct) {
kernel_Workspace/kernel/src/cpu/scheduler/collections/rbtree.rs (line 54)
[function] fn rb_set_color(node: *mut TaskStruct, color: usize) {
kernel_Workspace/kernel/src/cpu/scheduler/collections/rbtree.rs (line 116)
[function] fn rb_insert_fixup(&mut self, mut node: *mut TaskStruct) {
kernel_Workspace/kernel/src/cpu/scheduler/collections/rt_array.rs (line 34)
[function] fn bit_is_set(&self, prio: usize) -> bool {
kernel_Workspace/kernel/src/cpu/scheduler/collections/task.rs (line 116)
[function] fn hash_pid(pid: TaskId) -> usize { (pid as usize) % MAX_TASKS }
kernel_Workspace/kernel/src/cpu/scheduler/collections/task.rs (line 117)
[function] fn hash_tgid(tgid: TaskId) -> usize { (tgid as usize) % TGID_SLOTS }
kernel_Workspace/kernel/src/cpu/scheduler/collections/task.rs (line 287)
[function] fn next(&mut self) -> Option<Self::Item> {
kernel_Workspace/kernel/src/cpu/scheduler/collections/task.rs (line 319)
[function] fn next(&mut self) -> Option<Self::Item> {
kernel_Workspace/kernel/src/cpu/scheduler/collections/task.rs (line 350)
[function] fn next(&mut self) -> Option<Self::Item> {
kernel_Workspace/kernel/src/cpu/scheduler/collections/task.rs (line 375)
[function] fn next(&mut self) -> Option<Self::Item> {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 240)
[function] fn make_idle(pid: TaskId) -> TaskStructT {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 246)
[function] fn make_task(pid: TaskId, policy: SchedPolicy, nice: i8) -> TaskStructT {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 252)
[function] fn ptr_of(t: &mut TaskStructT) -> *mut TaskStructT {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 257)
[function] fn two_consecutive_allocations_are_distinct() {

```

```

kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 266)
[function] fn reserve_and_free_pid_roundtrip_on_a_dedicated_high_pid() {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 278)
[function] fn reserve_pid_rejects_out_of_range() {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 283)
[function] fn boot_bsp_registers_apic_and_runqueue() {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 294)
[function] fn wake_up_new_task_enqueues_and_marks_runnable() {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 312)
[function] fn exit_bookkeeping_dequeues_and_marks_zombie() {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 332)
[function] fn exit_bookkeeping_on_unqueued_task_returns_null_rq() {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 342)
[function] fn reap_zombie_destroys_and_frees_pid() {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 358)
[function] fn maybe_reschedule_is_noop_when_not_needed() {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 369)
[function] fn sys_nice_clamps_to_valid_range() {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 380)
[function] fn sys_nice_rejects_non_fair_policy() {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 388)
[function] fn sys_sched_setscheduler_moves_task_to_new_class() {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 407)
[function] fn sys_sched_rr_get_interval_matches_class_dispatch() {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 417)
[function] fn sys_sched_affinity_roundtrips() {
kernel_Workspace/kernel/src/cpu/scheduler/core.rs (line 427)
[function] fn priority_range_helpers_match_posix_expectations() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 189)
[function] fn insert_fixup(root: &mut *mut TaskStruct, mut z: *mut TaskStruct) {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 293)
[function] fn delete_fixup(root: &mut *mut TaskStruct, mut x: *mut TaskStruct, mut
x_parent: *mut TaskStruct) {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 423)
[function] fn check(node: *mut TaskStruct, key_of: KeyOf) -> Result<usize, &'static
str> {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 452)
[function] fn fair_key_of(node: *const TaskStruct) -> u64 {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 466)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 486)
[function] fn place_entity(&self, task: *mut TaskStruct, flags: EnqueueFlags) {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 563)
[function] fn dl_key_of(node: *const TaskStruct) -> u64 {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 579)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 607)
[function] fn task_bw(task: *const TaskStruct) -> u64 {

```

```

kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 714)
[function] fn set_bit(&mut self, prio: usize) {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 718)
[function] fn clear_bit(&mut self, prio: usize) {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 722)
[function] fn sched_find_first_bit(&self) -> Option<usize> {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 920)
[function] fn now(&self) -> u64 {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 934)
[function] fn set_current(&self, task: *mut TaskStruct) {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1001)
[function] fn nr_uninterruptible_dec_if(&self, task: *mut TaskStruct) {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1202)
[function] fn fair_max_vruntime(&self) -> Option<u64> {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1219)
[function] fn fair_root_for_test(&self) -> *mut TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1223)
[function] fn fair_root_internal(&self) -> *mut TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1246)
[function] fn fmt(&self, f: &mut core::fmt::Formatter<'>) -> core::fmt::Result {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1294)
[function] fn can_migrate_task(task: *const TaskStruct, dst_cpu: u32) -> bool {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1489)
[function] fn make_idle(pid: TaskId, cpu: u32) -> TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1496)
[function] fn make_task(pid: TaskId, policy: SchedPolicy, nice: i8) -> TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1502)
[function] fn ptr_of(t: &mut TaskStruct) -> *mut TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1507)
[function] fn fair_tree_maintains_rb_invariants_under_pseudorandom_inserts() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1537)
[function] fn fair_tree_inorder_traversal_is_sorted_by_vruntime() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1566)
[function] fn fair_tree_survives_random_removals_keeping_invariants() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1588)
[function] fn deadline_tree_orders_by_earliest_deadline() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1609)
[function] fn rt_queue_fifo_order_at_same_priority_without_cycles() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1648)
[function] fn rt_queue_picks_highest_priority_across_levels() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1667)
[function] fn rt_queue_requeue_moves_task_to_back_of_its_level() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1689)
[function] fn
pick_next_task_respects_stop_over_deadline_over_rt_over_fair_over_idle() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1739)
[function] fn pick_next_task_never_returns_null_even_when_fully_empty() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1754)
[function] fn deadline_task_is_picked_even_before_its_deadline_has_passed() {

```

```
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1783)
[function] fn min_vruntime_never_decreases_across_updates() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1797)
[function] fn newly_woken_task_does_not_start_before_min_vruntime() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1817)
[function] fn higher_class_always_preempts_lower_class() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1842)
[function] fn fair_preemption_requires_minimum_granularity() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1860)
[function] fn deadline_preempts_via_earliest_deadline_first() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1874)
[function] fn deadline_task_gets_throttled_when_budget_is_exhausted() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1892)
[function] fn deadline_task_is_replenished_after_period_rollover() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1909)
[function] fn deadline_admission_control_rejects_overcommitted_bandwidth() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1924)
[function] fn activate_and_deactivate_round_trip_updates_bookkeeping() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1951)
[function] fn double_enqueue_is_rejected_in_debug_builds() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1966)
[function] fn select_task_rq_prefers_idle_cpu_with_cache_affinity() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 1985)
[function] fn select_task_rq_picks_least_loaded_when_no_affinity_hit() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 2011)
[function] fn wake_up_process_transitions_state_and_enqueues_remotely() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 2030)
[function] fn wake_up_process_is_idempotent_when_already_queued() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 2049)
[function] fn idle_balance_pulls_one_task_from_busy_cpu() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 2081)
[function] fn idle_balance_does_nothing_when_balanced() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 2105)
[function] fn migrated_task_gets_updated_cpu_and_rq_pointer() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 2140)
[function] fn no_migration_respects_cpus_allowed_mask() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 2169)
[function] fn yield_task_pushes_vruntime_to_back_of_fair_queue() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 2192)
[function] fn schedule_tail_records_voluntary_vs_involuntary_switch() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 2218)
[function] fn clock_advances_and_update_curr_charges_real_delta() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 2243)
[function] fn update_curr_is_a_noop_on_idle_task() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 2257)
[function] fn lower_nice_task_accumulates_vruntime_slower() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 2281)
[function] fn load_balance_moves_task_between_two_uneven_queues() {
```

```

kernel_Workspace/kernel/src/cpu/scheduler/entities/runqueue.rs (line 2310)
[function] fn load_balance_is_noop_below_imbalance_threshold() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/stats.rs (line 265)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/stats.rs (line 315)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
kernel_Workspace/kernel/src/cpu/scheduler/entities/stats.rs (line 332)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 120)
[function] fn clone(&self) -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 200)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 239)
[function] fn from(policy: SchedPolicy) -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 358)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 371)
[function] fn next(&mut self) -> Option<u32> {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 463)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 469)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 493)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 647)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 682)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 720)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 744)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 824)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 955)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1066)
[function] fn drop(&mut self) {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1089)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1407)
[function] fn set_state_unchecked(&self, new_state: TaskState) {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1429)
[function] fn set_state_owned(&mut self, new_state: TaskState) -> Result<(),
TaskError> {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1578)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1592)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {

```

```
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1761)
[function] fn nice_to_weight_is_monotonically_decreasing() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1771)
[function] fn nice_zero_has_default_weight() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1776)
[function] fn nice_to_weight_clamps_out_of_range() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1782)
[function] fn weight_to_nice_round_trip_is_close() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1790)
[function] fn calc_delta_fair_is_identity_at_nice_zero() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1796)
[function] fn calc_delta_fair_grows_for_lower_weight() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1803)
[function] fn cpumask_basic_set_clear() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1818)
[function] fn cpumask_all_contains_every_cpu() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1826)
[function] fn cpumask_intersects() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1837)
[function] fn cpumask_and_or() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1850)
[function] fn cpumask_next_after_wraps() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1859)
[function] fn cpumask_first_n() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1867)
[function] fn task_state_valid_transitions() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1875)
[function] fn task_state_invalid_transitions_are_rejected() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1882)
[function] fn default_rlimits_have_sane_stack_and_nofile() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1890)
[function] fn credentials_kernel_has_full_capabilities() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1897)
[function] fn credentials_user_has_no_extra_capabilities() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1904)
[function] fn signal_state_pending_respects_blocked_mask() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1915)
[function] fn list_head_insert_and_remove_roundtrip() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1943)
[function] fn list_head_remove_never_creates_a_cycle_with_three_nodes() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1967)
[function] fn spinlock_lock_unlock_cycle() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1977)
[function] fn spinlock_try_lock_fails_when_held() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1987)
[function] fn spinlock_irqsave_guard_unlocks_on_drop() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 1997)
[function] fn spinlock_plain_guard_unlocks_on_drop() {
```

```

kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2007)
[function] fn atomic_task_flags_insert_remove_are_bitwise() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2020)
[function] fn atomic_task_flags_test_and_set_is_edge_triggered() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2027)
[function] fn rb_parent_color_encoding_roundtrips() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2038)
[function] fn fx_save_area_default_is_zeroed() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2046)
[function] fn cpu_context_default_has_no_valid_fpu_state() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2052)
[function] fn sched_policy_maps_to_expected_class() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2063)
[function] fn sched_class_ordering_matches_pick_next_priority() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2071)
[function] fn default_time_slice_matches_policy_expectations() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2078)
[function] fn load_avg_accumulate_grows_then_decays() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2087)
[function] fn bare_task_for_state_tests() -> TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2132)
[function] fn set_state_via_shared_reference_does_not_need_mut() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2142)
[function] fn set_state_rejects_illegal_transition_via_shared_reference() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2150)
[function] fn wake_up_process_pattern_from_remote_cpu_context() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2154)
[function] fn remote_wake(t: &TaskStruct) -> Result<>, TaskError> {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2163)
[function] fn rq_backpointer_roundtrips() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2172)
[function] fn need_resched_flag_is_settable_from_shared_reference() {
kernel_Workspace/kernel/src/cpu/scheduler/entities/task.rs (line 2182)
[function] fn rt_sched_entity_starts_with_initialized_list_and_no_queued_prio() {
kernel_Workspace/kernel/src/cpu/scheduler/power/em.rs (line 160)
[function] fn sort_states(&mut self) {
kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/active.rs (line 13)
[struct] struct ActiveBalanceArg {
kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/active.rs (line 84)
[function] fn active_balance_is_noop_with_zero_imbalance() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/active.rs (line 95)
[function] fn active_balance_is_noop_when_target_equals_busiest() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/calculate.rs (line 244)
[function] fn load_calculation_defaults() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/calculate.rs (line 251)
[function] fn group_classification_idle() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/calculate.rs (line 260)
[function] fn group_classification_has_idle_beats_overloaded() {

```

```

kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/calculate.rs (line 271)
[function] fn group_classification_overloaded_when_busy_and_full() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/calculate.rs (line 281)
[function] fn calculate_imbalance_moves_load_toward_equilibrium() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/calculate.rs (line 304)
[function] fn calculate_imbalance_is_zero_for_balanced_groups() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/env.rs (line 79)
[function] fn env() -> LoadBalanceEnv {
kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/env.rs (line 84)
[function] fn flags_set_clear_roundtrip() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/env.rs (line 94)
[function] fn should_stop_once_loop_max_reached() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/env.rs (line 106)
[function] fn record_failure_sets_some_pinned() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/balancing/env.rs (line 115)
[function] fn reset_clears_loop_counter_and_need_break() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/ipi.rs (line 75)
[function] fn migration_stop_ipi_increments_dedicated_counter() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/ipi.rs (line 85)
[function] fn out_of_range_cpu_is_a_safe_noop() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/ipi.rs (line 92)
[function] fn handle_ipi_entry_ignores_unimplemented_types_without_panicking() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/migration/stopper.rs (line 108)
[function] fn wake_stopper_task(&self) {
kernel_Workspace/kernel/src/cpu/scheduler/smp/migration/stopper.rs (line 280)
[function] fn stopper_state_transitions() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/migration/stopper.rs (line 295)
[function] fn stopper_registry_bounds_check() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/migration/stopper.rs (line 302)
[function] fn queue_execute_and_wait_roundtrip_returns_value_from_function() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/migration/stopper.rs (line 317)
[function] fn queue_work_rejects_a_second_job_while_busy() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/migration/stopper.rs (line 325)
[function] fn execute_work_without_queued_job_is_a_noop() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/topology.rs (line 393)
[function] fn topology_alloc_domains_respects_limits() {
kernel_Workspace/kernel/src/cpu/scheduler/smp/topology.rs (line 406)
[function] fn sched_domain_flags_logic() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_balance_math.rs (line 5)
[function] fn make_idle(pid: u64, cpu: u32) -> TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_balance_math.rs (line 12)
[function] fn make_task(pid: u64, policy: SchedPolicy, nice: i8) -> TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_balance_math.rs (line 18)
[function] fn ptr_of(t: &mut TaskStruct) -> *mut TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_balance_math.rs (line 23)
[function] fn select_task_rq_returns_preferred_cpu_when_idle() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_balance_math.rs (line 42)
[function] fn select_task_rq_falls_back_to_least_loaded() {

```

```
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_balance_math.rs (line 68)
[function] fn select_task_rq_respects_cpus_allowed_mask() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_balance_math.rs (line 88)
[function] fn wake_up_process_enqueues_to_target_cpu() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_balance_math.rs (line 107)
[function] fn idle_balance_pulls_task_from_overloaded_cpu() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_balance_math.rs (line 135)
[function] fn load_balance_moves_task_across_uneven_queues() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_balance_math.rs (line 161)
[function] fn no_migration_when_cpus_allowed_forbids_it() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_balance_math.rs (line 189)
[function] fn migrated_task_updates_cpu_and_rq_pointer() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_balance_math.rs (line 224)
[function] fn pf_no_migrate_blocks_migration() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_balance_math.rs (line 250)
[function] fn load_balance_is_noop_below_threshold() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 4)
[function] fn default_load_avg_is_zero() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 14)
[function] fn accumulate_zero_delta_does_not_change_state_except_time() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 23)
[function] fn accumulate_running_task_increases_util_and_load() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 34)
[function] fn accumulate_idle_task_increases_load_but_not_util() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 44)
[function] fn decay_reduces_load_avg_over_time() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 56)
[function] fn load_avg_never_exceeds_theoretical_maximum() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 67)
[function] fn higher_weight_produces_higher_load_avg() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 78)
[function] fn saturating_add_prevents_overflow_on_huge_delta() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 86)
[function] fn alternating_running_and_idle_smooths_util_avg() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 99)
[function] fn period_contrib_increments_on_every_accumulate() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 109)
[function] fn util_sum_accumulates_only_when_running() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 118)
[function] fn load_sum_accumulates_regardless_of_running_state() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 127)
[function] fn pelt_precision_under_one_millisecond() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 134)
[function] fn pelt_handles_max_weight_without_panic() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_pelt.rs (line 141)
[function] fn consecutive_accumulates_update_last_time_correctly() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 5)
[function] fn fair_key(node: *const TaskStruct) -> u64 {
```

```

kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 9)
[function] fn dl_key(node: *const TaskStruct) -> u64 {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 13)
[function] fn make_task(pid: u64, vruntime: u64, deadline: u64) -> TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 22)
[function] fn empty_tree_has_zero_count_and_ok_invariants() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 33)
[function] fn single_node_tree_is_black_and_valid() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 46)
[function] fn sequential_inserts_maintain_sorted_order_and_invariants() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 77)
[function] fn reverse_inserts_maintain_invariants() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 97)
[function] fn random_inserts_and_deletes_keep_tree_valid() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 136)
[function] fn delete_root_repeatedly_destroys_tree_cleanly() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 160)
[function] fn delete_successor_maintains_inorder_traversal() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 206)
[function] fn duplicate_vruntime_inserts_are_placed_to_the_right() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 234)
[function] fn deadline_key_orders_by_earliest_deadline() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 254)
[function] fn subtree_min_and_max_return_extremes() {
kernel_Workspace/kernel/src/cpu/scheduler/tests/test_rbtrees.rs (line 276)
[function] fn stress_test_insert_delete_cycles() {
kernel_Workspace/kernel/src/cpu/scheduler/time/plist.rs (line 20)
[function] fn plist_prio(node: *mut TaskStruct) -> i32 {
kernel_Workspace/kernel/src/cpu/scheduler/time/rbtrees.rs (line 23)
[function] fn rb_parent(node: *mut TaskStruct) -> *mut TaskStruct {
kernel_Workspace/kernel/src/cpu/scheduler/time/rbtrees.rs (line 29)
[function] fn rb_color(node: *mut TaskStruct) -> usize {
kernel_Workspace/kernel/src/cpu/scheduler/time/rbtrees.rs (line 35)
[function] fn rb_is_red(node: *mut TaskStruct) -> bool {
kernel_Workspace/kernel/src/cpu/scheduler/time/rbtrees.rs (line 40)
[function] fn rb_set_parent_color(node: *mut TaskStruct, parent: *mut TaskStruct,
color: usize) {
kernel_Workspace/kernel/src/cpu/scheduler/time/rbtrees.rs (line 48)
[function] fn rb_set_parent(node: *mut TaskStruct, parent: *mut TaskStruct) {
kernel_Workspace/kernel/src/cpu/scheduler/time/rbtrees.rs (line 54)
[function] fn rb_set_color(node: *mut TaskStruct, color: usize) {
kernel_Workspace/kernel/src/cpu/scheduler/time/rbtrees.rs (line 116)
[function] fn rb_insert_fixup(&mut self, mut node: *mut TaskStruct) {
kernel_Workspace/kernel/src/cpu/scheduler/time/rt_array.rs (line 34)
[function] fn bit_is_set(&self, prio: usize) -> bool {
kernel_Workspace/kernel/src/cpu/smp.rs (line 32)
[struct] struct ApStack([u8; AP_STACK_SIZE]);
kernel_Workspace/kernel/src/cpu/smp.rs (line 36)
[function] fn stack_top_of(i: usize) -> u64 {

```

```

kernel_Workspace/kernel/src/cpu/smp.rs (line 42)
[function] fn delay(iterations: u64) {
kernel_Workspace/kernel/src/cpu/smp.rs (line 48)
[function] fn delay_ms(ms: u64) {
kernel_Workspace/kernel/src/cpu/smp.rs (line 52)
[function] fn load_cpu_gdt(ist_stack_top: VirtAddr) {
kernel_Workspace/kernel/src/cpu/smp.rs (line 76)
[function] fn debug_halt(msg: &str) -> ! {
kernel_Workspace/kernel/src/cpu/smp.rs (line 131)
[function] fn wait_for(flag: &AtomicBool, max_ms: u64) -> bool {
kernel_Workspace/kernel/src/ctrlinstall/repo/fetch.rs (line 2)
[function] fn fetch(&mut self, manifest: &PackageManifest) ->
Result<alloc::vec::Vec<u8>, CtrlInstallError>;
kernel_Workspace/kernel/src/displayport/bridge.rs (line 5)
[function] fn dp_ready() -> bool;
kernel_Workspace/kernel/src/displayport/bridge.rs (line 6)
[function] fn dp_link_info(rate: *mut u32, lanes: *mut u32);
kernel_Workspace/kernel/src/displayport/bridge.rs (line 7)
[function] fn dp_mode_at(i: u32, id: *mut u32, w: *mut u32,
kernel_Workspace/kernel/src/displayport/bridge.rs (line 9)
[function] fn dp_mode_set_by_id(id: u32) -> bool;
kernel_Workspace/kernel/src/displayport/bridge.rs (line 10)
[function] fn dp_submit_fill(color: u32, x: u32, y: u32, w: u32, h: u32) -> u64;
kernel_Workspace/kernel/src/displayport/init.rs (line 2)
[function] fn dp_init() -> bool;
kernel_Workspace/kernel/src/displayport/init.rs (line 3)
[function] fn dp_ready() -> bool;
kernel_Workspace/kernel/src/drivers/pci/mod.rs (line 18)
[function] fn cfg_addr(bus: u32, dev: u32, func: u32, off: u32) -> u32 {
kernel_Workspace/kernel/src/drivers/usb/class/hid/mod.rs (line 26)
[function] fn submit(x: &mut Xhci, kb: &mut HidKeyboard) {
kernel_Workspace/kernel/src/drivers/usb/class/mass/blockdev.rs (line 5)
[function] fn name(&self) -> &'static str {
kernel_Workspace/kernel/src/drivers/usb/class/mass/blockdev.rs (line 9)
[function] fn block_size(&self) -> usize {
kernel_Workspace/kernel/src/drivers/usb/class/mass/blockdev.rs (line 13)
[function] fn block_count(&self) -> u64 {
kernel_Workspace/kernel/src/drivers/usb/class/mass/blockdev.rs (line 17)
[function] fn read_block(&self, block: u64, buf: &mut [u8]) -> Result<(),
DriverError> {
kernel_Workspace/kernel/src/drivers/usb/class/mass/blockdev.rs (line 32)
[function] fn write_block(&self, block: u64, buf: &[u8]) -> Result<(), DriverError>
{
kernel_Workspace/kernel/src/drivers/usb/class/mod.rs (line 6)
[function] fn probe(&self, dev: &UsbDevice) -> bool;
kernel_Workspace/kernel/src/drivers/usb/core/enumerate.rs (line 11)
[function] fn kprintf(fmt: *const u8, ...);
kernel_Workspace/kernel/src/drivers/usb/dma.rs (line 37)
[function] fn drop(&mut self) {

```

```

kernel_Workspace/kernel/src/drivers/usb/host/xhci/context.rs (line 80)
[function] fn in_add_drop(&mut self, add: u32, drop: u32) {
kernel_Workspace/kernel/src/drivers/usb/host/xhci/context.rs (line 89)
[function] fn slot_ptr(&mut self) -> *mut u32 {
kernel_Workspace/kernel/src/drivers/usb/host/xhci/context.rs (line 93)
[function] fn ep0_ptr(&mut self) -> *mut u32 {
kernel_Workspace/kernel/src/drivers/usb/host/xhci/event.rs (line 5)
[function] fn kprintf(fmt: *const u8, ...);
kernel_Workspace/kernel/src/drivers/usb/host/xhci/init.rs (line 8)
[function] fn kprintf(fmt: *const u8, ...);
kernel_Workspace/kernel/src/drivers/usb/host/xhci/init.rs (line 27)
[function] fn spin_wait<F: Fn() -> bool>(f: F) -> Result<(), UsbError> {
kernel_Workspace/kernel/src/drivers/usb/host/xhci/init.rs (line 39)
[function] fn op_write64(regs: &XhciRegs, off: usize, v: u64) {
kernel_Workspace/kernel/src/drivers/usb/host/xhci/init.rs (line 173)
[function] fn attach_port(&mut self, p: u32) {
kernel_Workspace/kernel/src/drivers/usb/host/xhci/regs.rs (line 91)
[function] fn op(&self) -> *mut u8 {
kernel_Workspace/kernel/src/drivers/usb/host/xhci/regs.rs (line 95)
[function] fn rt(&self) -> *mut u8 {
kernel_Workspace/kernel/src/drivers/usb/host/xhci/regs.rs (line 99)
[function] fn db(&self) -> *mut u8 {
kernel_Workspace/kernel/src/driverspaceinit/abi/src.rs (line 16)
[function] fn hdr(&self) -> *mut DsRing {
kernel_Workspace/kernel/src/driverspaceinit/init/init.rs (line 20)
[function] fn kv(phys: u64) -> *mut u8 {
kernel_Workspace/kernel/src/driverspaceinit/init/service.rs (line 10)
[function] fn kprintf(fmt: *const u8, ...);
kernel_Workspace/kernel/src/driverspaceinit/init/service.rs (line 17)
[struct] struct Grant {
kernel_Workspace/kernel/src/driverspaceinit/init/service.rs (line 33)
[function] fn ac97Bars() -> (u64, u64) {
kernel_Workspace/kernel/src/driverspaceinit/init/service.rs (line 48)
[function] fn grant_add(va: u64, phys: u64, pages: u64, kind: u8) -> bool {
kernel_Workspace/kernel/src/driverspaceinit/init/service.rs (line 65)
[struct] struct Slot {
kernel_Workspace/kernel/src/driverspaceinit/init/service.rs (line 73)
[function] fn arch_phys_to_virt(phys: u64) -> *mut u8;
kernel_Workspace/kernel/src/driverspaceinit/init/service.rs (line 76)
[function] fn ring() -> Option<*mut Slot> {
kernel_Workspace/kernel/src/driverspaceinit/init/service.rs (line 222)
[function] fn grant_take(va: u64) -> Option<Grant> {
kernel_Workspace/kernel/src/driverspaceinit/init/service.rs (line 235)
[function] fn grant_phys(va: u64) -> Option<(u64, u64)> {
kernel_Workspace/kernel/src/driverspaceinit/init/service.rs (line 271)
[function] fn handle(m: &DsMsg, r: &mut DsMsg) -> i32 {
kernel_Workspace/kernel/src/ds_ipc/buffer.rs (line 45)
[function] fn from(e: BufferError) -> Self {

```

```

kernel_Workspace/kernel/src/ds_ipc/buffer.rs (line 231)
[function] fn can_do_zero_copy(&self) -> bool {
kernel_Workspace/kernel/src/ds_ipc/buffer.rs (line 243)
[function] fn transfer_via_registers(&mut self) -> Result<(), BufferError> {
kernel_Workspace/kernel/src/ds_ipc/buffer.rs (line 256)
[function] fn transfer_zero_copy(&mut self) -> Result<(), BufferError> {
kernel_Workspace/kernel/src/ds_ipc/buffer.rs (line 344)
[function] fn transfer_via_bounce(&mut self) -> Result<(), BufferError> {
kernel_Workspace/kernel/src/ds_ipc/buffer.rs (line 522)
[function] fn arch_flush_tlb_single(task_id: u64, vaddr: VirtAddr) {
kernel_Workspace/kernel/src/ds_ipc/buffer.rs (line 534)
[function] fn arch_clean_invalidate_dcache_region(vaddr: VirtAddr, size: u64) {
kernel_Workspace/kernel/src/ds_ipc/buffer.rs (line 609)
[function] fn test_buffer_alignment_check() {
kernel_Workspace/kernel/src/ds_ipc/endpoint.rs (line 14)
[struct] struct EndpointState {
kernel_Workspace/kernel/src/ds_ipc/syscall.rs (line 60)
[function] fn transfer_message(_target: *mut Task, _info: MessageInfo, _regs:
&MessageRegisters) {
kernel_Workspace/kernel/src/ds_ipc/syscall.rs (line 64)
[function] fn extract_message(_sender: *mut Task) -> IpcMessage {
kernel_Workspace/kernel/src/ds_ipc/syscall.rs (line 72)
[function] fn block_current_task() {}
kernel_Workspace/kernel/src/ds_ipc/syscall.rs (line 73)
[function] fn wake_task(_task: *mut Task) {}
kernel_Workspace/kernel/src/ds_ipc/syscall.rs (line 74)
[function] fn switch_context() {}
kernel_Workspace/kernel/src/fs/disc.rs (line 18)
[function] fn block_size(&self) -> u64;
kernel_Workspace/kernel/src/fs/disc.rs (line 20)
[function] fn read_block(&mut self, lba: u64, buf: &[u8]) -> Result<()>;
kernel_Workspace/kernel/src/fs/disc.rs (line 22)
[function] fn write_block(&mut self, lba: u64, buf: &mut [u8]) -> Result<()>{
kernel_Workspace/kernel/src/fs/disc.rs (line 27)
[function] fn flush(&mut self) -> Result<()> {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 58)
[function] fn drive_lba(&self) -> u8 {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 62)
[function] fn drive_identify(&self) -> u8 {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 70)
[function] fn disable_irq(&self) {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 74)
[function] fn status(&self) -> u8 {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 78)
[function] fn wait_not_bsy(&self) -> Result<(), DriverError> {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 88)
[function] fn wait_drq(&self) -> Result<(), DriverError> {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 104)
[function] fn wait_ready(&self) -> Result<(), DriverError> {

```

```

kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 116)
[function] fn setup_lba28(&self, lba: u32, count: u8, cmd: u8) -> Result<(),
DriverError> {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 162)
[function] fn read_sector(&self, lba: u32, buf: &mut [u8]) -> Result<(),
DriverError> {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 177)
[function] fn write_sector(&self, lba: u32, buf: &[u8]) -> Result<(), DriverError> {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 196)
[function] fn name(&self) -> &'static str {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 200)
[function] fn block_size(&self) -> usize {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 204)
[function] fn block_count(&self) -> u64 {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 208)
[function] fn read_block(&self, block: u64, buf: &mut [u8]) -> Result<(),
DriverError> {
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 224)
[function] fn write_block(&self, block: u64, buf: &[u8]) -> Result<(), DriverError>
{
kernel_Workspace/kernel/src/fs/driver/ata_pio.rs (line 241)
[function] fn probe_dev(dev: &AtaPio) -> bool {
kernel_Workspace/kernel/src/fs/driver/block.rs (line 12)
[function] fn name(&self) -> &'static str;
kernel_Workspace/kernel/src/fs/driver/block.rs (line 13)
[function] fn block_size(&self) -> usize;
kernel_Workspace/kernel/src/fs/driver/block.rs (line 14)
[function] fn block_count(&self) -> u64;
kernel_Workspace/kernel/src/fs/driver/block.rs (line 16)
[function] fn read_block(&self, block: u64, buf: &mut [u8]) -> Result<(),
DriverError>;
kernel_Workspace/kernel/src/fs/driver/block.rs (line 17)
[function] fn write_block(&self, block: u64, buf: &[u8]) -> Result<(), DriverError>;
kernel_Workspace/kernel/src/fs/driver/block.rs (line 19)
[function] fn read_blocks(&self, start: u64, buf: &mut [u8]) -> Result<(),
DriverError> {
kernel_Workspace/kernel/src/fs/driver/block.rs (line 36)
[function] fn write_blocks(&self, start: u64, buf: &[u8]) -> Result<(), DriverError>
{
kernel_Workspace/kernel/src/fs/driver/lock.rs (line 20)
[function] fn drop(&mut self) {
kernel_Workspace/kernel/src/fs/ext4/mod.rs (line 49)
[function] fn u16le(b: &[u8], o: usize) -> u16 {
kernel_Workspace/kernel/src/fs/ext4/mod.rs (line 53)
[function] fn u32le(b: &[u8], o: usize) -> u32 {
kernel_Workspace/kernel/src/fs/ext4/mod.rs (line 57)
[function] fn u64le(b: &[u8], o: usize) -> u64 {
kernel_Workspace/kernel/src/fs/ext4/mod.rs (line 107)
[function] fn read_at(disk: &'static dyn BlockDevice,

```

```

kernel_Workspace/kernel/src/fs/ext4/mod.rs (line 138)
[function] fn inode_table(&self, ino: u32) -> Result<u64, ExtError> {
kernel_Workspace/kernel/src/fs/ext4/mod.rs (line 173)
[function] fn block_map(&self, inode: &RawInode, file_blk: u32) -> Option<u64> {
kernel_Workspace/kernel/src/fs/fat32/mod.rs (line 30)
[function] fn u16le(b: &[u8], o: usize) -> u16 {
kernel_Workspace/kernel/src/fs/fat32/mod.rs (line 34)
[function] fn u32le(b: &[u8], o: usize) -> u32 {
kernel_Workspace/kernel/src/fs/fat32/mod.rs (line 65)
[function] fn read_at(&self, off: u64, buf: &mut [u8]) -> Result<(), FatError> {
kernel_Workspace/kernel/src/fs/fat32/mod.rs (line 85)
[function] fn cluster_off(&self, clus: u32) -> u64 {
kernel_Workspace/kernel/src/fs/fat32/mod.rs (line 89)
[function] fn read_cluster(&self, clus: u32) -> Result<Vec<u8>, FatError> {
kernel_Workspace/kernel/src/fs/fat32/mod.rs (line 95)
[function] fn next_cluster(&self, clus: u32) -> Option<u32> {
kernel_Workspace/kernel/src/fs/fat32/mod.rs (line 113)
[function] fn short_name(raw: &[u8]) -> Vec<u8> {
kernel_Workspace/kernel/src/fs/fat32/mod.rs (line 138)
[function] fn lfn_char(c: u16) -> u8 {
kernel_Workspace/kernel/src/fs/mbr.rs (line 5)
[function] fn kprintf(fmt: *const u8, ...);
kernel_Workspace/kernel/src/fs/mbr.rs (line 28)
[function] fn name(&self) -> &'static str {
kernel_Workspace/kernel/src/fs/mbr.rs (line 32)
[function] fn block_size(&self) -> usize {
kernel_Workspace/kernel/src/fs/mbr.rs (line 36)
[function] fn block_count(&self) -> u64 {
kernel_Workspace/kernel/src/fs/mbr.rs (line 40)
[function] fn read_block(&self, block: u64, buf: &mut [u8]) -> Result<(),
DriverError> {
kernel_Workspace/kernel/src/fs/mbr.rs (line 48)
[function] fn write_block(&self, block: u64, buf: &[u8]) -> Result<(), DriverError>
{
kernel_Workspace/kernel/src/fs/tangfs/btree.rs (line 46)
[function] fn search_leaf_node(node: &BTreeNode, name: &str) -> Result<u64> {
kernel_Workspace/kernel/src/fs/tangfs/btree.rs (line 67)
[function] fn find_child_in_internal(node: &BTreeNode, name: &str) -> Result<u64> {
kernel_Workspace/kernel/src/fs/tangfs/btree.rs (line 134)
[function] fn collect_leaf_entries(node: &BTreeNode, entries: &mut Vec<DirEntry>) ->
Result<()> {
kernel_Workspace/kernel/src/fs/tangfs/file.rs (line 85)
[function] fn allocate_block_for_inode(fs: &TangFs, inode: &mut Inode,
logical_block: u64) -> Result<u64> {
kernel_Workspace/kernel/src/fs/tangfs/inode.rs (line 41)
[function] fn load_inode(&self) -> Result<Inode> {
kernel_Workspace/kernel/src/fs/tangfs/inode.rs (line 55)
[function] fn save_inode(&self, inode: &Inode) -> Result<()> {
kernel_Workspace/kernel/src/fs/tangfs/inode.rs (line 76)
[function] fn lookup(&self, name: &str) -> Result<Box<dyn VfsInode>> {

```

```

kernel_Workspace/kernel/src/fs/tangfs/inode.rs (line 95)
[function] fn readdir(&self) -> Result<Vec<DirEntry>> {
kernel_Workspace/kernel/src/fs/tangfs/inode.rs (line 105)
[function] fn read(&self, offset: u64, buf: &mut [u8]) -> Result<usize> {
kernel_Workspace/kernel/src/fs/tangfs/inode.rs (line 109)
[function] fn write(&self, offset: u64, data: &[u8]) -> Result<usize> {
kernel_Workspace/kernel/src/fs/tangfs/inode.rs (line 116)
[function] fn stat(&self) -> Result<crate::fs::vfs::Stat> {
kernel_Workspace/kernel/src/fs/tangfs/mod.rs (line 81)
[function] fn root_inode(&self) -> Box<dyn VfsInode> {
kernel_Workspace/kernel/src/fs/tangfs/mod.rs (line 89)
[function] fn statfs(&self) -> Result<crate::fs::vfs::StatFs> {
kernel_Workspace/kernel/src/fs/tangfs/superblock.rs (line 55)
[function] fn calculate_checksum(sb: &Superblock) -> u32 {
kernel_Workspace/kernel/src/fs/tangfs/superblock.rs (line 89)
[function] fn clone(&self) -> Self {
kernel_Workspace/kernel/src/fs/tfs.rs (line 39)
[function] fn rd32(b: &[u8], off: usize) -> u32 {
kernel_Workspace/kernel/src/fs/tfs.rs (line 43)
[function] fn wr32(b: &mut [u8], off: usize, v: u32) {
kernel_Workspace/kernel/src/fs/tfs.rs (line 98)
[struct] struct DirEntry {
kernel_Workspace/kernel/src/fs/tfs.rs (line 112)
[function] fn read_entry(block: &[u8], idx: usize) -> DirEntry {
kernel_Workspace/kernel/src/fs/tfs.rs (line 124)
[function] fn write_entry(block: &mut [u8], idx: usize, e: &DirEntry) {
kernel_Workspace/kernel/src/fs/tfs.rs (line 132)
[function] fn entry_name(e: &DirEntry) -> &str {
kernel_Workspace/kernel/src/fs/tfs.rs (line 137)
[function] fn find_entry(dev: &dyn BlockDevice, dir: u32, name: &str) ->
Result<(usize, DirEntry)> {
kernel_Workspace/kernel/src/gdt.rs (line 18)
[struct] struct Selectors {
kernel_Workspace/kernel/src/gfx/console.rs (line 28)
[function] fn fb() -> &'static mut Framebuffer {
kernel_Workspace/kernel/src/gfx/console.rs (line 54)
[function] fn framebuffer_info() -> Option<(u32, u32, u32, u64, bool)> {
kernel_Workspace/kernel/src/gfx/console.rs (line 90)
[function] fn set_palette_rgb332() {
kernel_Workspace/kernel/src/gfx/console.rs (line 111)
[function] fn set_palette16() {
kernel_Workspace/kernel/src/gfx/console.rs (line 127)
[function] fn disable_text_cursor() {
kernel_Workspace/kernel/src/gfx/console.rs (line 139)
[function] fn delay() {
kernel_Workspace/kernel/src/gfx/console.rs (line 363)
[function] fn draw_cell(row: usize, col: usize, ch: u8, attr: u8) {
kernel_Workspace/kernel/src/gfx/framebuffer.rs (line 29)
[function] fn rgb332_index(r: u32, g: u32, b: u32) -> u8 {

```

```

kernel_Workspace/kernel/src/gfx/framebuffer.rs (line 33)
[function] fn rgb332_from_index(idx: u8) -> (u32, u32, u32) {
kernel_Workspace/kernel/src/gfx/framebuffer.rs (line 40)
[function] fn rgb_to_index4(r: u32, g: u32, b: u32) -> u8 {
kernel_Workspace/kernel/src/gfx/framebuffer.rs (line 56)
[function] fn index4_to_rgb(idx: u8) -> (u32, u32, u32) {
kernel_Workspace/kernel/src/gfx/framebuffer.rs (line 61)
[function] fn ry(&self, y: usize) -> usize {
kernel_Workspace/kernel/src/gfx/framebuffer.rs (line 65)
[function] fn rx(&self, x: usize) -> usize {
kernel_Workspace/kernel/src/gfx/framebuffer.rs (line 119)
[function] fn planar_set(&self, x: usize, y: usize, color: u8) {
kernel_Workspace/kernel/src/gfx/framebuffer.rs (line 134)
[function] fn planar_get(&self, x: usize, y: usize) -> u8 {
kernel_Workspace/kernel/src/gfx/galaxy.rs (line 6)
[function] fn hash2(x: i64, y: i64) -> u32 {
kernel_Workspace/kernel/src/gfx/galaxy.rs (line 14)
[function] fn vnoise(xq: i64, yq: i64) -> i64 {
kernel_Workspace/kernel/src/gfx/galaxy.rs (line 34)
[function] fn fbm(xq: i64, yq: i64) -> i64 {
kernel_Workspace/kernel/src/gfx/galaxy.rs (line 42)
[function] fn band_fall(x: i64, y: i64, w: i64, h: i64) -> i64 {
kernel_Workspace/kernel/src/gfx/galaxy.rs (line 60)
[function] fn green_fall(x: i64, y: i64, w: i64, _h: i64) -> i64 {
kernel_Workspace/kernel/src/gfx/galaxy.rs (line 83)
[function] fn px_add(fb: &mut Framebuffer, x: i64, y: i64,
kernel_Workspace/kernel/src/gfx/vga.rs (line 9)
[function] fn write_regs(misc: u8, seq: &[u8], crtc: &[u8], gfx: &[u8], attr: &[u8])
{
kernel_Workspace/kernel/src/gfx/vga.rs (line 91)
[function] fn dispi_write(index: u16, value: u16) {
kernel_Workspace/kernel/src/gfx/vga.rs (line 98)
[function] fn dispi_read(index: u16) -> u16 {
kernel_Workspace/kernel/src/hdmi/bridge.rs (line 5)
[function] fn hdmi_iface_acquire(owner: u32) -> bool;
kernel_Workspace/kernel/src/hdmi/bridge.rs (line 6)
[function] fn hdmi_iface_release(owner: u32) -> bool;
kernel_Workspace/kernel/src/hdmi/bridge.rs (line 8)
[function] fn hdmi_iface_init(owner: u32, fb_phys: u64, w: u32, h: u32, stride: u32)
-> bool;
kernel_Workspace/kernel/src/hdmi/bridge.rs (line 9)
[function] fn hdmi_iface_ready() -> bool;
kernel_Workspace/kernel/src/hdmi/bridge.rs (line 11)
[function] fn hdmi_iface_mode_set(owner: u32, id: u32) -> bool;
kernel_Workspace/kernel/src/hdmi/bridge.rs (line 12)
[function] fn hdmi_iface_mode_current(id: *mut u32, w: *mut u32, h: *mut u32, r: *mut
u32) -> bool;
kernel_Workspace/kernel/src/hdmi/bridge.rs (line 13)
[function] fn hdmi_iface_mode_at(i: u32, id: *mut u32, w: *mut u32, h: *mut u32, r:
*mut u32) -> bool;

```

```

kernel_Workspace/kernel/src/hdmi/bridge.rs (line 15)
[function] fn hdmi_iface_submit_fill(owner: u32, color: u32, x: u32, y: u32, w: u32,
h: u32) -> u64;
kernel_Workspace/kernel/src/hdmi/bridge.rs (line 16)
[function] fn hdmi_iface_poll(owner: u32, out: *mut u64) -> bool;
kernel_Workspace/kernel/src/hdmi/bridge.rs (line 18)
[function] fn hdmi_iface_caps(w: *mut u32, h: *mut u32, s: *mut u32, phys: *mut u64);
kernel_Workspace/kernel/src/hdmi/bridge.rs (line 20)
[function] fn hdmi_iface_fb_grant(owner: u32, phys: *mut u64, w: *mut u32, h: *mut
u32, s: *mut u32) -> bool;
kernel_Workspace/kernel/src/hdmi/bridge.rs (line 21)
[function] fn hdmi_iface_fb_revoke(owner: u32) -> bool;
kernel_Workspace/kernel/src/hdmi/init.rs (line 2)
[function] fn hdmi_init_with(fb_phys: u64, w: u32, h: u32, stride: u32) -> bool;
kernel_Workspace/kernel/src/hdmi/init.rs (line 3)
[function] fn hdmi_ready() -> bool;
kernel_Workspace/kernel/src/interrupts.rs (line 56)
[function] fn as_u8(self) -> u8 {
kernel_Workspace/kernel/src/interrupts.rs (line 61)
[function] fn breakpoint_handler(stack_frame: InterruptStackFrame) {
kernel_Workspace/kernel/src/kernel_glue.rs (line 3)
[function] fn cstr_to_str<'a>(p: *const u8) -> Option<&'a str> {
kernel_Workspace/kernel/src/kernel_glue.rs (line 96)
[function] fn tfs_read_path(dev: &dyn crate::fs::driver::block::BlockDevice, path:
&str) -> Option<alloc::vec::Vec<u8>> {
kernel_Workspace/kernel/src/kstd_glue.rs (line 3)
[function] fn cstr_to_str<'a>(p: *const u8) -> Option<&'a str> {
kernel_Workspace/kernel/src/main.rs (line 229)
[function] fn kernel_bin_entry(boot_info_ptr: *const u8) -> !;
kernel_Workspace/kernel/src/mm/init.rs (line 20)
[function] fn kv(phys: u64) -> *mut u8 {
kernel_Workspace/kernel/src/mm/mm_bridge.rs (line 33)
[function] fn arch_memory_init(
kernel_Workspace/kernel/src/mm/mm_bridge.rs (line 42)
[function] fn arch_memory_dump();
kernel_Workspace/kernel/src/mm/mod.rs (line 51)
[struct] struct EntryStorage(UnsafeCell<[ffi::RawMemEntry; MAX_RAW_ENTRIES]>);
kernel_Workspace/kernel/src/mm/riscv.rs (line 10)
[struct] struct FramePool([u8; FRAME_POOL_BYTES]);
kernel_Workspace/kernel/src/mm/riscv.rs (line 14)
[struct] struct State {
kernel_Workspace/kernel/src/mm/riscv.rs (line 24)
[function] fn pool_base() -> u64 {
kernel_Workspace/kernel/src/mm/riscv.rs (line 35)
[function] fn bit_set(b: &mut [u64; BITMAP_WORDS], idx: usize) {
kernel_Workspace/kernel/src/mm/riscv.rs (line 39)
[function] fn bit_clear(b: &mut [u64; BITMAP_WORDS], idx: usize) {
kernel_Workspace/kernel/src/mm/riscv.rs (line 43)
[function] fn bit_get(b: &[u64; BITMAP_WORDS], idx: usize) -> bool {

```

```

kernel_Workspace/kernel/src/mm/riscv.rs (line 66)
[function] fn scan_run(s: &mut State, count: usize, align_frames: usize) ->
Option<usize> {
kernel_Workspace/kernel/src/mm/riscv.rs (line 180)
[struct] struct HeapPool([u8; HEAP_BYTES]);
kernel_Workspace/kernel/src/mm/riscv.rs (line 184)
[struct] struct HeapState {
kernel_Workspace/kernel/src/mm/riscv.rs (line 190)
[function] fn pool_base() -> usize {
kernel_Workspace/kernel/src/mm/riscv.rs (line 224)
[function] fn push_free(s: &mut HeapState, block: usize) {
kernel_Workspace/kernel/src/mm/riscv.rs (line 231)
[function] fn raw_alloc(size: usize, align: usize) -> *mut u8 {
kernel_Workspace/kernel/src/mm/riscv.rs (line 438)
[function] fn bitor(self, rhs: VmmFlags) -> VmmFlags {
kernel_Workspace/kernel/src/mm/riscv.rs (line 452)
[struct] struct DeviceMap {
kernel_Workspace/kernel/src/mm/riscv.rs (line 458)
[struct] struct State {
kernel_Workspace/kernel/src/mm/riscv.rs (line 477)
[function] fn overlaps(s: &State, va: u64, len: u64) -> bool {
kernel_Workspace/kernel/src/mm/riscv.rs (line 483)
[function] fn take_range(s: &mut State, len: u64) -> Option<u64> {
kernel_Workspace/kernel/src/mm/riscv.rs (line 588)
[function] fn bitor(self, rhs: ProtFlags) -> ProtFlags {
kernel_Workspace/kernel/src/mm/riscv.rs (line 617)
[function] fn bitor(self, rhs: MapFlags) -> MapFlags {
kernel_Workspace/kernel/src/mm/riscv.rs (line 626)
[function] fn sfence_all() {
kernel_Workspace/kernel/src/mm/riscv.rs (line 632)
[function] fn pte_for_prot(prot: ProtFlags) -> u64 {
kernel_Workspace/kernel/src/mm/riscv.rs (line 650)
[struct] struct Range {
kernel_Workspace/kernel/src/mm/riscv.rs (line 656)
[struct] struct Inner {
kernel_Workspace/kernel/src/mm/riscv.rs (line 668)
[function] fn alloc_table() -> Option<usize> {
kernel_Workspace/kernel/src/mm/riscv.rs (line 695)
[function] fn ensure_table(entry: u64, tables: &mut Vec<u64>) -> Option<usize> {
kernel_Workspace/kernel/src/mm/riscv.rs (line 704)
[function] fn map_page(
kernel_Workspace/kernel/src/mm/riscv.rs (line 852)
[function] fn set_pte_flags(&self, va: u64, flags: u64) -> bool {
kernel_Workspace/kernel/src/mm/riscv.rs (line 891)
[function] fn unmap_page_root(root: usize, va: u64) -> bool {
kernel_Workspace/kernel/src/mm/riscv.rs (line 916)
[function] fn drop(&mut self) {
kernel_Workspace/kernel/src/mm/space.rs (line 26)
[function] fn bitor(self, rhs: ProtFlags) -> ProtFlags {

```

```

kernel_Workspace/kernel/src/mm/space.rs (line 55)
[function] fn bitor(self, rhs: MapFlags) -> MapFlags {
kernel_Workspace/kernel/src/mm/space.rs (line 121)
[function] fn drop(&mut self) {
kernel_Workspace/kernel/src/mm/virt.rs (line 24)
[function] fn bitor(self, rhs: VmmFlags) -> VmmFlags {
kernel_Workspace/kernel/src/nic/arp.rs (line 106)
[struct] struct CacheEntry {
kernel_Workspace/kernel/src/nic/arp.rs (line 173)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/nic/arp.rs (line 183)
[function] fn arp_round_trip_and_cache_expiry() {
kernel_Workspace/kernel/src/nic/checksum.rs (line 47)
[function] fn checksum_round_trip() {
kernel_Workspace/kernel/src/nic/command.rs (line 85)
[function] fn parse_octet(input: &str) -> Option<u8> {
kernel_Workspace/kernel/src/nic/command.rs (line 107)
[function] fn parses_ipv4() {
kernel_Workspace/kernel/src/nic/command.rs (line 112)
[function] fn rejects_invalid_ipv4() {
kernel_Workspace/kernel/src/nic/device.rs (line 29)
[function] fn init(&mut self) -> Result<(), NetworkError>;
kernel_Workspace/kernel/src/nic/device.rs (line 30)
[function] fn mac_address(&self) -> MacAddress;
kernel_Workspace/kernel/src/nic/device.rs (line 31)
[function] fn mtu(&self) -> usize;
kernel_Workspace/kernel/src/nic/device.rs (line 32)
[function] fn submit_tx(&mut self, frame: TxFrame<'_>) -> Result<(), NetworkError>;
kernel_Workspace/kernel/src/nic/device.rs (line 33)
[function] fn poll(&mut self) -> Result<PollResult, NetworkError>;
kernel_Workspace/kernel/src/nic/device.rs (line 34)
[function] fn take_rx(&mut self) -> Option<RxFrame<'_>>;
kernel_Workspace/kernel/src/nic/device.rs (line 35)
[function] fn recycle_rx(&mut self, buffer_id: u16) -> Result<(), NetworkError>;
kernel_Workspace/kernel/src/nic/driver.rs (line 41)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/nic/ethernet.rs (line 97)
[function] fn ethernet_round_trip_and_padding() {
kernel_Workspace/kernel/src/nic/icmp.rs (line 83)
[function] fn echo_request_and_reply_keep_identity_and_payload() {
kernel_Workspace/kernel/src/nic/ipv4.rs (line 105)
[function] fn ipv4_build_then_parse() {
kernel_Workspace/kernel/src/nic/packet.rs (line 69)
[function] fn self_test_passes() {
kernel_Workspace/kernel/src/nic/ping.rs (line 82)
[function] fn send_pending(
kernel_Workspace/kernel/src/nic/ping.rs (line 115)
[function] fn map_packet_error(error: PacketError) -> NetworkError {

```

```

kernel_Workspace/kernel/src/nic/runtime.rs (line 23)
[struct] struct NetworkRuntime {
kernel_Workspace/kernel/src/nic/runtime.rs (line 67)
[function] fn legacy_virtio_device() -> Option<PciDevice> {
kernel_Workspace/kernel/src/nic/stack.rs (line 149)
[function] fn process_arp(
kernel_Workspace/kernel/src/nic/stack.rs (line 182)
[function] fn process_ipv4(&mut self, frame: EthernetFrame<'_>) ->
Result<StackEvent, PacketError> {
kernel_Workspace/kernel/src/nic/stack.rs (line 215)
[function] fn stack() -> NetworkStack<4> {
kernel_Workspace/kernel/src/nic/stack.rs (line 226)
[function] fn outside_subnet_uses_gateway() {
kernel_Workspace/kernel/src/nic/stack.rs (line 232)
[function] fn arp_request_and_ping_are_ethernet_padded() {
kernel_Workspace/kernel/src/nic/types.rs (line 38)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
kernel_Workspace/kernel/src/nic/types.rs (line 82)
[function] fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
kernel_Workspace/kernel/src/nic/types.rs (line 92)
[function] fn subnet_check_uses_mask() {
kernel_Workspace/kernel/src/nic/virtio/device.rs (line 12)
[function] fn mac_address(&self) -> MacAddress;
kernel_Workspace/kernel/src/nic/virtio/device.rs (line 13)
[function] fn mtu(&self) -> usize;
kernel_Workspace/kernel/src/nic/virtio/device.rs (line 14)
[function] fn capabilities(&self) -> Capabilities;
kernel_Workspace/kernel/src/nic/virtio/device.rs (line 15)
[function] fn transmit(&mut self, packet: &[u8]) -> Result<(), NetworkError>;
kernel_Workspace/kernel/src/nic/virtio/device.rs (line 16)
[function] fn receive(&mut self) -> Option<&[u8]>;
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 58)
[struct] struct LegacyQueue {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 75)
[function] fn allocate(size: u16) -> Result<Self, NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 101)
[function] fn descriptor_offset(&self, index: u16) -> usize {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 105)
[function] fn avail_offset(&self) -> usize {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 109)
[function] fn used_offset(&self) -> usize {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 164)
[struct] struct UsedElement {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 200)
[function] fn initialize(&mut self) -> Result<(), NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 246)
[function] fn configure_queue(&mut self, index: u16, queue: LegacyQueue) ->
Result<(), NetworkError> {

```

```

kernel_Workspace/kernel/src/nic/virtio/net.rs (line 260)
[function] fn post_rx(&mut self, index: u16) -> Result<(), NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 282)
[function] fn reclaim_tx(&mut self) -> u16 {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 291)
[function] fn notify(&self, queue: u16) {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 295)
[function] fn fail(&mut self) {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 300)
[function] fn mmio_read(&self, offset: usize) -> u32 {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 304)
[function] fn mmio_write(&self, offset: usize, value: u32) {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 312)
[function] fn init(&mut self) -> Result<(), NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 316)
[function] fn mac_address(&self) -> MacAddress {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 320)
[function] fn mtu(&self) -> usize {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 324)
[function] fn submit_tx(&mut self, frame: TxFrame<'_>) -> Result<(), NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 358)
[function] fn poll(&mut self) -> Result<PollResult, NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 375)
[function] fn take_rx(&mut self) -> Option<RxFrame<'_>> {
kernel_Workspace/kernel/src/nic/virtio/net.rs (line 393)
[function] fn recycle_rx(&mut self, buffer_id: u16) -> Result<(), NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 38)
[struct] struct VirtioNetHeader {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 48)
[struct] struct LegacyQueue {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 65)
[function] fn allocate(size: u16) -> Result<Self, NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 91)
[function] fn descriptor_offset(&self, index: u16) -> usize {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 95)
[function] fn avail_offset(&self) -> usize {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 99)
[function] fn used_offset(&self) -> usize {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 154)
[struct] struct UsedElement {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 192)
[function] fn initialize(&mut self) -> Result<(), NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 233)
[function] fn configure_queue(&mut self, index: u16, queue: LegacyQueue) ->
Result<(), NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 245)
[function] fn post_rx(&mut self, index: u16) -> Result<(), NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 267)
[function] fn reclaim_tx(&mut self) -> u16 {

```

```

kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 276)
[function] fn notify(&self, queue: u16) {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 280)
[function] fn fail(&mut self) {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 285)
[function] fn read_u8(&self, offset: u16) -> u8 {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 290)
[function] fn read_u16(&self, offset: u16) -> u16 {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 295)
[function] fn read_u32(&self, offset: u16) -> u32 {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 300)
[function] fn write_u8(&self, offset: u16, value: u8) {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 307)
[function] fn write_u16(&self, offset: u16, value: u16) {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 314)
[function] fn write_u32(&self, offset: u16, value: u32) {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 323)
[function] fn init(&mut self) -> Result<(), NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 327)
[function] fn mac_address(&self) -> MacAddress {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 331)
[function] fn mtu(&self) -> usize {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 335)
[function] fn submit_tx(&mut self, frame: TxFrame<'_>) -> Result<(), NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 369)
[function] fn poll(&mut self) -> Result<PollResult, NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 383)
[function] fn take_rx(&mut self) -> Option<RxFrame<'_>> {
kernel_Workspace/kernel/src/nic/virtio/pci_legacy.rs (line 401)
[function] fn recycle_rx(&mut self, buffer_id: u16) -> Result<(), NetworkError> {
kernel_Workspace/kernel/src/nic/virtio/queue.rs (line 135)
[function] fn default() -> Self {
kernel_Workspace/kernel/src/nic/virtio/queue.rs (line 173)
[function] fn pool_allocates_and_releases_chain_once() {
kernel_Workspace/kernel/src/nic/virtio/queue.rs (line 186)
[function] fn zero_sized_pool_fails_cleanly() {
kernel_Workspace/kernel/src/nic/virtio/transport.rs (line 12)
[function] fn reset(&mut self) -> Result<(), NetworkError>;
kernel_Workspace/kernel/src/nic/virtio/transport.rs (line 13)
[function] fn status(&self) -> u8;
kernel_Workspace/kernel/src/nic/virtio/transport.rs (line 14)
[function] fn set_status(&mut self, status: u8);
kernel_Workspace/kernel/src/nic/virtio/transport.rs (line 16)
[function] fn device_features(&self) -> u64;
kernel_Workspace/kernel/src/nic/virtio/transport.rs (line 17)
[function] fn set_driver_features(&mut self, features: u64);
kernel_Workspace/kernel/src/nic/virtio/transport.rs (line 19)
[function] fn queue_max_size(&self, queue_index: u16) -> u16;

```

```

kernel_Workspace/kernel/src/nic/virtio/transport.rs (line 20)
[function] fn configure_queue(&mut self, queue_index: u16, setup: QueueSetup) ->
Result<(), NetworkError>;
kernel_Workspace/kernel/src/nic/virtio/transport.rs (line 22)
[function] fn notify_queue(&mut self, queue_index: u16);
kernel_Workspace/kernel/src/nic/virtio/transport.rs (line 24)
[function] fn read_config(&self, offset: u16, out: &mut [u8]) -> Result<(),
NetworkError>;
kernel_Workspace/kernel/src/nimcore.rs (line 2)
[function] fn nim_u64_to_str(v: u64, base: u8, buf: *mut u8, cap: u32) -> u32;
kernel_Workspace/kernel/src/nimcore.rs (line 3)
[function] fn nim_parse_u64(s: *const u8, len: u32, base: u8, out: *mut u64) -> u8;
kernel_Workspace/kernel/src/nimcore.rs (line 4)
[function] fn nim_rb_push(b: u8) -> u8;
kernel_Workspace/kernel/src/nimcore.rs (line 5)
[function] fn nim_rb_pop() -> i32;
kernel_Workspace/kernel/src/nimcore.rs (line 6)
[function] fn nim_shell_register(name: *const u8, nlen: u32,
kernel_Workspace/kernel/src/nimcore.rs (line 8)
[function] fn nim_shell_run(line: *const u8, len: u32) -> i32;
kernel_Workspace/kernel/src/nimcore.rs (line 9)
[function] fn nim_banner(buf: *mut u8, cap: u32) -> u32;
kernel_Workspace/kernel/src/pci.rs (line 28)
[function] fn config_address(addr: PciAddress, offset: u8) -> u32 {
kernel_Workspace/kernel/src/pci.rs (line 66)
[function] fn probe_function(bus: u8, device: u8, function: u8) -> Option<PciDevice>
{
kernel_Workspace/kernel/src/policy/bridge.rs (line 2)
[function] fn policy_evaluate(ring: u8, cls: u8, op: u8, arg: u64) -> u8;
kernel_Workspace/kernel/src/policy/bridge.rs (line 3)
[function] fn nim_policy_log(ring: u8, cls: u8, op: u8, dec: u8);
kernel_Workspace/kernel/src/policy/mod.rs (line 68)
[struct] struct LogInner {
kernel_Workspace/kernel/src/process/fd.rs (line 32)
[function] fn kprintf(fmt: *const u8, ...);
kernel_Workspace/kernel/src/process/fd.rs (line 35)
[function] fn pool_take() -> Option<i16> {
kernel_Workspace/kernel/src/process/fd.rs (line 48)
[function] fn pool_drop(slot: i16) {
kernel_Workspace/kernel/src/serial.rs (line 27)
[function] fn tx_empty() -> bool {
kernel_Workspace/kernel/src/serial.rs (line 50)
[function] fn tx_empty() -> bool {
kernel_Workspace/kernel/src/serial.rs (line 83)
[function] fn write_str(&mut self, s: &str) -> fmt::Result {
kernel_Workspace/kernel/src/terminal/mod.rs (line 7)
[function] fn editor_run(path: *const u8) -> i32;
kernel_Workspace/kernel/src/terminal/mod.rs (line 24)
[function] fn kbuf_push(c: u8) {

```

```

kernel_Workspace/kernel/src/terminal/mod.rs (line 34)
[function] fn kbuf_pop() -> Option<u8> {
kernel_Workspace/kernel/src/terminal/mod.rs (line 45)
[function] fn scancode_to_char(code: u8) -> Option<char> {
kernel_Workspace/kernel/src/terminal/mod.rs (line 133)
[function] fn scancode_to_keycode(code: u8) -> Option<u32> {
kernel_Workspace/kernel/src/terminal/mod.rs (line 152)
[function] fn keycode_push(k: u32) {
kernel_Workspace/kernel/src/terminal/mod.rs (line 195)
[function] fn line_as_str(buf: &mut [u8]) -> &str {
kernel_Workspace/kernel/src/terminal/mod.rs (line 203)
[function] fn line_clear() {
kernel_Workspace/kernel/src/terminal/mod.rs (line 207)
[function] fn draw_prompt() {
kernel_Workspace/kernel/src/terminal/mod.rs (line 226)
[function] fn redraw_line() {
kernel_Workspace/kernel/src/terminal/mod.rs (line 247)
[function] fn handle_char(c: char) {
kernel_Workspace/kernel/src/terminal/mod.rs (line 296)
[function] fn split_once_space(s: &str) -> (&str, &str) {
kernel_Workspace/kernel/src/terminal/mod.rs (line 304)
[function] fn parse_resolution(s: &str) -> Option<(u32, u32)> {
kernel_Workspace/kernel/src/terminal/mod.rs (line 315)
[function] fn dev() -> Option<&'static dyn BlockDevice> {
kernel_Workspace/kernel/src/terminal/mod.rs (line 319)
[function] fn execute(line: &str) {
kernel_Workspace/kernel/src/terminal/mod.rs (line 528)
[function] fn print_ping_result(result: crate::nic::PingResult) {
kernel_Workspace/kernel/src/terminal/mod.rs (line 544)
[function] fn poll_network() {
kernel_Workspace/kernel/src/terminal/mod.rs (line 553)
[struct] struct Sink;
kernel_Workspace/kernel/src/terminal/mod.rs (line 556)
[function] fn write_str(&mut self, s: &str) -> core::fmt::Result {
kernel_Workspace/kernel/src/trampoline_rings/arch/aarch64/trampoline_rings.rs (line 23)
[function] fn tr_init();
kernel_Workspace/kernel/src/trampoline_rings/arch/aarch64/trampoline_rings.rs (line 68)
[function] fn write_ttbr0(v: u64) {
kernel_Workspace/kernel/src/trampoline_rings/arch/aarch64/trampoline_rings.rs (line 74)
[function] fn pick_next(from: Option<usize>) -> usize {
kernel_Workspace/kernel/src/trampoline_rings/arch/risc-v/trampoline_rings.rs (line 25)
[function] fn tr_init(kernel_stack_top: u64);
kernel_Workspace/kernel/src/trampoline_rings/arch/risc-v/trampoline_rings.rs (line 73)
[function] fn write_satp(v: u64) {
kernel_Workspace/kernel/src/trampoline_rings/arch/risc-v/trampoline_rings.rs (line 79)
[function] fn pick_next(from: Option<usize>) -> usize {
kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.rs (line 29)
[function] fn tr_init(rsp0: u64);

```

```

kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.rs (line 37)
[struct] struct IdtGate {
kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.rs (line 51)
[function] fn set_gate(i: usize, handler: u64, dpl: u8) {
kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.rs (line 80)
[function] fn sel_for(ring: u8) -> (u64, u64) {
kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.rs (line 122)
[struct] struct IdtPtr {
kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.rs (line 154)
[function] fn write_cr3(v: u64) {
kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.rs (line 158)
[function] fn pick_next(from: Option<usize>) -> usize {
kernel_Workspace/kernel/src/trampoline_rings/arch/x86_64/trampoline_rings.rs (line 227)
[function] fn ctx_mut(&mut self) -> &mut CpuCtx {
kernel_Workspace/kernel/src/userspace/process/runc1.rs (line 2)
[function] fn k_fs_read(path: *const u8, buf: *mut u8, cap: u32) -> i32;
kernel_Workspace/kernel/src/userspace/process/runc1.rs (line 4)
[function] fn cl_compile_source(src: *const u8, len: usize, ar: *mut u8,
kernel_Workspace/kernel/src/userspace/process/runc1.rs (line 8)
[function] fn cl_vm_init(vm: *mut u8, prog: *mut u8);
kernel_Workspace/kernel/src/userspace/process/runc1.rs (line 9)
[function] fn cl_bridge_init(vm: *mut u8, ring: u8) -> i32;
kernel_Workspace/kernel/src/userspace/process/runc1.rs (line 10)
[function] fn cl_vm_run(vm: *mut u8) -> i32;
kernel_Workspace/kernel/src/userspace/process/runc1.rs (line 16)
[struct] struct ArenaBuf([u8; 196608]);
kernel_Workspace/kernel/src/userspace/process/runc1.rs (line 20)
[struct] struct ProgBuf([u8; 65536]);
kernel_Workspace/kernel/src/userspace/process/runc1.rs (line 24)
[struct] struct VmBuf([u8; 98304]);
kernel_Workspace/kernel/src/userspace/process/syscall.rs (line 17)
[function] fn paging_translate_in(pml4: u64, virt: u64) -> u64;
kernel_Workspace/kernel/src/userspace/process/syscall.rs (line 18)
[function] fn kprintf(fmt: *const u8, ...);
kernel_Workspace/kernel/src/userspace/process/syscall.rs (line 23)
[function] fn user_copy_in(cr3: u64, src: u64, dst: &mut [u8]) -> bool {
kernel_Workspace/kernel/src/userspace/process/syscall.rs (line 50)
[function] fn user_cstr(cr3: u64, ptr: u64, buf: &mut [u8]) -> Option<&str> {
kernel_Workspace/kernel/src/userspace/process/syscall.rs (line 70)
[function] fn do_spawn(cr3: u64, path_ptr: u64, parent_pid: u32) -> i64 {
kernel_Workspace/kernel/src/userspace/process/syscall.rs (line 207)
[function] fn hdmi_caps_raw(w: *mut u32, h: *mut u32,
kernel_Workspace/kernel/src/userspace/process/syscall.rs (line 209)
[function] fn kvirt_to_phys(p: *const u8) -> u64;
kernel_Workspace/kernel/src/userspace/process/syscall.rs (line 210)
[function] fn paging_map_page_in(pml4: u64, virt: u64,
kernel_Workspace/kernel/src/vga_buffer.rs (line 34)
[struct] struct ColorCode(u8);

```

```

kernel_Workspace/kernel/src/vga_buffer.rs (line 37)
[function] fn new(foreground: Color, background: Color) -> ColorCode {
kernel_Workspace/kernel/src/vga_buffer.rs (line 44)
[struct] struct ScreenChar {
kernel_Workspace/kernel/src/vga_buffer.rs (line 53)
[struct] struct Buffer {
kernel_Workspace/kernel/src/vga_buffer.rs (line 83)
[function] fn new_line(&mut self) {
kernel_Workspace/kernel/src/vga_buffer.rs (line 94)
[function] fn clear_row(&mut self, row: usize) {
kernel_Workspace/kernel/src/vga_buffer.rs (line 153)
[function] fn write_str(&mut self, s: &str) -> fmt::Result {
kernel_Workspace/lib/tg-ipc-dispatch/src/router.rs (line 7)
[function] fn handle_data(&mut self, hdr: &MsgHeader, payload: &[u8]) -> Result<(),
IpError>;
kernel_Workspace/lib/tg-ipc-dispatch/src/router.rs (line 8)
[function] fn handle_request(&mut self, hdr: &MsgHeader, payload: &[u8]) ->
Result<(), IpError>;
kernel_Workspace/lib/tg-ipc-dispatch/src/router.rs (line 9)
[function] fn handle_notification(&mut self, hdr: &MsgHeader, payload: &[u8]) ->
Result<(), IpError>;
kernel_Workspace/lib/tg-ipc-dispatch/src/router.rs (line 45)
[function] fn handle_cap_transfer(
kernel_Workspace/lib/tg-ipc-ring/src/spsc.rs (line 36)
[function] fn cap(&self) -> u64 {
kernel_Workspace/lib/tg-ipc-ring/src/spsc.rs (line 41)
[function] fn head(&self) -> u64 {
kernel_Workspace/lib/tg-ipc-ring/src/spsc.rs (line 46)
[function] fn tail(&self) -> u64 {
mp4_to_bmp/src/main.rs (line 23)
[function] fn main() {
mp4_to_bmp/src/main.rs (line 30)
[function] fn run() -> Result<(), String> {
mp4_to_bmp/src/main.rs (line 103)
[function] fn check_tool(name: &str) -> Result<(), String> {
mp4_to_bmp/src/main.rs (line 114)
[function] fn probe_resolution(input: &str) -> Result<(usize, usize), String> {
mp4_to_bmp/src/main.rs (line 152)
[function] fn read_exact_or_eof<R: Read>(reader: &mut R, buf: &mut [u8]) ->
Result<bool, String> {
mp4_to_bmp/src/main.rs (line 173)
[function] fn write_bmp(path: &str, pixels: &[u8], width: usize, height: usize) ->
std::io::Result<()> {
net/lib/net-buffer/src/lib.rs (line 10)
[function] fn it_works() {
net/lib/net-core/src/lib.rs (line 10)
[function] fn it_works() {
net/lib/net-types/src/lib.rs (line 10)
[function] fn it_works() {

```

```
server_workspace/c/c-bridge/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/compute/dag-exec/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/compute/jit-compiler/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/compute/wasm-runtime/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/core/core-alloc/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/core/core-crypto/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/core/core-ffi/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/core/core-io/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/core/core-math/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/core/core-sync/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/core/core-telemetry/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/domain/auth-core/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/domain/catalog-core/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/domain/graph-core/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/domain/identity-core/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/domain/ledger-core/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/domain/orders-core/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/domain/ts-core/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/net/dns-resolver/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/net/proto-grpc/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/net/proto-rpc/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/net/stack-http3/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/net/stack-quick/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/net/stack-tcp/src/lib.rs (line 10)
[function] fn it_works() {
```

```

server_workspace/net/stack-udp/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/storage/store-btree/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/storage/store-disk/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/storage/store-lsm/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/storage/store-page/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/storage/store-wal/src/lib.rs (line 10)
[function] fn it_works() {
server_workspace/svc/svc-api/src/main.rs (line 1)
[function] fn main() {
server_workspace/svc/svc-gateway/src/main.rs (line 1)
[function] fn main() {
server_workspace/svc/svc-ingest/src/main.rs (line 1)
[function] fn main() {
server_workspace/svc/svc-query/src/main.rs (line 1)
[function] fn main() {
server_workspace/svc/svc-sync/src/main.rs (line 1)
[function] fn main() {
server_workspace/tools/tool-bench/src/main.rs (line 1)
[function] fn main() {
server_workspace/tools/tool-codegen/src/main.rs (line 1)
[function] fn main() {
server_workspace/tools/tool-migrator/src/main.rs (line 1)
[function] fn main() {
trangorgelibc/src/lib.rs (line 31)
[function] fn sc0(n: u64) -> u64 {
trangorgelibc/src/lib.rs (line 38)
[function] fn sc1(n: u64, a0: u64) -> u64 {
trangorgelibc/src/lib.rs (line 45)
[function] fn sc3(n: u64, a0: u64, a1: u64, a2: u64) -> u64 {
trangorgelibc/src/lib.rs (line 58)
[function] fn cstr(s: &str) -> ([u8; 256], usize) {
triang-lang/src/codegen/asm.rs (line 8)
[struct] struct Emitter {
triang-lang/src/codegen/asm.rs (line 14)
[function] fn label(&mut self, tag: &str) -> String {
triang-lang/src/codegen/asm.rs (line 19)
[function] fn line(&mut self, s: &str) {
triang-lang/src/codegen/asm.rs (line 26)
[function] fn op(t: &Target, v: &Val) -> String {
triang-lang/src/codegen/asm.rs (line 33)
[function] fn mem_len(ir: &[Ir], name: &str) -> u64 {
triang-lang/src/codegen/c.rs (line 4)
[struct] struct FnChunk {

```

```

triang-lang/src/codegen/c.rs (line 11)
[function] fn val(v: &Val) -> String {
triang-lang/src/codegen/c.rs (line 18)
[function] fn binop(op: BinOp) -> &'static str {
triang-lang/src/codegen/c.rs (line 30)
[function] fn cmpop(op: CmpOp) -> &'static str {
triang-lang/src/codegen/c.rs (line 37)
[function] fn is_param(name: &str, args: usize) -> bool {
triang-lang/src/codegen/c.rs (line 47)
[function] fn split(ir: &[Ir]) -> Vec<FnChunk> {
triang-lang/src/ir.rs (line 58)
[function] fn label(&mut self, tag: &str) -> String {
triang-lang/src/ir.rs (line 70)
[function] fn lower_function(&mut self, f: &Function) {
triang-lang/src/ir.rs (line 83)
[function] fn lower_stmt(&mut self, s: &Stmt) {
triang-lang/src/ir.rs (line 143)
[function] fn lower_op(&mut self, call: &OpCall) {
triang-lang/src/ir.rs (line 263)
[function] fn val(e: &Expr) -> Val {
triang-lang/src/ir.rs (line 271)
[function] fn invert(op: CmpOp) -> CmpOp {
triang-lang/src/ir.rs (line 278)
[function] fn binop(s: &str) -> BinOp {
triang-lang/src/iso.rs (line 8)
[function] fn dstring(s: &str, len: usize) -> Vec<u8> {
triang-lang/src/iso.rs (line 18)
[function] fn push_both_u16(out: &mut Vec<u8>, v: u16) {
triang-lang/src/iso.rs (line 23)
[function] fn push_both_u32(out: &mut Vec<u8>, v: u32) {
triang-lang/src/iso.rs (line 28)
[function] fn put_both_u16(buf: &mut [u8], off: usize, v: u16) {
triang-lang/src/iso.rs (line 33)
[function] fn put_both_u32(buf: &mut [u8], off: usize, v: u32) {
triang-lang/src/iso.rs (line 38)
[function] fn dir_record(name: &[u8], extent: u32, size: u32, flags: u8) -> Vec<u8> {
triang-lang/src/lexer.rs (line 28)
[function] fn peek(&self) -> Option<char> {
triang-lang/src/lexer.rs (line 32)
[function] fn peek2(&self) -> Option<char> {
triang-lang/src/lexer.rs (line 36)
[function] fn bump(&mut self) -> Option<char> {
triang-lang/src/lexer.rs (line 98)
[function] fn skip_ws_and_comments(&mut self) {
triang-lang/src/lexer.rs (line 114)
[function] fn read_number(&mut self) -> Result<TokenKind, LexError> {
triang-lang/src/lexer.rs (line 161)
[function] fn read_ident(&mut self) -> TokenKind {

```

```

triang-lang/src/lexer.rs (line 192)
[function] fn is_ident_start(c: char) -> bool {
triang-lang/src/lexer.rs (line 196)
[function] fn is_ident_cont(c: char) -> bool {
triang-lang/src/main.rs (line 18)
[function] fn main() {
triang-lang/src/main.rs (line 29)
[function] fn read_libs(dir: &str) -> Vec<String> {
triang-lang/src/main.rs (line 50)
[function] fn pipeline(srcs: &[String]) -> Vec<ir::Ir> {
triang-lang/src/main.rs (line 83)
[function] fn cmd_new(args: &[String]) {
triang-lang/src/main.rs (line 114)
[function] fn cmd_build(args: &[String]) {
triang-lang/src/main.rs (line 178)
[function] fn cmd_file(args: &[String]) {
triang-lang/src/main.rs (line 256)
[function] fn cmd_iso(_args: &[String]) {
triang-lang/src/main.rs (line 288)
[function] fn route_c(ir: &[ir::Ir], text_path: &str, elf_path: &str, bin_path:
&str, want_elf: bool, want_bin: bool) {
triang-lang/src/main.rs (line 309)
[function] fn route_asm(
triang-lang/src/main.rs (line 357)
[function] fn run_objcopy(elf: &str, bin: &str) -> bool {
triang-lang/src/parser.rs (line 21)
[function] fn cur(&self) -> &Token {
triang-lang/src/parser.rs (line 25)
[function] fn kind(&self) -> TokenKind {
triang-lang/src/parser.rs (line 29)
[function] fn at(&self, kind: &TokenKind) -> bool {
triang-lang/src/parser.rs (line 33)
[function] fn bump(&mut self) -> TokenKind {
triang-lang/src/parser.rs (line 41)
[function] fn err(&self, msg: String) -> ParseError {
triang-lang/src/parser.rs (line 49)
[function] fn expect(&mut self, want: TokenKind) -> Result<TokenKind, ParseError> {
triang-lang/src/parser.rs (line 57)
[function] fn expect_ident(&mut self) -> Result<String, ParseError> {
triang-lang/src/parser.rs (line 64)
[function] fn expect_int(&mut self) -> Result<u64, ParseError> {
triang-lang/src/parser.rs (line 79)
[function] fn parse_function(&mut self) -> Result<Function, ParseError> {
triang-lang/src/parser.rs (line 111)
[function] fn parse_block(&mut self) -> Result<Vec<Stmt>, ParseError> {
triang-lang/src/parser.rs (line 120)
[function] fn parse_stmt(&mut self) -> Result<Stmt, ParseError> {
triang-lang/src/parser.rs (line 134)
[function] fn parse_type(&mut self) -> Result<Type, ParseError> {

```

```

triang-lang/src/parser.rs (line 148)
[function] fn parse_layout(&mut self) -> Result<Layout, ParseError> {
triang-lang/src/parser.rs (line 160)
[function] fn parse_const(&mut self) -> Result<Stmt, ParseError> {
triang-lang/src/parser.rs (line 169)
[function] fn parse_static(&mut self) -> Result<Stmt, ParseError> {
triang-lang/src/parser.rs (line 187)
[function] fn parse_reg(&mut self) -> Result<Stmt, ParseError> {
triang-lang/src/parser.rs (line 195)
[function] fn parse_mem(&mut self) -> Result<Stmt, ParseError> {
triang-lang/src/parser.rs (line 207)
[function] fn parse_target(&mut self) -> Result<Target, ParseError> {
triang-lang/src/parser.rs (line 219)
[function] fn parse_op_call(&mut self) -> Result<OpCall, ParseError> {
triang-lang/src/parser.rs (line 224)
[function] fn parse_op_suffix(&mut self, target: Target) -> Result<OpCall,
ParseError> {
triang-lang/src/parser.rs (line 239)
[function] fn parse_op_stmt(&mut self) -> Result<Stmt, ParseError> {
triang-lang/src/parser.rs (line 245)
[function] fn parse_expr(&mut self) -> Result<Expr, ParseError> {
triang-lang/src/parser.rs (line 266)
[function] fn parse_cond(&mut self) -> Result<Cond, ParseError> {
triang-lang/src/parser.rs (line 277)
[function] fn parse_if(&mut self) -> Result<Stmt, ParseError> {
triang-lang/src/parser.rs (line 294)
[function] fn parse_while(&mut self) -> Result<Stmt, ParseError> {
triang-lang/src/parser.rs (line 305)
[function] fn parse_return(&mut self) -> Result<Stmt, ParseError> {
triang-lang/src/project.rs (line 19)
[function] fn parse(text: &str) -> Project {
triang-lang/src/sema.rs (line 28)
[function] fn err(&self, msg: String) -> SemaError {
triang-lang/src/sema.rs (line 43)
[function] fn check_function(&mut self, f: &Function) -> Result<(), SemaError> {
triang-lang/src/sema.rs (line 62)
[function] fn declare(&mut self, name: &str, sym: Symbol) -> Result<(), SemaError> {
triang-lang/src/sema.rs (line 70)
[function] fn check_stmt(&mut self, s: &Stmt) -> Result<(), SemaError> {
triang-lang/src/sema.rs (line 104)
[function] fn check_cond(&self, cond: &Cond) -> Result<(), SemaError> {
triang-lang/src/sema.rs (line 109)
[function] fn check_operand(&self, e: &Expr) -> Result<(), SemaError> {
triang-lang/src/sema.rs (line 125)
[function] fn check_mem_access(&self, name: &str, idx: u64) -> Result<(), SemaError>
{
triang-lang/src/sema.rs (line 141)
[function] fn expect_arity(&self, call: &OpCall, n: usize) -> Result<(), SemaError>
{

```

triang-lang/src/sema.rs (line 149)

```
[function] fn check_op(&self, call: &OpCall) -> Result<(), SemaError> {
```

userspace_workspace/base_apps/file_manager/src/main.rs (line 1)

```
[function] fn main() {
```

userspace_workspace/base_apps/settings_app/src/main.rs (line 1)

```
[function] fn main() {
```

userspace_workspace/base_apps/shell/src/main.rs (line 1)

```
[function] fn main() {
```

userspace_workspace/base_apps/system_monitor/src/main.rs (line 1)

```
[function] fn main() {
```

userspace_workspace/base_apps/terminal/src/main.rs (line 1)

```
[function] fn main() {
```

userspace_workspace/base_apps/text_editor/src/main.rs (line 1)

```
[function] fn main() {
```

userspace_workspace/build_tools/os_build_utils/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/crates/error_codes/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/crates/hal_types/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/crates/kernel_abi/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/crates/logging/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/crates/memory/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/crates/sync/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/ipc/ipc_channel/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/ipc/ipc_core/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/ipc/ipc_router/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/ipc/ipc_serde/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/libs/c_shim/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/libs/odin_runtime_shim/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/libs/vise_lg/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/libs/vise_lg_sys/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/protocols/audio_protocol/src/lib.rs (line 10)

```
[function] fn it_works() {
```

userspace_workspace/protocols/gfx_protocol/src/lib.rs (line 10)

```
[function] fn it_works() {
```

```

userspace_workspace/protocols/input_protocol/src/lib.rs (line 10)
[function] fn it_works() {
userspace_workspace/protocols/net_protocol/src/lib.rs (line 10)
[function] fn it_works() {
userspace_workspace/protocols/vfs_protocol/src/lib.rs (line 10)
[function] fn it_works() {
userspace_workspace/services/audio_server/src/lib.rs (line 10)
[function] fn it_works() {
userspace_workspace/services/compositor/src/lib.rs (line 10)
[function] fn it_works() {
userspace_workspace/services/display_server/src/lib.rs (line 10)
[function] fn it_works() {
userspace_workspace/services/init/src/lib.rs (line 10)
[function] fn it_works() {
userspace_workspace/services/input_server/src/lib.rs (line 10)
[function] fn it_works() {
userspace_workspace/services/logger_daemon/src/lib.rs (line 10)
[function] fn it_works() {
userspace_workspace/services/network_manager/src/lib.rs (line 10)
[function] fn it_works() {
userspace_workspace/services/session_manager/src/lib.rs (line 10)
[function] fn it_works() {
userspace_workspace/services/vfs_server/src/lib.rs (line 10)
[function] fn it_works() {
vise_lg_workspace/lang/vise-codegen/src/main.rs (line 1)
[function] fn main() {
vise_lg_workspace/lang/vise-lexer/src/lib.rs (line 165)
[function] fn advance(&mut self) {
vise_lg_workspace/lang/vise-lexer/src/lib.rs (line 178)
[function] fn eat(&mut self, expected: u8) -> bool {
vise_lg_workspace/lang/vise-lexer/src/lib.rs (line 188)
[function] fn skip_whitespace(&mut self) {
vise_lg_workspace/lang/vise-lexer/src/lib.rs (line 215)
[function] fn lex_string(&mut self) -> TokenKind {
vise_lg_workspace/lang/vise-lexer/src/lib.rs (line 229)
[function] fn lex_number(&mut self) -> TokenKind {
vise_lg_workspace/lang/vise-lexer/src/lib.rs (line 255)
[function] fn lex_identifier(&mut self) -> TokenKind {
vise_lg_workspace/lang/vise-lexer/src/lib.rs (line 317)
[function] fn current_span(&self) -> Span {
vise_lg_workspace/lang/vise-optimizer/src/main.rs (line 1)
[function] fn main() {
vise_lg_workspace/lang/vise-parser/src/parser.rs (line 36)
[function] fn parse_top_level(&mut self) -> Option<TopLevel> {
vise_lg_workspace/lang/vise-parser/src/parser.rs (line 46)
[function] fn parse_function(&mut self) -> Option<Function> {
vise_lg_workspace/lang/vise-parser/src/parser.rs (line 93)
[function] fn parse_struct(&mut self) -> Option<StructDef> {

```

```

viselg_workspace/lang/viselg-parser/src/parser.rs (line 113)
[function] fn parse_enum(&mut self) -> Option<EnumDef> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 134)
[function] fn parse_static(&mut self) -> Option<StaticData> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 149)
[function] fn parse_block(&mut self) -> Option<Vec<Stmt>> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 165)
[function] fn parse_stmt(&mut self) -> Option<Stmt> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 188)
[function] fn parse_let(&mut self) -> Option<Stmt> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 208)
[function] fn parse_if(&mut self) -> Option<Stmt> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 232)
[function] fn parse_when(&mut self) -> Option<Stmt> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 252)
[function] fn parse_expr(&mut self) -> Option<Expr> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 256)
[function] fn parse_assignment(&mut self) -> Option<Expr> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 271)
[function] fn parse_or(&mut self) -> Option<Expr> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 286)
[function] fn parse_and(&mut self) -> Option<Expr> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 301)
[function] fn parse_equality(&mut self) -> Option<Expr> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 322)
[function] fn parse_comparison(&mut self) -> Option<Expr> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 345)
[function] fn parse_addition(&mut self) -> Option<Expr> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 366)
[function] fn parse_multiplication(&mut self) -> Option<Expr> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 388)
[function] fn parse_unary(&mut self) -> Option<Expr> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 405)
[function] fn parse_postfix(&mut self) -> Option<Expr> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 446)
[function] fn parse_primary(&mut self) -> Option<Expr> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 476)
[function] fn parse_type(&mut self) -> Option<Type> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 508)
[function] fn peek(&self) -> Option<&Token> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 512)
[function] fn advance(&mut self) -> Option<&Token> {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 519)
[function] fn check(&self, kind: TokenKind) -> bool {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 523)
[function] fn match_token(&mut self, kind: TokenKind) -> bool {
viselg_workspace/lang/viselg-parser/src/parser.rs (line 532)
[function] fn expect(&mut self, kind: TokenKind) -> Option<&Token> {

```

```
viselg_workspace/lang/vise-parser/src/parser.rs (line 540)
[function] fn expect_ident(&mut self) -> Option<String> {
viselg_workspace/lang/vise-parser/src/parser.rs (line 551)
[function] fn expect_number(&mut self) -> Option<i64> {
viselg_workspace/lang/vise-parser/src/parser.rs (line 562)
[function] fn is_at_end(&self) -> bool {
viselg_workspace/lang/vise-sema/src/sema.rs (line 39)
[function] fn declare_top(&mut self, item: &TopLevel) {
viselg_workspace/lang/vise-sema/src/sema.rs (line 68)
[function] fn check_top(&mut self, item: &TopLevel) {
viselg_workspace/lang/vise-sema/src/sema.rs (line 101)
[function] fn check_stmt(&mut self, stmt: &Stmt) {
viselg_workspace/lang/vise-sema/src/sema.rs (line 155)
[function] fn check_expr(&mut self, expr: &Expr) -> CType {
viselg_workspace/runtime/vise-api/src/lib.rs (line 76)
[function] fn compile_shader(stage: ShaderStage, source: &[u8]) -> Option<Vec<u8>> {
viselg_workspace/runtime/vise-device/src/lib.rs (line 10)
[function] fn it_works() {
viselg_workspace/runtime/vise-pipeline/src/lib.rs (line 10)
[function] fn it_works() {
viselg_workspace/tools/vise-compiler/src/main.rs (line 5)
[function] fn main() {
viselg_workspace/tools/vise-compiler/src/main.rs (line 37)
[function] fn compile(source: &str) -> Option<Vec<u8>> {
viselg_workspace/tools/vise-inspector/src/main.rs (line 1)
[function] fn main() {
```