

# Customizable Sidebar Labels

---

Super Admins can rename the sidebar navigation items shown in **both** access levels — the Super Admin portal ( `/admin` ) and the Tenant Admin portal ( `/app` ) — without changing any routes. Only the visible label text changes.

## How it works

---

- Each nav item has a **stable key** (e.g. `dashboard` , `tenants` , `settings` , `sidebar` for admin; `dashboard` , `modules` , `team` for tenant) plus an overridable display label. Defaults mirror the built-in labels.
- Overrides are stored as a **non-secret** JSON platform setting ( `sidebar_labels` ) via the existing `settings_service` / `PlatformSetting` pattern — **not encrypted**. No schema change / migration is required.
- Clearing a field (or setting it back to the default) removes the override, so that item falls back to its default label.

## Editing

---

Open **Sidebar Labels** in the Super Admin sidebar ( `/admin/settings/sidebar` ). Labels are grouped by access level, each field shows its default as placeholder and a per-field **Reset** control, and a single **Save Labels** button persists all changes.

## Backend

---

- `services/settings_service.py` — `DEFAULT_SIDEBAR_LABELS` , `get_sidebar_labels(db, level=None)` (defaults merged with overrides) and `set_sidebar_labels(db, overrides)` (stores only non-default values; writes `{}` so a full reset persists).
- `schemas/settings.py` — `SidebarLabelsConfig` , `SidebarLabelsUpdate` .
- `api/v1/admin.py` :
- `GET /api/v1/admin/settings/sidebar` — SA-protected, full effective config.
- `PUT /api/v1/admin/settings/sidebar` — SA-protected, save overrides.
- `GET /api/v1/admin/sidebar-labels` — **public**, lightweight (labels only, no secrets) so each shell can fetch its effective labels without SA auth.

## Frontend

---

- `lib/api.ts` — `getSidebarLabels` , `updateSidebarLabels` (SA) and `getPublicSidebarLabels` (public).
- `app/admin/settings/sidebar/page.tsx` — the editor page.
- `components/admin/AdminShell.tsx` and `components/tenant/TenantShell.tsx` fetch the public labels and render nav using overrides, **falling back to defaults** while loading or if the fetch fails so navigation never breaks.