# Chapter 18

# STROBE — observational studies

*R. Heller · Date: 2026-05-08 · Last changed: 2026-10-30*

STROBE — *Strengthening the Reporting of Observational Studies in Epidemiology* — covers cohort, case-control, and cross-sectional studies. The 22-item checklist is at https://www.strobe-statement.org/. The templates below cover the analytic methods you are most likely to use in a STROBE-aligned paper.

This page contains **186 method-specific templates**. Each is a skeleton with placeholders in italics; the prose is written so you can paste it into a manuscript and replace only the bracketed values.

### 18.0.1 2^k Factorial Designs

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **2^k Factorial Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> 2^k Factorial Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `factorial-2k` — For Reviewers

### 18.0.2 3^k Factorial Designs

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **3^k Factorial Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> 3^k Factorial Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `factorial-3k` — For Reviewers

### 18.0.3 Accelerated Failure Time Models

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Accelerated Failure Time Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Accelerated Failure Time Models yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `accelerated-failure-time` — For Reviewers

### 18.0.4 Added-Variable Plots

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Added-Variable Plots** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Added-Variable Plots yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `added-variable-plots` — For Reviewers

### 18.0.5 Anderson-Darling Test

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Anderson-Darling Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Anderson-Darling Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `anderson-darling-test` — For Reviewers

### 18.0.6 Balanced Incomplete Block Designs

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Balanced Incomplete Block Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Balanced Incomplete Block Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `balanced-incomplete-block` — For Reviewers

### 18.0.7 Bartlett's Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Bartlett's Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Bartlett's Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `bartlett-test` — For Reviewers

### 18.0.8 Benjamini-Hochberg FDR

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Benjamini-Hochberg FDR** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Benjamini-Hochberg FDR yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `benjamini-hochberg-fdr` — For Reviewers

### 18.0.9 Benjamini-Yekutieli FDR

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Benjamini-Yekutieli FDR** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Benjamini-Yekutieli FDR yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `benjamini-yekutieli` — For Reviewers

### 18.0.10 Best Subset Selection

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Best Subset Selection** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Best Subset Selection yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `best-subset-selection` — For Reviewers

### 18.0.11 Beta Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Beta Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Beta Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `beta-regression` — For Reviewers

### 18.0.12 Bonferroni Correction

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Bonferroni Correction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Bonferroni Correction yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `bonferroni-correction` — For Reviewers

### 18.0.13 Bootstrap Confidence Intervals

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Bootstrap Confidence Intervals** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Bootstrap Confidence Intervals yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `bootstrap-confidence-intervals` — For Reviewers

### 18.0.14 Box-Behnken Designs

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Box-Behnken Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Box-Behnken Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `box-behnken-design` — For Reviewers

### 18.0.15 Censoring Types

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Censoring Types** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Censoring Types yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `censoring-types` — For Reviewers

### 18.0.16 Central Composite Designs

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Central Composite Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Central Composite Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `central-composite-design` — For Reviewers

### 18.0.17 Centring and Scaling Predictors

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Centring and Scaling Predictors** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Centring and Scaling Predictors yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `centered-scaled-predictors` — For Reviewers

### 18.0.18 Checking Cox Assumptions

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Checking Cox Assumptions** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Checking Cox Assumptions yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `cox-assumptions-check` — For Reviewers

### 18.0.19 Chi-Squared Goodness-of-Fit Test

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Chi-Squared Goodness-of-Fit Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Chi-Squared Goodness-of-Fit Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `chi-squared-goodness-of-fit` — For Reviewers

### 18.0.20 Chi-Squared Test of Independence

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Chi-Squared Test of Independence** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Chi-Squared Test of Independence yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `chi-squared-independence` — For Reviewers

### 18.0.21 Cochran-Mantel-Haenszel Test

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Cochran-Mantel-Haenszel Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Cochran-Mantel-Haenszel Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `cochran-mantel-haenszel` — For Reviewers

### 18.0.22 Competing Risks: Cumulative Incidence

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Competing Risks: Cumulative Incidence** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Competing Risks: Cumulative Incidence yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `competing-risks-cif` — For Reviewers

### 18.0.23 Completely Randomised Design

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Completely Randomised Design** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Completely Randomised Design yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `completely-randomized-design` — For Reviewers

### 18.0.24 Concordance and the C-Index

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Concordance and the C-Index** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Concordance and the C-Index yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `concordance-c-index` — For Reviewers

### 18.0.25 Conditional Survival

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Conditional Survival** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Conditional Survival yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `conditional-survival` — For Reviewers

### 18.0.26 Constrained Mixture Designs

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Constrained Mixture Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Constrained Mixture Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `constrained-mixture` — For Reviewers

### 18.0.27 Contrasts in R

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Contrasts in R** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Contrasts in R yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `contrasts-in-r` — For Reviewers

### 18.0.28 Cook's Distance

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Cook's Distance** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Cook's Distance yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `cooks-distance` — For Reviewers

### 18.0.29 Cox Proportional Hazards Regression

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Cox Proportional Hazards Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Cox Proportional Hazards Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `cox-proportional-hazards` — For Reviewers

### 18.0.30 Cox Regression as Regression

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Cox Regression as Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Cox Regression as Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `survival-regression-cox` — For Reviewers

### 18.0.31 Crossover Designs

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Crossover Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions

were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Crossover Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `crossover-designs` — For Reviewers

### 18.0.32 Desirability Functions

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Desirability Functions** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Desirability Functions yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `desirability-function` — For Reviewers

### 18.0.33 Dirichlet Regression

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Dirichlet Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Dirichlet Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `dirichlet-regression` — For Reviewers

### 18.0.34 Dummy Coding

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Dummy Coding** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Dummy Coding yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `dummy-coding` — For Reviewers

### 18.0.35 Effect (Deviation) Coding

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Effect (Deviation) Coding** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Effect (Deviation) Coding yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `effect-coding` — For Reviewers

### 18.0.36 Effect Size: Cohen's d

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Effect Size: Cohen's d** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Effect Size: Cohen's d yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `effect-size-cohens-d` — For Reviewers

### 18.0.37 Effect Size: Cohen's h

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Effect Size: Cohen's h** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Effect Size: Cohen's h yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `effect-size-cohens-h` — For Reviewers

### 18.0.38 Effect Size: Eta-Squared

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Effect Size: Eta-Squared** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Effect Size: Eta-Squared yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `effect-size-eta-squared` — For Reviewers

### 18.0.39 Effect Sizes: Overview

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Effect Sizes: Overview** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Effect Sizes: Overview yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `effect-sizes-overview` — For Reviewers

### 18.0.40 Elastic Net

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Elastic Net** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha$ = *0.05*; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Elastic Net yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `elastic-net` — For Reviewers

### 18.0.41 Equivalence Testing with TOST

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Equivalence Testing with TOST** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha$ = *0.05*; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Equivalence Testing with TOST yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `equivalence-tost` — For Reviewers

### 18.0.42 Fine-Gray Subdistribution Hazards

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Fine-Gray Subdistribution Hazards** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect*

*size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Fine-Gray Subdistribution Hazards yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `fine-gray-regression` — For Reviewers

### 18.0.43 Fisher's Exact Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Fisher's Exact Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Fisher's Exact Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `fisher-exact-test` — For Reviewers

### 18.0.44 Fractional Factorial Designs

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Fractional Factorial Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Fractional Factorial Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `fractional-factorial-design` — For Reviewers

### 18.0.45 Frailty Models

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Frailty Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Frailty Models yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `frailty-models` — For Reviewers

### 18.0.46 Friedman Test

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Friedman Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Friedman Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `friedman-test` — For Reviewers

### 18.0.47 GAMMs: Additive Mixed Models

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **GAMMs: Additive Mixed Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> GAMMs: Additive Mixed Models yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `gamm-additive-mixed` — For Reviewers

### 18.0.48 GAMs: Introduction

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **GAMs: Introduction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> GAMs: Introduction yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `gam-introduction` — For Reviewers

### 18.0.49 Generalised Estimating Equations

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Generalised Estimating Equations** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Generalised Estimating Equations yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `generalized-estimating-equations` — For Reviewers

### 18.0.50 glmer: Generalised Mixed Models

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **glmer: Generalised Mixed Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> glmer: Generalised Mixed Models yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `glmer-generalized-mixed` — For Reviewers

### 18.0.51 Graeco-Latin Square Designs

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Graeco-Latin Square Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Graeco-Latin Square Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `graeco-latin-square` — For Reviewers

### 18.0.52 Hazard, Survival, and Cumulative Hazard

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Hazard, Survival, and Cumulative Hazard** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Hazard, Survival, and Cumulative Hazard yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `hazard-survival-cumulative` — For Reviewers

### 18.0.53 Holm's Step-Down Correction

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Holm's Step-Down Correction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Holm's Step-Down Correction yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `holm-correction` — For Reviewers

### 18.0.54 Hurdle Models

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Hurdle Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Hurdle Models yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `hurdle-models` — For Reviewers

### 18.0.55 Interactions in Regression

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Interactions in Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Interactions in Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `interactions-in-regression` — For Reviewers

### 18.0.56 Interval-Censored Data

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Interval-Censored Data** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Interval-Censored Data yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `interval-censored-data` — For Reviewers

### 18.0.57 Joint Longitudinal-Survival Models

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Joint Longitudinal-Survival Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Joint Longitudinal-Survival Models yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `joint-longitudinal-survival` — For Reviewers

### 18.0.58 Kaplan-Meier Estimation

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Kaplan-Meier Estimation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Kaplan-Meier Estimation yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `kaplan-meier` — For Reviewers

### 18.0.59 Kendall's Tau

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Kendall's Tau** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha$ = *0.05*; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Kendall's Tau yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `kendall-tau` — For Reviewers

### 18.0.60 Kolmogorov-Smirnov Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Kolmogorov-Smirnov Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha$ = *0.05*; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Kolmogorov-Smirnov Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `kolmogorov-smirnov-test` — For Reviewers

### 18.0.61 Kruskal-Wallis Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Kruskal-Wallis Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].*

Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Kruskal-Wallis Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `kruskal-wallis` — For Reviewers

### 18.0.62 Landmark Analysis

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Landmark Analysis** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Landmark Analysis yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `landmark-analysis` — For Reviewers

### 18.0.63 Lasso Regression

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Lasso Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Lasso Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `lasso-regression` — For Reviewers

### 18.0.64 Latin Square Designs

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Latin Square Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Latin Square Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `latin-square` — For Reviewers

### 18.0.65 Left Truncation

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Left Truncation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Left Truncation yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `left-truncation` — For Reviewers

### 18.0.66 Levene's Test of Variances

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Levene's Test of Variances** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Levene's Test of Variances yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `levene-test` — For Reviewers

### 18.0.67 Leverage and Influence

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Leverage and Influence** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Leverage and Influence yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `leverage-influence` — For Reviewers

### 18.0.68 Linear Regression Assumptions

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Linear Regression Assumptions** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Linear Regression Assumptions yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `regression-assumptions` — For Reviewers

### 18.0.69 Log-Rank Test: Details

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Log-Rank Test: Details** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Log-Rank Test: Details yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `log-rank-test-details` — For Reviewers

### 18.0.70 Logistic Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Logistic Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Logistic Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `logistic-regression` — For Reviewers

### 18.0.71 Logistic Regression Diagnostics

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Logistic Regression Diagnostics** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Logistic Regression Diagnostics yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `logistic-regression-diagnostics` — For Reviewers

### 18.0.72 Mann-Whitney U Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Mann-Whitney U Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Mann-Whitney U Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `mann-whitney-u` — For Reviewers

### 18.0.73 McNemar's Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **McNemar's Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

McNemar's Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `mcnemar-test` — For Reviewers

### 18.0.74 Method of Steepest Ascent

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Method of Steepest Ascent** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Method of Steepest Ascent yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `steepest-ascent` — For Reviewers

### 18.0.75 Minimum Detectable Effect

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Minimum Detectable Effect** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Minimum Detectable Effect yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `minimum-detectable-effect` — For Reviewers

### 18.0.76 Mixed ANOVA

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Mixed ANOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Mixed ANOVA yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `mixed-anova` — For Reviewers

### 18.0.77 Mixed-Effects Models: Introduction

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Mixed-Effects Models: Introduction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Mixed-Effects Models: Introduction yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `mixed-models-intro` — For Reviewers

### 18.0.78 Model Selection with AIC and BIC

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Model Selection with AIC and BIC** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Model Selection with AIC and BIC yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `model-selection-aic-bic` — For Reviewers

### 18.0.79 Multi-State Models

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Multi-State Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Multi-State Models yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `multi-state-models` — For Reviewers

### 18.0.80 Multicollinearity and VIF

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Multicollinearity and VIF** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Multicollinearity and VIF yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `multicollinearity-vif` — For Reviewers

### 18.0.81 Multinomial Logistic Regression

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Multinomial Logistic Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Multinomial Logistic Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `multinomial-logistic` — For Reviewers

### 18.0.82 Multiple Comparisons: Overview

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Multiple Comparisons: Overview** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Multiple Comparisons: Overview yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `multiple-comparisons-overview` — For Reviewers

### 18.0.83 Multiple Linear Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Multiple Linear Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Multiple Linear Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `multiple-linear-regression` — For Reviewers

### 18.0.84 Negative Binomial Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Negative Binomial Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Negative Binomial Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `negative-binomial-regression` — For Reviewers

### 18.0.85 Nested vs Crossed Random Effects

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Nested vs Crossed Random Effects** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Nested vs Crossed Random Effects yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `nested-crossed-random-effects` — For Reviewers

### 18.0.86 Null and Alternative Hypotheses

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Null and Alternative Hypotheses** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Null and Alternative Hypotheses yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `null-alternative-hypotheses` — For Reviewers

### 18.0.87 Offsets in Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Offsets in Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Offsets in Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `offsets-in-regression` — For Reviewers

### 18.0.88 One-Proportion Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **One-Proportion Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

One-Proportion Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `one-proportion-test` — For Reviewers

### 18.0.89 One-Sample t-Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **One-Sample t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

One-Sample t-Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `one-sample-t-test` — For Reviewers

### 18.0.90 One-Sample z-Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **One-Sample z-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

One-Sample z-Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `one-sample-z-test` — For Reviewers

### 18.0.91 One-Way ANOVA

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **One-Way ANOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> One-Way ANOVA yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `one-way-anova` — For Reviewers

### 18.0.92 Optimal Designs: D, A, I

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Optimal Designs: D, A, I** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Optimal Designs: D, A, I yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `optimal-design-d-a-i` — For Reviewers

### 18.0.93 Ordinal Logistic Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Ordinal Logistic Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Ordinal Logistic Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `ordinal-logistic` — For Reviewers

### 18.0.94 Orthogonal Arrays

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Orthogonal Arrays** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Orthogonal Arrays yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `orthogonal-arrays` — For Reviewers

### 18.0.95 P-Values Explained

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **P-Values Explained** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

P-Values Explained yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `p-values-explained` — For Reviewers

### 18.0.96 Paired t-Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Paired t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence*

*interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Paired t-Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `paired-t-test` — For Reviewers

### 18.0.97 Parametric Survival: Log-Normal

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Parametric Survival: Log-Normal** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Parametric Survival: Log-Normal yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `parametric-survival-lognormal` — For Reviewers

### 18.0.98 Parametric Survival: Weibull

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Parametric Survival: Weibull** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Parametric Survival: Weibull yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `parametric-survival-weibull` — For Reviewers

### 18.0.99 Partial Correlation

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Partial Correlation** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Partial Correlation yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `partial-correlation` — For Reviewers

### 18.0.100 Pearson Correlation Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Pearson Correlation Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Pearson Correlation Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `pearson-correlation-test` — For Reviewers

### 18.0.101 Permutation Tests

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Permutation Tests** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Permutation Tests yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `permutation-tests` — For Reviewers

### 18.0.102 Plackett-Burman Designs

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Plackett-Burman Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Plackett-Burman Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `plackett-burman` — For Reviewers

### 18.0.103 Poisson Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Poisson Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Poisson Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `poisson-regression` — For Reviewers

### 18.0.104 Polynomial Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Polynomial Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Polynomial Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `polynomial-regression` — For Reviewers

### 18.0.105 Post-Hoc Power: A Controversy

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Post-Hoc Power: A Controversy** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Post-Hoc Power: A Controversy yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `post-hoc-power-controversy` — For Reviewers

### 18.0.106 Post-Hoc Tests with Tukey HSD

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Post-Hoc Tests with Tukey HSD** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Post-Hoc Tests with Tukey HSD yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `post-hoc-tests-tukey` — For Reviewers

### 18.0.107 Power Analysis for DOE

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power Analysis for DOE** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Power Analysis for DOE yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `power-in-doe` — For Reviewers

### 18.0.108 Power Analysis: Introduction

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power Analysis: Introduction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Power Analysis: Introduction yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `power-analysis-introduction` — For Reviewers

### 18.0.109 Power for Agreement (Kappa)

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for Agreement (Kappa)** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Power for Agreement (Kappa) yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `power-agreement-kappa` — For Reviewers

### 18.0.110 Power for Bland-Altman Studies

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for Bland-Altman Studies** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Power for Bland-Altman Studies yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `power-bland-altman` — For Reviewers

### 18.0.111 Power for Chi-Squared Tests

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for Chi-Squared Tests** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Power for Chi-Squared Tests yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `power-chi-squared` — For Reviewers

### 18.0.112 Power for Cluster-RCT

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Power for Cluster-RCT** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Power for Cluster-RCT yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `power-cluster-rct` — For Reviewers

### 18.0.113 Power for Correlation Tests

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Power for Correlation Tests** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Power for Correlation Tests yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `power-correlation` — For Reviewers

### 18.0.114 Power for Cox Regression

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Power for Cox Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Power for Cox Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `power-cox-regression` — For Reviewers

### 18.0.115 Power for Crossover Trials

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for Crossover Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Power for Crossover Trials yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `power-crossover` — For Reviewers

### 18.0.116 Power for Diagnostic Accuracy

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for Diagnostic Accuracy** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Power for Diagnostic Accuracy yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `power-diagnostic-accuracy` — For Reviewers

### 18.0.117 Power for Equivalence (TOST)

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for Equivalence (TOST)** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Power for Equivalence (TOST) yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `power-equivalence-tost` — For Reviewers

### 18.0.118 Power for ICC

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for ICC** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Power for ICC yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `power-icc` — For Reviewers

### 18.0.119 Power for Linear Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for Linear Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Power for Linear Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `power-linear-regression` — For Reviewers

### 18.0.120 Power for Logistic Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for Logistic Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*.

Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Power for Logistic Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `power-logistic-regression` — For Reviewers

### 18.0.121 Power for McNemar's Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Power for McNemar's Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Power for McNemar's Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `power-mcnemar` — For Reviewers

### 18.0.122 Power for Non-Inferiority Trials

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Power for Non-Inferiority Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Power for Non-Inferiority Trials yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `power-non-inferiority` — For Reviewers

### 18.0.123 Power for One-Proportion Test

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for One-Proportion Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Power for One-Proportion Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `power-one-proportion` — For Reviewers

### 18.0.124 Power for One-Sample t-Test

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for One-Sample t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Power for One-Sample t-Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `power-one-sample-t` — For Reviewers

### 18.0.125 Power for One-Way ANOVA

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for One-Way ANOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Power for One-Way ANOVA yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `power-anova` — For Reviewers

### 18.0.126 Power for Paired t-Test

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for Paired t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Power for Paired t-Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `power-paired-t` — For Reviewers

### 18.0.127 Power for Repeated-Measures ANOVA

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Power for Repeated-Measures ANOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Power for Repeated-Measures ANOVA yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `power-repeated-measures` — For Reviewers

### 18.0.128 Power for Stepped-Wedge Trials

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Power for Stepped-Wedge Trials** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Power for Stepped-Wedge Trials yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `power-stepped-wedge` — For Reviewers

### 18.0.129 Power for the Log-Rank Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Power for the Log-Rank Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Power for the Log-Rank Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `power-logrank-test` — For Reviewers

### 18.0.130 Power for Two-Proportion Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Power for Two-Proportion Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Power for Two-Proportion Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `power-two-proportions` — For Reviewers

### 18.0.131 Principles of Blocking

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Principles of Blocking** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Principles of Blocking yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `blocking-principles` — For Reviewers

### 18.0.132 Probit Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Probit Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Probit Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `probit-regression` — For Reviewers

### 18.0.133 Quantile Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Quantile Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Quantile Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `quantile-regression` — For Reviewers

### 18.0.134 Quasi-Poisson Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Quasi-Poisson Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Quasi-Poisson Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `quasi-poisson` — For Reviewers

### 18.0.135 R-Squared and Adjusted R-Squared

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **R-Squared and Adjusted R-Squared** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> R-Squared and Adjusted R-Squared yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `r-squared-adjusted` — For Reviewers

### 18.0.136 Random-Intercept Models

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Random-Intercept Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Random-Intercept Models yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `random-intercepts` — For Reviewers

### 18.0.137 Random-Slope Models

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Random-Slope Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Random-Slope Models yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `random-slopes` — For Reviewers

### 18.0.138 Randomisation in Design

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Randomisation in Design** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Randomisation in Design yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `randomization-in-design` — For Reviewers

### 18.0.139 Randomised Complete Block Design

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Randomised Complete Block Design** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Randomised Complete Block Design yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `randomised-complete-block` — For Reviewers

### 18.0.140 Recurrent Events

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Recurrent Events** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Recurrent Events yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `recurrent-events` — For Reviewers

### 18.0.141 Repeated-Measures ANOVA

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Repeated-Measures ANOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Repeated-Measures ANOVA yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `repeated-measures-anova` — For Reviewers

### 18.0.142 Repeated-Measures Designs

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Repeated-Measures Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Repeated-Measures Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `repeated-measures-design` — For Reviewers

### 18.0.143 Residual Diagnostics

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Residual Diagnostics** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Residual Diagnostics yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `residual-diagnostics` — For Reviewers

### 18.0.144 Resolution and Aliasing

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Resolution and Aliasing** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Resolution and Aliasing yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `resolution-aliasing` — For Reviewers

### 18.0.145 Response Surface Methodology

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Response Surface Methodology** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Response Surface Methodology yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `response-surface-methodology` — For Reviewers

### 18.0.146 Restricted Mean Survival Time (RMST)

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Restricted Mean Survival Time (RMST)** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Restricted Mean Survival Time (RMST) yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `restricted-mean-survival-time` — For Reviewers

### 18.0.147 Ridge Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Ridge Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Ridge Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `ridge-regression` — For Reviewers

### 18.0.148 Robust Parameter Design

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Robust Parameter Design** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Robust Parameter Design yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `robust-parameter-design` — For Reviewers

### 18.0.149 Robust Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Robust Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Robust Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `robust-regression` — For Reviewers

### 18.0.150 ROC and AUC for Logistic Models

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **ROC and AUC for Logistic Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> ROC and AUC for Logistic Models yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `roc-auc-for-logistic` — For Reviewers

### 18.0.151 Royston-Parmar Flexible Parametric Models

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Royston-Parmar Flexible Parametric Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Royston-Parmar Flexible Parametric Models yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `flexible-parametric-royston-parmar` — For Reviewers

### 18.0.152 Sample Size for a Two-Sample t-Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Sample Size for a Two-Sample t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Sample Size for a Two-Sample t-Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `power-two-sample-t` — For Reviewers

### 18.0.153 Sample Size Sensitivity Analysis

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Sample Size Sensitivity Analysis** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Sample Size Sensitivity Analysis yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `sensitivity-analysis-sample-size` — For Reviewers

### 18.0.154 Schoenfeld Residuals

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Schoenfeld Residuals** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Schoenfeld Residuals yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `schoenfeld-residuals` — For Reviewers

### 18.0.155 Shapiro-Wilk Normality Test

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Shapiro-Wilk Normality Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Shapiro-Wilk Normality Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `shapiro-wilk-test` — For Reviewers

### 18.0.156 Signal-to-Noise Ratios

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Signal-to-Noise Ratios** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Signal-to-Noise Ratios yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `signal-to-noise-ratio` — For Reviewers

### 18.0.157 Simple Linear Regression

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Simple Linear Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Simple Linear Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `simple-linear-regression` — For Reviewers

### 18.0.158 Simplex Centroid Designs

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Simplex Centroid Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Simplex Centroid Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `mixture-centroid` — For Reviewers

### 18.0.159 Simplex Lattice Mixture Designs

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Simplex Lattice Mixture Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Simplex Lattice Mixture Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `mixture-designs-simplex` — For Reviewers

### 18.0.160 Simulating Survival Data

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Simulating Survival Data** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Simulating Survival Data yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `survival-simulation` — For Reviewers

### 18.0.161 Spearman Rank Correlation Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Spearman Rank Correlation Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Spearman Rank Correlation Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `spearman-correlation-test` — For Reviewers

### 18.0.162 Spline Regression

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Spline Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Spline Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `spline-regression` — For Reviewers

### 18.0.163 Split-Plot Designs

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Split-Plot Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Split-Plot Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `split-plot-design` — For Reviewers

### 18.0.164 Stepwise Regression: Pitfalls

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Stepwise Regression: Pitfalls** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Stepwise Regression: Pitfalls yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `stepwise-regression-pitfalls` — For Reviewers

### 18.0.165 Stratified Cox Models

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Stratified Cox Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Stratified Cox Models yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `stratified-cox` — For Reviewers

### 18.0.166 Strip-Plot Designs

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Strip-Plot Designs** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Strip-Plot Designs yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `strip-plot-design` — For Reviewers

### 18.0.167 Taguchi Methods

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Taguchi Methods** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Taguchi Methods yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `taguchi-methods` — For Reviewers

### 18.0.168 The Bootstrap: Introduction

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **The Bootstrap: Introduction** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha$ = *0.05*; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> The Bootstrap: Introduction yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `bootstrap-introduction` — For Reviewers

### 18.0.169 The Brier Score for Survival

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **The Brier Score for Survival** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha$ = *0.05*; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> The Brier Score for Survival yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `brier-score-survival` — For Reviewers

### 18.0.170 The Jackknife

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **The Jackknife** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha$ = *0.05*; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

The Jackknife yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `jackknife` — For Reviewers

### 18.0.171 The Nelson-Aalen Estimator

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **The Nelson-Aalen Estimator** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

The Nelson-Aalen Estimator yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `nelson-aalen-estimator` — For Reviewers

### 18.0.172 The Runs Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **The Runs Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

The Runs Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `runs-test` — For Reviewers

### 18.0.173 The Sign Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **The Sign Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> The Sign Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `sign-test` — For Reviewers

### 18.0.174 Time-Dependent ROC

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Time-Dependent ROC** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Time-Dependent ROC yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `time-dependent-roc` — For Reviewers

### 18.0.175 Time-Varying Covariates

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Time-Varying Covariates** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

> Time-Varying Covariates yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `time-varying-covariates` — For Reviewers

### 18.0.176 Tobit Regression

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Tobit Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Tobit Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `tobit-regression` — For Reviewers

### 18.0.177 Truncated Regression

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Truncated Regression** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Truncated Regression yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `truncated-regression` — For Reviewers

### 18.0.178 Two-Proportion Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Two-Proportion Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Two-Proportion Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `two-proportion-test` — For Reviewers

### 18.0.179 Two-Sample t-Test

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Two-Sample t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Two-Sample t-Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `two-sample-t-test` — For Reviewers

### 18.0.180 Two-Way ANOVA

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Two-Way ANOVA** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

> Two-Way ANOVA yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]*. *[Sensitivity analysis result]*.

**Reviewer checklist for this method.** → `two-way-anova` — For Reviewers

### 18.0.181 Type I and Type II Errors

**Methods paragraph (copy-paste, fill in italics):**

> *[N=]* participants/observations were analysed using **Type I and Type II Errors** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]*. *[Effect size with 95% confidence interval reported as the primary outcome]*. Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any]*.

**Results paragraph (copy-paste):**

Type I and Type II Errors yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `type-i-type-ii-errors` — For Reviewers

### 18.0.182 Weighted Log-Rank Tests

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Weighted Log-Rank Tests** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Weighted Log-Rank Tests yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `weighted-log-rank` — For Reviewers

### 18.0.183 Welch's t-Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Welch's t-Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Welch's t-Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `welch-t-test` — For Reviewers

### 18.0.184 Wilcoxon Signed-Rank Test

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Wilcoxon Signed-Rank Test** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size*

*with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Wilcoxon Signed-Rank Test yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `wilcoxon-signed-rank` — For Reviewers

### 18.0.185 Worked lme4::lmer Examples

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Worked lme4::lmer Examples** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Worked lme4::lmer Examples yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `lme4-lmer-examples` — For Reviewers

### 18.0.186 Zero-Inflated Models

**Methods paragraph (copy-paste, fill in italics):**

*[N=]* participants/observations were analysed using **Zero-Inflated Models** as implemented in *[package vX.Y]* in R *[vX.Y]*. Assumptions were checked: *[list checks performed]. [Effect size with 95% confidence interval reported as the primary outcome].* Two-sided p-values use $\alpha = 0.05$; *[multiple-comparison adjustment if any].*

**Results paragraph (copy-paste):**

Zero-Inflated Models yielded *[estimate]* (95% CI *[lower, upper]*, p = *[value]*). *[Diagnostic / assumption summary]. [Sensitivity analysis result].*

**Reviewer checklist for this method.** → `zero-inflated-models` — For Reviewers