21 Text Mining Bibliographic Corpora

21.1 Learning objectives

After completing this chapter, you will be able to:

- Build a text corpus from OpenAlex titles and abstracts
- Apply standard preprocessing steps: tokenisation, stopword removal, stemming
- Construct a document-term matrix (DTM) and a document-feature matrix (DFM)
- Compute TF-IDF weights to identify distinctive terms
- Visualise term frequency patterns across time or groups

21.2 Setup

```
library(tidyverse)
library(openalexR)
library(quanteda)
library(quanteda.textstats)
library(glue)
library(gt)

set.seed(20260509)

source(here::here("R", "api_helpers.R"))
source(here::here("R", "utils.R"))
source(here::here("R", "sci_palette.R"))
```

21.3 Conceptual background

Bibliometric metadata — titles, abstracts, and keywords — constitutes a rich but noisy text corpus. Text mining transforms this unstructured data into structured representations suitable for statistical analysis. The pipeline typically follows three stages: preprocessing, representation, and analysis.

Preprocessing converts raw text into a standardised form. Tokenisation splits text into individual words or n-grams. Lowercasing removes case variation. Stopword removal eliminates high-frequency function words (“the”, “of”, “and”) that carry little topical information. Stemming or lemmatisation reduces words to their root forms (“computing”, “computed”, “computation” → “comput” or “compute”). Each step involves trade-offs: aggressive stemming can merge distinct concepts, while minimal preprocessing retains noise.

The **document-term matrix** (DTM) or **document-feature matrix** (DFM) is the fundamental representation. Rows are documents; columns are terms; cells contain counts or weights. Raw term frequencies overweight common words. **TF-IDF** (term frequency–inverse

document frequency) addresses this by upweighting terms that are frequent in a document but rare across the corpus, highlighting words that distinguish one document from others.

`quanteda` (Aria and Cuccurullo 2017) provides a fast, well-designed toolkit for text analysis in R. Its `corpus → tokens → dfm` pipeline integrates naturally with the tidyverse. For very large corpora, `quanteda` uses sparse matrix representations that scale to millions of documents.

Text mining complements network-based methods (17.3). Co-word networks reveal term associations; text mining provides the frequency distributions, temporal trends, and discriminative features that characterise a field's vocabulary.

21.4 Worked example

21.4.1 Building a text corpus

```
works ← fetch_openalex(
  entity = "works",
  primary_location.source.id = "S148561398",
  from_publication_date = "2019-01-01",
  to_publication_date = "2023-12-31",
  options = list(sample = 500, seed = 42)
)

text_df ← works ▷
  filter(!is.na(abstract), nchar(abstract) > 50) ▷
  transmute(
    doc_id = id,
    text = paste(display_name, abstract, sep = ". "),
    year = year(publication_date)
  )

cat(glue("Documents with abstracts: {nrow(text_df)}\n"))
```

```
#> Documents with abstracts: 130
```

```
corp ← corpus(text_df, docid_field = "doc_id", text_field = "text")
docvars(corp, "year") ← text_df$year

cat(glue("Corpus size: {ndoc(corp)} documents\n"))
```

```
#> Corpus size: 130 documents
```

```
cat(glue("Total tokens: {sum(ntoken(corp))}\n"))
```

```
#> Total tokens: 32111
```

21.4.2 Tokenisation and preprocessing

```
toks ← tokens(corp,
              remove_punct = TRUE,
              remove_numbers = TRUE,
              remove_symbols = TRUE) ▷
  tokens_tolower() ▷
  tokens_remove(stopwords("en")) ▷
  tokens_remove(c("also", "however", "using", "based", "study",
                  "paper", "results", "research", "analysis")) ▷
  tokens_wordstem()

cat(glue("Tokens after preprocessing: {sum(ntoken(toks))}\n"))
```

```
#> Tokens after preprocessing: 16208
```

21.4.3 Document-feature matrix

```
dfmat ← dfm(toks) ▷
  dfm_trim(min_termfreq = 5, min_docfreq = 3)

cat(glue("DFM dimensions: {nrow(dfmat)} docs x {ncol(dfmat)} features\n"))
```

```
#> DFM dimensions: 130 docs x 675 features
```

```
cat(glue("Sparsity: {scales::percent(sparsity(dfmat))}\n"))
```

```
#> Sparsity: 91%
```

```
top_terms ← topfeatures(dfmat, 20) ▷
  enframe(name = "term", value = "frequency") ▷
  mutate(term = fct_reorder(term, frequency))

ggplot(top_terms, aes(x = frequency, y = term)) +
  geom_col(fill = palette_sci(1)) +
  labs(x = "Frequency", y = NULL) +
  theme_sci()
```




Figure 21.1: Top 20 most frequent terms in the Scientometrics corpus.

21.4.4 TF-IDF weighting

```
dfmat_tfidf ← dfm_tfidf(dfmat)

tfidf_by_year ← text_df ▷
  group_by(year) ▷
  group_keys() ▷
  pull(year) ▷
  map_dfr(function(yr) {
    docs ← docvars(dfmat_tfidf, "year") == yr
    if (sum(docs) < 5) return(tibble())
    top ← topfeatures(dfmat_tfidf[docs, ], 10)
    tibble(year = yr, term = names(top), tfidf = unname(top))
  })

tfidf_by_year ▷
  group_by(year) ▷
  slice_max(tfidf, n = 5) ▷
  gt() ▷
  fmt_number(columns = tfidf, decimals = 1)
```

term	tfidf
2019	
journal	20.2
econom	18.6
manuscript	16.6
score	16.6
doctor	16.4
2020	
lis	24.6
citat	19.5
classifi	15.7
machin	13.9
practic	13.6
2021	
retract	40.8
journal	28.9
book	24.6
sars-cov-2	24.2
review	23.4
2022	
journal	29.5
p	25.7
public	25.6
citat	25.5
problem	24.4
2023	
mention	31.7
polici	22.0
document	14.5
academ	13.1
open	12.7

21.4.5 Term frequency over time

```
target_terms ← c("bibliometr", "open", "network", "impact", "collabor")

freq_by_year ← map_dfr(unique(text_df$year), function(yr) {
  docs ← docvars(dfmat, "year") == yr
  if (sum(docs) < 5) return(tibble())
  freq ← colSums(dfmat[docs, ]) / sum(dfmat[docs, ])
  tibble(
    year = yr,
    term = target_terms,
    rel_freq = freq[target_terms]
  )
})

ggplot(freq_by_year, aes(x = year, y = rel_freq, colour = term)) +
  geom_line(linewidth = 1) +
  geom_point(size = 2) +
  scale_colour_manual(values = palette_sci(length(target_terms))) +
  scale_y_continuous(labels = scales::percent_format(accuracy = 0.01)) +
  labs(x = "Year", y = "Relative frequency", colour = "Term") +
  theme_sci()
```




Figure 21.2: Relative frequency of selected terms over time.

21.5 Diagnostics and interpretation

- **Vocabulary size vs. documents**: A typical DFM has far more features than documents. Trim aggressively (minimum document frequency of 3–5) to reduce noise and computation.

- **Sparsity**: Bibliometric DFMs are typically 95–99% sparse. This is normal. Sparse matrix representations keep memory usage manageable.
- **Preprocessing sensitivity**: Results change with preprocessing choices. Always report stopword list, stemming method, and trimming thresholds.
- **Abstract availability**: Not all OpenAlex records have abstracts. Report the coverage rate and consider whether missing abstracts introduce bias (e.g., older papers, certain publishers).

21.6 Limitations and responsible use

21.7 Limitations and responsible use

- **Abstracts are summaries.** They capture the main claims but miss nuance, methodology details, and negative results. Full-text analysis (8.3) provides richer data but is harder to obtain.
- **Language bias.** Text mining tools work best for English. Non-English abstracts may be poorly tokenised, incorrectly stemmed, or excluded entirely. This biases results toward Anglophone research (Visser et al. 2021).
- **Stemming conflates concepts.** "Stem" and "stemming" are merged, but so are "cell" (biology) and "cell" (spreadsheet). Lemmatisation is more precise but slower.
- **Bag-of-words ignores context.** TF-IDF and frequency-based methods treat documents as unordered collections of words. Phrase meaning ("machine learning" vs. "learning machine") is lost unless you use n-grams or embeddings (24.3).

21.8 Common pitfalls

21.9 Common pitfalls

- **Not removing domain-specific stop words.** Generic stopword lists miss terms like "study", "results", "paper" that dominate academic text without conveying topical information.
- **Applying TF-IDF before trimming.** Rare terms get extreme TF-IDF scores. Trim the DFM first, then apply TF-IDF.
- **Comparing raw frequencies across groups of different sizes.** A year with 200 papers will have higher raw counts than a year with 50. Always normalise to relative frequency.

- **Stemming titles but not abstracts (or vice versa).** Apply identical preprocessing to all text fields.

21.10 Exercises

1. **Bigram analysis.** Build a DFM using bigrams (two-word sequences) instead of unigrams. What meaningful phrases emerge that single words miss?
2. **Lexical diversity.** Compute the type-token ratio (TTR) for each publication year. Is the vocabulary growing more diverse or more standardised over time?
3. **Keyness analysis.** Use `quanteda.textstats::textstat_keyness()` to identify terms that distinguish one year from all others. What terms characterise 2023 specifically?
4. **Preprocessing sensitivity.** Run the same analysis with and without stemming. How do the top terms differ? Which version is more interpretable?

21.11 Solutions

Solutions are provided in E.

21.12 Further reading

- Silge and Robinson (2017) — *Text Mining with R*; comprehensive guide to tidy text analysis.
- Aria and Cuccurullo (2017) — `bibliometrix` text-mining features for bibliometric data.
- Priem et al. (2022) — OpenAlex abstract availability and coverage.

21.13 Session info

```
sessionInfo()
```

```
#> R version 4.6.1 (2026-06-24)
#> Platform: x86_64-pc-linux-gnu
#> Running under: Ubuntu 24.04.5 LTS
#>
#> Matrix products: default
#> BLAS:   /usr/lib/x86_64-linux-gnu/openblas-pthread/libblas.so.3
#> LAPACK: /usr/lib/x86_64-linux-gnu/openblas-pthread/libopenblasp-r0.3.26.so;  LAPACK
version 3.12.0
#>
#> locale:
#>  [1] LC_CTYPE=C.UTF-8       LC_NUMERIC=C           LC_TIME=C.UTF-8
#>  [4] LC_COLLATE=C.UTF-8     LC_MONETARY=C.UTF-8    LC_MESSAGES=C.UTF-8
#>  [7] LC_PAPER=C.UTF-8       LC_NAME=C              LC_ADDRESS=C
#> [10] LC_TELEPHONE=C         LC_MEASUREMENT=C.UTF-8 LC_IDENTIFICATION=C
#>
#> time zone: UTC
#> tzcode source: system (glibc)
#>
#> attached base packages:
#> [1] stats     graphics  grDevices utils     datasets  methods   base
#>
#> other attached packages:
#>  [1] quanteda.textstats_0.97.2 visNetwork_2.1.4
#>  [3] ggraph_2.2.2              tidygraph_1.3.1
#>  [5] igraph_2.3.4              quanteda_4.5.1
#>  [7] pdftools_3.9.1            arrow_26.0.0
#>  [9] bibliometrix_5.5.0        RefManageR_1.4.0
#> [11] bib2df_1.1.2.0            rcrossref_1.2.1
#> [13] gt_1.4.0                  tidytext_0.4.3
#> [15] glue_1.8.1                openalexR_3.1.2
#> [17] lubridate_1.9.5           forcats_1.0.1
#> [19] stringr_1.6.0             dplyr_1.2.1
#> [21] purrr_1.2.2               readr_2.2.0
#> [23] tidyr_1.3.2               tibble_3.3.1
#> [25] ggplot2_4.0.3             tidyverse_2.0.0
#>
#> loaded via a namespace (and not attached):
#>   [1] bibtex_0.5.3           RColorBrewer_1.1-3     rstudioapi_0.19.0
#>   [4] jsonlite_2.0.0         magrittr_2.0.5         farver_2.1.2
#>   [7] rmarkdown_2.32         fs_2.1.0               vctrs_0.7.3
#>  [10] memoise_2.0.1          askpass_1.2.1          base64enc_0.1-6
#>  [13] htmltools_0.5.9        contentanalysis_1.1.1  curl_8.1.0
#>  [16] janeaustenr_1.0.0      cellranger_1.1.0       sass_0.4.10
#>  [19] bslib_0.12.0           htmlwidgets_1.6.4      tokenizers_0.3.0
#>  [22] plyr_1.8.9             httr2_1.3.0            plotly_4.12.1
#>  [25] cachem_1.1.0           dimensionsR_0.0.3      mime_0.13
#>  [28] lifecycle_1.0.5        pkgconfig_2.0.3        Matrix_1.7-5
#>  [31] R6_2.6.1               fastmap_1.2.0          shiny_1.14.0
#>  [34] digest_0.6.39          patchwork_1.3.2        shinycssloaders_1.1.0
#>  [37] rprojroot_2.1.1        SnowballC_0.7.1        labeling_0.4.3
#>  [40] urltools_1.7.3.1       timechange_0.4.0       polyclip_1.10-7
#>  [43] httr_1.4.9             compiler_4.6.1         here_1.0.2
#>  [46] bit64_4.8.6            withr_3.0.3            S7_0.2.2
#>  [49] viridis_0.6.5          ggforce_0.5.0          MASS_7.3-65
#>  [52] bibliometrixData_0.3.0 tools_4.6.1            otel_0.2.0
#>  [55] stopwords_2.3          zip_3.0.2              httpuv_1.6.17
#>  [58] rentrez_1.2.4          promises_1.5.0         grid_4.6.1
#>  [61] stringdist_0.9.17      generics_0.1.4         gtable_0.3.6
#>  [64] tzdb_0.5.0             rscopus_0.9.0          ca_0.72
#>  [67] data.table_1.18.6.1    hms_1.1.4              xml2_1.6.0
#>  [70] utf8_1.2.6             ggrepel_0.9.8          pillar_1.11.1
#>  [73] nsyllable_1.0.1        vroom_1.7.1            later_1.4.8
#>  [76] tweenr_2.0.3           lattice_0.22-9         bit_4.6.0
```

```
#>  [79] tidyselect_1.2.1       miniUI_0.1.2           downlit_0.4.5
#>  [82] knitr_1.52             gridExtra_2.3.1        bookdown_0.48
#>  [85] crul_1.6.0             xfun_0.62              graphlayouts_1.2.5
#>  [88] DT_0.34.0              humaniformat_0.6.0     stringi_1.8.9
#>  [91] qpdf_1.4.1             yaml_2.3.12            evaluate_1.0.5
#>  [94] httpcode_0.3.0         cli_3.6.6              xtable_1.8-8
#>  [97] jquerylib_0.1.4        Rcpp_1.1.2             readxl_1.6.0
#> [100] triebeard_0.4.1        XML_3.99-0.25          parallel_4.6.1
#> [103] assertthat_0.2.1       pubmedR_1.0.2          viridisLite_0.4.3
#> [106] scales_1.4.0           crayon_1.5.3           openxlsx_4.2.9
#> [109] rlang_1.3.0            fastmatch_1.1-8
```