# Chapter 21

# Evolutionarily Stable Strategies

*R. Heller · Date: 2026-05-08 · Last changed: 2026-11-10*

Formalizing evolutionary stability: ESS conditions, computational verification for symmetric games, invasion dynamics, and the Hawk-Dove-Retaliator game.

## Learning objectives

- State the formal ESS conditions and explain why they strengthen Nash equilibrium.
- Implement a computational check for ESS in arbitrary symmetric games.
- Construct invasion fitness diagrams that show whether a mutant can invade.
- Analyze the Hawk-Dove-Retaliator game to identify all evolutionarily stable strategies.

## 21.1 Motivation

Natural selection does not optimize — it filters. A population playing strategy $\sigma^*$ is stable not because $\sigma^*$ is "best" in some absolute sense, but because no rare mutant strategy can gain a foothold. This idea, formalized by Maynard Smith (1982) as the **evolutionarily stable strategy** (ESS), gives us a refinement of Nash equilibrium with real predictive power: if a population reaches an ESS, small perturbations cannot dislodge it.

The concept matters beyond biology. Any setting where agents imitate successful neighbors — technology adoption, social norms, market conventions — exhibits the same invasion-and-stability logic. In this chapter, we formalize ESS conditions, implement them computationally, and apply them to the classic Hawk-Dove-Retaliator game.

## 21.2 Theory

### 21.2.1 The ESS definition

Consider a symmetric two-player game with payoff function $u(\sigma_i, \sigma_j)$ giving the payoff to a player using strategy $\sigma_i$ against an opponent using $\sigma_j$. A strategy $\sigma^*$ is an **evolutionarily stable strategy** if for every mutant strategy $\sigma \neq \sigma^*$, at least one of the following holds:

1. **Strict Nash condition**: $u(\sigma^*, \sigma^*) > u(\sigma, \sigma^*)$
2. **Stability condition**: $u(\sigma^*, \sigma^*) = u(\sigma, \sigma^*)$ **and** $u(\sigma^*, \sigma) > u(\sigma, \sigma)$

The first condition says the incumbent does strictly better against itself than any mutant does against the incumbent. If this fails — meaning the mutant does equally well against the incumbent — the second condition requires that the incumbent does strictly better against the mutant than the mutant does against itself.

### 21.2.2 Relationship to Nash equilibrium

Every ESS is a symmetric Nash equilibrium, but not every Nash equilibrium is an ESS. A symmetric Nash equilibrium $(\sigma^*, \sigma^*)$ satisfies $u(\sigma^*, \sigma^*) \geq u(\sigma, \sigma^*)$ for all $\sigma$. The ESS adds a second layer: when the inequality binds, the incumbent must still outperform the mutant in head-to-head encounters. This rules out "weakly stable" equilibria that are Nash but vulnerable to drift.

### 21.2.3 Invasion dynamics

When a small fraction $\epsilon$ of mutants enters a population of incumbents, the expected payoff to a mutant is:

$$W_{\text{mutant}}(\epsilon) = (1 - \epsilon)\, u(\sigma, \sigma^*) + \epsilon\, u(\sigma, \sigma)$$

and the expected payoff to an incumbent is:

$$W_{\text{incumbent}}(\epsilon) = (1-\epsilon)\,u(\sigma^*, \sigma^*) + \epsilon\,u(\sigma^*, \sigma)$$

The strategy $\sigma^*$ resists invasion if $W_{\text{incumbent}}(\epsilon) > W_{\text{mutant}}(\epsilon)$ for all sufficiently small $\epsilon > 0$. This is exactly the ESS condition restated in terms of population payoffs.

## 21.3 Implementation in R

### 21.3.1 Checking ESS conditions for a symmetric game

We write a function that takes a payoff matrix for a symmetric game and checks each pure strategy for ESS status.

```
check_ess <- function(A) {
  n <- nrow(A)
  strategies <- rownames(A)
  if (is.null(strategies)) strategies <- paste("S", seq_len(n))

  results <- tibble(
    strategy = strategies,
    is_nash = FALSE,
    strict_nash = FALSE,
    is_ess = FALSE,
    failing_mutant = NA_character_
  )

  for (i in seq_len(n)) {
    # Check Nash: u(i, i) >= u(j, i) for all j
    payoff_ii <- A[i, i]
    payoffs_ji <- A[, i]  # column i: payoffs of all strategies
↪   against i
    is_nash <- all(payoff_ii >= payoffs_ji)
    is_strict <- all(payoff_ii > payoffs_ji[-i])

    results$is_nash[i] <- is_nash
    results$strict_nash[i] <- is_strict

    if (!is_nash) {
      worst <- which.max(payoffs_ji - payoff_ii)
      results$failing_mutant[i] <- strategies[worst]
      next
    }
```

```
    if (is_strict) {
      results$is_ess[i] <- TRUE
      next
    }

    # Check stability condition for ties
    ess <- TRUE
    for (j in seq_len(n)) {
      if (j == i) next
      if (A[j, i] == payoff_ii) {
        # Tied - must have u(i, j) > u(j, j)
        if (A[i, j] <= A[j, j]) {
          ess <- FALSE
          results$failing_mutant[i] <- strategies[j]
          break
        }
      }
    }
    results$is_ess[i] <- ess
  }
  results
}
```

### 21.3.2 Testing on the Hawk-Dove game

The classic Hawk-Dove game (also called Chicken) with value $V = 2$ and cost $C = 4$:

```
V <- 2
C_cost <- 4

hd_matrix <- matrix(
  c((V - C_cost) / 2,  V,
    0,                 V / 2),
  nrow = 2, byrow = TRUE,
  dimnames = list(c("Hawk", "Dove"), c("Hawk", "Dove"))
)

cat("Hawk-Dove payoff matrix:\n")
```

```
#> Hawk-Dove payoff matrix:
```

```
print(hd_matrix)
```

```
#>      Hawk Dove
#> Hawk   -1    2
#> Dove    0    1
```

```
cat("\nESS check:\n")
```

```
#>
#> ESS check:
```

```
hd_ess <- check_ess(hd_matrix)
print(hd_ess)
```

```
#> # A tibble: 2 x 5
#>   strategy is_nash strict_nash is_ess failing_mutant
#>   <chr>    <lgl>   <lgl>       <lgl>  <chr>
#> 1 Hawk     FALSE   FALSE       FALSE  Dove
#> 2 Dove     FALSE   FALSE       FALSE  Hawk
```

Neither pure strategy is an ESS — Hawks can be invaded by Doves and vice versa. The ESS in this game is the mixed strategy playing Hawk with probability $V/C = 0.5$.

### 21.3.3 Invasion fitness landscape

```
eps <- seq(0, 0.5, length.out = 200)
p_star <- V / C_cost  # ESS mixture: Hawk with probability 0.5

# Effective payoffs for mixed ESS incumbent vs pure mutants
A <- hd_matrix
u_mix_mix <- p_star^2*A[1,1] + p_star*(1-p_star)*(A[1,2]+A[2,1])
 ↪  + (1-p_star)^2*A[2,2]
u_H_mix <- p_star*A[1,1] + (1-p_star)*A[1,2]
u_mix_H <- p_star*A[1,1] + (1-p_star)*A[2,1]
u_H_H   <- A[1,1]

W_inc_H <- (1 - eps) * u_mix_mix + eps * u_mix_H
W_mut_H <- (1 - eps) * u_H_mix   + eps * u_H_H
adv_hawk <- W_inc_H - W_mut_H
```

```
# Pure Dove mutant invading mixed ESS
u_D_mix <- p_star * hd_matrix[2,1] + (1-p_star) * hd_matrix[2,2]
u_mix_D <- p_star * hd_matrix[1,2] + (1-p_star) * hd_matrix[2,2]
u_D_D   <- hd_matrix[2,2]

W_inc_D <- (1 - eps) * u_mix_mix + eps * u_mix_D
W_mut_D <- (1 - eps) * u_D_mix   + eps * u_D_D
adv_dove <- W_inc_D - W_mut_D

invasion_df <- tibble(
  epsilon = rep(eps, 2),
  advantage = c(adv_hawk, adv_dove),
  mutant = rep(c("Hawk mutant", "Dove mutant"), each =
   ↪  length(eps))
)

p_invasion <- ggplot(invasion_df, aes(x = epsilon, y = advantage,
 ↪  colour = mutant)) +
  geom_line(linewidth = 1) +
  geom_hline(yintercept = 0, linetype = "dashed", colour =
   ↪  "grey40") +
  scale_colour_manual(values = c("Hawk mutant" = okabe_ito[6],
                                 "Dove mutant" = okabe_ito[3]),
                      name = "Mutant type") +
  theme_publication() +
  labs(title = "Invasion Fitness: Mixed ESS in Hawk-Dove",
       x = expression("Mutant fraction " * epsilon),
       y = "Incumbent advantage (payoff difference)")

p_invasion
```

```
save_pub_fig(p_invasion, "ess-invasion", width = 7, height = 5)
```

### 21.3.4 Basins of attraction in a 3-strategy game

We visualize the dynamics on the 2-simplex using the replicator equation from `R/replicator.R`. Points inside the simplex represent population states $(x_1, x_2, x_3)$ with $x_1 + x_2 + x_3 = 1$. We plot trajectories from many initial conditions to reveal the basins of attraction.

```
# Hawk-Dove-Retaliator payoff matrix (V=2, C=4)
# Retaliator: plays Dove against Dove, plays Hawk against Hawk
```





Figure 21.1: Invasion fitness landscape for the Hawk-Dove game. The plot shows the payoff advantage of the incumbent over a mutant as a function of mutant fraction. A positive value means the incumbent resists invasion. At the ESS mixture (Hawk with probability 0.5), both pure-strategy mutants have zero advantage at low frequency but negative advantage as they grow, confirming evolutionary stability of the mixed ESS.

```
hdr_matrix <- matrix(
  c((V - C_cost)/2,   V,           (V - C_cost)/2,
    0,                 V/2,         V/2,
    (V - C_cost)/2,   V/2,         V/2),
  nrow = 3, byrow = TRUE,
  dimnames = list(c("Hawk", "Dove", "Retaliator"),
                  c("Hawk", "Dove", "Retaliator"))
)

cat("Hawk-Dove-Retaliator payoff matrix:\n")
```

```
#> Hawk-Dove-Retaliator payoff matrix:
```

```
print(hdr_matrix)
```

```
#>            Hawk Dove Retaliator
#> Hawk         -1    2         -1
#> Dove          0    1          1
#> Retaliator   -1    1          1
```

```
# Simplex coordinates: map (x1, x2, x3) to 2D
# Vertices: Hawk = (0, 0), Dove = (1, 0), Retaliator = (0.5,
 ↪  sqrt(3)/2)
to_simplex_xy <- function(x1, x2, x3) {
  px <- x2 + 0.5 * x3
  py <- (sqrt(3) / 2) * x3
  tibble(sx = px, sy = py)
}

# Generate initial conditions on a grid inside the simplex
generate_simplex_grid <- function(n_per_side = 8) {
  pts <- list()
  for (i in seq(0, n_per_side)) {
    for (j in seq(0, n_per_side - i)) {
      k <- n_per_side - i - j
      x1 <- i / n_per_side
      x2 <- j / n_per_side
      x3 <- k / n_per_side
      # Avoid vertices and edges
      if (x1 > 0.02 && x2 > 0.02 && x3 > 0.02) {
        pts <- c(pts, list(c(x1, x2, x3)))
      }
    }
  }
```

```
  pts
}

initial_conditions <- generate_simplex_grid(12)

# Run replicator dynamics from each initial condition
all_trajectories <- list()

for (idx in seq_along(initial_conditions)) {
  x0 <- initial_conditions[[idx]]
  names(x0) <- c("Hawk", "Dove", "Retaliator")
  sol <- run_replicator(hdr_matrix, x0, times = seq(0, 80, by =
 ↪  0.5))

  coords <- to_simplex_xy(sol$Hawk, sol$Dove, sol$Retaliator)
  traj_df <- tibble(
    sx = coords$sx,
    sy = coords$sy,
    time = sol$time,
    traj_id = idx,
    start_hawk = x0[1]
  )
  all_trajectories[[idx]] <- traj_df
}

traj_data <- bind_rows(all_trajectories)

# Simplex triangle vertices
tri <- tibble(
  x = c(0, 1, 0.5, 0),
  y = c(0, 0, sqrt(3)/2, 0)
)

vertex_labels <- tibble(
  x = c(-0.06, 1.06, 0.5),
  y = c(-0.04, -0.04, sqrt(3)/2 + 0.04),
  label = c("Hawk", "Dove", "Retaliator")
)

p_simplex <- ggplot() +
  geom_path(data = tri, aes(x = x, y = y), colour = "grey30",
   ↪  linewidth = 0.5) +
  geom_path(data = traj_data,
            aes(x = sx, y = sy, group = traj_id, colour =
             ↪  start_hawk),
            linewidth = 0.3, alpha = 0.6) +
```

```
  scale_colour_gradient(low = okabe_ito[3], high = okabe_ito[6],
                        name = "Initial Hawk\nfraction") +
  geom_text(data = vertex_labels, aes(x = x, y = y, label =
   ↪  label),
            fontface = "bold", size = 3.8) +
  coord_fixed() +
  theme_publication() +
  theme(axis.text = element_blank(),
        axis.ticks = element_blank(),
        axis.title = element_blank(),
        panel.grid = element_blank()) +
  labs(title = "Replicator Dynamics on the Hawk-Dove-Retaliator
   ↪  Simplex")

p_simplex
```





Figure 21.2: Basins of attraction in the Hawk-Dove-Retaliator game under replicator dynamics. Trajectories from different initial conditions (coloured by starting region) converge toward the Retaliator vertex, confirming its ESS status. The interior mixed equilibrium is unstable.

```
save_pub_fig(p_simplex, "ess-simplex", width = 7, height = 6)
```

## 21.4 Worked example

We now systematically find all ESS candidates in the Hawk-Dove-Retaliator game and verify the conditions.

### 21.4.1 Step 1: Check pure strategies

```
hdr_ess <- check_ess(hdr_matrix)

cat("ESS analysis for Hawk-Dove-Retaliator:\n\n")
```

```
#> ESS analysis for Hawk-Dove-Retaliator:
```

```
for (i in seq_len(nrow(hdr_ess))) {
  cat(sprintf("  %-12s  Nash: %-5s  Strict Nash: %-5s  ESS:
   ↪  %-5s",
              hdr_ess$strategy[i],
              hdr_ess$is_nash[i],
              hdr_ess$strict_nash[i],
              hdr_ess$is_ess[i]))
  if (!is.na(hdr_ess$failing_mutant[i])) {
    cat(sprintf("  (fails against %s)",
     ↪  hdr_ess$failing_mutant[i]))
  }
  cat("\n")
}
```

```
#>   Hawk          Nash: FALSE  Strict Nash: FALSE  ESS: FALSE  (fails against Dove)
#>   Dove          Nash: FALSE  Strict Nash: FALSE  ESS: FALSE  (fails against Hawk)
#>   Retaliator    Nash: TRUE   Strict Nash: FALSE  ESS: FALSE  (fails against Dove)
```

### 21.4.2 Step 2: Interpret the results

```
cat("Detailed verification:\n\n")
```

```
#> Detailed verification:
```

```
# Hawk vs Hawk
cat("Hawk as candidate ESS:\n")
```

```
#> Hawk as candidate ESS:
```

```
cat(sprintf("  u(Hawk, Hawk) = %.1f\n", hdr_matrix["Hawk",
 ↪  "Hawk"]))
```

```
#>   u(Hawk, Hawk) = -1.0
```

```
cat(sprintf("  u(Dove, Hawk) = %.1f  -> Dove does better against
 ↪  Hawk\n",
            hdr_matrix["Dove", "Hawk"]))
```

```
#>   u(Dove, Hawk) = 0.0  -> Dove does better against Hawk
```

```
cat("  Hawk is NOT a Nash equilibrium - Dove can invade.\n\n")
```

```
#>   Hawk is NOT a Nash equilibrium - Dove can invade.
```

```
# Dove vs Dove
cat("Dove as candidate ESS:\n")
```

```
#> Dove as candidate ESS:
```

```
cat(sprintf("  u(Dove, Dove) = %.1f\n", hdr_matrix["Dove",
 ↪  "Dove"]))
```

```
#>   u(Dove, Dove) = 1.0
```

```
cat(sprintf("  u(Hawk, Dove) = %.1f  -> Hawk does better against
 ↪  Dove\n",
            hdr_matrix["Hawk", "Dove"]))
```

```
#>   u(Hawk, Dove) = 2.0  -> Hawk does better against Dove
```

```
cat("  Dove is NOT a Nash equilibrium - Hawk can invade.\n\n")
```

```
#>   Dove is NOT a Nash equilibrium - Hawk can invade.
```

```
# Retaliator vs all
cat("Retaliator as candidate ESS:\n")
```

```
#> Retaliator as candidate ESS:
```

```
cat(sprintf("  u(Ret, Ret) = %.1f\n", hdr_matrix["Retaliator",
 ↪  "Retaliator"]))
```

```
#>   u(Ret, Ret) = 1.0
```

```
cat(sprintf("  u(Hawk, Ret) = %.1f  -> Hawk does equally well\n",
            hdr_matrix["Hawk", "Retaliator"]))
```

```
#>   u(Hawk, Ret) = -1.0  -> Hawk does equally well
```

```
cat(sprintf("  u(Dove, Ret) = %.1f  -> Dove does equally well\n",
            hdr_matrix["Dove", "Retaliator"]))
```

```
#>   u(Dove, Ret) = 1.0  -> Dove does equally well
```

```
cat("  Ties exist - check stability condition:\n")
```

```
#>   Ties exist - check stability condition:
```

```
cat(sprintf("  u(Ret, Hawk) = %.1f vs u(Hawk, Hawk) = %.1f  ->
 ↪  Ret wins\n",
            hdr_matrix["Retaliator", "Hawk"], hdr_matrix["Hawk",
 ↪  "Hawk"]))
```

```
#>   u(Ret, Hawk) = -1.0 vs u(Hawk, Hawk) = -1.0  -> Ret wins
```

```
cat(sprintf("  u(Ret, Dove) = %.1f vs u(Dove, Dove) = %.1f  ->
 ↪  Tied\n",
            hdr_matrix["Retaliator", "Dove"], hdr_matrix["Dove",
 ↪  "Dove"]))
```

```
#>   u(Ret, Dove) = 1.0 vs u(Dove, Dove) = 1.0  -> Tied
```

### 21.4.3 Step 3: Verify with replicator dynamics

The simplex diagram above (21.2) confirms the analytic result. Trajectories from most initial conditions converge to the Retaliator vertex, though the Dove-Retaliator edge shows neutral drift because these two strategies are payoff-equivalent against each other. In a strict sense, Retaliator is not ESS because Dove is a neutral mutant that satisfies neither the strict Nash condition nor the stability condition (they tie on both counts). This is a well-known subtlety: Retaliator is **neutrally stable** but not strictly ESS in the 3-strategy game.

```
# Verify: start near Retaliator, introduce small Hawk mutation
x0_test <- c(Hawk = 0.05, Dove = 0.0, Retaliator = 0.95)
sol_test <- run_replicator(hdr_matrix, x0_test, times = seq(0,
 ↪  100, by = 1))

cat("Hawk invasion attempt (starting at 5% Hawk, 95%
 ↪  Retaliator):\n")
```

```
#> Hawk invasion attempt (starting at 5% Hawk, 95% Retaliator):
```

```
cat(sprintf("  t=0:   Hawk=%.3f  Dove=%.3f  Ret=%.3f\n",
            sol_test$Hawk[1], sol_test$Dove[1],
 ↪  sol_test$Retaliator[1]))
```

```
#>   t=0:   Hawk=0.050  Dove=0.000  Ret=0.950
```

```
final <- nrow(sol_test)
cat(sprintf("  t=100: Hawk=%.3f  Dove=%.3f  Ret=%.3f\n",
            sol_test$Hawk[final], sol_test$Dove[final],
 ↪  sol_test$Retaliator[final]))
```

```
#>   t=100: Hawk=-0.000  Dove=0.000  Ret=1.000
```

```
cat("  Hawk is driven out - Retaliator resists Hawk invasion.\n")
```

```
#>   Hawk is driven out - Retaliator resists Hawk invasion.
```

## 21.5 Extensions

- **Mixed ESS**: When no pure strategy is ESS, the stable outcome may be a mixed strategy. For 2-strategy games, the ESS mixture can be found analytically; for larger games, the Bishop-Cannings theorem provides necessary conditions (Maynard Smith, 1982).

- **Finite populations**: In finite populations, stochastic effects mean that even ESS populations can be invaded by neutral drift. Nowak et al. (2004) introduced stochastic stability concepts for evolutionary dynamics.
- **Multi-population ESS**: When different roles exist (e.g., buyer and seller), the relevant concept is the **asymmetric ESS** analyzed in bimatrix games.
- **Connection to replicator dynamics**: The replicator equation (20) provides the dynamic justification for ESS — every ESS is an asymptotically stable rest point of the replicator dynamics, though the converse is not always true.

# Exercises

1. **Stag Hunt ESS.** Consider the Stag Hunt game with payoff matrix $A = \begin{pmatrix} 4 & 0 \\ 3 & 2 \end{pmatrix}$. Use `check_ess()` to verify that both (Stag, Stag) and (Hare, Hare) are Nash equilibria, but only one is an ESS. Which one, and why?

2. **Three-strategy Rock-Paper-Scissors.** Construct the symmetric payoff matrix for RPS with win = 1, loss = -1, draw = 0. Show computationally that no pure strategy is a Nash equilibrium (and hence none is ESS). Then argue from the invasion fitness formula why the uniform mixture $(\frac{1}{3}, \frac{1}{3}, \frac{1}{3})$ is not ESS either — it is neutrally stable.

3. **Invasion barrier.** For the Hawk-Dove game with $V = 6$ and $C = 10$, compute the mixed ESS analytically ($p^* = V/C$). Then write code to find the maximum mutant fraction $\bar{\epsilon}$ at which the incumbent still has a payoff advantage over a pure-Hawk mutant. Plot the advantage curve and mark $\bar{\epsilon}$ on the graph.

Solutions appear in D.