

- 1.) Screenshot of mac address-table:

```
Switch>show mac address-table
      Mac Address Table
-----
Vlan    Mac Address      Type    Ports
----    -
1       0010.111a.d901    DYNAMIC Fa0/2
1       0060.3e7a.2501    DYNAMIC Fa0/1
1       0060.3e7a.2502    DYNAMIC Fa0/3
1       0090.2bb0.e218    DYNAMIC Fa0/24
Switch>
```

Copy Paste

Top

- 2.) Router MAC addresses:

```
Router#show interfaces g0/0
GigabitEthernet0/0 is up, line protocol is up (connected)
  Hardware is CN Gigabit Ethernet, address is 0060.3e7a.2501 (bia 0060.3e7a.2501)
  Internet address is 192.168.10.1/24
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is RJ45
  output flow-control is unsupported, input flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00,
  Last input 00:00:08, output 00:00:05, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0 (size/max/drops); Total output drops: 0
  Queueing strategy: fifo
  Output queue :0/40 (size/max)
  5 minute input rate 5 bits/sec, 0 packets/sec
  5 minute output rate 5 bits/sec, 0 packets/sec
    4 packets input, 188 bytes, 0 no buffer
    Received 4 broadcasts, 0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
    0 watchdog, 1017 multicast, 0 pause input
    0 input packets with dribble condition detected
    4 packets output, 188 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 unknown protocol drops
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier
  --More--
```

Copy Paste

- 3.) Ping:

```
Router>ping 192.168.20.1

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/3 ms
```

- 4.) MAC table after ping:

- 5.) MAC table after clearing:

6.) IP route:

```
Router# show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

    192.168.10.0/24 is variably subnetted, 2 subnets, 2 masks
C       192.168.10.0/24 is directly connected, GigabitEthernet0/0
L       192.168.10.1/32 is directly connected, GigabitEthernet0/0
    192.168.20.0/24 is variably subnetted, 2 subnets, 2 masks
C       192.168.20.0/24 is directly connected, GigabitEthernet0/1
L       192.168.20.1/32 is directly connected, GigabitEthernet0/1
S       192.168.40.0/24 [1/0] via 192.168.10.2

Router#
```

Copy Paste

Top

7.) IP interface brief:

```
Router#show ip interface brief
Interface                IP-Address      OK? Method Status      Protocol
GigabitEthernet0/0        192.168.10.1    YES manual up          up
GigabitEthernet0/1        192.168.20.1    YES manual up          up
GigabitEthernet0/2        unassigned      YES unset  administratively down down
Vlan1                     unassigned      YES unset  administratively down down

Router#
```

Copy Paste

Top

8.) Screenshot showing static routes:

```
    192.168.10.0/24 is variably subnetted, 2 subnets, 2 masks
C       192.168.10.0/24 is directly connected, GigabitEthernet0/0
L       192.168.10.1/32 is directly connected, GigabitEthernet0/0
    192.168.20.0/24 is variably subnetted, 2 subnets, 2 masks
C       192.168.20.0/24 is directly connected, GigabitEthernet0/1
L       192.168.20.1/32 is directly connected, GigabitEthernet0/1
S       192.168.40.0/24 [1/0] via 192.168.10.2

Router#
```

Copy