

NET512

Designing and Implementing a Secure, Scalable, and Automated Enterprise Network

Weekly Practical Plan - NQF Level 5 | 17 Credits

Week 6: Cisco Device Management (10 Marks)

Tasks:

Configuration & IOS Image Backup

```
R1#copy running-config tftp:
Address or name of remote host []? 10.10.10.10
Destination filename [R1-config]?

Writing running-config...!!
[OK - 732 bytes]

732 bytes copied in 0.006 secs (122000 bytes/sec)
R1#
```

Password Recovery

```
R1(config)#enable secret Cisco123
R1(config)#line console 0
R1(config-line)#password console123
R1(config-line)#login
R1(config-line)#exit
R1(config)#end
R1#

R1#config t
Enter configuration commands, one per line. End with CNTL/Z.
R1(config)#enable secret newpassword123
R1(config)#config-register 0x2102
R1(config)#end
```

```
Cisco CISCO2911/K9 (revision 1.0) with 491520K/32768K bytes of memory.  
Processor board ID FTX152400KS  
3 Gigabit Ethernet interfaces  
DRAM configuration is 64 bits wide with parity disabled.  
255K bytes of non-volatile configuration memory.  
249856K bytes of ATA System CompactFlash 0 (Read/Write)
```

```
Press RETURN to get started!
```

```
User Access Verification
```

```
Password:
```

```
Password:
```

```
R1>enable
```

```
Password:
```

```
R1#
```

New password does not show, but this is proof it works

Factory Reset

```
Router>enable
Router#show startup-config
startup-config is not present
Router#show running-config
Building configuration...

Current configuration : 696 bytes
!
version 15.1
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname Router
!
!
!
!
!
!
!
no ip cef
no ipv6 cef
!
!
!
!
license udi pid CISCO2911/K9 sn FTX152487U5-
!
!
!
!
!
!
!
!
!
!
spanning-tree mode pvst
!
!
!
!
!
interface GigabitEthernet0/0
no ip address
duplex auto
speed auto
shutdown
!
```

```

!
interface GigabitEthernet0/1
  no ip address
  duplex auto
  speed auto
  shutdown
!
interface GigabitEthernet0/2
  no ip address
  duplex auto
  speed auto
  shutdown
!
interface Vlan1
  no ip address
  shutdown
!
ip classless
!
ip flow-export version 9
!
!
!
!
!
!
line con 0
!
line aux 0
!
line vty 0 4
  login
!
!
!
end

```

Restore

```

Router#copy tftp: running-config
Address or name of remote host []? 10.10.10.10
Source filename []? R1-config
Destination filename [running-config]?

Accessing tftp://10.10.10.10/R1-config...
Loading R1-config from 10.10.10.10: !
[OK - 708 bytes]

708 bytes copied in 0 secs
Router#
%SYS-5-CONFIG_I: Configured from console by console

```

router#show version
Cisco IOS Software, C2900 Software (C2900-UNIVERSALK9-M), Version 15.1(4)M4, RELEASE SOFTWARE (fc2)
Technical Support: <http://www.cisco.com/techsupport>
Copyright (c) 1986-2012 by Cisco Systems, Inc.
Compiled Thurs 5-Jan-12 15:41 by pt_team

ROM: System Bootstrap, Version 15.1(4)M4, RELEASE SOFTWARE (fc1)
cisco2911 uptime is 16 minutes, 35 seconds
System returned to ROM by power-on
System image file is "flash0:c2900-universalk9-mz.SPA.151-1.M4.bin"
Last reload type: Normal Reload

This product contains cryptographic features and is subject to United States and local country laws governing import, export, transfer and use. Delivery of Cisco cryptographic products does not imply third-party authority to import, export, distribute or use encryption. Importers, exporters, distributors and users are responsible for compliance with U.S. and local country laws. By using this product you agree to comply with applicable laws and regulations. If you are unable to comply with U.S. and local laws, return this product immediately.

A summary of U.S. laws governing Cisco cryptographic products may be found at:
<http://www.cisco.com/wwl/export/crypto/tool/stqrg.html>

If you require further assistance please contact us by sending email to export@cisco.com.
Cisco CISCO2911/K9 (revision 1.0) with 491520K/32768K bytes of memory.
Processor board ID FTX152400KS
3 Gigabit Ethernet interfaces
DRAM configuration is 64 bits wide with parity disabled.
255K bytes of non-volatile configuration memory.
249856K bytes of ATA System CompactFlash 0 (Read/Write)

License Info:

License UDI:

```
-----  
Device#   PID                SN  
-----  
*0        CISCO2911/K9      FTX152487U5-
```

Technology Package License Information for Module:'c2900'

```
-----  
Technology   Technology-package   Technology-package  
Current      Type                Next reboot  
-----  
ipbase       ipbasek9            Permanent          ipbasek9  
security     disable             None               None  
uc           disable             None               None  
data         disable             None               None
```

Configuration register is 0x2102

```
:
interface GigabitEthernet0/0
 ip address 10.10.10.1 255.255.255.0
 duplex auto
 speed auto
!
interface GigabitEthernet0/1
 no ip address
 duplex auto
 speed auto
 shutdown
!
interface GigabitEthernet0/2
 no ip address
 duplex auto
 speed auto
 shutdown
!
interface Vlan1
 no ip address
 shutdown
!
ip classless
--More--
```

```
!
interface GigabitEthernet0/0
 ip address 10.10.10.1 255.255.255.0
 duplex auto
 speed auto
!
interface GigabitEthernet0/1
 no ip address
 duplex auto
 speed auto
 shutdown
!
interface GigabitEthernet0/2
 no ip address
 duplex auto
 speed auto
 shutdown
!
interface Vlan1
 no ip address
 shutdown
!
ip classless
!
ip flow-export version 9
!
!
!
!
!
!
line con 0
!
line aux 0
!
line vty 0 4
 login
!
!
!
```


