


Week 1

TASK 1



TASK 2

Image text-base: 0x80008098, data-base: 0x814129C4

Cisco WS-C2960-24TT (RC32300) processor (revision C0) with 21039K bytes of memory.

24 FastEthernet/IEEE 802.3 interface(s)
2 Gigabit Ethernet/IEEE 802.3 interface(s)

63488K bytes of flash-simulated non-volatile configuration memory.

Base ethernet MAC Address : 00D0.5826.93AB
Motherboard assembly number : 73-9832-06
Power supply part number : 341-0097-02
Motherboard serial number : FOC103248MJ
Power supply serial number : DCA102133JA
Model revision number : B0
Motherboard revision number : C0
Model number : WS-C2960-24TT
System serial number : FOC103321EY
Top Assembly Part Number : 800-26671-02
Top Assembly Revision Number : B0
Version ID : V02
CLEI Code Number : COM3K00BRA
Hardware Board Revision Number : 0x01

Switch	Ports	Model	SW Version	SW Image
-----	-----	-----	-----	-----
* 1	26	WS-C2960-24TT	12.2	C2960-LANBASE-M

Cisco IOS Software, C2960 Software (C2960-LANBASE-M), Version 12.2(25)FX, RELEASE SOFTWARE (fc1)
Copyright (c) 1986-2005 by Cisco Systems, Inc.
Compiled Wed 12-Oct-05 22:05 by pt_team

Press RETURN to get started!

Switch>?

Exec commands:

connect	Open a terminal connection
disable	Turn off privileged commands
disconnect	Disconnect an existing network connection
enable	Turn on privileged commands
exit	Exit from the EXEC
logout	Exit from the EXEC
ping	Send echo messages
resume	Resume an active network connection
show	Show running system information
telnet	Open a telnet connection
terminal	Set terminal line parameters
traceroute	Trace route to destination

```

Switch>?
!xec commands:
  connect      Open a terminal connection
  disable      Turn off privileged commands
  disconnect   Disconnect an existing network connection
  enable       Turn on privileged commands
  exit         Exit from the EXEC
  logout       Exit from the EXEC
  ping         Send echo messages
  resume       Resume an active network connection
  show         Show running system information
  telnet       Open a telnet connection
  terminal     Set terminal line parameters
  traceroute   Trace route to destination
Switch>t
: Ambiguous command: "t"
Switch>t?
:elnet terminal traceroute
Switch>te
: Ambiguous command: "te"
Switch>?
!xec commands:
  connect      Open a terminal connection
  disable      Turn off privileged commands
  disconnect   Disconnect an existing network connection
  enable       Turn on privileged commands
  exit         Exit from the EXEC
  logout       Exit from the EXEC
  ping         Send echo messages
  resume       Resume an active network connection
  show         Show running system information
  telnet       Open a telnet connection
  terminal     Set terminal line parameters
  traceroute   Trace route to destination
Switch>en
Switch>enable
Switch#S1#
:ranslating "S1#"...domain server (255.255.255.255)
: Unknown command or computer name, or unable to find computer address

Switch#S1 configure
      ^
: Invalid input detected at '^' marker.

Switch#

```

TASK 3

```
Switch#S1 configure
      ^
% Invalid input detected at '^' marker.

Switch#c
Switch#configure
Configuring from terminal, memory, or network [terminal]?
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#
```

```
Switch#c
Switch#configure
Configuring from terminal, memory, or network [terminal]?
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#exit
Switch#
%SYS-5-CONFIG_I: Configured from console by console
```

TASK 4

```
Switch#c
Switch#configure
Configuring from terminal, memory, or network [terminal]?
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#exit
Switch#
%SYS-5-CONFIG_I: Configured from console by console
S1 (config) # exit
      ^
% Invalid input detected at '^' marker.

Switch#show clock
*0:28:26.87 UTC Mon Mar 1 1993
Switch#clock
% Incomplete command.
Switch#clock ?
    set  Set the time and date
Switch#clock set 15:00:00 ?
    <1-31> Day of the month
    MONTH Month of the year
Switch#clock set 15:00:00
% Incomplete command.
Switch#show clock
*0:32:55.31 UTC Mon Mar 1 1993
Switch#clock set 15:00:00 31 Jan 2035
Switch#
```

```
Switch#cl
% Ambiguous command: "cl"
Switch#clock
% Incomplete command.
Switch#clock set 25:00:00
      ^
% Invalid input detected at '^' marker.
```

```
Switch#
```

```
% Ambiguous command: "cl"
Switch#clock
% Incomplete command.
Switch#clock set 25:00:00
      ^
% Invalid input detected at '^' marker.
```

```
Switch#clock set 15:00:00 32
                        ^
% Invalid input detected at '^' marker.
```

```
Switch#
```