

Optical Audio Reconstruction for Stereo Phonograph Records using White-light Interferometry

Beinan Li, Jordan B. L. Smith, Ichiro Fujinaga

Music Technology Area, Schulich School of Music, McGill University, Montreal, Canada

1. Background



Our Optical Audio Reconstruction (OAR) using white-light interferometry has successfully reconstructed a tiny stereo signal from a small area of an LP.


Challenge:

The workflow must be modified to scale up and handle a larger scanned area.


2. Large-scale Scanning

Problem:

Disc surface warping demands a greatly increased scanning depth, but this takes too much time.




Solution: Hierarchical Scan



Disc surface is divided into *flat* sub-regions.

Use a representative FOV's scanning settings for the whole sub-region.

3. Image Alignment



Greedy alignment introduces accumulated errors.

These gaps are eliminated during post-processing

4. Groove Recognition




CC: Top

CC: Bottom

Identify the parts of the grooves with Connected Component (CC) Analysis.


5. Noise Removal




Remove CCs that violate expected topology.

Detach and re-attach dust-affected grooves.

6. Undulation Extraction



7. Audio Conversion




$$\text{Channel}_{\text{left}}(t) = \Delta T(t) - \Delta D(t)$$

$$\text{Channel}_{\text{right}}(t) = \Delta T(t) + \Delta D(t)$$

Stereo Output

8. Results




Excerpt of stereo audio reconstructed using our OAR

Excerpt of digitized stereo audio output from turntable



la fondation Daniel Langlois
pour l'art, la science et la technologie



Canada Foundation
for Innovation
Fondation canadienne
pour l'innovation



Schulich School of Music
École de musique Schulich

CIR
MMT Centre for Interdisciplinary Research
in Music Media and Technology

9. Conclusion

Our white-light interferometry-based optical audio recognition system has successfully reconstructed digital stereo audio signals from LPs. Among future strategies of improving audio quality while decreasing scanning time:

1. Better center correction
2. Determining the minimum scanning resolution required
3. Using the groove width information to substitute for the noisy depth information