
Building Blocks of Handlebars



Ryan Lewis
ryanhlewis.com | @ryanmurakami

Today's Menu



Smooth Demonstration

Dawn of a Conversion

Lots of Lists


"As if? Or else!"

Partially Partials

They're called illusions, Michael...

Get the Class Starter Code

http://www.ryanhlewis.com/pluralsight/



Dependencies

Handlebars

jQuery

Material Design Lite

Having Issues?

Tell Bower to use https:// instead of git:// with this command:

```
$ git config --global url."https://".insteadOf git://
```



{{im_an_expression}}

```
{{id}}}
      {{name}}
         {{image}}
```

Handlebars Example

```
Template

Data (Context)

{
dog_quality}}!

dog_quality: 'besest'
}
```

Handlebars Output

Dogs are the besest!

Handlebars

Global JavaScript object

How to Render a Template

Handlebars.compile(template) options)



Handlebars.compile(myTemplate);



-Function

myTemplate

Simple Handlebars Rendering Example

```
var template = 'My name is {{name}}.';

var compiled = Handlebars.compile(template);

var rendered = compiled({ name: 'Ryan' });
```

The Handlebars Dance

Get Template

Compile Template

Render with Data

Insert Rendered HTML

Nested Paths in Mustache

```
{ { myObj } }
                                Can you imagine having to do this
    Name: { { name } }
    Age: {{age}}
    Address: {{#address}}
       {{street}}
       {{city}}, {{state}} {{zip_code}}
     {{/address}}
{ { /myObj } }
```

Nested Paths in Handlebars

Localization with Handlebars

Handlebar's Most Used Helper

Each!

Each Helper Structure

```
{ {#each objectOrArray } Object or Array to iterate over { {prop1} } { {prop2} } { {prop3} } Current element becomes context
```

Each Helper Example

```
Template
                                                    Template Data
               arguments!?
{{#each dogs}}
                                                    'dogs': [
   {{this}}
                                                       'Spot',
{{/each}}
                                                       `Fluffy',
                             Output
                                                       'Maybe'
                              Spot
                             Fluffy
                              Maybe
```

Handlebars Blocks

Begin opening expression with #

Begin closing expression with /

Use the same property in both expressions

Block Examples

```
Object Context
```

Each Helper Block

```
{{#each dogs}}
  {{this}}

{{/each}}
```

Handlebars Expression Arguments

```
{{siteTitle}}
first argument
```

```
{{someHelper arg1 arg2}}
```



Each Helper Example ~ Object Edition!

Template

```
{ {#each users} }
    Name: {{name}}
    <img src="{{image}}" />
{{/each}}
```

Output

```
Name: Ryan
<img src="ryan.jpg" />
Name: Joe
<img src="joe.jpg" />
```

Template Data

@data variables

Special properties in Handlebars


@root

Root context of the template

mustache

logic-less templates™

handlebars



I've got if/else helpers!

What about me?!

mustache

If / Else in Mustache

```
{ { #propOrNot } }
   I exist!
{{/propOrNot}}
{ { ^propOrNot } }
                                            else
   I don't exist!
{{/propOrNot}}
```

Handlebars Brings the If's

```
{{#if truthyOrFalsy}}

I am truthy!

{{/if}}
```

Handlebars If Helper Limitations

No Comparisons No Operations Only One Argument

Don't Forget Else

```
{{#if truthyOrFalsy}}
  Wait, I thought I was falsy?
{{else}}
  I knew I was falsy!
{{/if}}
```

Each + Else Example

```
{{#each dogs}}

{{dog_stuff}}

{{else}}

No dogs!

{{/each}}
```


Handlebars Partials

"basically mini-templates" - Ryan Lewis

Partial Usage

Modularize templates for sanity

Modularize templates to remove redundancy



Simplify Your Templates



Registering a Partial

```
var dog_template = '<div>{{dog.name}} is a cutie!</div>';
Handlebars.registerPartial('dog', dog_template);
                                            Partial
                        Partial
                                           Template
                       Reference
                        Name
```

Using a Partial

```
<script id="my_template">
  { { > dog } }
                                   Receives same context as
</script>
                                   outer template
```


Handlebars Escapes HTML


```
data: { html : 'ampersand => &' }
```

template: <div>{{html}}</div>

output: <div>ampersand => &</div>

The Secret to Raw HTML





Handlebars with Raw HTML

data: { html : 'DOG' }

ttempolette: «cdiv» {{\html}} \div»

outpout:tpdtv×&it,b>DOG&/th/b&/gti,v>div>

Handlebars Output Can Look Funky


```
<l
     >Dog #1
Dog #2Dog #3
  Last Dog
```

Tilde Killed the Whitespace

```
{{~prop1}}
   {{prop1~}}
   {{~prop1~}}
{{~#each prop1~}}
```

Summary

- Dog Demo
- JQ, Hbars & MDL acquired!
- Basic Handlebars Expressions
- Built-in Each Helper
- I said 'dog' a lot!
- If / Else is okay
- Partials
- Raw, Vegan HTML
- Whitespace Extinction Event



Next Time on JavaScript Templating with Handlebars

Helpers

"They are very helpful." - Ryan Lewis