

Experiment 6

Student Name: Raushan Kr. Thakur

UID: 22BCS50121

Branch: BE-CSE

Section/Group: KRG2B

Semester: 6th

Date of Performance: 04/03/2025

Subject Name: Project Based Learning with JAVA

Subject Code: 22CSH-359

1. Aim:

Easy Level: Write a program to sort a list of Employee objects (name, age, salary) using lambda expressions.

2. Implementation/Code:

```
import java.util.*;
import java.util.stream.Collectors;

class Employee {
    String    name;
    int age;
    double salary;

    public Employee(String name, int age, double salary) {
        this.name = name;    this.age = age;    this.salary =
        salary;
    }

    public String toString() {
        return "Name: " + name + ", Age: " + age + ", Salary: " + salary;
    }
}

public class EmployeeSort {    public
static void main(String[] args) {
    List<Employee> employees = new ArrayList<>();
    employees.add(new Employee("John", 30, 50000));
    employees.add(new Employee("Alice", 25, 60000));
    employees.add(new Employee("Bob", 35, 45000));

    System.out.println("Sorted by Name:");
```

```
List<Employee> sortedByName = employees.stream()
    .sorted((e1, e2) -> e1.name.compareTo(e2.name))
    .collect(Collectors.toList());
sortedByName.forEach(System.out::println);

System.out.println("\nSorted by Age:");
List<Employee> sortedByAge = employees.stream()
    .sorted((e1, e2) -> Integer.compare(e1.age, e2.age))
    .collect(Collectors.toList());
sortedByAge.forEach(System.out::println);

System.out.println("\nSorted by Salary:");
List<Employee> sortedBySalary = employees.stream()
    .sorted((e1, e2) -> Double.compare(e1.salary, e2.salary))
    .collect(Collectors.toList());
sortedBySalary.forEach(System.out::println);
}
```

OUTPUT:

```
(41) [ java Employee ]
Sorted by Name:
Name: Ravi, Age: 20, Salary: 50000.0
Name: Sahil, Age: 35, Salary: 40000.0
Name: Sumit, Age: 25, Salary: 60000.0

Sorted by Age:
Name: Ravi, Age: 20, Salary: 50000.0
Name: Sumit, Age: 25, Salary: 60000.0
Name: Sahil, Age: 35, Salary: 40000.0

Sorted by Salary:
Name: Sahil, Age: 35, Salary: 40000.0
Name: Ravi, Age: 20, Salary: 50000.0
Name: Sumit, Age: 25, Salary: 60000.0
```

1. **Aim:** Create a program to use lambda expressions and stream operations to filter students scoring above 75%, sort them by marks, and display their names.

2. Implementation/Code:

```
import java.util.*;
import java.util.stream.Collectors;

class Student {
    String name;
    double percentage;

    public Student(String name, double percentage) {
        this.name = name;
        this.percentage = percentage;
    }

    public String toString() {
        return "Name: " + name + ", Percentage: " + percentage;
    }
}

public class StudentFilterSort {    public static
void main(String[] args) {        List<Student>
students = new ArrayList<>();
students.add(new Student("Shreya", 92.5));
students.add(new Student("Aditi", 85.0));
students.add(new Student("Ansh", 90.0));
students.add(new Student("Raju", 78.5));
System.out.println("Students scoring above 75%,
sorted by marks:");

    students.stream()
        .filter(student -> student.percentage > 75)
        .sorted((s1, s2) -> Double.compare(s2.percentage, s1.percentage))
        .map(student -> student.name)
        .forEach(System.out::println);
    }
}
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

OUTPUT:

```
Students scoring above 75%, sorted by marks:  
Ravi  
Anita  
Aashu  
kunal
```

1. **Aim:** Write a Java program to process a large dataset of products using streams. Perform operations such as grouping products by category, finding the most expensive product in each category, and calculating the average price of all products.

2. **Implementation/code:**

```
import java.util.*; import
java.util.stream.Collectors;

class Product {
    String    name;
    String    category;
    double price;

    public Product(String name, String category, double price) {
this.name = name;        this.category = category;
this.price = price;
    }
    public String toString() {
        return "Name: " + name + ", Category: " + category + ", Price: " + price;
    }
}

public class ProductProcessor {    public static void
main(String[] args) {        List<Product> products = new
ArrayList<>();        products.add(new Product("Laptop",
"Electronics", 999.99));        products.add(new Product("Phone",
"Electronics", 599.99));        products.add(new Product("Shirt",
"Clothing", 29.99));        products.add(new Product("Jacket",
"Clothing", 89.99));        products.add(new Product("Book",
"Stationery", 15.99));        products.add(new Product("Pen",
"Stationery", 2.99));
```

```
System.out.println("Products grouped by category:");
```

```
Map<String, List<Product>> byCategory = products.stream()  
    .collect(Collectors.groupingBy(product -> product.category));
```

```
    byCategory.forEach((category, productList) -> {  
System.out.println(category + ":");  
productList.forEach(System.out::println);  
    });
```

```
System.out.println("\nMost expensive product in each category:");  
Optional<Product> mostExpensive = products.stream()  
    .collect(Collectors.groupingBy(  
product -> product.category,  
    Collectors.maxBy((p1, p2) -> Double.compare(p1.price, p2.price))  
    ));
```


```
mostExpensive.forEach((category, product) ->  
    System.out.println(category + ": " + product.get()));
```

```
double averagePrice = products.stream()  
    .mapToDouble(product -> product.price)  
    .average()  
    .orElse(0.0);
```

```
System.out.println("\nAverage price of all products: $" + String.format("%.2f", averagePrice));
```

```
}
```

```
}
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Output:

```
Products grouped by category:
Clothing:
Name: Shirt, Category: Clothing, Price: 30.0
Name: denim, Category: Clothing, Price: 120.0
Electronics:
Name: Pc, Category: Electronics, Price: 1000.0
Name: Phone, Category: Electronics, Price: 600.0
Stationery:
Name: Book, Category: Stationery, Price: 150.0
Name: Pen, Category: Stationery, Price: 5.0

Most expensive product in each category:
Clothing: Name: denim, Category: Clothing, Price: 120.0
Electronics: Name: Pc, Category: Electronics, Price: 1000.0
Stationery: Name: Book, Category: Stationery, Price: 150.0

Average price of all products: $317.50
```

3. Learning Outcome:

- Understand how to sort by different data types (String, int, double) using lambda expressions
- Gain knowledge of the sorted() method in streams
- Understand how to handle more complex data processing tasks with streams
- Understand how to replace traditional loops with stream-based operations.
- Using how lambda expression works in java.