



Experiment - 6

Name: Akash
Branch: BE-IT
Semester: 6th
Subject: AP LAB-2

UID: 22BET10018
Section: 22BET_IOT_703/A
DOP: 25/02/25
Subject Code: 22ITH-351

1. **Aim:** Maximum Depth of Binary Tree - To determine the maximum depth (or height) of a binary tree, which represents the longest path from the root node to a leaf node.

2. **Objective:**

1. Understand recursive depth-first traversal in binary trees.
2. Calculate the maximum depth by exploring all left and right subtrees.
3. Implement a solution that efficiently handles various tree structures.

3. **Code (C++):**

```
//AKASH_22BET10018
```

```
#include <iostream>
```

```
using namespace std;
```

```
struct TreeNode {  
    int val;  
    TreeNode *left;  
    TreeNode *right;  
    TreeNode(int x) : val(x), left(NULL), right(NULL) {}  
};
```

```
int maxDepth(TreeNode* root) {  
    if (!root) return 0;  
    return 1 + max(maxDepth(root->left), maxDepth(root->right));  
}
```

4. **Aim:** Validate Binary Search Tree- To verify if a given binary tree is a valid Binary Search Tree (BST) where the left subtree nodes are smaller, and the right subtree nodes are larger than the root.
5. **Objective:**
 - Implement an in-order traversal to check the BST property.
 - Ensure the tree satisfies all conditions of a valid BST.
 - Handle edge cases like duplicate values and empty trees.



DEPARTMENT OF COMPUTERSCIENCE & ENGINEERING

Discover. Learn. Empower.

6. Code (C++):

```
//AKASH_22BET10018
#include <iostream>
#include <climits>
using namespace std;

struct TreeNode {
    int val;
    TreeNode *left;
    TreeNode *right;
    TreeNode(int x) : val(x), left(NULL), right(NULL) {}
};

bool isValid(TreeNode* root, long minVal, long maxVal) {
    if (!root) return true;
    if (root->val <= minVal || root->val >= maxVal) return false;
    return isValid(root->left, minVal, root->val) && isValid(root->right, root->val, maxVal);
}

bool isValidBST(TreeNode* root) {
    return isValid(root, LONG_MIN, LONG_MAX);
}
```

7. **Aim:** Symmetric Tree- To determine if a binary tree is symmetric, meaning it is a mirror image of itself around its center.

8. Objective:


- Implement a recursive or iterative solution to check symmetry.
- Compare corresponding left and right subtrees for mirror properties.
- Handle edge cases like empty and single-node trees.

9. Code (C++):

```
//AKASH_22BET10018
#include <iostream>
using namespace std;

struct TreeNode {
    int val;
    TreeNode *left;
    TreeNode *right;
    TreeNode(int x) : val(x), left(NULL), right(NULL) {}
};

bool isMirror(TreeNode* t1, TreeNode* t2) {
    if (!t1 && !t2) return true;
```



DEPARTMENT OF COMPUTERSCIENCE & ENGINEERING

Discover. Learn. Empower.

```
    if (!t1 || !t2) return false;
    return (t1->val == t2->val) && isMirror(t1->left, t2->right) && isMirror(t1->right, t2->left);
}
```

```
bool isSymmetric(TreeNode* root) {
    return isMirror(root, root);
}
```

10. **Aim:** Binary Tree Level Order Traversal- To perform a level-order traversal of a binary tree, returning nodes level by level from top to bottom.

11. **Objective:**

- Implement breadth-first search (BFS) using a queue.
- Traverse the tree level by level.
- Return a list of nodes at each depth.

12. **Code (C++):**

```
//AKASH_22BET10018
```

```
#include <iostream>
```

```
#include <vector>
```

```
#include <queue>
```

```
using namespace std;
```

```
struct TreeNode {
    int val;
    TreeNode *left;
    TreeNode *right;
    TreeNode(int x) : val(x), left(NULL), right(NULL) {}
};
```

```
vector<vector<int>> levelOrder(TreeNode* root) {
    vector<vector<int>> result;
    if (!root) return result;
    queue<TreeNode*> q;
    q.push(root);
    while (!q.empty()) {
        vector<int> level;
        int size = q.size();
        for (int i = 0; i < size; i++) {
            TreeNode* node = q.front(); q.pop();
            level.push_back(node->val);
            if (node->left) q.push(node->left);
            if (node->right) q.push(node->right);
        }
        result.push_back(level);
    }
}
```



DEPARTMENT OF COMPUTERSCIENCE & ENGINEERING

Discover. Learn. Empower.

```
        return result;  
    }
```

13. **Aim:** Convert Sorted Array to Binary Search Tree- To convert a sorted array into a height-balanced Binary Search Tree (BST).

14. **Objective:**

- Implement a recursive approach to divide the array.
- Construct a balanced BST from a sorted array.
- Ensure minimal tree height for optimal performance.

15. **Code (C++):**

```
//AKASH_22BET10018  
#include <iostream>  
#include <vector>  
using namespace std;  
  
struct TreeNode {  
    int val;  
    TreeNode *left;  
    TreeNode *right;  
    TreeNode(int x) : val(x), left(NULL), right(NULL) {}  
};  
  
TreeNode* buildBST(vector<int>& nums, int left, int right) {  
    if (left > right) return nullptr;  
    int mid = left + (right - left) / 2;  
    TreeNode* root = new TreeNode(nums[mid]);  
    root->left = buildBST(nums, left, mid - 1);  
    root->right = buildBST(nums, mid + 1, right);  
    return root;  
}  
  
TreeNode* sortedArrayToBST(vector<int>& nums) {  
    return buildBST(nums, 0, nums.size() - 1);  
}
```

16. **Aim:** Binary Tree Inorder Traversal- To perform an in-order traversal of a binary tree and return the node values in left-root-right order.

17. **Objective:**

- Implement recursive and iterative in-order traversal.
- Collect the values of nodes in the correct order.
- Optimize the algorithm for time and space complexity.



DEPARTMENT OF COMPUTERSCIENCE & ENGINEERING

Discover. Learn. Empower.

18. Code (C++):

```
//AKASH_22BET10018
#include <iostream>
#include <vector>
using namespace std;

struct TreeNode {
    int val;
    TreeNode *left;
    TreeNode *right;
    TreeNode(int x) : val(x), left(NULL), right(NULL) {}
};

void inorder(TreeNode* root, vector<int>& res) {
    if (!root) return;
    inorder(root->left, res);
    res.push_back(root->val);
    inorder(root->right, res);
}

vector<int> inorderTraversal(TreeNode* root) {
    vector<int> res;
    inorder(root, res);
    return res;
}
```

19. **Aim:** Binary Zigzag Level Order Traversal-To perform a zigzag level order traversal of a binary tree, where nodes are traversed left-to-right on one level and right-to-left on the next.

20. Objective:

- Implement a breadth-first search (BFS) approach.
- Alternate the traversal direction on each level.
- Ensure efficient handling of large trees using queues and stacks.

21. Code (C++):

```
//AKASH_22BET10018
#include <iostream>
#include <vector>
#include <queue>
#include <deque>
using namespace std;

struct TreeNode {
    int val;
    TreeNode *left;
```



DEPARTMENT OF COMPUTERSCIENCE & ENGINEERING

Discover. Learn. Empower.

```
TreeNode *right;
TreeNode(int x) : val(x), left(NULL), right(NULL) {}
};

vector<vector<int>> zigzagLevelOrder(TreeNode* root) {
    vector<vector<int>> result;
    if (!root) return result;

    queue<TreeNode*> q;
    q.push(root);
    bool leftToRight = true;

    while (!q.empty()) {
        int size = q.size();
        deque<int> level;

        for (int i = 0; i < size; ++i) {
            TreeNode* node = q.front(); q.pop();
            if (leftToRight) level.push_back(node->val);
            else level.push_front(node->val);
            if (node->left) q.push(node->left);
            if (node->right) q.push(node->right);
        }

        result.push_back(vector<int>(level.begin(), level.end()));
        leftToRight = !leftToRight;
    }

    return result;
}
```

22. **Aim:** Construct Binary Tree from Inorder and Postorder Traversal- To construct a binary tree from given inorder and postorder traversal sequences.

23. **Objective:**

- Reconstruct the tree by identifying root nodes from postorder traversal.
- Use inorder traversal to segment left and right subtrees.
- Ensure correct tree structure and handle all input sizes.

24. **Code (C++):**

```
//AKASH_22BET10018
#include <iostream>
#include <vector>
#include <unordered_map>
using namespace std;
```



DEPARTMENT OF COMPUTERSCIENCE & ENGINEERING

Discover. Learn. Empower.

```
struct TreeNode {
    int val;
    TreeNode *left;
    TreeNode *right;
    TreeNode(int x) : val(x), left(NULL), right(NULL) {}
};
```

```
TreeNode* buildTreeHelper(vector<int>& inorder, vector<int>& postorder, int& postIndex, int inLeft,
int inRight, unordered_map<int, int>& inMap) {
```

```
    if (inLeft > inRight) return nullptr;
```

```
    int rootVal = postorder[postIndex--];
```

```
    TreeNode* root = new TreeNode(rootVal);
```

```
    int inIndex = inMap[rootVal];
```

```
    root->right = buildTreeHelper(inorder, postorder, postIndex, inIndex + 1, inRight, inMap);
```

```
    root->left = buildTreeHelper(inorder, postorder, postIndex, inLeft, inIndex - 1, inMap);
```

```
    return root;
```

```
}
```

```
TreeNode* buildTree(vector<int>& inorder, vector<int>& postorder) {
```

```
    unordered_map<int, int> inMap;
```

```
    for (int i = 0; i < inorder.size(); ++i) {
```

```
        inMap[inorder[i]] = i;
```

```
    }
```

```
    int postIndex = postorder.size() - 1;
```

```
    return buildTreeHelper(inorder, postorder, postIndex, 0, inorder.size() - 1, inMap);
```

```
}
```

25. **Aim:** Kth Smallest Element in a BST- To find the kth smallest element in a Binary Search Tree (BST).

26. Objective:

- Implement in-order traversal to retrieve elements in sorted order.
- Efficiently find the kth element during traversal.
- Handle large trees while maintaining optimal performance.

27. Code (C++):

```
//AKASH_22BET10018
```

```
#include <iostream>
```

```
using namespace std;
```

```
struct TreeNode {
```

```
    int val;
```



DEPARTMENT OF COMPUTERSCIENCE & ENGINEERING

Discover. Learn. Empower.

```
TreeNode *left;
TreeNode *right;
TreeNode(int x) : val(x), left(NULL), right(NULL) {}
};
```

```
void inorder(TreeNode* root, int& k, int& result) {
    if (!root) return;
    inorder(root->left, k, result);
    if (--k == 0) {
        result = root->val;
        return;
    }
    inorder(root->right, k, result);
}
```

```
int kthSmallest(TreeNode* root, int k) {
    int result = -1;
    inorder(root, k, result);
    return result;
}
```

28. **Aim:** Populating Next Right Pointers in Each Node-To populate each node's next pointer to its right neighbor in a perfect binary tree.

29. **Objective:**

- Use level-order traversal to connect nodes on the same level.
- Optimize space by linking nodes without using extra storage.
- Handle all levels and edge cases efficiently.

30. **Code (C++):**

```
//AKASH_22BET10018
#include <iostream>
#include <queue>
using namespace std;

struct Node {
    int val;
    Node* left;
    Node* right;
    Node* next;
    Node(int x) : val(x), left(NULL), right(NULL), next(NULL) {}
};
```

```
Node* connect(Node* root) {
    if (!root) return nullptr;
    queue<Node*> q;
```




DEPARTMENT OF COMPUTERSCIENCE & ENGINEERING

Discover. Learn. Empower.

```
q.push(root);

while (!q.empty()) {
    int size = q.size();
    Node* prev = nullptr;

    for (int i = 0; i < size; ++i) {
        Node* node = q.front();
        q.pop();
        if (prev) prev->next = node;
        prev = node;

        if (node->left) q.push(node->left);
        if (node->right) q.push(node->right);
    }
}

return root;
}
```