

## 1 Longest Nice Substring

```
class Solution {
public:
    string longestNiceSubstring(string s) {
        if (s.length() < 2)
            return "";
        unordered_set<char> seen{s.begin(), s.end()};
        for (int i = 0; i < s.size(); ++i)
            if (!seen.contains(toggleCase(s[i]))) {
                const string prefix = longestNiceSubstring(s.substr(0, i));
                const string suffix = longestNiceSubstring(s.substr(i + 1));
                return prefix.length() >= suffix.length() ? prefix : suffix;
            }

        return s;
    }
private:
    char toggleCase(char c) {
        return islower(c) ? toupper(c) : tolower(c);
    }
};
```



leetcode.com/problems/longest-nice-substring/submissions/1549660280/

Problem List < > < Run < Submit < < < Premium

Description Accepted Editorial Solutions Submissions

All Submissions

Accepted 73 / 73 testcases passed  
Aditee\_Agrawal submitted at Feb 20, 2025 19:00

**Runtime** 7 ms | Beats 65.20%  
**Memory** 14.09 MB | Beats 69.79%

Analyze Complexity

Code C++

```
class Solution {
public:
    string longestNiceSubstring(string s) {
        if (s.length() < 2)
            return "";
        unordered_set<char> seen(s.begin(), s.end());
        for (int i = 0; i < s.size(); ++i)
            if (!seen.contains(toggleCase(s[i]))) {
                return "";
            }
    }
};
```

Testcase > Test Result

Accepted Runtime: 0 ms

Case 1 Case 2 Case 3

Input

s = "YazaAay"

Output

"aAa"


Expected

.. ..

61°F Heavy rain 7:00 PM 2/20/2025

## 2. Reverse bits

```
class Solution {  
  
public:  
  
    uint32_t reverseBits(uint32_t n) {  
  
        uint32_t ans = 0;  
  
        for (int i = 0; i < 32; ++i)  
            if (n >> i & 1)  
                ans |= 1 << 31 - i;  
  
        return ans;  
    }  
};
```




### 3 Number of 1 bit

```
class Solution {
public:
    int hammingWeight(uint32_t n) {
        int ans = 0;


        for (int i = 0; i < 32; ++i)
            if ((n >> i) & 1)
                ++ans;

        return ans;
    }
};
```



## 4. maximum Subarray

```
class Solution {  
  
public:  
  
    int maxSubArray(vector<int>& nums) {  
  
        vector<int> dp(nums.size());  
  
        dp[0] = nums[0];  
  
        for (int i = 1; i < nums.size(); ++i)  
            dp[i] = max(nums[i], dp[i - 1] + nums[i]);  
  
        return ranges::max(dp);  
    }  
};
```



## 5. Search a 2D Matrix

```
class Solution {
public:
    bool searchMatrix(vector<vector<int>>& matrix, int target) {
        if (matrix.empty())
            return false;
        const int m = matrix.size();
        const int n = matrix[0].size();
        int l = 0;
        int r = m * n;
        while (l < r) {
            const int mid = (l + r) / 2;
            const int i = mid / n;
            const int j = mid % n;
            if (matrix[i][j] == target)
                return true;
            if (matrix[i][j] < target)
                l = mid + 1;
            else
                r = mid;
        }
        return false;
    }
};
```

**Accepted** 133 / 133 testcases passed  
Aditee Agrawal submitted at Feb 20, 2025 19:11

**Runtime** 0 ms Beats 100.00%  
**Memory** 13.30 MB Beats 75.99%

```

class Solution {
public:
    bool searchMatrix(vector<vector<int>>& matrix, int target) {
        if (matrix.empty())
            return false;

        const int m = matrix.size();
        const int n = matrix[0].size();
        int l = 0;
        int r = m * n;

        while (l < r) {
            const int mid = (l + r) / 2;
            const int i = mid / n;
            const int j = mid % n;
            if (matrix[i][j] == target)
                return true;
            if (matrix[i][j] < target)
                l = mid + 1;
            else
                r = mid;
        }
    }
}

```

**Accepted** Runtime: 0 ms  
Case 1 Case 2

Input: matrix = [[1, 3, 5, 7], [10, 11, 16, 20], [22, 25, 28, 31]]

## 6. Super Pow

```

class Solution {
public:
    int modPow(int a, int b, int mod) {
        int result = 1;
        a %= mod;
        while (b > 0) {
            if (b % 2 == 1) {
                result = (result * a) % mod;
            }
            a = (a * a) % mod;
            b /= 2;
        }
        return result;
    }
    int superPow(int a, vector<int>& b) {
        const int mod = 1337;
        int result = 1;
        for (int digit : b) {
            result = modPow(result, 10, mod) * modPow(a, digit, mod) % mod;
        }
        return result;
    }
};

```

Problem List

RunSubmit

Premium

DescriptionAcceptedEditorialSolutionsSubmissions

All Submissions

Accepted57 / 57 testcases passed

Aditee\_Agrawal submitted at Feb 20, 2025 19:14

Solution


Runtime

2 ms | Beats 35.77%

Analyze Complexity

Memory

15.27 MB | Beats 52.85%



CodeC++

```
class Solution {
public:
    int superPow(int a, vector<int>& b) {
        int ans = 1;
        a %= kMod;
        for (const int i : b) {
            ans = modPow(ans, 10) * modPow(a, i) % kMod;
        }
        return ans;
    }
private:
    static constexpr int kMod = 1337;
    long modPow(long x, long n) {
        if (n == 0)
            return 1;
        if (n % 2 == 1)
            return x * modPow(x % kMod, (n - 1)) % kMod;
        return modPow(x * x % kMod, (n / 2)) % kMod;
    }
};
```

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1Case 2Case 3

Input

a =

2