



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Experiment -9

Student Name: Vipul Madotra
Branch: BE-CSE

Semester: 6th

Subject Name: Project-Based Learning in
Java with Lab

UID: 22BCS13889
Section/Group: IOT_NTPP_603-B
Date of
Performance: 17/03/2025
Subject Code: 22CSH-359

9.1.1.Aim: To demonstrate dependency injection using Spring Framework with Java-based configuration.

9.1.2 Objective:

Define Course and Student classes.

Use Configuration and Bean annotations to inject dependencies. Load Spring context and print student details.

9.1.3 Code: // Course.java
public class Course {
private String courseName;
private String duration;

```
    public Course(String courseName, String duration) {  
        this.courseName = courseName;    this.duration =  
        duration;  
    }
```

```
    public String getCourseName() { return courseName; }  
    public String getDuration() { return duration; }
```

```
    @Override  
    public String toString() {  
        return "Course: " + courseName + ", Duration: " + duration;  
    }  
}
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
// Student.java public
class Student {    private
String name;    private
Course course;    public
Student(String name,
Course course) {
    this.name = name;
this.course = course;
}

    public void showDetails() {
        System.out.println("Student: " + name);
        System.out.println(course);
    }
}

} // AppConfig.java
import org.springframework.context.annotation.*;

@Configuration public
class AppConfig {
    @Bean
    public Course course() {
        return new Course("Java", "3 months");
    }

    @Bean
    public Student student() {
        return new Student("Aman", course());
    }
}

} // MainApp.java
import org.springframework.context.ApplicationContext;
import org.springframework.context.annotation.AnnotationConfigApplicationContext;

public class MainApp {
    public static void main(String[] args) {
        ApplicationContext context = new
        AnnotationConfigApplicationContext(AppConfig.class);
        Student student = context.getBean(Student.class);
        student.showDetails();
    } } }
```

Output:

```
Student: Sarthak  
Course: Java, Duration: 3 months
```

9.2.1 Aim: To perform CRUD operations on a Student entity using Hibernate ORM with MySQL.

Objective: Define Course and Student classes.

Use Configuration and Bean annotations to inject dependencies.

Load Spring context and print student details.

9.2.2 Code:

```
<hibernate-configuration>  
  <session-factory>  
    <property  
name="hibernate.connection.driver_class">com.mysql.cj.jdbc.Driver</property>  
    <property  
name="hibernate.connection.url">jdbc:mysql://localhost:3306/testdb</property>  
    <property name="hibernate.connection.username">root</property>  
    <property name="hibernate.connection.password">password</property>  
    <property  
name="hibernate.dialect">org.hibernate.dialect.MySQL8Dialect</property>  
    <property name="hibernate.hbm2ddl.auto">update</property>  
    <mapping class="Student"/>  
  </session-factory>  
</hibernate-configuration>
```

```
import javax.persistence.*;
```

Entity

```
public class Student {
```

```
    Id
```

```
    GeneratedValue(strategy = GenerationType.IDENTITY)
```

```
    private int id;    private String name;
```

```
private int age;

public Student() {}
public Student(String name, int age) {
this.name = name;    this.age = age;
}

// Getters, setters, toString
} import
org.hibernate.SessionFactory;
import org.hibernate.cfg.Configuration;

public class HibernateUtil {
private static final SessionFactory sessionFactory;
static
{
    sessionFactory = new Configuration().configure().buildSessionFactory();
}

public static SessionFactory getSessionFactory() {
return sessionFactory;
}
}

import org.hibernate.*;

public class MainCRUD {
public static void main(String[] args) {
    Session session = HibernateUtil.getSessionFactory().openSession();

    // Create
    Transaction tx = session.beginTransaction();
    Student s1 = new Student("Aman", 22);
    session.save(s1);
    tx.commit();

    // Read
    Student student = session.get(Student.class, 1);
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
System.out.println(student);
```

```
// Update
```

```
tx = session.beginTransaction();
```

```
student.setAge(23);
```

```
session.update(student);      tx.commit();
```

```
// Delete
```

```
tx = session.beginTransaction();
```

```
session.delete(student);
```

```
tx.commit();  
  
session.close();  
}  
}
```

9.2.3 Output:

```
Student{id=1, name='Sallu', age=22}  
Updated age to 23  
Deleted student with id 1
```

9.3.1 Aim: To implement a banking system using Spring and Hibernate that ensures transaction consistency during fund transfers.

Objective:

Integrate Spring + Hibernate.

Handle transactions atomically (rollback on failure).

Demonstrate success and failure cases.

Code:

```
import javax.persistence.*;
```

Entity

```
public class Account {
```

```
    @Id    private int  
    accountId;    private String  
    holderName;  
    private double balance;
```

```
    // Constructors, getters, setters  
}
```

```
import javax.persistence.*;  
import java.util.Date;
```

@Entity

```
public class BankTransaction {
```

```
    @Id  
    @GeneratedValue(strategy = GenerationType.IDENTITY)  
    private int txnId;    private int fromAcc;    private int toAcc;  
    private double amount;  
    private Date txnDate = new Date();
```

```
    // Constructors, getters, setters  
}
```

```
import org.hibernate.*;  
import org.springframework.transaction.annotation.Transactional;
```

```
public class BankService {
    private SessionFactory sessionFactory;

    public BankService(SessionFactory sessionFactory) {
        this.sessionFactory = sessionFactory;
    }

    @Transactional
    public void transferMoney(int fromId, int toId, double amount) {
        Session session = sessionFactory.getCurrentSession();

        Account from = session.get(Account.class, fromId);
        Account to = session.get(Account.class, toId);

        if (from.getBalance() < amount) {
            throw new RuntimeException("Insufficient Balance");
        }

        from.setBalance(from.getBalance() - amount);
        to.setBalance(to.getBalance() + amount);

        session.update(from);
        session.update(to);

        BankTransaction txn = new BankTransaction(fromId, toId, amount);
        session.save(txn);
    }

    @Configuration
    @EnableTransactionManagement public
    class AppConfig {
        @Bean
        public DataSource dataSource() {
            DriverManagerDataSource ds = new DriverManagerDataSource();
        }
    }
}
```



```
        ds.setDriverClassName("com.mysql.cj.jdbc.Driver");  
ds.setUrl("jdbc:mysql://localhost:3306/testdb");  
ds.setUsername("root");        ds.setPassword("password");  
    return ds;  
}
```

```
@Bean  
public LocalSessionFactoryBean sessionFactory() {  
    LocalSessionFactoryBean lsf = new LocalSessionFactoryBean();  
lsf.setDataSource(dataSource());  
lsf.setPackagesToScan("your.package");    Properties props =  
new Properties();  
    props.put("hibernate.dialect", "org.hibernate.dialect.MySQL8Dialect");  
props.put("hibernate.hbm2ddl.auto", "update");  
    lsf.setHibernateProperties(props);  
return lsf;  
}
```

```
@Bean  
public HibernateTransactionManager transactionManager(SessionFactory sf) {  
return new HibernateTransactionManager(sf);  
}
```

```
@Bean  
public BankService bankService(SessionFactory sf) {  
return new BankService(sf);  
}  
}
```

```
public class MainApp {  
    public static void main(String[] args) {  
        AnnotationConfigApplicationContext ctx = new  
AnnotationConfigApplicationContext(AppConfig.class);  
        BankService service = ctx.getBean(BankService.class);  
        try  
{  
            service.transferMoney(101, 102, 500);  
}
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
        System.out.println("Transaction Successful!");  
    } catch (Exception e) {  
        System.out.println("Transaction Failed: " + e.getMessage());  
    }
```



DEPARTMENT OF

Discover Learn Empower

COMPUTER SCIENCE & ENGINEERING

```
ctx.close();  
}
```

```
Transaction Successful!  
OR  
Transaction Failed: Insufficient Balance
```

```
}
```

OUTPUT