



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Experiment 1.2

Student Name: Tushar

Branch: CSE

Semester: 6th

Subject: AP

UID:22BCS10372

Section: NTPP-603(A)

Date of Performance: 15/01/2025

Subject Code:22CSP-351

Aim:

Problem 1.2.1: Two Sum

- **Problem Statement:** Given an array of integers `nums` and an integer `target`, return the indices of the two numbers such that they add up to `target`. Each input has exactly one solution, and you cannot use the same element twice.

Problem 1.2.2: Jump Game II

- **Problem Statement:** You are given a 0-indexed array `nums` of length `n`. You are initially positioned at `nums[0]`. Each element `nums[i]` represents the maximum length of a forward jump from index `i`. Return the minimum number of jumps to reach `nums[n - 1]`.

Problem 1.2.3: Simplify Path

- **Problem Statement:** Given a string `path`, which is an absolute path to a file or directory in a Unix-style file system, convert it to the simplified canonical path.

Algorithm:

1. Initialize an empty hash map (dict).
2. Iterate through the `nums` array:
 - For each element `num`, calculate the complement: `complement = target - num`.
 - Check if the complement exists in the hash map:
 - If it does, return the indices of the complement and the current number.
 - If it doesn't, add the current number and its index to the hash map.
3. Return the indices of the two numbers that add up to the target.

Code: 1.2.1

```
</> Code
Python3  Auto
class Solution:
    def twoSum(self, nums, target):
        seen = {}
        for i, num in enumerate(nums):
            complement = target - num
            if complement in seen:
                return [seen[complement], i]
            seen[num] = i
# ROSH
solution = Solution()
nums1 = [2, 7, 11, 15]
target1 = 9
print(solution.twoSum(nums1, target1))
nums2 = [3, 2, 4]
target2 = 6
print(solution.twoSum(nums2, target2))
nums3 = [3, 3]
target3 = 6
print(solution.twoSum(nums3, target3))
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Output:

✓ Testcase | >_ Test Result

Accepted Runtime: 0 ms

• Case 1 • Case 2 • Case 3

Input

```
nums =  
[2, 7, 11, 15]
```

```
target =  
9
```

Stdout

```
[0, 1]  
[1, 2]  
[0, 1]
```

Output

```
[0, 1]
```

Expected

```
[0, 1]
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

☒ Testcase | [> Test Result](#)

Accepted Runtime: 0 ms

• Case 1 • **Case 2** • Case 3

Input

nums =
[3,2,4]

target =
6

Output

[1,2]

Expected

[1,2]

☒ Testcase | [> Test Result](#)

Accepted Runtime: 0 ms

• Case 1 • Case 2 • **Case 3**

Input

nums =
[3,3]

target =
6

Output

[0,1]

Expected

[0,1]

CODE: 1.2.2

```
</> Code
Python3  Auto
class Solution:
    def jump(self, nums):
        n = len(nums)
        jumps = 0
        current_end = 0
        farthest = 0

        for i in range(n - 1):
            farthest = max(farthest, i + nums[i])
            if i == current_end:
                jumps += 1
                current_end = farthest
                if current_end >= n - 1:
                    break

        return jumps

# ROSH
solution = Solution()

nums1 = [2, 3, 1, 1, 4]
print(solution.jump(nums1))

nums2 = [2, 3, 0, 1, 4]
print(solution.jump(nums2))
```

OUTPUT:



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

☒ Testcase | [> Test Result](#)

Accepted Runtime: 0 ms

• Case 1 • Case 2

Input

```
nums =  
[2, 3, 1, 1, 4]
```

Stdout

```
2  
2
```

Output

```
2
```

Expected

```
2
```

☒ Testcase | [> Test Result](#)

Accepted Runtime: 0 ms

• Case 1 • Case 2

Input

```
nums =  
[2, 3, 0, 1, 4]
```

Output

```
2
```

Expected

```
2
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

CODE: 1.2.3

</> Code

Python3 ▾ 🔒 Auto

```
2     def simplifyPath(self, path):
3         stack = []
4         parts = path.split('/')
5         for part in parts:
6             if part == '..':
7                 if stack:
8                     stack.pop()
9             elif part and part != '.':
10                stack.append(part)
11        return '/' + '/'.join(stack)
12
13    # ROSH
14    solution = Solution()
15
16    path1 = "/home/"
17    print(solution.simplifyPath(path1))
18
19    path2 = "/home//foo/"
20    print(solution.simplifyPath(path2))
21
22    path3 = "/home/user/Documents/../Pictures"
23    print(solution.simplifyPath(path3))
24
25    path4 = "/../"
26    print(solution.simplifyPath(path4))
27
28    path5 = "/.../a/../b/c/../d/./"
29    print(solution.simplifyPath(path5))
```

OUTPUT:



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

☒ Testcase | [Test Result](#)

Accepted Runtime: 0 ms

• Case 1 • Case 2 • Case 3 • Case 4 • Case 5

Input

```
path =  
"/home/"
```

Stdout

```
/home  
/home/foo  
/home/user/Pictures  
/  
/.../b/d
```

Output

```
"/home"
```

Expected

```
"/home"
```

☒ Testcase | [Test Result](#)

Accepted Runtime: 0 ms

• Case 1 • **Case 2** • Case 3 • Case 4 • Case 5

Input

```
path =  
"/home//foo/"
```

Output

```
"/home/foo"
```

Expected

```
"/home/foo"
```




DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

☒ Testcase | [>_ Test Result](#)

Accepted Runtime: 0 ms

• Case 1 • Case 2 • **Case 3** • Case 4 • Case 5

Input

```
path =  
"/home/user/Documents/../Pictures"
```

Output

```
"/home/user/Pictures"
```

Expected

```
"/home/user/Pictures"
```

☒ Testcase | [>_ Test Result](#)

Accepted Runtime: 0 ms

• Case 1 • Case 2 • Case 3 • **Case 4** • Case 5

Input

```
path =  
"/../"
```

Output

```
"/"
```

Expected

```
"/"
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

☒ Testcase | [> Test Result](#)

Accepted Runtime: 0 ms

- Case 1
- Case 2
- Case 3
- Case 4
- **Case 5**

Input

```
path =  
"/.../a/..b/c/...d/./"
```

Output

```
"/.../b/d"
```

Expected

```
"/.../b/d"
```