

# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## Medium problems for Average Learners

**Student Name:** Nayan Kumar

**UID:** 22BCS16748

**Branch:** BE-CSE

**Section/Group:** NTPP\_602-A

**Semester:** 6

**Date of Performance:** 10-04-25

**Subject Name:** Advanced Programming Lab-2

**Subject Code:** 22CSH-359

### Problem-1

1. **Title:** Palindrome Number
2. **Objective:** To determine whether a given integer is a palindrome (reads the same forward and backward).
3. **Algorithm:**
  - Input: An integer x
  - Edge Case:
    - If  $x < 0$ , it cannot be a palindrome.
  - Convert to String (or use digit reverse logic):
    - Convert number to string and compare it with its reverse.
  - Output:
    - Return true if both match, else false.
4. **Implementation/Code:**


```
class Solution {  
    public boolean isPalindrome(int x) {  
        if (x < 0) return false;  
        String s = Integer.toString(x);  
        StringBuilder rev = new StringBuilder(s).reverse();  
        return s.equals(rev.toString());  
    }  
}
```

5. **Output:**

- Input: 121 → Output: true
- Input: -121 → Output: false

6. **Time Complexity:**  $O(n)$

7. **Space Complexity:**  $O(n)$



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## Problem-2

### 1. Title: Two Sum

2. Objective: To find the indices of two numbers in an array that sum up to a specific target value.

### 3. Algorithm:

- Input: Array nums, Integer target
- Use Hash Map:
  - Store each number and its index as you iterate.
  - Check if (target - current number) exists in the map.
- Output: Return the pair of indices.

### 4. Implementation/Code:


```
class Solution {
    public int[] twoSum(int[] nums, int target) {
        Map<Integer, Integer> map = new HashMap<>();
        for (int i = 0; i < nums.length; i++) {
            int diff = target - nums[i];
            if (map.containsKey(diff)) {
                return new int[]{map.get(diff), i};
            }
            map.put(nums[i], i);
        }
        return new int[]{}; // No solution found
    }
}
```

### 5. Output:

- Input: `nums = [2, 7, 11, 15]`, `target = 9` → Output: `[0, 1]`

6. Time Complexity:  $O(n)$

7. Space Complexity:  $O(n)$



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## Problem-3

### 1. Title: Longest Substring Without Repeating Characters

2. Objective: To find the length of the longest substring with all unique characters.

### 3. Algorithm:

- Input: A string s
- Sliding Window + Set:
  - Use two pointers (left, right) to maintain a window of non-repeating characters.
  - Move window when duplicate is found.
- Output: Return max length found.

### 4. Implementation/Code:


```
class Solution {  
    public int lengthOfLongestSubstring(String s) {  
        Set<Character> set = new HashSet<>();  
        int left = 0, maxLen = 0;  
  
        for (int right = 0; right < s.length(); right++) {  
            while (set.contains(s.charAt(right))) {  
                set.remove(s.charAt(left++));  
            }  
            set.add(s.charAt(right));  
            maxLen = Math.max(maxLen, right - left + 1);  
        }  
        return maxLen;  
    }  
}
```

### 5. Output:

• Input: "abcabcbb" → Output: 3

8. Time Complexity:  $O(n)$

9. Space Complexity:  $O(\min(n,m))$



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## 10. Learning Outcomes:

- Understood how to handle edge cases like negatives.
- Practiced string operations to simplify integer problems.
- Applied hash map for constant-time lookup.
- Strengthened logic for pair-sum problems.
- Mastered sliding window technique.
- Learned to track seen characters efficiently with sets.