Experiment 7

Student Name: Premprakash Motwani   **UID:** 22BCS15179

Branch: BE-CSE   **Section/Group:** KPIT-902/B

Semester: 6th   **Date:** 28/03/2025

Subject Name: Project Based Learning in Java with Lab

Subject Code: 22CSH-359

7.1.1.Aim: Create a Java program to connect to a MySQL database and fetch data from a single table. The program should: Use DriverManager and Connection objects. Retrieve and display all records from a table named Employee with columns EmpID, Name, and Salary.

7.1.2 Objective: To develop a Java program that connects to a MySQL database, retrieves data from the Employee table, and displays all records, demonstrating basic JDBC connectivity and data retrieval operations.

7.1.3 Code: import
java.sql.*;

```java
public class FetchEmployeeData { public
    static void main(String[] args) {
        String url = "jdbc:mysql://localhost:3306/testdb";
        String user = "root";
        String password = "password";

        String query = "SELECT EmpID, Name, Salary FROM Employee";

        try {
            // Load MySQL JDBC driver
            Class.forName("com.mysql.cj.jdbc.Driver");

            // Establish connection
            Connection con = DriverManager.getConnection(url, user, password);
            System.out.println("Connected to the database!");
```

```java
            // Create statement and execute query
            Statement stmt = con.createStatement();
            ResultSet rs = stmt.executeQuery(query);

            // Display results
            System.out.println("\nEmployee Records:");
            System.out.println(" -------------------------");
            System.out.printf("%-10s    %-20s    %-10s%n", "EmpID", "Name", "Salary");
            System.out.println(" ----------------------    ");

            while  (rs.next())  {  int  empID  =
                rs.getInt("EmpID");  String  name  =
                rs.getString("Name"); double  salary =
                rs.getDouble("Salary");

                System.out.printf("%-10d %-20s %-10.2f%n", empID, name, salary);
            }

            // Close resources
            rs.close();
            stmt.close();
            con.close();
            System.out.println("\nConnection closed.");

        } catch (ClassNotFoundException e) {
            System.out.println("MySQL Driver not found: " + e.getMessage());
        } catch (SQLException e) {
            System.out.println("SQL Error: " + e.getMessage()); }
    }
}
```

7.1.4 Output:

```
(base) PS C:\Users\virat\OneDrive\Desktop\java exp7> java -cp ".;lib/mysql-connector-j-9.2.0.jar" FetchEmployeeD
ata
>>
Connected to the database!

Employee Records:
-------------------------------------
EmpID      Name              Salary
-------------------------------------
1          Alice             50000.00
2          Bob               60000.00
3          Charlie           55000.00

Connection closed.
(base) PS C:\Users\virat\OneDrive\Desktop\java exp7>
```

7.2.1 Aim: Build a program to perform CRUD operations (Create, Read, Update, Delete) on a database table Product with columns: ProductID, ProductName, Price, and Quantity. The program should include: Menu-driven options for each operation. Transaction handling to ensure data integrity.

7.2.2 Objective: To develop a Java program that connects to a MySQL database and performs CRUD operations (Create, Read, Update, Delete) on the Product table. The program ensures data integrity by using transaction handling and provides a menu-driven interface for user-friendly interaction.

7.2.3 Code:

```java
import java.sql.*; import
java.util.Scanner;

public class ProductCRUD {

    private static final String URL = "jdbc:mysql://localhost:3306/ProductDB"; private
    static final String USER = "root";
    private static final String PASSWORD = "password";

    public static void main(String[] args) { Scanner
        scanner = new Scanner(System.in);

        try (Connection conn = DriverManager.getConnection(URL, USER, PASSWORD)) {
            Class.forName("com.mysql.cj.jdbc.Driver");

            System.out.println("Connected to the database!");

            boolean exit = false;
```

```java
        while (!exit) {
            System.out.println("\n=== Product CRUD Operations ===");
            System.out.println("1. Create Product");
            System.out.println("2. Read Products");
            System.out.println("3. Update Product");
            System.out.println("4. Delete Product");
            System.out.println("5. Exit");
            System.out.print("Choose an option: "); int

            choice        =        scanner.nextInt();

            scanner.nextLine(); switch (choice) { case

            1 -> createProduct(conn, scanner); case 2 -

            >   readProducts(conn);   case   3   ->

            updateProduct(conn, scanner); case 4 ->

            deleteProduct(conn, scanner);

                case 5 -> exit = true;
                default -> System.out.println("Invalid option. Try again.");
            }
        }

    } catch (ClassNotFoundException e) {
        System.out.println("MySQL Driver not found: " + e.getMessage());
    } catch (SQLException e) {
        System.out.println("SQL Error: " + e.getMessage()); }

    scanner.close();
}

private static void createProduct(Connection conn, Scanner scanner) throws SQLException {
    System.out.print("Enter product name: ");
    String name = scanner.nextLine();
    System.out.print("Enter  price:  ");
    double price = scanner.nextDouble();
```

```java
        System.out.print("Enter quantity: ");
        int quantity = scanner.nextInt();

        String query = "INSERT INTO Product (ProductName, Price, Quantity) VALUES (?, ?, ?)";

        try    (PreparedStatement    pstmt    =    conn.prepareStatement(query))    {
            conn.setAutoCommit(false);

            pstmt.setString(1, name);
            pstmt.setDouble(2,
            price);    pstmt.setInt(3,
            quantity);

            int rows = pstmt.executeUpdate(); conn.commit();

            System.out.println(rows + " product(s) inserted successfully!");
        } catch (SQLException e) { conn.rollback();
            System.out.println("Transaction rolled back due to error: " + e.getMessage());
        } finally {
        conn.setAutoCommit(true); }
    }

    private static void readProducts(Connection conn) throws SQLException { String
        query = "SELECT * FROM Product";

        try (Statement stmt = conn.createStatement();
            ResultSet rs = stmt.executeQuery(query)) {

            System.out.println("\nProduct Records:");
            System.out.println(" ------------------------------------------------ ");
            System.out.printf("%-10s %-20s %-10s %-10s%n", "ProductID", "ProductName",
"Price", "Quantity");
            System.out.println(" -----------------------------");

            while (rs.next()) { int id =
                rs.getInt("ProductID");
```

```java
            String name = rs.getString("ProductName");
            double  price  =  rs.getDouble("Price");  int
            quantity = rs.getInt("Quantity");

            System.out.printf("%-10d %-20s %-10.2f %-10d%n", id, name, price, quantity);
        }
    }
}


    private static void updateProduct(Connection conn, Scanner scanner) throws SQLException
{
        System.out.print("Enter product ID to update: "); int
        id = scanner.nextInt();
        scanner.nextLine();

        System.out.print("Enter new name: ");
        String name = scanner.nextLine();
        System.out.print("Enter new price: ");
        double  price  =  scanner.nextDouble();
        System.out.print("Enter new quantity: ");
        int quantity = scanner.nextInt();

        String query = "UPDATE Product SET ProductName = ?, Price = ?, Quantity = ? WHERE
ProductID = ?";

        try      (PreparedStatement      pstmt      =      conn.prepareStatement(query))      {
            conn.setAutoCommit(false);

            pstmt.setString(1,  name);
            pstmt.setDouble(2,
            price);       pstmt.setInt(3,
            quantity);   pstmt.setInt(4,
            id);

            int rows = pstmt.executeUpdate(); conn.commit();

            System.out.println(rows + " product(s) updated successfully!");

        } catch (SQLException e) { conn.rollback();
```

```java
            System.out.println("Transaction rolled back due to error: " + e.getMessage());
        } finally {
        conn.setAutoCommit(true); }
    }

    private static void deleteProduct(Connection conn, Scanner scanner) throws
        SQLException {
        System.out.print("Enter product ID to delete: "); int
        id = scanner.nextInt();

        String query = "DELETE FROM Product WHERE ProductID = ?";

        try    (PreparedStatement    pstmt    =    conn.prepareStatement(query))    {
            conn.setAutoCommit(false);

            pstmt.setInt(1, id);
            int rows = pstmt.executeUpdate();
            conn.commit(); System.out.println(rows + "
            product(s) deleted successfully!");

        } catch (SQLException e) { conn.rollback();
            System.out.println("Transaction rolled back due to error: " + e.getMessage());
        } finally { conn.setAutoCommit(true);
        }
    }
}
```

7.2.4 Output:

```
(base) PS C:\Users\virat\OneDrive\Desktop\java exp7> java -cp ".;lib/mysql-connector-j-9.2.0.jar
" ProductCRUD
>>
Connected to the database!

=== Product CRUD Operations ===
1. Create Product
2. Read Products
3. Update Product
4. Delete Product
5. Exit
Choose an option: 2

Product Records:
---------------------------------------------------
ProductID  ProductName         Price       Quantity
---------------------------------------------------
1          Laptop              75000.00    10
2          Mobile Phone        30000.00    25
3          Tablet              20000.00    15
4          Headphones          5000.00     50
5          Smartwatch          12000.00    30
6          Camera              45000.00    12
```

7.3.1 Aim: Develop a Java application using JDBC and MVC architecture to manage student data. The application should: Use a Student class as the model with fields like StudentID, Name, Department, and Marks. Include a database table to store student data. Allow the user to perform CRUD operations through a simple menu-driven view. Implement database operations in a separate controller class.

7.3.2 Objective: The objective of this program is to develop a menu-driven Java application that allows users to add employee details, display all stored employees, and exit the program. Employee details, including ID, name, designation, and salary, are stored persistently in a file using serialization.

7.3.3 Code:

StudentController.java package controller;

import   model.Student;
import java.sql.*; import
java.util.ArrayList;
import java.util.List;

public class StudentController {

```java
private static final String URL = "jdbc:mysql://localhost:3306/StudentDB"; private
static final String USER = "root";
private static final String PASSWORD = "rishuraman1@V";

// Method to create a new student
public void createStudent(Student student) throws SQLException {
    String query = "INSERT INTO Student (Name, Department, Marks) VALUES (?, ?, ?)";

    try (Connection conn = DriverManager.getConnection(URL, USER, PASSWORD);
        PreparedStatement pstmt = conn.prepareStatement(query)) {

        pstmt.setString(1,      student.getName());
        pstmt.setString(2,
        student.getDepartment());
        pstmt.setDouble(3, student.getMarks());

        pstmt.executeUpdate();
        System.out.println("Student added successfully!");
    }
}

// Method to retrieve all students
public List<Student> getAllStudents() throws SQLException {
    List<Student> students = new ArrayList<>(); String
    query = "SELECT * FROM Student";

    try (Connection conn = DriverManager.getConnection(URL, USER, PASSWORD);
        Statement stmt = conn.createStatement();
        ResultSet rs = stmt.executeQuery(query)) {

        while       (rs.next())         {
            students.add(new        Student(
            rs.getInt("StudentID"),
            rs.getString("Name"),
            rs.getString("Department"),
                rs.getDouble("Marks")
            ));
        } }
    return students;
```

```java
    }

    // Method to update student data
    public void updateStudent(Student student) throws SQLException {
        String query = "UPDATE Student SET Name = ?, Department = ?, Marks = ? WHERE StudentID = ?";

        try (Connection conn = DriverManager.getConnection(URL, USER, PASSWORD);
            PreparedStatement pstmt = conn.prepareStatement(query)) {

            pstmt.setString(1,      student.getName());
            pstmt.setString(2,
            student.getDepartment());
            pstmt.setDouble(3,      student.getMarks());
            pstmt.setInt(4, student.getStudentID());

            int rows = pstmt.executeUpdate();
            if (rows > 0) {
                System.out.println("Student updated successfully!");
            } else {
                System.out.println("Student not found."); }
        }
    }
    // Method to delete a student
    public void deleteStudent(int studentID) throws SQLException {
        String query = "DELETE FROM Student WHERE StudentID = ?";

        try (Connection conn = DriverManager.getConnection(URL, USER, PASSWORD);
            PreparedStatement pstmt = conn.prepareStatement(query)) {

            pstmt.setInt(1,   studentID);   int
            rows = pstmt.executeUpdate(); if
            (rows > 0) {
                System.out.println("Student deleted successfully!");
            } else {
                System.out.println("Student not found."); }
        }
    }
}
```

Student.java

```java
package model;

public class Student {
    private int studentID;
    private String name;
    private String department;
    private double marks;

    public Student(int studentID, String name, String department, double marks) {
        this.studentID = studentID; this.name = name; this.department = department;
        this.marks = marks;
    }

    // Getters and Setters
    public int getStudentID() {
    return studentID;
    }

    public void setStudentID(int studentID) { this.studentID
        = studentID;
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public String getDepartment() {
        return department;
    }

    public void setDepartment(String department) {
        this.department = department;
```

```java
    }

    public double getMarks() {
        return marks;
    }

    public void setMarks(double marks) {
        this.marks = marks;
    }

    @Override
    public String toString() {
        return String.format("ID: %d, Name: %s, Dept: %s, Marks: %.2f",
    studentID, name, department, marks); }
}
```

StudentView.java

```java
package view;

import controller.StudentController; import
model.Student;

import java.util.List;
import java.util.Scanner; public

class StudentView {

    private static final Scanner scanner = new Scanner(System.in);
    private static final StudentController controller = new StudentController();

    public void displayMenu() { boolean
        exit = false;

        while (!exit) {
            System.out.println("\n=== Student Management System ===");
            System.out.println("1. Add Student");
            System.out.println("2. View All Students");
```

```java
        System.out.println("3. Update Student");
        System.out.println("4. Delete Student");
        System.out.println("5. Exit");
        System.out.print("Choose an option: ");

        int choice = scanner.nextInt(); scanner.nextLine();
        // Consume newline

        try { switch (choice) { case 1 -
          > addStudent(); case 2 ->
          viewStudents(); case 3 ->
          updateStudent(); case 4 ->
          deleteStudent(); case 5 ->
          exit = true;
             default -> System.out.println("Invalid option. Try again."); }
        } catch (Exception e) {
          System.out.println("Error: " +
    e.getMessage()); } }
    scanner.close();
    }
    private void addStudent() throws Exception {
        System.out.print("Enter name: ");
        String name = scanner.nextLine();
        System.out.print("Enter department: ");
        String department = scanner.nextLine();
        System.out.print("Enter marks: "); double
        marks = scanner.nextDouble();

        Student student = new Student(0, name, department, marks);
        controller.createStudent(student);
    }
    private void viewStudents() throws Exception {
        List<Student> students = controller.getAllStudents();
        System.out.println("\nStudents List:");
        for (Student student : students) {
        System.out.println(student);
        } }
    private void updateStudent() throws Exception {
        System.out.print("Enter student ID to update: ");
        int id = scanner.nextInt(); scanner.nextLine();
```

```java
        System.out.print("Enter new name: ");
        String name = scanner.nextLine();
        System.out.print("Enter new department: ");
        String department = scanner.nextLine(); System.out.print("Enter
        new marks: ");
        double marks = scanner.nextDouble();

        Student    student    =    new    Student(id,    name,    department,    marks);
        controller.updateStudent(student);
    }

    private void deleteStudent() throws Exception {
        System.out.print("Enter student ID to delete: ");
        int        id        =        scanner.nextInt();
        controller.deleteStudent(id);
    }
}
```

MainApp.java   import view.StudentView;

```java
public class MainApp {
    public static void main(String[] args) {
        StudentView view = new StudentView();
        view.displayMenu();}}
```

7.3.4 Output:

```
Student added successfully!

=== Student Management System ===
1. Add Student
2. View All Students
3. Update Student
4. Delete Student
5. Exit
Choose an option: 2

Students List:
ID: 1, Name: Alice, Dept: Computer Science, Marks: 85.50
ID: 2, Name: Bob, Dept: Electronics, Marks: 78.00
ID: 3, Name: Charlie, Dept: Mechanical, Marks: 92.30
ID: 4, Name: Virat, Dept: CSE, Marks: 70.00
```

Learning Outcomes:
1. Understanding JDBC Integration:Gained practical experience in integrating JDBC with a Java application for database connectivity.
2. MVC Architecture Implementation:Learned how to implement the Model- View-Controller (MVC) architecture in Java for better code organization and separation of concerns.
3. Database CRUD Operations:Acquired the ability to perform CRUD operations (Create, Read, Update, Delete) using SQL queries in Java applications.
4. Transaction Handling:Understood the importance of transaction handling for maintaining data integrity during database operations.