



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Experiment -7

Student Name: Sweta singh

Branch: BE-CSE

Semester:6th

Subject Name: Project Based Learning in
Java with Lab

UID:22BCS10664

Section/Group:Kpit-902-B

Date of

Performance:17/03/2025

Subject Code: 22CSH-359

7.1.1.Aim: Create a Java program to connect to a MySQL database and fetch data from a single table. The program should: Use DriverManager and Connection objects. Retrieve and display all records from a table named Employee with columns EmpID, Name, and Salary..

7.1.2Objective: To develop a Java program that connects to a MySQL database, retrieves data from the Employee table, and displays all records, demonstrating basic JDBC connectivity and data retrieval operations.

7.1.3 Code:

```
import java.sql.*;
```

```
public class FetchEmployeeData {  
    public static void main(String[] args) {  
        String url = "jdbc:mysql://localhost:3306/testdb";  
        String user = "root";  
        String password = "password";  
  
        String query = "SELECT EmpID, Name, Salary FROM Employee";  
  
        try {  
            // Load MySQL JDBC driver  
            Class.forName("com.mysql.cj.jdbc.Driver");  
  
            // Establish connection  
            Connection con = DriverManager.getConnection(url, user, password);  
            System.out.println("Connected to the database!");  
  
            // Create statement and execute query  
            Statement stmt = con.createStatement();
```

```
ResultSet rs = stmt.executeQuery(query);

// Display results
System.out.println("\nEmployee Records:");   System.out.println("-----
-----");
System.out.printf("%-10s %-20s %-10s\n", "EmpID", "Name", "Salary");
System.out.println("-----");

    while (rs.next()) {        int empID =
rs.getInt("EmpID");           String name =
rs.getString("Name");         double salary =
rs.getDouble("Salary");

        System.out.printf("%-10d %-20s %-10.2f\n", empID, name, salary);
    }

// Close resources
rs.close();
stmt.close();
con.close();
System.out.println("\nConnection closed.");

} catch (ClassNotFoundException e) {
    System.out.println("MySQL Driver not found: " + e.getMessage());
} catch (SQLException e) {
    System.out.println("SQL Error: " + e.getMessage());
}
}
}
```

7.1.4 Output:

```
(base) PS C:\Users\virat\OneDrive\Desktop\java exp7> java -cp ".\lib/mysql-connector-j-9.2.0.jar" FetchEmployeeD
ata
>>
Connected to the database!

Employee Records:
-----
EmpID      Name      Salary
-----
1          Alice    50000.00
2          Bob      60000.00
3          Charlie  55000.00

Connection closed.
(base) PS C:\Users\virat\OneDrive\Desktop\java exp7>
```

7.2.1 Aim: Build a program to perform CRUD operations (Create, Read, Update, Delete) on a database table Product with columns: ProductID, ProductName, Price, and Quantity. The program should include: Menu-driven options for each operation. Transaction handling to ensure data integrity.

7.2.2 Objective: To develop a Java program that connects to a MySQL database and performs CRUD operations (Create, Read, Update, Delete) on the Product table. The program ensures data integrity by using transaction handling and provides a menu-driven interface for user-friendly interaction.

7.2.3 Code:

```
import java.sql.*;
import java.util.Scanner;

public class ProductCRUD {

    private static final String URL = "jdbc:mysql://localhost:3306/ProductDB";
    private static final String USER = "root";
    private static final String PASSWORD = "password";

    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        try (Connection conn = DriverManager.getConnection(URL, USER, PASSWORD)) {
            Class.forName("com.mysql.cj.jdbc.Driver");
            System.out.println("Connected to the database!");
```

```
boolean exit = false;

while (!exit) {
    System.out.println("\n=== Product CRUD Operations ===");
    System.out.println("1. Create Product");
    System.out.println("2. Read Products");
    System.out.println("3. Update Product");
    System.out.println("4. Delete Product");
    System.out.println("5. Exit");
    System.out.print("Choose an option: ");

    int choice = scanner.nextInt();
    scanner.nextLine();
    switch (choice) {
        case 1 -> createProduct(conn, scanner);
        case 2 -> readProducts(conn);
        case 3 -> updateProduct(conn, scanner);
        case 4 -> deleteProduct(conn, scanner);
        case 5 -> exit = true;
        default -> System.out.println("Invalid option. Try again.");
    }
}

} catch (ClassNotFoundException e) {
    System.out.println("MySQL Driver not found: " + e.getMessage());
} catch (SQLException e) {
    System.out.println("SQL Error: " + e.getMessage());
}

scanner.close();
}

private static void createProduct(Connection conn, Scanner scanner) throws SQLException {
    System.out.print("Enter product name: ");
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
String name = scanner.nextLine();
System.out.print("Enter price: ");
double price = scanner.nextDouble();
System.out.print("Enter quantity: ");    int
quantity = scanner.nextInt();

String query = "INSERT INTO Product (ProductName, Price, Quantity) VALUES (?, ?,
?)";

try (PreparedStatement pstmt = conn.prepareStatement(query)) {
conn.setAutoCommit(false);

    pstmt.setString(1, name);
pstmt.setDouble(2, price);    pstmt.setInt(3,
quantity);

    int rows = pstmt.executeUpdate();
conn.commit();

    System.out.println(rows + " product(s) inserted successfully!");
} catch (SQLException e) {
    conn.rollback();
    System.out.println("Transaction rolled back due to error: " + e.getMessage());
} finally {
    conn.setAutoCommit(true);
}
}

private static void readProducts(Connection conn) throws SQLException {
String query = "SELECT * FROM Product";

    try (Statement stmt = conn.createStatement();
ResultSet rs = stmt.executeQuery(query)) {

        System.out.println("\nProduct Records:");
        System.out.println("-----");
        System.out.printf("%-10s %-20s %-10s %-10s\n", "ProductID", "ProductName",
"Price", "Quantity");
        System.out.println("-----");
```

```
        while (rs.next()) {
            int id = rs.getInt("ProductID");
            String name = rs.getString("ProductName");
            double price = rs.getDouble("Price");           int
            quantity = rs.getInt("Quantity");

            System.out.printf("%-10d %-20s %-10.2f %-10d\n", id, name, price, quantity);
        }
    }
}
```

```
private static void updateProduct(Connection conn, Scanner scanner) throws SQLException
{
    System.out.print("Enter product ID to update: ");
    int id = scanner.nextInt();
    scanner.nextLine();

    System.out.print("Enter new name: ");
    String name = scanner.nextLine();
    System.out.print("Enter new price: ");
    double price = scanner.nextDouble();
    System.out.print("Enter new quantity: ");
    int quantity = scanner.nextInt();

    String query = "UPDATE Product SET ProductName = ?, Price = ?, Quantity = ? WHERE
    ProductID = ?";

    try (PreparedStatement pstmt = conn.prepareStatement(query)) {
        conn.setAutoCommit(false);

        pstmt.setString(1, name);
        pstmt.setDouble(2, price);
        pstmt.setInt(3, quantity);           pstmt.setInt(4,
        id);
    }
}
```

```
int rows = pstmt.executeUpdate();
conn.commit();

System.out.println(rows + " product(s) updated successfully!");

    } catch (SQLException e) {
conn.rollback();
        System.out.println("Transaction rolled back due to error: " + e.getMessage());
    } finally {
        conn.setAutoCommit(true);
    }
}

private static void deleteProduct(Connection conn, Scanner scanner) throws SQLException {
    System.out.print("Enter product ID to delete: ");
    int id = scanner.nextInt();

    String query = "DELETE FROM Product WHERE ProductID = ?";

    try (PreparedStatement pstmt = conn.prepareStatement(query)) {
        conn.setAutoCommit(false);

        pstmt.setInt(1, id);
        int rows = pstmt.executeUpdate();
        conn.commit();

        System.out.println(rows + " product(s) deleted successfully!");
    } catch (SQLException e) {
conn.rollback();
        System.out.println("Transaction rolled back due to error: " + e.getMessage());
    } finally {
        conn.setAutoCommit(true);
    }
}
}
```

7.2.4Output:

```
(base) PS C:\Users\virat\OneDrive\Desktop\java exp7> java -cp ".;lib/mysql-connector-j-9.2.0.jar" ProductCRUD
>>
Connected to the database!

=== Product CRUD Operations ===
1. Create Product
2. Read Products
3. Update Product
4. Delete Product
5. Exit
Choose an option: 2

Product Records:
-----
ProductID  ProductName      Price      Quantity
-----
1          Laptop           75000.00   10
2          Mobile Phone     30000.00   25
3          Tablet           20000.00   15
4          Headphones       5000.00    50
5          Smartwatch       12000.00   30
6          Camera           45000.00   12
```

7.3.1 Aim: Develop a Java application using JDBC and MVC architecture to manage student data. The application should: Use a Student class as the model with fields like StudentID, Name, Department, and Marks. Include a database table to store student data. Allow the user to perform CRUD operations through a simple menu-driven view. Implement database operations in a separate controller class.

7.3.2 Objective: The objective of this program is to develop a menu-driven Java application that allows users to add employee details, display all stored employees, and exit the program. Employee details, including ID, name, designation, and salary, are stored persistently in a file using serialization.

7.3.3 Code:

StudentController.java
package controller;

```
import model.Student;
import java.sql.*; import
java.util.ArrayList;
import java.util.List;
```




DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

```
public class StudentController {

    private static final String URL = "jdbc:mysql://localhost:3306/StudentDB";
    private static final String USER = "root";
    private static final String PASSWORD = "rishuraman1@V";

    // Method to create a new student
    public void createStudent(Student student) throws SQLException {
        String query = "INSERT INTO Student (Name, Department, Marks) VALUES (?, ?, ?)";

        try (Connection conn = DriverManager.getConnection(URL, USER, PASSWORD);
            PreparedStatement pstmt = conn.prepareStatement(query)) {

            pstmt.setString(1, student.getName());
            pstmt.setString(2, student.getDepartment());
            pstmt.setDouble(3, student.getMarks());

            pstmt.executeUpdate();
            System.out.println("Student added successfully!");
        }
    }

    // Method to retrieve all students
    public List<Student> getAllStudents() throws SQLException {
        List<Student> students = new ArrayList<>();
        String query = "SELECT * FROM Student";

        try (Connection conn = DriverManager.getConnection(URL, USER, PASSWORD);
            Statement stmt = conn.createStatement();
            ResultSet rs = stmt.executeQuery(query)) {

            while (rs.next()) {
                students.add(new Student(
                    rs.getInt("StudentID"),
                    rs.getString("Name"),
                    rs.getString("Department"),
                    rs.getDouble("Marks")
                ));
            }
        }
    }
}
```

```
    }  
    return students;  
}  
  
// Method to update student data  
public void updateStudent(Student student) throws SQLException {  
    String query = "UPDATE Student SET Name = ?, Department = ?, Marks = ? WHERE  
StudentID = ?";  
  
    try (Connection conn = DriverManager.getConnection(URL, USER, PASSWORD);  
        PreparedStatement pstmt = conn.prepareStatement(query)) {  
  
        pstmt.setString(1, student.getName());  
        pstmt.setString(2, student.getDepartment());  
        pstmt.setDouble(3, student.getMarks());           pstmt.setInt(4,  
student.getStudentID());  
  
        int rows = pstmt.executeUpdate();  
        if (rows > 0) {  
            System.out.println("Student updated successfully!");  
        } else {  
            System.out.println("Student not found.");  
        }  
    }  
}  
  
// Method to delete a student    public void deleteStudent(int  
studentID) throws SQLException {  
    String query = "DELETE FROM Student WHERE StudentID = ?";  
  
    try (Connection conn = DriverManager.getConnection(URL, USER, PASSWORD);  
        PreparedStatement pstmt = conn.prepareStatement(query)) {  
  
        pstmt.setInt(1, studentID);  
        int rows = pstmt.executeUpdate();  
        if (rows > 0) {  
            System.out.println("Student deleted successfully!");  
        } else {
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
        System.out.println("Student not found.");
    }
}
}
```

Student.java

```
package model;
```

```
public class Student {
    private int studentID;
    private String name;
    private String department;
    private double marks;
```

```
    public Student(int studentID, String name, String department, double marks) {
        this.studentID = studentID;    this.name = name;    this.department =
        department;    this.marks = marks;
    }
```

```
    // Getters and Setters
    public int getStudentID() {
        return studentID;
    }
```

```
    public void setStudentID(int studentID) {
        this.studentID = studentID;
    }
```

```
    public String getName() {
        return name;
    }
```

```
    public void setName(String name) {
        this.name = name;
    }
```

```
    public String getDepartment() {
```

```
        return department;
    }

    public void setDepartment(String department) {
        this.department = department;
    }

    public double getMarks() {
        return marks;
    }

    public void setMarks(double marks) {
        this.marks = marks;
    }

    @Override    public
    String toString() {
        return String.format("ID: %d, Name: %s, Dept: %s, Marks: %.2f",
        studentID, name, department, marks);
    }
}
```

StudentView.java

```
package view;

import controller.StudentController; import
model.Student;

import java.util.List;
import java.util.Scanner;

public class StudentView {

    private static final Scanner scanner = new Scanner(System.in);
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
private static final StudentController controller = new StudentController();

public void displayMenu() {
    boolean exit = false;

    while (!exit) {
        System.out.println("\n=== Student Management System ===");
        System.out.println("1. Add Student");
        System.out.println("2. View All Students");
        System.out.println("3. Update Student");
        System.out.println("4. Delete Student");
        System.out.println("5. Exit");
        System.out.print("Choose an option: ");

        int choice = scanner.nextInt();
        scanner.nextLine(); // Consume newline

        try {
            switch (choice) {
            case 1 -> addStudent();
            case 2 -> viewStudents();
            case 3 -> updateStudent();
            case 4 -> deleteStudent();
            case 5 -> exit = true;
            default -> System.out.println("Invalid option. Try again.");
            }
        } catch (Exception e) {
            System.out.println("Error: " + e.getMessage());
        }
    }
    scanner.close();
}

private void addStudent() throws Exception {
    System.out.print("Enter name: ");
    String name = scanner.nextLine();
    System.out.print("Enter department: ");
    String department = scanner.nextLine();
    System.out.print("Enter marks: ");
    double marks = scanner.nextDouble();
}
```

```
        Student student = new Student(0, name, department, marks);
        controller.createStudent(student);
    }
    private void viewStudents() throws Exception {
        List<Student> students = controller.getAllStudents();
        System.out.println("\nStudents List:");
        for (Student student : students) {
            System.out.println(student);
        }
    }
    private void updateStudent() throws Exception {
        System.out.print("Enter student ID to update: ");
        int id = scanner.nextInt();
        scanner.nextLine();

        System.out.print("Enter new name: ");
        String name = scanner.nextLine();
        System.out.print("Enter new department: ");
        String department = scanner.nextLine();
        System.out.print("Enter new marks: ");
        double marks = scanner.nextDouble();

        Student student = new Student(id, name, department, marks);
        controller.updateStudent(student);
    }

    private void deleteStudent() throws Exception {
        System.out.print("Enter student ID to delete: ");
        int id = scanner.nextInt();
        controller.deleteStudent(id);
    }
}

MainApp.java import
view.StudentView;
```

```
public class MainApp {  
    public static void main(String[] args) {  
        StudentView view = new StudentView();  
        view.displayMenu();  
    }  
}
```

7.3.4Output:

```
Student added successfully!  
  
=== Student Management System ===  
1. Add Student  
2. View All Students  
3. Update Student  
4. Delete Student  
5. Exit  
Choose an option: 2  
  
Students List:  
ID: 1, Name: Alice, Dept: Computer Science, Marks: 85.50  
ID: 2, Name: Bob, Dept: Electronics, Marks: 78.00  
ID: 3, Name: Charlie, Dept: Mechanical, Marks: 92.30  
ID: 4, Name: Virat, Dept: CSE, Marks: 70.00
```

Learning Outcomes:

1. **Understanding JDBC Integration:** Gained practical experience in integrating JDBC with a Java application for database connectivity.
2. **MVC Architecture Implementation:** Learned how to implement the ModelView-Controller (MVC) architecture in Java for better code organization and separation of concerns.
3. **Database CRUD Operations:** Acquired the ability to perform CRUD operations (Create, Read, Update, Delete) using SQL queries in Java applications.
4. **Transaction Handling:** Understood the importance of transaction handling for maintaining data integrity during database operations.