



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## Experiment -9

**Student Name:** Dhruv Paliwal

**UID:**22BCS10279

**Branch:** BE-CSE

**Section/Group:**IOT\_639-B

**Semester:**6th

**Date of**

**Subject Name:** Project-Based Learning in  
Java with Lab

**Performance:**17/03/2025

**Subject Code:** 22CSH-359

**9.1.1.Aim:** To demonstrate dependency injection using Spring Framework with Java-based configuration.

### **9.1.2 Objective:**

Define Course and Student classes.

Use Configuration and Bean annotations to inject dependencies. Load Spring context and print student details.

**9.1.3 Code:** // Course.java

```
public class Course {  
    private String courseName;  
    private String duration;
```

```
    public Course(String courseName, String duration) {  
        this.courseName = courseName;    this.duration =  
        duration;  
    }
```

```
    public String getCourseName() { return courseName; }  
    public String getDuration() { return duration; }
```

```
    @Override  
    public String toString() {  
        return "Course: " + courseName + ", Duration: " + duration;  
    }  
}
```

```
// Student.java public  
class Student {    private
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
String name;    private
Course course;  public
Student(String name,
Course course) {
    this.name = name;
this.course = course;
}
```

```
    public void showDetails() {
        System.out.println("Student: " + name);
        System.out.println(course);
    }
} // AppConfig.java
import org.springframework.context.annotation.*;
```

```
@Configuration public
class AppConfig {
    @Bean
    public Course course() {
        return new Course("Java", "3 months");
    }
}
```

```
    @Bean
    public Student student() {
        return new Student("Aman", course());
    }
} // MainApp.java
import org.springframework.context.ApplicationContext;
import org.springframework.context.annotation.AnnotationConfigApplicationContext;
```

```
public class MainApp {
    public static void main(String[] args) {
        ApplicationContext context = new
        AnnotationConfigApplicationContext(AppConfig.class);
        Student student = context.getBean(Student.class);
        student.showDetails();
    } }

```

**Output:**

```
Student: Sarthak  
Course: Java, Duration: 3 months
```

**9.2.1 Aim:** To perform CRUD operations on a Student entity using Hibernate ORM with MySQL.

**Objective:** Define Course and Student classes.

Use Configuration and Bean annotations to inject dependencies.

Load Spring context and print student details.

**9.2.2 Code:**

```
<hibernate-configuration>  
  <session-factory>  
    <property  
name="hibernate.connection.driver_class">com.mysql.cj.jdbc.Driver</property>  
    <property  
name="hibernate.connection.url">jdbc:mysql://localhost:3306/testdb</property>  
    <property name="hibernate.connection.username">root</property>  
    <property name="hibernate.connection.password">password</property>  
    <property  
name="hibernate.dialect">org.hibernate.dialect.MySQL8Dialect</property>  
    <property name="hibernate.hbm2ddl.auto">update</property>  
    <mapping class="Student"/>  
  </session-factory>  
</hibernate-configuration>
```

```
import javax.persistence.*;
```

Entity

```
public class Student {  
  Id  
  GeneratedValue(strategy = GenerationType.IDENTITY)  
  private int id;  private String name;  
  private int age;
```

```
public Student() {}  
public Student(String name, int age) {  
this.name = name;    this.age = age;  
}  
  
// Getters, setters, toString  
} import  
org.hibernate.SessionFactory;  
import org.hibernate.cfg.Configuration;  
  
public class HibernateUtil {  
    private static final SessionFactory sessionFactory;  
    static  
{  
        sessionFactory = new Configuration().configure().buildSessionFactory();  
    }  
  
    public static SessionFactory getSessionFactory() {  
        return sessionFactory;  
    }  
}  
  
import org.hibernate.*;  
  
public class MainCRUD {  
    public static void main(String[] args) {  
        Session session = HibernateUtil.getSessionFactory().openSession();  
  
        // Create  
        Transaction tx = session.beginTransaction();  
        Student s1 = new Student("Aman", 22);  
        session.save(s1);  
        tx.commit();  
  
        // Read  
        Student student = session.get(Student.class, 1);  
        System.out.println(student);  
    }  
}
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
// Update
tx = session.beginTransaction();
student.setAge(23);
session.update(student);      tx.commit();
```

```
// Delete
tx = session.beginTransaction();
session.delete(student);
```

```
tx.commit();  
  
session.close();  
}  
}
```

### 9.2.3 Output:

```
Student{id=1, name='Sallu', age=22}  
Updated age to 23  
Deleted student with id 1
```

**9.3.1 Aim:** To implement a banking system using Spring and Hibernate that ensures transaction consistency during fund transfers.

**Objective:**

Integrate Spring + Hibernate.

Handle transactions atomically (rollback on failure).

Demonstrate success and failure cases.

**Code:**

```
import javax.persistence.*;
```

**Entity**

```
public class Account {
```

```
    @Id    private int  
    accountId;    private String  
    holderName;  
    private double balance;
```

```
    // Constructors, getters, setters  
}
```

```
import javax.persistence.*;
```

```
import java.util.Date;
```

**@Entity**

```
public class BankTransaction {
```

```
    @Id  
    @GeneratedValue(strategy = GenerationType.IDENTITY)  
    private int txnId;    private int fromAcc;    private int toAcc;  
    private double amount;  
    private Date txnDate = new Date();
```

```
    // Constructors, getters, setters  
}
```

```
import org.hibernate.*;
```

```
import org.springframework.transaction.annotation.Transactional;
```

```
public class BankService {
    private SessionFactory sessionFactory;

    public BankService(SessionFactory sessionFactory) {
        this.sessionFactory = sessionFactory;
    }

    @Transactional
    public void transferMoney(int fromId, int toId, double amount) {
        Session session = sessionFactory.getCurrentSession();

        Account from = session.get(Account.class, fromId);
        Account to = session.get(Account.class, toId);

        if (from.getBalance() < amount) {
            throw new RuntimeException("Insufficient Balance");
        }

        from.setBalance(from.getBalance() - amount);
        to.setBalance(to.getBalance() + amount);

        session.update(from);
        session.update(to);

        BankTransaction txn = new BankTransaction(fromId, toId, amount);
        session.save(txn);
    }
}

@Configuration
@EnableTransactionManagement public
class AppConfig {
    @Bean
    public DataSource dataSource() {
        DriverManagerDataSource ds = new DriverManagerDataSource();
```



```
        ds.setDriverClassName("com.mysql.cj.jdbc.Driver");
ds.setUrl("jdbc:mysql://localhost:3306/testdb");
ds.setUsername("root");        ds.setPassword("password");
    return ds;
}
```

```
@Bean
public LocalSessionFactoryBean sessionFactory() {
    LocalSessionFactoryBean lsf = new LocalSessionFactoryBean();
lsf.setDataSource(dataSource());
lsf.setPackagesToScan("your.package");    Properties props =
new Properties();
    props.put("hibernate.dialect", "org.hibernate.dialect.MySQL8Dialect");
props.put("hibernate.hbm2ddl.auto", "update");
    lsf.setHibernateProperties(props);
return lsf;
}
```

```
@Bean
public HibernateTransactionManager transactionManager(SessionFactory sf) {
return new HibernateTransactionManager(sf);
}
```

```
@Bean
public BankService bankService(SessionFactory sf) {
return new BankService(sf);
}
}
```

```
public class MainApp {
    public static void main(String[] args) {
        AnnotationConfigApplicationContext ctx = new
AnnotationConfigApplicationContext(AppConfig.class);
        BankService service = ctx.getBean(BankService.class);
        try
        {
            service.transferMoney(101, 102, 500);
        }
    }
}
```



**DEPARTMENT OF**

**COMPUTER SCIENCE & ENGINEERING**

*Discover. Learn. Empower.*

```
        System.out.println("Transaction Successful!");  
    } catch (Exception e) {  
        System.out.println("Transaction Failed: " + e.getMessage());  
    }
```



**DEPARTMENT OF**

Discover Learn Empower

# COMPUTER SCIENCE & ENGINEERING

```
ctx.close();  
}
```

```
Transaction Successful!  
OR  
Transaction Failed: Insufficient Balance
```

```
}
```

**OUTPUT**