

# Comparing Hyperdimensional Computing to Deep Learning for Natural Language Processing Tasks

Todd Morrill  
*Computer Science Department*  
*Columbia University*  
tm3229@columbia.edu

Satyam Sharma  
*Computer Science Department*  
*Columbia University*  
ss6522@columbia.edu

**Abstract**—In this project, we will compare the performance of deep learning models (e.g. Transformers, Convolutional Neural Networks (CNN), Long Short-Term Memory (LSTM) models) to HDC models on a variety of NLP tasks using a range of metrics and evaluate their relative strengths and weaknesses.

**Index Terms**—hyperdimensional computing, HDC, deep learning, natural language processing, NLP

## I. INTRODUCTION

[1]

## II. RESULTS

TABLE I  
HDC ACCURACY SCORES BY DATASET SIZE.

Examples	Dataset Pct.	Accuracy
21	0.0001	0.2682
210	0.0010	0.8375
2100	0.0100	0.9593
4200	0.0200	0.9659
10501	0.0500	0.9700

## REFERENCES

- [1] N. Thakur, N. Reimers, A. Rüklé, A. Srivastava, and I. Gurevych, “BEIR: A heterogenous benchmark for zero-shot evaluation of information retrieval models,” *CoRR*, vol. abs/2104.08663, 2021. [Online]. Available: <https://arxiv.org/abs/2104.08663>