

A generalized gravity model for influential spreaders identification in complex networks

Hanwen Li^a, Qiuyan Shang^{a,b}, Yong Deng^{a,c,*}

^a Institute of Fundamental and Frontier Science, University of Electronic Science and Technology of China, Chengdu 610054, China

^b Yingcai Honors of school, University of Electronic Science and Technology of China, Chengdu, 610054, China

^c School of Education, Shannxi Normal University, Xi'an, 710062, China

ARTICLE INFO

Article history:

Received 6 May 2020

Revised 12 October 2020

Accepted 9 November 2020

Available online 23 December 2020

Keywords:

Influential spreaders identification

Complex networks

Generalized gravity model

ABSTRACT

How to identify influential spreaders in complex networks is still an open issue in network science. Many approaches from different perspectives have been proposed to identify vital nodes in complex networks. In these models, gravity model is an effective model to find vital nodes based on local information and path information. However, gravity model just uses degree of the node to judge local information, which is not precise. To address this issue, a generalized gravity model is proposed in this paper. Generalized gravity model measures local information from both local clustering coefficient and degree of each node, which is more comprehensive. Also, parameter α can be modified in different applications to get better performance. Generalized gravity model can degenerate into gravity model when $\alpha = 0$. Promising results from experiments on four real-world networks demonstrate the effectiveness of the proposed method.

© 2020 Elsevier Ltd. All rights reserved.

1. Introduction

Massive complex systems in the world, including but not limiting to biology systems [1,2], social systems [3–5], and multi-agent systems [6,7] can be well described and presented in the form of complex networks. Network science is a subject for studying properties of complex networks. There are many hot topics in network science, like node similarity analysis [8], network division [9,10], self-similarity analysis [11,12], vulnerability analysis [13], resilience analysis [14,15], message passing [16–18], network evolution [19–22], uncertainty modeling [23–25], network cascading [26] and so on. Complex network theory is effective to present the components of a complex system and components' relationship. Properties of the complex network can be analyzed to get useful information. Methods and mathematical models in network science are widely used in massive applications under the real world, including but not limiting to time series analysis [27–29], decision making [30,31], image processing [32], social network analysis [33], traffic flow analysis [34]. We have witnessed the rapid development of network science in recent years [35–40].

Recently, influential spreaders identification problem is widely paid attention by many researchers [41,42]. Influential spreaders identification can be widely used in many fields and applications,

like disease analysis [43,44], rumor analysis [45], knowledge graph [46], social computing [47,48] and so on. Nevertheless, how to find vital nodes in complex networks is still an open issue. There are many methods for finding influential spreaders in complex networks, like degree centrality (DC) [49], betweenness centrality (BC) [50], closeness centrality (CC) [51], PageRank [52,53], Leader-Rank [54], eigenvector centrality (EC) [55], H-index [56] and so on. Mainstream of methods can fall into many categories. Some methods, like DC, local centrality (LC) [57] just use local information to judge which nodes are vital. Among these methods, local information dimensionality is presented as an effective model to rank influential nodes in complex networks with entropy function [58–60]. Local information dimensionality is also a special form of multi-local dimension [61]. These methods are easy to compute but they are not precise. Some methods use global information, like closeness centrality [51], betweenness centrality [50], Katz centrality [62] and so on. They are precise but they are time consuming, which will hinder their applications in some occasions. There are also many other methods to find vital nodes in a comprehensive perspective, considering both global and local information, like gravity formula based models [63,64], entropy models [65], evolutionary computation based methods [66] and other hybrid methods [67–71].

Gravity-formula is natural and has potential to represent the interaction between nodes or agents in the network. If a node or agent has more interaction with others, this node should be more important. Hence, there are many studies on how to use gravity-

* Corresponding author.

E-mail addresses: dengentropy@uestc.edu.cn, prof.deng@hotmail.com (Y. Deng).

formula to identify influential spreaders. Gravity model is proposed by Ma et al. [72] as it uses local and path information to identify influential nodes. However, gravity model is time consuming in some large networks, which will limit its application. Li et al. solve this problem by introducing a truncation radius to gravity model [63], which greatly reduces the complexity of calculation. Liu et al. propose weighted gravity model [64], which considers self importance of the node compared to gravity model by introducing the eigenvector centrality of the node to gravity model. However, the eigenvector centrality may conflict with local and path information, which may influence the result of finding vital nodes.

The main contribution of this paper is to propose a generalized gravity model. The highlight of this paper is that the mass of each node is not its degree, but substituted by spreading ability of the node. The spreading ability of a node is decided by not only the degree of the node, but also the local clustering coefficient of the node. Assuming a node with the same degrees, if the local clustering coefficient of the node is higher, which corresponding to more edges among its neighbors, it is easier for information to propagate in its neighbors, not outer nodes, and this node is less influential. Hence, the local information is measured more precisely by spreading ability of the node compared with degrees of the node.

The remaining part of this paper is organized as follows. Preliminaries, including several centrality measures, Susceptible-Infected (SI) model and Kendall's tau coefficient will be briefly introduced in Section 2. In Section 3, generalized gravity model is proposed and presented. In Section 4, encouraging results of experiments

on four real-world networks will be used to verify the effectiveness of the proposed method. Finally, conclusions will be given in Section 5.

2. Preliminaries

Preliminaries include centrality measures in complex networks, SI model and the Kendall's tau coefficient will be introduced in this section.

2.1. Centrality measures in complex networks

A network can be denoted as $G = (V, E)$, V and E are the set of nodes and edges respectively. Several centrality measures, degree centrality (DC) [49], betweenness centrality [50], closeness centrality [51], gravity model [63] and weighted gravity model [64] are presented as follows.

Definition 2.1. The DC of node v is defined as follows [49].

$$C_D(v) = k(v) \quad (1)$$

where $k(v)$ denotes the degree of node x .

Definition 2.2. The BC of node v is defined as follows [50].

$$C_B(v) = \frac{\sum_{j \neq k, i \neq j, k} g_{j,k}(i)}{\sum_{j \neq k, i \neq j, k} g_{k,j}} \quad (2)$$




Fig. 1. This figure shows the centrality score of nodes in Jazz network.

where $g_{j,k}$ and $g_{j,k}(i)$ denotes the number of shortest paths between node j and k and the number of shortest paths between node j and k that go through node i .

Definition 2.3. The CC of node i is defined as follows [51].

$$C_C(v) = \frac{1}{\sum_w d_{vw}} \quad (3)$$

where N denotes the number of nodes in the network and d_{vw} denotes the topological distance between node v and node w .

Definition 2.4. The gravity model is used for influential spreaders identification. The gravity centrality (GC) is presented as follows [63].

$$C_G(i) = \sum_j \frac{k(i) \times k(j)}{d_{ij}^2} \quad (4)$$

However, gravity model is time-consuming. Li et al. solve this problem by introducing a truncation radius to gravity model [63].

$$C_G(i) = \sum_{d_{ij} \leq R} \frac{k(i) \times k(j)}{d_{ij}^2} \quad (5)$$

where the truncation radius $R = \frac{\langle d \rangle}{2}$, d is the average length of the shortest paths of the network. In this paper, gravity centrality is calculated by Eq. (5).

Table 1

Descriptions of parameters of SI model.

| Parameter | Description of parameter |
|-----------|---|
| T | The simulation time of SI model |
| F(t) | The average number of infected nodes at time t |
| β | Probability of susceptible node infected by infected node |
| N | Number of independent experiments |

Definition 2.5. The weighted gravity model is proposed by Liu et al. [64]. The weighted gravity centrality (WGC) can be calculated as following equations.

$$\begin{aligned} AX &= \lambda X \\ e_i &= X_i \\ C_{WG}(i) &= \sum_{d_{ij} \leq R} e_i \times \frac{k(i) \times k(j)}{d_{ij}^2} \end{aligned} \quad (6)$$

where λ and X the largest eigenvalue and normalized eigenvector respectively. e_i is the value of node i in X .

2.2. SI model

SI model is used to evaluate the performance of top rank-nodes selected by different centrality measures [73]. Every node has two states: susceptible or infected. Infected node keeps infected and infect its neighbors that are susceptible. Table 1 describes the parameters of the SI model.

NS




Fig. 2. This figure shows the centrality score of nodes in NS network.

2.3. The Kendall's tau coefficient

Kendall's tau coefficient is used to measure the correlation between centrality measures and infection ability [74].

Given two sets of sequences x and y . x_i and y_i are the i th value of sequence x and y respectively. Given a sequence pair (x_i, y_i) . If $x_i > x_j$ and $y_i > y_j$ then (x_i, y_i) is recorded as a positive sequence pair otherwise negative sequence pair.

$$\tau = \frac{n^+ - n^-}{n(n-1)} \quad (7)$$

where n^+ and n^- denotes the number of positive sequence pairs and negative pairs respectively. If τ value is larger, the centrality measure is more accurate compared with the real spreading process. Centrality measure has the best performance when $\tau = 1$.

3. Proposed method

Gravity model uses degree of nodes as masses, which represents the local information of nodes, which is rough.

The local clustering coefficient of node v is defined as

$$C_v = \frac{2n_v}{k(v)(k(v)-1)} \quad (8)$$

where $k(v)$ denotes the degree of node v . n_v denotes the number of edges between neighbors of node v .

The spreading ability of node v is defined as

$$Sp(v) = e^{-\alpha C_v} \times k(v) \quad (9)$$

where $\alpha \geq 0$ and $k(v)$ is the degree of node v . α is a free parameter that can be modified flexibly in real applications.

The generalized gravity centrality (GGC) is defined as follows.

$$C_{GG}(i) = \sum_{d_{ij} \leq R \& j} \frac{Sp(i) \times Sp(j)}{d_{ij}^2} \quad (10)$$

when $\alpha = 0$, generalized gravity model will degenerate into gravity model. In this paper, we take $\alpha = 2$ for calculation.

In previous studies on gravity model, the local information is judged only by the degree of the node, which is not reasonable. Some studies show that the local clustering coefficient will also affect the spreading ability of the node [75]. In generalized gravity model, the spreading ability of the node is not only decided by the degree, but also the local clustering coefficient of the node, which is more reasonable. The mass of gravity model is substituted with the spreading ability of the node, which better considers the local information of the node.

4. Case studies

In this section, proposed method is compared with other centrality measures by three experiments on four real-world networks. Information of datasets is shown in Table 2. Jazz is a network




Fig. 3. This figure shows the centrality score of nodes in USAir network.

PB




Fig. 4. This figure shows the centrality score of nodes in PB network.

Table 2

Information of datasets, n , m , $\langle k \rangle$ and $\langle d \rangle$ are number of nodes, edges, average degree and average shortest distance of the network respectively.

| Network | n | m | $\langle k \rangle$ | $\langle d \rangle$ |
|-----------|------|-------|---------------------|---------------------|
| Jazz [76] | 198 | 2472 | 27.6970 | 2.2350 |
| NS [77] | 379 | 914 | 4.8232 | 6.0419 |
| USAir | 332 | 2126 | 12.8072 | 2.7381 |
| PB [78] | 1222 | 16714 | 27.3552 | 2.7375 |

that describes the relationship between Jazz musicians [76]. NS is a network of scientists that work together [77]. USAir is the aviation network of US transportation. PB is a network of political blogs [78]. All of the data is available and can be downloaded from <https://github.com/MLIF/Network-Data>. The code is available at <https://github.com/Hanwen22Li/Generalized-gravity-model>.

4.1. Centrality measures of different measures

In this experiment, different centrality measures, like DC, CC, BC, GC, WGC, GGC, are used to calculate the centrality scores of nodes in different networks. The calculation results are demonstrated in Figs. 1–4. The results are normalized. In the figures, if the color of the node is darker, the centrality score of the node is higher.

Generally, the values calculated by CC are large. GGC has similar distributions with GC and WGC. They all judge vital nodes based on local information and path information and calculate with gravity formula. So results of GGC are consistent with GC and WGC in general.

4.2. The comparisons of spreading ability

Figs. 5–6 demonstrate the spreading ability of three centrality measures, gravity centrality, weighted gravity centrality and generalized gravity centrality. In this experiment, the independent experiments are executed 100 times. The simulation time of SI model t is set to be 25. β is set to be 0.1. The top-10 ranked nodes by centrality measures are labeled as infected nodes in initial phase of the SI model in this experiment.

In Fig. 5, generalized gravity model is compared with gravity model. In Jazz network, when t is small, the number of infected nodes with GGC is higher than GC. When t is higher, the numbers of infected nodes of two methods converge to the certain value, because majority nodes of the network have been infected. In NS network, the infected nodes of two methods are increasing. However, the number of infected nodes of GGC is always higher than GC, which demonstrates the effectiveness of generalized gravity model. In USAir and PB model, the values of infected nodes by two methods are almost the same with t increases.

In Fig. 6, generalized gravity model is compared with weighted gravity model. In Jazz network, GGC has greater values than WC in the initial phase. In NS network, the value of infected nodes of GGC is greater than WGC in the whole process. In USAir network, when $t < 20$, the values of GGC are higher than WGC. In PB network, we can see that the values of infected nodes of two methods keep almost the same in the whole process. In overall, generalized gravity model performs better than weighted gravity model.

In a nutshell, we can conclude that generalized gravity model can find influential spreaders more effectively than gravity model and weighted gravity model. Generalized gravity model inherits




Fig. 5. Infection ability of GGC and GC in four different real-world networks.

some properties of gravity model as they both judge information from local information and path information. However, generalized gravity model judge local information by both cluster coefficient and degree of nodes, which is more precise.

Then we compare the proposed generalized gravity model with three classical centrality measures, CC, DC and BC. The results are shown in Figs. 7–9.

In Fig. 7, generalized gravity model is compared with degree centrality. Generalized gravity model is outperformed by DC in Jazz, NS and USAir networks. Only in PB network can the generalized gravity model be competitive with DC.

In Fig. 8, generalized gravity model is compared with closeness centrality. CC has better performance than GGC except in PB network.

In Fig. 9, generalized gravity model is compared with betweenness centrality. GGC has similar performance with BC in PB network. GGC has better performance than BC in Jazz network in the initial phase. GGC performs also slightly better than BC in USAir network when $t \leq 15$. GGC is only outperformed by BC in NS network.

It can be concluded that in four networks, GGC is better than BC for identifying influential spreaders and worse than CC and DC. However, GGC beats two state of the arts gravity-formula based models like GC and WGC. As of now, GGC is the best gravity-formula based approach and effective for influential spreaders identification.

4.3. The comparisons of centralities measures and SI model

τ value demonstrates the difference between SI model and centrality measures. In this experiment, the propagation time T is set to be 25. The infection probability β ranges from 0.1 to 1. The independent experiments have been done by 100 times. Results of experiments are shown in Figs. 10 and 11.

In Fig. 10, GGC is compared with GC. In Jazz network, when $t = 0.4, 0.5, 0.6, 0.7, 0.9$, the τ value of GGC is higher than GC. Hence, the performance of GGC is compatible with GC in Jazz network. In NS network, most of the values of GGC are higher than GC. In USAir and PB network, there are also five times that the value of GGC is higher than GC.

In Fig. 11, GGC is compared with WGC. In Jazz network, GGC is outperformed by WGC that there are only three times that the value of GGC is higher. In NS network, the values of GGC are higher than WGC in the whole process. In USAir network, when $t = 0.2$ and t from 0.4 to 0.9, the value of GGC is higher than WGC. In PB network, there are five times that the value of GGC is higher than WGC.

In all, it is rarely that generalized gravity model is outperformed by gravity model and weighted gravity model. However, generalized gravity model outperforms other two methods in NS network and is compatible with other two methods in other three networks, which shows the effectiveness of generalized gravity model.




Fig. 6. Infection ability of GGC and WGC in four different real-world networks.




Fig. 7. Infection ability of GGC and DC in four different real-world networks.




Fig. 8. Infection ability of GGC and CC in four different real-world networks.




Fig. 9. Infection ability of GGC and BC in four different real-world networks.




Fig. 10. The τ value of GGC and GC in four networks.




Fig. 11. The τ value of GGC and WGC in four networks.

Jazz




Fig. 12. The figure describes the relationship between generalized gravity model and other methods in Jazz networks. Generalized gravity model has good correlation with gravity and degree centrality.

NS




Fig. 13. The figure describes the relationship between generalized gravity model and other methods in NS networks. Generalized gravity model has good correlation with gravity centrality.

USAir




Fig. 14. The figure describes the relationship between generalized gravity model and other methods in USAir networks. Generalized gravity model has good correlation with degree centrality.

PB




Fig. 15. The figure describes the relationship between generalized gravity model and other methods in PB networks. Generalized gravity model has good correlation with weighted gravity centrality, gravity centrality and degree centrality.

4.4. Correlations with other centrality measures

In this experiment, the generalized gravity centrality is compared with five other centrality measures, including DC, BC, CC, GC and WGC, which identify influential spreaders from different perspective. The points in the correlation graph means the values of centralities of points. The values of axis correspond to values obtained by different centrality measures. In this experiment, the color of points means the infectious ability of this node obtained by SI model in 25 steps, which is obtained by 100 independent experiments results when $\beta = 0.1$. The correlations between GGC and other centralities are shown in Figs. 12–15.

In a nutshell, the generalized gravity model has high correlation with gravity model, weighted gravity model and DC. Generalized gravity model find vital nodes by local and path information, which is inherited from gravity model. Weighted gravity model uses local and path information as well. Hence, generalized gravity model and weighted gravity model has high correlation. Also, DC uses local information, which is consistent with models based on gravity formula that also uses local information.

5. Conclusions

In this paper, a generalized gravity model is proposed for influential spreaders identification. The generalized gravity model can degenerate into gravity model when $\alpha = 0$. Compared with gravity model and weighted gravity model, generalized gravity model takes the local clustering coefficient into account, which better captures the local information of the node. The effectiveness of the proposed method is demonstrated by experiments on four real networks in the real world compared with gravity model and weighted gravity model. The proposed method has made a progress in making gravity-formula applicable in the realm of important nodes identification.

There are still some potential problems in the future. For example, how to use generalized gravity model in the weighted networks is still an open problem. Also, how to find proper parameter α quickly and accurately needs to be further investigated. We will also develop some other better methods based on gravity-formula to identify influential spreaders.

Declaration of Competing Interest

The authors declare that there is no conflict of interests.

CRediT authorship contribution statement

Hanwen Li: Writing - original draft, Investigation, Conceptualization, Methodology, Software, Validation. **Qiuyan Shang:** Methodology, Software, Validation. **Yong Deng:** Writing - review & editing, Supervision, Funding acquisition.

Acknowledgment

The authors greatly appreciate the reviews' suggestions and the editor's encouragement. The work is partially supported by [National Natural Science Foundation of China](#) (Grant No. 61973332).

References

- [1] Kovács IA, Luck K, Spirohn K, Wang Y, Pollis C, Schlabach S, et al. Network-based prediction of protein interactions. *Nat Commun* 2019;10(1):1–8.
- [2] Vermeulen R, Schymanski EL, Barabási A-L, Miller GW. The exposome and health: where chemistry meets biology. *Science* 2020;367(6476):392–6.
- [3] Gao J, Zhang Y-C, Zhou T. Computational socioeconomics. *Phys Rep* 2019.

- [4] Lü L, Zhou T. Link prediction in weighted networks: the role of weak ties. *EPL* 2010;89(1):18001.
- [5] Sarkar S, Bhowmick S, Mukherjee A. On rich clubs of path-based centralities in networks. In: Proceedings of the 27th ACM international conference on information and knowledge management; 2018. p. 567–76.
- [6] Birdsey L. A framework for large scale complex adaptive systems modeling, simulation, and analysis. In: Proceedings of the 16th conference on autonomous agents and multiagent systems; 2017. p. 1824–5.
- [7] Weng J, Xiao F, Cao Z. Uncertainty modelling in multi-agent information fusion systems. In: Proceedings of the 19th international conference on autonomous agents and multiagent systems; 2020. p. 1494–502.
- [8] Wen T, Duan S, Jiang W. Node similarity measuring in complex networks with relative entropy. *Commun Nonlinear Sci Numer Simul* 2019;78:104867.
- [9] Yang H, Deng Y, Mayne R. A bio-inspired network design method for intelligent transportation. *Int J Unconv Comput* 2019;14(3,4):199–215.
- [10] Yang H, Deng Y. A bio-inspired optimal network division method. *Physica A* 2019;527:210–19.
- [11] Song C, Havlin S, Makse HA. Self-similarity of complex networks. *Nature* 2005;433(7024):392–5.
- [12] Ramirez-Arellano A, Hernández-Simón LM, Bory-Reyes J. A box-covering Tsalis information dimension and non-extensive property of complex networks. *Chaos Solitons Fractals* 2020;132:109590.
- [13] Wei D, Zhang X, Mahadevan S. Measuring the vulnerability of community structure in complex networks. *Reliab Eng Syst Saf* 2018;174:41–52.
- [14] Zhang Y, Shao C, He S, Gao J. Resilience centrality in complex networks. *Phys Rev E* 2020;101(2):022304.
- [15] Ramirez-Marquez JE, Rocco CM, Barker K, Moronta J. Quantifying the resilience of community structures in networks. *Reliab Eng Syst Saf* 2018;169:466–74.
- [16] Newman M. Spectra of networks containing short loops. *Phys Rev E* 2019;100(1):012314.
- [17] Li S, Zhao D, Wu X, Tian Z, Li A, Wang Z. Functional immunization of networks based on message passing. *Appl Math Comput* 2020;366:124728.
- [18] Zhao D, Yang S, Han X, Zhang S, Wang Z. Dismantling and vertex cover of network through message passing. *IEEE Trans Circuits Syst II* 2020. doi:10.1109/TCSII.2020.2973414.
- [19] Ye Y, Hang XR, Koh JM, Miszczak JA, Cheong KH, Xie N-g. Passive network evolution promotes group welfare in complex networks. *Chaos Solitons Fractals* 2020;130:109464.
- [20] Shi L, Shen C, Shi Q, Wang Z, Zhao J, Li X, et al. Recovering network structures based on evolutionary game dynamics via secure dimensional reduction. *IEEE Trans Netw Sci Eng* 2020.
- [21] Zhao D, Wang L, Wang Z, Xiao G. Virus propagation and patch distribution in multiplex networks: modeling, analysis, and optimal allocation. *IEEE Trans Inf Forensics Secur* 2018;14(7):1755–67.
- [22] Jia D, Shen C, Li X, Boccaletti S, Wang Z. Ability-based evolution promotes cooperation in interdependent graphs. *EPL* 2019;127(6):68002.
- [23] Jiang W, Cao Y, Deng X. A novel Z-network model based on Bayesian network and Z-number. *IEEE Trans Fuzzy Syst* 2019. doi:10.1109/TFUZZ.2019.2918999.
- [24] Liu F, Deng Y. Determine the number of unknown targets in Open World based on Elbow method. *IEEE Trans Fuzzy Syst* 2020. doi:10.1109/TFUZZ.2020.2966182.
- [25] Zhao J, Deng Y. Complex network modeling of evidence theory. *IEEE Trans Fuzzy Syst* 2020. doi:10.1109/TFUZZ.2020.3023760.
- [26] Duan D, Lv C, Si S, Wang Z, Li D, Gao J, et al. Universal behavior of cascading failures in interdependent networks. *Proc Natl Acad Sci* 2019;116(45):22452–7.
- [27] Liu F, Deng Y. A fast algorithm for network forecasting time series. *IEEE Access* 2019;7(1):102554–60.
- [28] Zhao J, Mo H, Deng Y. An efficient network method for time series forecasting based on the DC algorithm and visibility relation. *IEEE Access* 2020;8:7598–608.
- [29] Huang Y, Gao Y, Gan Y, Ye M. A new financial data forecasting model using genetic algorithm and long short-term memory network. *Neurocomputing* 2020. doi:10.1016/j.neucom.2020.04.086.
- [30] Mao S, Deng Y, Pelusi D. Alternatives selection for produced water management: a network-based methodology. *Eng Appl Artif Intell* 2020;91:103556.
- [31] Zhou L, Xiao F. DCM: D number extended cognitive map. Application on location selection in SCM. *Int J Comput Commun Control* 2019;14(5).
- [32] Iacovacci J, Lacasa L. Visibility graphs for image processing. *IEEE Trans Pattern Anal Mach Intell* 2019. doi:10.1109/TPAMI.2019.2891742.
- [33] Colizza V, Flammini A, Serrano MA, Vespignani A. Detecting rich-club ordering in complex networks. *Nat Phys* 2006;2(2):110–15.
- [34] Wang H, Fang Y, Zio E. Risk assessment of an electrical power system considering the influence of traffic congestion on a hypothetical scenario of electrified transportation system in new york state. *IEEE Trans Intell Transp Syst* 2019;1–14. doi:10.1109/ITS.2019.2955359.
- [35] Dai J, Deng Y. A new method to predict the interference effect in quantum-Like Bayesian networks. *Soft Comput* 2020;24(14):10287–94. doi:10.1007/s00500-020-04693-2.
- [36] Baxter G, Timár G, Mendes J. Targeted damage to interdependent networks. *Phys Rev E* 2018;98(3):032307.
- [37] da Silva DC, Bianconi G, da Costa RA, Dorogovtsev SN, Mendes JF. Complex network of evolving manifolds. *Phys Rev E* 2018;97(3):032316.
- [38] Timár G, da Costa RA, Dorogovtsev SN, Mendes JF. Nonbacktracking expansion of finite graphs. *Phys Rev E* 2017;95(4):042322.
- [39] Baxter GJ, Cellai D, Dorogovtsev SN, Mendes JF. Cycles and clustering in multiplex networks. *Phys Rev E* 2016;94(6):062308.

- [40] Tao Y. Self-referential Boltzmann machine. *Physica A* 2020;545:123775.
- [41] Berahmand K, Bouyer A, Samadi N. A new centrality measure based on the negative and positive effects of clustering coefficient for identifying influential spreaders in complex networks. *Chaos Solitons Fractals* 2018;110:41–54.
- [42] Zhang T, Zhang K, Lv L, Bardou D. Co-Ranking for nodes, layers and timestamps in multilayer temporal networks. *Chaos Solitons Fractals* 2019;125:88–96.
- [43] Barabási A-L, Gulbahce N, Loscalzo J. Network medicine: a network-based approach to human disease. *Nat Rev Genet* 2011;12(1):56–68.
- [44] Zhu P, Zhi Q, Guo Y, Wang Z. Analysis of epidemic spreading process in adaptive networks. *IEEE Trans Circuits Syst II Express Briefs* 2018;66(7):1252–6.
- [45] Borge-Holthoefer J, Moreno Y. Absence of influential spreaders in rumor dynamics. *Phys Rev E* 2012;85(2):026116.
- [46] Park N, Kan A, Dong XL, Zhao T, Faloutsos C. Estimating node importance in knowledge graphs using graph neural networks. In: *Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining*; 2019. p. 596–606.
- [47] Yu Z, Shao J, Yang Q, Sun Z. ProfitLeader: identifying leaders in networks with profit capacity. *World Wide Web* 2019;22(2):533–53.
- [48] Fan C, Zeng L, Sun Y, Liu Y-Y. Finding key players in complex networks through deep reinforcement learning. *Nat Mach Intell* 2020;1–8. doi:10.1038/s42256-020-0177-2.
- [49] Bonacich P. Factoring and weighting approaches to status scores and clique identification. *J Math Sociol* 1972;2(1):113–20.
- [50] Newman ME. A measure of betweenness centrality based on random walks. *Soc Networks* 2005;27(1):39–54.
- [51] Freeman LC. Centrality in social networks conceptual clarification. *Soc Networks* 1978;1(3):215–39.
- [52] Brin S, Page L. The anatomy of a large-scale hypertextual web search engine, 1998.
- [53] Aleja D, Criado R, del Amo AJG, Pérez Á, Romance M. Non-backtracking pagerank: from the classic model to hashimoto matrices. *Chaos Solitons Fractals* 2019;126:283–91.
- [54] Lü L, Zhang Y-C, Yeung CH, Zhou T. Leaders in social networks, the delicious case. *PLoS ONE* 2011;6(6).
- [55] Bonacich P. Some unique properties of eigenvector centrality. *Soc Netw* 2007;29(4):555–64.
- [56] Lü L, Zhou T, Zhang Q-M, Stanley HE. The H-index of a network node and its relation to degree and coreness. *Nat Commun* 2016;7:10168.
- [57] Chen D, Lü L, Shang M-S, Zhang Y-C, Zhou T. Identifying influential nodes in complex networks. *Physica A* 2012;391(4):1777–87.
- [58] Wen T, Deng Y. Identification of influencers in complex networks by local information dimensionality. *Inf Sci* 2020;512:549–62.
- [59] Gao X, Deng Y. The pseudo-pascal triangle of maximum deng entropy. *Int J Comput Commun Control* 2020;15(1):1006. doi:10.15837/3735/ijccc.2020.1.3735.
- [60] Deng Y. Uncertainty measure in evidence theory. *Sci China Inf Sci* 2020;63(11):210201.
- [61] Wen T, Pelusi D, Deng Y. Vital spreaders identification in complex networks with multi-local dimension. *Knowl Based Syst* 2020;195:105717. doi:10.1016/j.knsys.2020.105717.
- [62] Katz L. A new status index derived from sociometric analysis. *Psychometrika* 1953;18(1):39–43.
- [63] Li Z, Ren T, Ma X, Liu S, Zhang Y, Zhou T. Identifying influential spreaders by gravity model. *Sci Rep* 2019;9(1):1–7.
- [64] Liu F, Wang Z, Deng Y. GMM: A generalized mechanics model for identifying the importance of nodes in complex networks. *Knowl Based Syst* 2020;105464.
- [65] Zareie A, Sheikahmadi A, Fatemi A. Influential nodes ranking in complex networks: an entropy-based approach. *Chaos Solitons Fractals* 2017;104:485–94.
- [66] Zareie A, Sheikahmadi A, Jalili M. Identification of influential users in social network using gray wolf optimization algorithm. *Expert Syst Appl* 2020;142:112971.
- [67] Zhao J, Wang Y, Deng Y. Identifying influential nodes in complex networks from global perspective. *Chaos Solitons Fractals* 2020;133:109637.
- [68] Fu Y-H, Huang C-Y, Sun C-T. Using global diversity and local topology features to identify influential network spreaders. *Physica A* 2015;433:344–55.
- [69] Ren Z-M, Zeng A, Chen D-B, Liao H, Liu J-G. Iterative resource allocation for ranking spreaders in complex networks. *EPL* 2014;106(4):48005.
- [70] Zareie A, Sheikahmadi A, Jalili M, Fasaie MSK. Finding influential nodes in social networks based on neighborhood correlation coefficient. *Knowl Based Syst* 2020;105580.
- [71] Zareie A, Sheikahmadi A, Jalili M. Influential node ranking in social networks based on neighborhood diversity. *Future Gener Comput Syst* 2019;94:120–9.
- [72] Ma L-L, Ma C, Zhang H-F, Wang B-H. Identifying influential spreaders in complex networks based on gravity formula. *Physica A* 2016;451:205–12.
- [73] Zhou T, Liu J-G, Bai W-J, Chen G, Wang B-H. Behaviors of susceptible-infected epidemics on scale-free networks with identical infectivity. *Phys Rev E* 2006;74(5):056109.
- [74] Kendall MG. The treatment of ties in ranking problems. *Biometrika* 1945;33(3):239–51.
- [75] Liu Z, He J-L, Kapoor K, Srivastava J. Correlations between community structure and link formation in complex networks. *PLoS ONE* 2013;8(9).
- [76] Gleiser PM, Danon L. Community structure in jazz. *Adv Complex Syst* 2003;6(04):565–73.
- [77] Newman ME. Finding community structure in networks using the eigenvectors of matrices. *Phys Rev E* 2006;74(3):036104.
- [78] Adamic LA, Glance N. The political blogosphere and the 2004 US election: divided they blog. In: *Proceedings of the 3rd international workshop on link discovery*; 2005. p. 36–43.